

Description

FIELD OF THE INVENTION AND RELATED ART

The present invention relates to an image forming apparatus such as an image transfer type electrophotographic copying apparatus, a laser beam printer or the like, wherein a surface of an image bearing member such as a photosensitive member in the form of a drum, an endless belt or the like which is rotated or revolved, is uniformly charged and is subjected to an image exposure by which an electrostatic latent image is formed; the latent image is developed into a toner image, which is then transferred onto an image receiving material such as paper, so that an image is formed on the image receiving member, while the image bearing member is repeatedly used.

Referring first to Figure 8, there is shown a structure of one of generally used image transfer type electrophotographic copying machines using a photosensitive member in the form of a drum.

The copying machine shown in this Figure comprises a photosensitive drum 1 functioning as the image bearing member, which is rotatable about a shaft 1a in the direction indicated by an arrow at a predetermined peripheral speed. While the photosensitive drum 1 is being rotated, it is subjected to an operation of a charging device 2, by which the peripheral surface thereof is electrically charged to a predetermined potential in a negative or positive polarity. After the uniform charging, the photosensitive drum is exposed to image light L at an exposure station 3 by an unshown exposing device through a slit or by a laser beam scanning action. By this, an electrostatic latent image is sequentially formed in accordance with the light image on the peripheral surface of the photosensitive member. The electrostatic latent image is developed by a developing device 4 with toner into a toner image, which is then transferred by a transfer device 5 onto an image receiving material P which is supplied into a space between the photosensitive member 1 and the image transfer device 5 in timed relation with the rotation of the photosensitive member 1.

The image receiving material P having received the image is separated from the surface of the photosensitive drum 1, and is conveyed into an image fixing device 8, where the toner image is fixed, and thereafter, the image receiving material P is discharged out of the copying machine as a copy.

On the other hand, the surface of the photosensitive drum 1, after the image is transferred from the image receiving material P, is cleaned by a cleaning device 6 on its outer periphery, so that the residual toner remaining thereon is removed, thus being prepared for a repeated image forming operation.

As for the charging device 2 for uniformly charging the photosensitive member 1, a corona charging

device with a wire electrode, which is known, is widely used. Also, as for the transfer device 5, a corona transfer device is widely used.

When a corona charging device is used as the charging device, it has been considered that a pre-exposure step is required which electrically discharges the photosensitive member 1 which is used repetitively, by exposing the photosensitive member 1 to uniform light prior to the uniform charging step, and that a post-exposure step is required which discharges the photosensitive member after completion of the image information to remove the potential remaining thereon.

In other words, in order to allow the photosensitive member 1 to be used repetitively, the electric potential contrast of the electrostatic latent image remaining on the surface of the photosensitive member 1 by the previous image formation, is required to be dissipated prior to the uniform charging step for the next image forming operation. This is because, if the surface of the photosensitive member is subjected to a uniform charging operation for the next image formation without removing the electrostatic contrast of the previous electrostatic latent image when a conventional corona charging device 2 is used, the whole surface of the photosensitive member is not uniformly charged, and therefore, electrostatic contrast by the previous electrostatic latent image remains, by which the remaining image appears as a ghost image in the next image formed.

Also, after the completion of the image forming operation, it is required that the image forming machine is required to be stopped after the potential on the photosensitive member 1 is dissipated. This is because if the photosensitive member 1 is left with the electric charge remaining thereon, the characteristics of the photosensitivity of the photosensitive member or the like is liable to be changed.

To obviate this problem, a whole surface exposure device 7 (eraser) for exposing the photosensitive member 1 to uniform light is disposed between the corona charging device 2 and a cleaning device 6 to electrically discharge the photosensitive member 1. By this, in each of the image forming cycles using the photosensitive member 1 repetitively, the photosensitive member 1 is exposed to uniform light by the whole exposure device 7 to be electrically discharged before the charging by the charging device 2, and therefore, the photosensitive member can be uniformly charged by the corona charging device 2 for the next image forming operation. The photosensitive member 1 is rotated through at least one full turn (post-rotation or post-revolution) after the corona charging device 2 and the corona transfer device 5 are deactivated. During the post rotation or post-revolution, the entire surface of the photosensitive member is exposed to uniform light by the whole surface exposure device 7 so that the whole surface

thereof is electrically discharged, and thereafter, the rotation of the photosensitive member is stopped and is prepared for the next image forming operation.

When the conventional corona transfer device 5 is used, the photosensitive member 1 is directly charged by the corona charging device 5 except when the toner image on the photosensitive member 1 is transferred onto the image receiving material, that is, when the image receiving material is not present in the space between the photosensitive member 1 and the corona transfer device 5. On the other hand, during the image transfer operation, the image receiving material is in the space between the photosensitive member 1 and the corona transfer device 5, that area on the photosensitive member 1 which corresponds to the image receiving material, is not charged by the corona transfer device 5. This produces an electrical potential difference between the area charged by the corona transfer device 5 and the area not charged.

This difference is not eliminated completely by the whole exposure device 7, and therefore, it can appear as a density difference in accordance with the potential difference.

In the electrophotographic apparatus such as a laser beam printer or the like wherein the reversal development is performed, the photosensitive drum 1 is uniformly charged to a high negative potential, when, for example, the photosensitive drum 1 has a photosensitive layer made of a negative property OPC (organic photoconductor). Then, a laser beam is projected onto the photosensitive member 1 in accordance with image information to be recorded to leave a high negative potential area not exposed to the laser beam and produce a low negative potential area upon exposure to the laser beam. Thereafter, the photosensitive member 1 is subjected to a reversal development with the toner particles electrically charged to a high negative particle which is the same as the polarity to which the photosensitive member is charged by the charging device 2, by which the toner particles are deposited onto the area of the photosensitive member 1 which has the low negative potential. Using the corona transfer device 5 supplied with a positive voltage, the developed image is transferred from the photosensitive member 1 to the image receiving material P. At this time, if the photosensitive member 1 is directly charged by the transfer device 5 without the image receiving material P therebetween, the positive charge provided by the corona transfer device 5 is not discharged by the whole surface exposure device 7, because the photosensitive member is of a negative property. Therefore, particularly when reversal development is employed, an image density difference can be noticeable in the next image produced.

Figure 9 is a timing chart illustrating the timed relation between operations of each of the elements to avoid the above-described problems. As will be un-

derstood from this chart, the corona transfer device 5 is required to operate only during the period in which the image receiving material P is contacted to the photosensitive member 1 to transfer the image onto the image receiving material P. Therefore, the charging device 2, the corona transfer device 5 and the whole surface exposure device 7 have to be controlled in different sequential schedules, whereby the sequential operations are complicated.

When a corona discharging device having a wire electrode is used as the transfer device, it is required that the wire electrode is supplied with a high voltage such as several KV. In addition, in order to maintain a large distance between the wire electrode and the shield electrode (known) enclosing the wire electrode, the size of the discharging device is large. Also, the corona discharging device produces a relatively large amount of ozone, the photosensitive member is deteriorated thereby, which leads to blurred images. Furthermore, when the corona transfer device 5 is employed, there are such problems that an additional means for conveying the image receiving material P is required and that the image is deviated due to transfer deviation when the image receiving material P is not correctly contacted to the photosensitive member 1, because of the existence of the space between the photosensitive member 1 and the corona charging device 5.

US Patents Nos. 3,697,171 and 3,832,055 propose that a transfer roller is used in place of the corona transfer device in order to prevent the transfer deviation and to improve the conveyance of the image receiving material P. However, this does not solve the problem of the image density difference in the next image due to the presence and the absence of the image receiving material P on the photosensitive member 1 at the transfer station.

The present invention is intended as a solution to the problem aforesaid. In accordance with a first aspect of the present invention there is provided:

an image bearing member;

image forming means for forming an image on a surface of said image bearing member; and

transfer means for transferring the image formed on said image bearing member by said image forming means onto an image receiving member, said transfer means including a transfer member and voltage application means for applying a voltage to the transfer member to transfer the image from said image bearing member to the image receiving member;

which apparatus is characterised in that said transfer means and said image bearing member are arranged to be in contact and said voltage application means is operable, at least during image transfer action, to apply a voltage to said transfer member which is lower than that minimum DC voltage of said transfer member for which charging of the surface of said image bearing member would occur if no image re-

ceiving member were located between the respective surfaces of said transfer member and said image bearing member.

A comparison is drawn with apparatus disclosed in United States Patent US-A-4,268,157. As described therein, the apparatus is adapted to allow multiple copies to be produced from a single electrostatic image. Discharge of the electrostatic image during image transfer is prevented by limiting the voltage of the transfer member to a voltage of magnitude which is slightly less than a magnitude at which charge transfer between the transfer member and the image receiving member would occur either due to dielectric breakdown through the image receiving member or due to field emission from the image receiving member. This is to be contrasted with the present invention wherein the transfer member is arranged to contact the image bearing member and the voltage applied to the transfer member is limited to a voltage which is less than a voltage at which charge transfer between the transfer member and the image bearing member would occur when the image receiving member is not located between the transfer member and the latter two thus are in direct contact. Consequently, as the image receiving member passes between the transfer member and the image bearing member no abrupt discharge occurs as the transfer member and the image bearing member come into contact.

The present invention is applicable both to image reversal development and to image non-reversal development processing. In the latter case it would be usual to include in the apparatus a means of discharging the developed image prior to image transfer.

The image receiving member may have the form of a rotatable belt or revolveable drum. Advantageously, strict synchrony between the feeding of the image receiving member and rotation or revolution of the image receiving member is not a requisite, nor is it a requisite to synchronise the application of voltage to the transfer member with start point and end point of the feeding of the image receiving member. Consequently, the apparatus design can be simplified.

Ordinarily, the image forming means will include a charging means for pre-charging the surface of the image bearing member. While said charging means may include a corona discharge device, it is preferable that the charging means is of a type including a charging member, such as a roller, which can be arranged to contact the image receiving member. Since then both said charging member and said transfer member contact said image receiving member, lower voltages can be employed. As a result, ozone production is avoided, or in the least significantly reduced. Consequently, pollution is avoided or reduced and deterioration of the receiving member by ozone action also is avoided or reduced.

As mentioned above, the transfer member is arranged to contact the image bearing member. It may

have thus the form of a roller or a belt. Where the transfer member is revolveable or rotateable with revolution or rotation of the image bearing member it can be used as a means of conveying the image receiving member. Transfer deviation can thus be effectively avoided.

It is preferable that the voltage applied to the charging member includes both DC and AC components. The latter effects improvement in charging uniformity. The AC component may be used, for example, during at least a full rotation or revolution of the image bearing member, as a means of final discharge. Furthermore, the aforesaid AC component of this voltage can be rectified and the rectified voltage that is produced used as voltage for the transfer means. Voltage sourcing therefore can be simplified.

In accordance with a further aspect of the present invention there is provided a method of image forming including the steps of:

pre-charging the surface of an image bearing member;

exposing an area of the surface of said image bearing member to produce an electrostatic image;

developing said electrostatic image to produce a developed image;

feeding an image receiving member between said image bearing member and a transfer member; and

applying a voltage to said transfer member to cause transfer of said developed image from said image bearing member onto said image receiving member;

which method is characterised in that: said image bearing member is arranged to be in contact with said transfer member and

in supplying said voltage to said transfer member, the voltage applied is maintained less than a minimum DC voltage of said transfer member for which charging of the surface of said image bearing member would occur if no image receiving member were passing between the respective surfaces of said transfer member and said image bearing member.

In the accompanying drawings:

Figure 1 is a somewhat schematic sectional view of an example of a laser beam printer according to an embodiment of the present invention.

Figure 2 is a somewhat sectional view of a laser beam printer according to another embodiment of the present invention.

Figure 3 is a graph of a surface potential of the charged photosensitive member and a DC voltage applied to the transfer roller when an OPC photosensitive drum is used.

Figure 4 is a timing chart (sequence) of the laser beam printer.

Figure 5 is a somewhat sectional view of a copying apparatus according to an embodiment of the

present invention.

Figures 6 and 7 are sectional views of image forming machines wherein contact type charging devices in the forms of a conductive rubber blade and a conductive brush are employed.

Figure 8 is a somewhat schematic conventional image forming apparatus which employs a uniform charging means in the form of a corona charging device and a corona transfer device in the form of a corona charging device.

Figure 9 is a timing chart (sequence) of the apparatus shown in Figure 8.

Figure 10 is a somewhat schematic sectional view of a laser beam printer according to a further embodiment of the present invention employing a conductive belt as a transfer device.

For a better understanding of this invention, preferred embodiments thereof will be described now in particular detail and reference will be made to the drawings. The description that follows is given by way of example only.

Referring to Figure 1, there is shown a laser beam printer according to an embodiment of the present invention which employs a reversal development. In Figure 1, the same reference numerals are assigned as with Figure 8 to the elements performing the corresponding functions to avoid repeated description.

The photosensitive member 1 is made of an organic photoconductor (OPC) and is uniformly charged to -700 V by a conventional corona charging device.

The toner image formed on the photosensitive member 1 is transferred onto the image receiving material P not by a corona transfer device 5 as shown in Figure 8 but by a roller transfer device. The roller transfer device includes a conductive transfer roller 50 which is contacted to the photosensitive member 1. The transfer roller 50 comprises a core metal and a conductive layer having a resistance of $10^2 - 10^8$ ohm and having a conductivity at its surface (made of conductive urethane rubber having the resistivity of 10^5 ohm.). Here, the resistance is the one from the core metal to the roller surface per 1 cm^2 at the roller surface. Other usable rubber materials are EPDM, NBP, CR or the like. The transfer roller 50 is maintained normally in press-contact with the surface of the photosensitive member 1 under a predetermined pressure, for example, 10 - 100 g/cm (line pressure) by employing the urethane rubber having continuous pores, the pressure between the transfer roller 50 and the photosensitive member 1 can be reduced, and simultaneously, the nip between the transfer roller 50 and the photosensitive member 1 can be made sufficient, and it is preferable. In this embodiment, the transfer roller 50 is driven from an unshown photosensitive drum driving gear, and the peripheral speeds of the photosensitive member 1 and the transfer roller 50 are the same so that the transfer deviation

is avoided. However, it is possible to allow the transfer roller 50 to rotate following the photosensitive member 1 by the contact therebetween.

The transfer roller 50 and the corona charger 2 are supplied with electric power by a voltage source 40.

The apparatus comprises a known laser scanner unit 30, by which a laser beam is modulated in accordance with an image signal and is scanningly deflected. The laser beam is projected by way of a mirror 31 onto the surface of the photosensitive member 1, so that an electrostatic latent image is formed by lowering to -150 V the electric potential at the portions where the laser beam is projected. A developing device 4 performs a reversal development with one component insulative magnetic toner which has been charged to a negative potential by which a toner image is formed on the photosensitive drum surface.

This toner image is transferred at the transfer station from the photosensitive member 1 to the image receiving material P by the transfer roller 50. It has been confirmed that good image transfer can be performed without the transfer deviation when a DC voltage of +500 V is applied thereto from the power source 40.

In the absence of the image receiving material P, when a DC voltage is applied to the transfer roller 50, the surface of the photosensitive member 1 starts to be electrically charged when the voltage becomes approximately 560 V.

Figure 3 is a graph of the relationship between the voltage and the surface potential when the voltage is over the charge starting voltage (approximately 560 V), which was experimentally obtained. As will be understood, the relationship is linear with inclination of 1:1. Since the DC voltage applied to the transfer roller 50 is +500 V which is lower than the charge starting voltage, and therefore, the photosensitive member 1 is not charged by the transfer roller. Since however, the transfer roller 50 has to be effective to transfer the toner image from the photosensitive member 1 to the image receiving material P under good conditions, it is preferably not less than 250 V.

Here, the charge starting voltage is defined in the following manner. The DC voltage is applied to the transfer roller 50 functioning as a charging member contacted to the image bearing member functioning as a member to be charged and having an initial voltage of 0 V, and the voltage is gradually increased. Then, the surface potential of the photosensitive member charged by the transfer roller 50 is plotted against the applied DC voltage. The DC voltages are increased at intervals of 100 V from the voltage at which any surface potential other than 0 V appears first on the photosensitive drum, and ten plots are obtained. On the basis of those ten points, a rectilinear line is drawn using the least square approximation method. The rectilinear line is extended to cross with

the line indicative of the surface potential of 0 V, and the applied voltage corresponding to the crossing point is defined as the charge starting (on-set) voltage. The line shown in Figure 3 was provided by the least square approximation method.

The charge starting voltage varies depending on the materials and thicknesses or the like of the photosensitive member to be charged and the transfer roller as the charging member. In this example, the photosensitive layer of the photosensitive drum 1 is of azo pigment for CGL (carrier generating layer) and a mixture of hydrazone and resin thereon as CRL (carrier transportation layer) having a thickness of 19 μm to constitute a negative polarity organic photoconductor layer (OPC layer). The transfer roller 50 comprises a core metal (steel) having a diameter of 6 mm and a conductive urethane rubber layer. The transfer roller 50 has a diameter of 16 mm and a volume resistivity of 10^5 ohm.cm .

As described in the foregoing, the transfer roller 50 is supplied with a DC voltage of +500 V irrespective of the presence and absence of the image receiving material P. However, it does not charge the surface of the photosensitive member. Therefore, there is no problem that the negative polarity OPC photosensitive member is positively charged and is unable to be discharged electrically. The voltage applied to the transfer roller 50 is not limited to a DC voltage, but a triangular, rectangular, pulsewise and sine pulse having a component of a polarity opposite to the electric charge of the toner, provided that it does not charge the photosensitive member.

In this manner, the photosensitive member 1 is repeatedly used to form images, repeatedly. After completion of the image formation, the surface of the photosensitive member 1 is subjected to a whole surface exposure by the whole surface exposure device 7 so as to stop the image forming apparatus after being electrically discharged.

According to this embodiment, the toner image transfer from the photosensitive member 1 to the transfer material P is effected not by a corona transfer device but by a transfer roller 50 supplied with a DC voltage which is lower than the charge starting voltage at which the photosensitive member starts to be charged. Therefore, even in the absence of the image receiving material P at the transfer station, as when the pre-rotation or the post rotation of the photosensitive drum 1 is performed, the DC voltage supply to the transfer roller 50 may be maintained to be supplied, without production of the potential difference on the surface of the photosensitive member 1 depending on the presence or absence of the image receiving material P at the transfer station.

This provides a larger latitude of the sequential control of the transfer device. For example, the timing at which the charging devices 2 is actuated or deactuated may be made the same as the timing at which

the voltage supply to the transfer roller 50 is started or stopped. This makes the sequential control simpler. Since the power supply to the charging device 2 and the power supply to the transfer roller 50 may be performed at the same time, the same transformer can be used as the power source for supplying voltage to the charging device 2 and the transfer device 50. Therefore, the apparatus may be made smaller, simpler and lower in cost.

Since the corona discharger 5 is not used as the transfer device, but a transfer roller 50 is used in place thereof, the production of ozone is reduced; the transfer material can be conveyed with certainty at the transfer operation; and a good image can be provided without transfer deviation. Referring to Figure 2, another embodiment of the present invention will be described. The same reference numerals as with the foregoing embodiment are assigned to the elements having the corresponding functions, and the description thereof is omitted for the sake of simplicity.

In this embodiment, the photosensitive member 1 is charged not by the corona charging device 2 as shown in Figure 1, but by a contact type charging device 20. The details of the contact type charging device 20 may be the same as described in U.S. Application Serial No. 159,917 filed on February 24, 1988 and European Patent Application No. 88301603.2 filed on 25th February 1988 and having been assigned to the assignee of this application, and, the detailed explanation is omitted. In this embodiment, the charging device 20 is a roller made of a conductive rubber contacted to the photosensitive member 1. The charging device or the charging roller 20 may be the same as the transfer roller 50 in the foregoing embodiment, and is press-contacted to the surface of the photosensitive member 1 under predetermined pressure, for example, 10 - 100 g/cm (line pressure). In this embodiment, the charging roller 20 rotates following the rotation of the photosensitive member 1. The charging roller 20 may be rotated in the same direction as or the opposite direction to the photosensitive member 1 at the position where they are contacted, or it may be non-rotated. However, what is preferable is that the charging roller 20 is rotated at the same speed and in the same peripheral direction at the photosensitive member 1 at the position where they are contacted, or that the charging roller 20 is driven by the contact with the photosensitive member. This is because, the friction between the charging roller 20 and the photosensitive member 1 is smaller than when there exist a speed difference between the charging roller 20 and the photosensitive member 1, and therefore, the problem of wearing of those elements is not significant.

The charging roller 20 and the transfer roller 50 are supplied with voltages from the voltage source 40.

To the charging roller 20, a superimposed voltage

$V_{DC} + V_{AC}$ of a DC voltage V_{DC} and an AC voltage V_{AC} is applied from the voltage source 40 during the pre-rotation period of the photosensitive member 1 and during each of the image forming cycles repeated. In this embodiment, the DC component V_{DC} was -700 V, and the AC component V_{AC} had a peak-to-peak voltage V_{pp} of 1500 V and a frequency of 1000 Hz in the form of a sine wave. By this, the surface of the photosensitive member 1 was uniformly charged to -700 V. The laser beam produced and modulated in accordance with an image signal by the laser scanning unit 30 is applied by way of the mirror 31 onto the surface of the photosensitive member 1, so that the surface potential of the photosensitive member at the image portion (exposed portion) becomes -150 V. In this manner, an electrostatic latent image is formed, and the developing device 4 performs a reversal development with the toner negatively charged to form a toner image on the surface of the photosensitive drum 1.

The toner image is transferred onto the image receiving material P by the transfer roller 50 supplied with a DC voltage of +500 V from the power source 40. It has been confirmed that good image transfer is obtained with those conditions. In this embodiment, too, the DC voltage of +500 V applied to the transfer roller 50 is not more than the charge starting voltage, and therefore, the photosensitive member 1 is not charged by the transfer roller 50. For this reason, no potential difference is produced on the photosensitive member 1 irrespective of the presence or absence of the image receiving material P in the transfer station, and therefore, no image density difference is produced in the next image formation resulting from the presence and absence of the image receiving material P.

Since this structure does not include the pre-exposure means which has been necessitated in the conventional art for the surface of the photosensitive member immediately before the charging roller 20, the potential contrast of the electrostatic latent image due to the previous image formation remains when the photosensitive member 1 is repeatedly used for the image formation. However, the photosensitive member 1 is uniformly charged to -700 V in this embodiment, after it has passed by the charging roller 20. Therefore, even without the pre-exposure, the image is substantially free from the ghost resulting from the previous electrostatic latent image. The uniformity of the charging by the charging roller 20 derives from the fact that the superimposed DC and AC voltages are applied thereto. When a DC voltage only was applied to the charging roller 20 to charge the photosensitive member with the DC voltage of -1200 V - -1300 V, the surface of the photosensitive member 1 was charged to approximately -700 V, but the uniformity of the charging was not good so that when the photosensitive member 1 was used repeatedly, the potential contrast of the previous electrostatic latent

image appeared as a ghost in the next image. The reason why the uniformity is provided by superimposing the AC voltage is considered as follows. The charging mechanism is considered as being dependent on the electric discharge occurring at or adjacent the position where the charging roller 20 and the photosensitive member 1 are contacted, and it is considered that due to the AC voltage component reversal discharge from the photosensitive member 1 to the charging roller 20 takes place, and this improves the uniformity of the charging.

The photosensitive member 1 is repeatedly used to repeatedly form images. After completion of the image formations, the DC voltage component is removed, and only the AC voltage is supplied to the charging roller 20 so as to electrically discharge the surface of the photosensitive member 1 to be prepared for stopping and waiting for the next image forming operation. More particularly, during at least one full turn of the photosensitive member 1 for the post-rotation after the completion of the image forming operation, the voltage source 40 applies only the AC voltage V_{AC} to the charging roller 20.

By applying the AC voltage only, the surface potential of the photosensitive member 1 is uniformly discharged to 0 V. This operation is effected more than one rotation of the photosensitive member 1, so that the entire surface of the photosensitive member 1 is electrically discharged. In this embodiment, the DC component is made zero, but this is not limiting, and a voltage of the DC component may be determined if it is a level at which the photosensitive member 1 is not influenced even if the photosensitive member is left as it is after the post rotation. As for usual photosensitive members, there will be no problem if the DC component is not more than 100 V. The AC voltage may be in a usual form, or may be in another form, if it is a vibratory voltage which periodically vibrates, and the waveform may be a sine wave, a triangular wave, a rectangular wave, a pulse wave or the like.

Similarly to the foregoing embodiment, the voltage to the transfer roller 50 is maintained +500 V, but it does not charge the photosensitive member surface.

After the post-rotation, the AC voltage applied to the charging roller 20 and the DC voltage (+500 V) applied to the transfer roller 50 are stopped, and the rotation of the photosensitive member 1 is stopped, then the apparatus is waiting for the next image forming operation.

Referring to Figure 4, there is shown a timing chart showing the timing of the rotation of the photosensitive drum 1, the application of the voltage to the charging roller 20 and the voltage application to the transfer roller 50. Since, as will be understood from this figure, the time of the voltage application to the transfer roller 50 is the same as the AC component

application to the charging roller 20, the AC component of the voltage applied to the charging roller 20 may be rectified and used as a voltage to be applied to the transfer roller 50. In this embodiment, the voltage applied to the transfer roller 50 is stopped simultaneously with the AC component of the voltage applied to the charging roller 20, but this is not limiting, and as shown by the broken lines, the voltage application to the transfer roller 50 is stopped earlier than shown in Figure 4 by the time period T2 (more than one full turn of the photosensitive member 1), and then, the voltage application to the transfer roller 50 may be stopped simultaneously with the DC component of the voltage applied to the transfer roller 20.

In Figure 4, the voltage applications to the charging roller and the transfer roller are started simultaneously with the start of the photosensitive drum 1 rotation, but this is not limiting, and the voltage applications to the charging roller and the transfer roller may be started after the start of the photosensitive drum 1 rotation.

According to this embodiment, the high voltage such as 5 - 6 KV as in conventional corona discharging device is not necessitated, and the sequential control for the voltage output is simple, and therefore, the cost and the size of the voltage source can be reduced. Additionally, the production of ozone is almost nothing as compared with the case of corona discharging, and therefore, the necessity for the means for disposing of the ozone or the means for preventing deterioration of the photosensitive member by ozone, is eliminated. Also, the necessities for the exposure device for the pre-exposure prior to the charging step for the photosensitive member and the exposure device for the post-exposure after the completion of the image formation, are eliminated, and the apparatus may be made smaller in size, simpler in structure and lower in cost.

Referring to Figure 10, it is possible to use in place of the roller for the transfer device, a conductive belt 60 rotated by a roller or the like. When a transfer belt 60 is used, the image receiving material P is discharged out of the transfer station in close contact with the belt, and therefore, the image receiving material is slowly separated from the image bearing member, and therefore, the change in the electric field between the charge on the image bearing member and the toner on the image receiving material becomes slow, so that the transferred image is not disturbed.

Figure 5 illustrates a copying machine according to a further embodiment of the present invention, wherein the same reference numerals are assigned as with Figures 1, 2 and 8 embodiments to the elements having the corresponding functions, and the detailed description thereof is omitted for the sake of simplicity.

The copying machine of this embodiment com-

prises an original supporting glass 60, on which an original O to be copied is placed thereon face down. The bottom side of the original O is illuminated and scanned by the exposure lamp 61 during a forward or backward stroke of the original supporting glass movement. The light reflected by the original is directed to the exposure station 3 by way of mirrors 62 and 63, an imaging lens 64 and mirrors 65 and 66, by which the surface of the photosensitive member 1 is exposed to the light image of the original through a slit, as indicated by a reference L.

The photosensitive drum 1 is charged to -700 V by the charging roller 20 and is exposed to the light image of the original by the exposure means, so that an electrostatic latent image is formed on the surface thereof. The electrostatic latent image is developed by the developing device 4 into a toner image (regular development). The photosensitive drum surface having the toner image is subjected to a whole surface exposure by a pre-transfer exposure device 70 for charge removal from the photosensitive member 1, prior to reaching the transfer roller 50. By this, the electric charge on the photosensitive drum is removed. The toner image is transferred onto the image receiving material P by the transfer roller 50 to which a DC voltage of -500 V is applied. It has been confirmed that a good image transfer operation can be performed with those conditions. Also, it has been found that without the pre-transfer exposure 70, a good image transfer action does not occur unless the transfer roller 50 is supplied with a DC voltage of not less than -1000 V. In the case of the reversal development, as in the foregoing embodiments, the good image transfer action can be obtained with +500 V although the pre-transfer exposure is not used, either. This difference can be explained as follows. In the case of the reversal development, the toner image present at a portion where the potential has been attenuated from the surface of the photosensitive drum, is transferred. By the provision of the pre-transfer exposure 70, the good image transfer action can be accomplished with the voltage of not more than 560 V (charge starting voltage) to the transfer roller 50. With this voltage, the photosensitive drum 1 is not electrically charged even if the voltage is applied to the transfer roller 50 when there is no image receiving material P in the transfer station. Therefore, the sequential control similar to that shown in Figure 4 can be employed. The pre-transfer exposure 70 is effected through the toner image, so that it is not possible to completely dissipate the surface potential of the photosensitive drum 1, but it is effective to make the image transfer easier.

In the foregoing embodiments, the contact charging device 20 is in the form of a conductive roller, but a conductive rubber blade 21 may be conducted to the photosensitive drum 1, as shown in Figure 6; and it may be in the form of a conductive brush 22 contact-

ed to the photosensitive drum 1, as shown in Figure 7.

As for another means for the pre-transfer processing to lower the voltage applied to the transfer roller 50 or the transfer belt 60 down to not more than the charge starting voltage, may be another means such as pre-transfer charging means or the like.

The material of the photosensitive member (image bearing member) is not limited to the OPC, but may be amorphous silicon, selenium, ZnO or the like. In addition, the image bearing member is not limited to the photosensitive ones, but may be a dielectric material drum. The image forming process is not limited to the Carlson process, but it may be a process including a step for uniformly charging the photosensitive member and a step for transferring the toner image onto the image receiving material. The image exposure means may be of a type wherein the original is stationary, while an optical system is moved, or in the form of a laser beam scanning exposure system, LED array control system, a liquid crystal shutter array control system or the like. Further, various process means disposed around the photosensitive drum for the image formation may be contained in a process cartridge as a unit.

As described in the foregoing, according to the present invention, when the image is transferred from the image bearing member to the image receiving member, a transfer member contacted to the image bearing member is supplied with a voltage less than the charge starting voltage with respect to the image bearing member, so that the sequential control for the voltage supply to the transfer member can have a larger latitude, whereby the sequential control for the charging, transferring, discharging operations or the like including the drive of the image bearing member, can be made simpler. The power source for the image transfer can have a lower voltage output, and, a good image without the transfer deviation can be obtained with lower production of ozone. Therefore, the size and the cost of the image forming apparatus of this kind can be minimized. Also, the structure of the image forming apparatus can be simple.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

Claims

1. An image forming apparatus, comprising:
an image bearing member (1);
image forming means (30,31,4) for forming an image on a surface of said image bearing member; and

transfer means (50,60) for transferring the image formed on said image bearing member (1) by said image forming means (2,4,30,31) onto an image receiving member (P), said transfer means (50,60) including a transfer member (50,60) and voltage application means (40) for applying a voltage to the transfer member (50,60) to transfer the image from said image bearing member (1) to the image receiving member (P);

which apparatus is characterised in that said transfer means (50,60) and said image bearing member (1) are arranged to be in contact and said voltage application means (40) is operable, at least during image transfer action, to apply a voltage to said transfer member (50,60) which is lower than that minimum DC voltage of said transfer member (50,60) for which charging of the surface of said image bearing member (1) would occur if no image receiving member (P) were located between the respective surfaces of said transfer member (50,60) and said image bearing member (1).

2. An apparatus according to claim 1, wherein the transfer member includes a rotatable roller (50).
3. An apparatus according to claim 1, wherein said transfer member includes a rotatable belt (60).
4. An apparatus according to claim 1, 2 or 3, wherein said image forming means (2,4,30,31) includes charging means (2,20) for charging said image bearing member (1), said charging means (2,20) including a charging member (2,20) and voltage application means (40) for applying a voltage to the charging member (2,20), said image forming means (2,4,30,31) further including means (30,31) for forming a latent image in accordance with image formation on the surface of said image bearing member (1) which has been electrically charged by said charging means (2,20) and developing means (4) for developing the latent image.
5. An apparatus according to claim 4, wherein said developing means (4) is operable to effect a reversal development to develop the latent image and said voltage applying means (40) is operable to apply a voltage to said transfer member (50,60) which is opposite in polarity to that voltage effected by said charging means (2,20).
6. An apparatus according to claim 4, wherein said developing means (4) is operable to effect a non-reversal development to develop the latent image, said apparatus further comprising discharging means (70), disposed between said developing means and said transfer means (50), for elec-



ed to the photosensitive drum 1, as shown in Figure 7.

As for another means for the pre-transfer processing to lower the voltage applied to the transfer roller 50 or the transfer belt 60 down to not more than the charge starting voltage, may be another means such as pre-transfer charging means or the like.

The material of the photosensitive member (image bearing member) is not limited to the OPC, but may be amorphous silicon, selenium, ZnO or the like. In addition, the image bearing member is not limited to the photosensitive ones, but may be a dielectric material drum. The image forming process is not limited to the Carlson process, but it may be a process including a step for uniformly charging the photosensitive member and a step for transferring the toner image onto the image receiving material. The image exposure means may be of a type wherein the original is stationary, while an optical system is moved, or in the form of a laser beam scanning exposure system, LED array control system, a liquid crystal shutter array control system or the like. Further, various process means disposed around the photosensitive drum for the image formation may be contained in a process cartridge as a unit.

As described in the foregoing, according to the present invention, when the image is transferred from the image bearing member to the image receiving member, a transfer member contacted to the image bearing member is supplied with a voltage less than the charge starting voltage with respect to the image bearing member, so that the sequential control for the voltage supply to the transfer member can have a larger latitude, whereby the sequential control for the charging, transferring, discharging operations or the like including the drive of the image bearing member, can be made simpler. The power source for the image transfer can have a lower voltage output, and, a good image without the transfer deviation can be obtained with lower production of ozone. Therefore, the size and the cost of the image forming apparatus of this kind can be minimized. Also, the structure of the image forming apparatus can be simple.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

Claims

1. An image forming apparatus, comprising:
an image bearing member (1);
image forming means (30,31,4) for forming an image on a surface of said image bearing member; and

transfer means (50,60) for transferring the image formed on said image bearing member (1) by said image forming means (2,4,30,31) onto an image receiving member (P), said transfer means (50,60) including a transfer member (50,60) and voltage application means (40) for applying a voltage to the transfer member (50,60) to transfer the image from said image bearing member (1) to the image receiving member (P);

which apparatus is characterised in that said transfer means (50,60) and said image bearing member (1) are arranged to be in contact and said voltage application means (40) is operable, at least during image transfer action, to apply a voltage to said transfer member (50,60) which is lower than that minimum DC voltage of said transfer member (50,60) for which charging of the surface of said image bearing member (1) would occur if no image receiving member (P) were located between the respective surfaces of said transfer member (50,60) and said image bearing member (1).

2. An apparatus according to claim 1, wherein the transfer member includes a rotatable roller (50).
3. An apparatus according to claim 1, wherein said transfer member includes a rotatable belt (60).
4. An apparatus according to claim 1, 2 or 3, wherein said image forming means (2,4,30,31) includes charging means (2,20) for charging said image bearing member (1), said charging means (2,20) including a charging member (2,20) and voltage application means (40) for applying a voltage to the charging member (2,20), said image forming means (2,4,30,31) further including means (30,31) for forming a latent image in accordance with image formation on the surface of said image bearing member (1) which has been electrically charged by said charging means (2,20) and developing means (4) for developing the latent image.
5. An apparatus according to claim 4, wherein said developing means (4) is operable to effect a reversal development to develop the latent image and said voltage applying means (40) is operable to apply a voltage to said transfer member (50,60) which is opposite in polarity to that voltage effected by said charging means (2,20).
6. An apparatus according to claim 4, wherein said developing means (4) is operable to effect a non-reversal development to develop the latent image, said apparatus further comprising discharging means (70), disposed between said developing means and said transfer means (50), for elec-



- trically discharging said image bearing member (1) prior to transfer.
7. An apparatus according to claim 4, 5 or 6, wherein the voltage application means (40) for said charging member (20) and the voltage application means (40) for the transfer member (50,60) are operable synchronously.
 8. An apparatus according to any of claims 4 to 7, wherein said charging member (20) is arranged to contact said image bearing member (1) to charge it.
 9. An apparatus according to claim 8, wherein said voltage application means (40) is operable to apply to said charging member (20) both a DC voltage and a superimposed AC voltage.
 10. An apparatus according to any of claims 7 to 9, wherein the voltage application means (40) for the charging member (20) and the voltage application means (40) for the transfer member (50,60) include a common voltage source.
 11. An apparatus according to claim 8, wherein said charging member (20) is operable to function as a discharging member for electrically discharging said image bearing member (1).
 12. An apparatus according to claim 11, wherein said discharging member (20) is operable to effect a discharging operation for the surface of said image bearing member (1) at least for one complete rotation of said image bearing member (1) after completion of image formation, and during which an AC voltage is applied by the voltage application means (40) for the charging member (20).
 13. An apparatus according to claim 12, wherein the voltage application means (40) for applying AC voltage to the charging member (20) and the voltage application means (40) for applying voltage to the transfer member (50,60) are operable synchronously, and wherein the voltage applied to the transfer member (50,60) is a rectified voltage produced from said AC voltage.
 14. An apparatus according to claim 1, wherein the image bearing member (1) is movable and images can be formed on it repetitively, wherein the apparatus has a charging member (20) supplied with a cyclically varying AC voltage or with a combination of an AC and a DC voltage to charge the image bearing member (1) prior to production of an image and simultaneously to destroy the charge pattern of any previous image.
 15. An apparatus according to any one of the preceding claims, wherein the transfer member (50,60), at least in part, is of a conductive rubber.
 16. An apparatus according to any one of the preceding claims, wherein the transfer member (50,60) is electrically conductive.
 17. An apparatus according to claim 16, wherein the transfer member (50,60) has a resistance of 10^2 – 10^8 ohm per 1 cm^2 of its surface.
 18. An apparatus according to any one of the preceding claims, wherein said image bearing member (1) includes an organic photoconductor.
 19. A method of image forming including the steps of:
 - pre-charging the surface of an image bearing member (1);
 - exposing an area of the surface of said image bearing member (1) to produce an electrostatic image;
 - developing said electrostatic image to produce a developed image;
 - feeding an image receiving member (P) between said image bearing member (1) and a transfer member (50,60); and
 - applying a voltage to said transfer member (50,60) to cause transfer of said developed image from said image bearing member (1) onto said image receiving member (P);
 - which method is characterised in that:
 - said image bearing member (1) is arranged to be in contact with said transfer member (50,60) and in supplying said voltage to said transfer member (50,60), the voltage applied is maintained less than a minimum DC voltage of said transfer member (50,60) for which charging of the surface of said image bearing member (1) would occur if no image receiving member (P) were passing between the respective surfaces of said transfer member (50,60) and said image bearing member (1).
 20. A method as claimed in claim 19 wherein:
 - both a DC voltage and an AC voltage are applied for pre-charging the surface of said image bearing member (1); and
 - thereafter application of said DC voltage is ceased while application of said AC voltage is maintained, for at least a full rotation of said image bearing member (1), to allow a full discharge of said surface.
 21. A method as claimed in claim 20, wherein application of voltage to said transfer member (50,60) is ceased from a time defined in an interval of time (T_2) starting with cessation of the applica-



tion of said DC voltage and ending with cessation of said AC voltage.

22. A method as claimed in claim 21, wherein said AC voltage, and said voltage applied to said transfer member (50,60), cease simultaneously.

23. A method as claimed in claim 22, wherein said voltage applied to said transfer member (50,60) is produced by rectifying said AC voltage.

24. A method as claimed in any of claims 19 to 23, wherein:

a non-reversed developed image is produced; and

the developed image is exposed to partially discharge the surface of said image bearing member (1) to ease image transfer performed thereafter.

25. A method as claimed in any of claims 19 to 23, wherein:

a reversed developed image is produced; and said developed image is transferred without any exposure and consequent discharge being performed between development and transfer.

Patentansprüche

1. Bilderzeugungsgesamt mit einem Bildträgermaterial (1), einer Bilderzeugungseinrichtung (30, 31, 4) zum Erzeugen eines Bildes auf einer Oberfläche des Bildträgermaterials und einer Übertragungseinrichtung (50, 60) zum Übertragen des auf dem Bildträgermaterial (1) durch die Bilderzeugungseinrichtung (2, 4, 30, 31) erzeugten Bildes auf ein Bildempfangsmaterial (P), wobei die Übertragungseinrichtung (50, 60) ein Übertragungsteil (50, 60) und eine Spannungsanlage-Einrichtung (40) zum Anlegen einer Spannung an das Übertragungsteil (50, 60) enthält, damit das Bild von dem Bildträgermaterial (1) auf das Bildempfangsmaterial (P) übertragen wird, dadurch gekennzeichnet, daß die Übertragungseinrichtung (50, 60) und das Bildträgermaterial (1) derart angeordnet sind, daß sie sich berühren, und die Spannungsanlage-Einrichtung (40) zumindest während des Bildübertragungsvorgangs zum Anlegen einer Spannung an das Übertragungsteil (50, 60) betreibbar ist, die niedriger als die Mindest-Gleichspannung des Übertragungsteils (50, 60) ist, bei der das Laden der Oberfläche des Bildträgermaterials (1) auftreten würde, wenn sich kein Bildempfangsmaterial (P) zwischen den jeweili-

gen Oberflächen des Übertragungsteils (50, 60) und des Bildträgermaterials (1) befände.

2. Gerät nach Anspruch 1, dadurch gekennzeichnet, daß das Übertragungsteil eine drehbare Walze (50) enthält.

3. Gerät nach Anspruch 1, dadurch gekennzeichnet, daß das Übertragungsteil ein drehbares Band (60) enthält.

4. Gerät nach Anspruch 1, 2 oder 3, wobei die Bilderzeugungseinrichtung (2, 4, 30, 31) eine Ladeeinrichtung (2, 20) zum Laden des Bildträgermaterials (1) enthält, wobei die Ladeeinrichtung (2, 20) ein Ladeteil (2, 20) und eine Spannungsanlage-Einrichtung (40) zum Anlegen einer Spannung an das Ladeteil (2, 20) enthält, wobei die Bilderzeugungseinrichtung (2, 4, 30, 31) weiterhin eine Einrichtung (30, 31) zum Erzeugen eines Latentbildes gemäß der Bilderzeugung auf der Oberfläche des Bildträgermaterials (1), das durch die Ladeeinrichtung (2, 20) elektrisch aufgeladen worden ist, und eine Entwicklungseinrichtung (4) zum Entwickeln des Latentbildes enthält.

5. Gerät nach Anspruch 4, wobei die Entwicklungseinrichtung (4) derart betreibbar ist, daß sie eine Umkehrentwicklung zum Entwickeln des Latentbildes ausführt, und die Spannungsanlage-Einrichtung (40) derart betreibbar ist, daß sie eine Spannung an das Übertragungsteil (50, 60) anlegt, die eine entgegengesetzte Polarität zu der durch die Ladeeinrichtung (2, 20) bewirkten Spannung hat.

6. Gerät nach Anspruch 4, wobei die Entwicklungseinrichtung (4) derart betreibbar ist, daß sie eine Nicht-Umkehrentwicklung zum Entwickeln des Latentbildes ausführt, und das Gerät außerdem eine zwischen der Entwicklungseinrichtung und der Übertragungseinrichtung (50) angeordnete Entladeeinrichtung (70) zum elektrischen Entladen des Bildträgermaterials (1) vor der Übertragung aufweist.

7. Gerät nach Anspruch 4, 5 oder 6, wobei die Spannungsanlage-Einrichtung (40) für das Ladeteil (20) und die Spannungsanlage-Einrichtung (40) für das Übertragungsteil (50, 60) synchron betreibbar sind.

8. Gerät nach irgendeinem der Ansprüche 4 bis 7, wobei das Ladeteil (20) derart angeordnet ist, daß es das Bildträgermaterial (1) zu dessen Aufladung berührt.



9. Gerät nach Anspruch 8, wobei die Spannungsanlege-Einrichtung (40) derart betreibbar ist, daß sie sowohl eine Gleichspannung als auch eine überlagerte Wechselspannung an das Ladeteil (20) anlegt. 5
10. Gerät nach irgendeinem der Ansprüche 7 bis 9, wobei die Spannungsanlege-Einrichtung (40) für das Ladeteil (2, 20) und die Spannungsanlege-Einrichtung (40) für das Übertragungsteil (50, 60) eine gemeinsame Spannungsquelle enthalten. 10
11. Gerät nach Anspruch 8, wobei das Ladeteil (20) derart betreibbar ist, daß es als Entladeteil zum elektrischen Entladen des Bildträgermaterials (1) arbeitet. 15
12. Gerät nach Anspruch 11, wobei das Entladeteil (20) derart betreibbar ist, daß es einen Entladevorgang für die Oberfläche des Bildträgermaterials (1) zumindest für eine vollständige Drehung des Bildträgermaterials (1) nach Abschluß der Bilderzeugung ausführt, während von der Spannungsanlege-Einrichtung (40) eine Wechselspannung an das Ladeteil (20) angelegt wird. 20
13. Gerät nach Anspruch 12, wobei die Spannungsanlege-Einrichtung (40) zum Anlegen einer Wechselspannung an das Ladeteil (20) und die Spannungsanlege-Einrichtung (40) zum Anlegen einer Spannung an das Übertragungsteil (50, 60) synchron betreibbar sind, wobei die an das Übertragungsteil (50, 60) angelegte Spannung eine gleichgerichtete Spannung ist, die aus der Wechselspannung erzeugt wurde. 25
14. Gerät nach Anspruch 1, dadurch gekennzeichnet, daß das Bildträgermaterial (1) bewegbar ist und Bilder auf ihm wiederholt erzeugt werden können und das Gerät ein Ladeteil (20) aufweist, an das eine sich zyklisch verändernde Wechselspannung oder eine Kombination aus einer Wechsel- und einer Gleichspannung angelegt wird, damit das Bildträgermaterial (1) vor der Bilderzeugung aufgeladen wird und zugleich das Lademuster irgendeines vorangegangenen Bildes zerstört wird. 30
15. Gerät nach irgendeinem der vorangehenden Ansprüche, wobei das Übertragungsteil (50, 60) zumindest zu einem Teil aus einem Leitgummi besteht. 35
16. Gerät nach irgendeinem der vorangehenden Ansprüche, wobei das Übertragungsteil (50, 60) elektrisch leitend ist. 40
17. Gerät nach Anspruch 16, wobei das Übertragungsteil (50, 60) einen Widerstand von 10^2 bis $10^8 \Omega$ pro cm^2 seiner Oberfläche hat. 45
18. Gerät nach irgendeinem der vorangehenden Ansprüche, wobei das Bildträgermaterial (1) einen organischen Photoleiter enthält. 50
19. Verfahren der Bilderzeugung, das folgende Schritte enthält:
Vorladen der Oberfläche eines Bildträgermaterials (1),
Belichten eines Bereichs der Oberfläche des Bildträgermaterials (1) zum Erzeugen eines elektrostatischen Bildes,
Entwickeln des elektrostatischen Bildes zu einem entwickelten Bild,
Zuführen eines Bildempfangsmaterials (P) zwischen das Bildträgermaterial (1) und ein Übertragungsteil (50, 60) und
Anlegen einer Spannung an das Übertragungsteil (50, 60) zum Auslösen der Übertragung des entwickelten Bildes von dem Bildträgermaterial (1) auf das Bildempfangsmaterial (P),
dadurch gekennzeichnet, daß
das Bildträgermaterial (1) derart angeordnet ist, daß es das Übertragungsteil (50, 60) berührt, und bei Anlegen der Spannung an das Übertragungsteil (50, 60) die angelegte Spannung niedriger als eine Mindest-Gleichspannung des Übertragungsteils (50, 60) gehalten wird, bei der das Laden der Oberfläche des Bildträgermaterials (1) auftreten würde, wenn kein Bildempfangsmaterial (P) zwischen den jeweiligen Oberflächen des Übertragungsteils (50, 60) und dem Bildträgermaterial (1) durchlaufen würde. 55
20. Verfahren nach Anspruch 19, dadurch gekennzeichnet, daß
sowohl eine Gleich- als auch eine Wechselspannung zum Vorladen der Oberfläche des Bildträgermaterials (1) angelegt werden und danach das Anlegen der Gleichspannung beendet wird, während das Anlegen der Wechselspannung zumindest für eine volle Umdrehung des Bildträgermaterials (1) zum vollständigen Entladen der Oberfläche aufrecht erhalten wird. 60
21. Verfahren nach Anspruch 20, wobei das Anlegen der Spannung an das Übertragungsteil (50, 60) von einem Zeitpunkt an eingestellt wird, der in einem Zeitintervall (T_2) liegt, das mit Einstellung des Anlegens der Gleichspannung beginnt und mit Einstellung des Anlegens der Wechselspannung endet. 65
22. Verfahren nach Anspruch 21, wobei die Wechselspannung und die an das Übertragungsteil (50, 60) angelegte Spannung zugleich aufhören. 70



23. Verfahren nach Anspruch 22, wobei die an das Übertragungsteil (50, 60) angelegte Spannung durch Gleichrichten der Wechselfspannung erzeugt wird.

24. Verfahren nach irgendeinem der Ansprüche 19 bis 23, wobei:
ein nicht-umkehrentwickeltes Bild erzeugt und das entwickelte Bild zum teilweisen Entladen der Oberfläche des Bildträgermaterials (1) zum Erleichtern der danach durchgeführten Bildübertragung belichtet wird.

25. Verfahren nach irgendeinem der Ansprüche 19 bis 23, wobei:
ein umkehrentwickeltes Bild erzeugt und das entwickelte Bild ohne irgendeine Belichtung und nachfolgende Entladung zwischen Entwicklung und Übertragung übertragen wird.

Revendications

1. Appareil de formation d'images, comportant :

un élément (1) porteur d'image ;
des moyens (30, 31, 4) de formation d'image destinés à former une image sur une surface dudit élément porteur d'image ; et

des moyens de report (50, 60) destinés à reporter l'image formée sur ledit élément (1) porteur d'image par lesdits moyens (2, 4, 30, 31) de formation d'image sur un élément (P) de réception d'image, lesdits moyens de report (50, 60) comprenant un élément de report (50, 60) et des moyens (40) d'application de tension destinés à appliquer une tension à l'élément de report (50, 60) pour reporter l'image dudit élément (1) porteur d'image sur l'élément (P) de réception d'image ;

lequel appareil est caractérisé en ce que lesdits moyens de report (50, 60) et ledit élément (1) porteur d'image sont agencés de façon à être en contact, et lesdits moyens (40) d'application de tension peuvent être mis en oeuvre, au moins durant une action de report d'image, de façon à appliquer une tension audit élément (50, 60) de report qui est inférieure à la tension continue minimale dudit élément (50, 60) de report pour laquelle une charge de la surface dudit élément (1) porteur d'image se produirait si aucun élément (P) de réception d'image ne se trouvait entre les surfaces respectives dudit élément (50, 60) de report et dudit élément (1) porteur d'image.

2. Appareil selon la revendication 1, dans lequel l'élément de report comprend un rouleau tournant (50).

3. Appareil selon la revendication 1, dans lequel ledit élément de report comprend une bande tournante (60).

4. Appareil selon la revendication 1, 2 ou 3, dans lequel lesdits moyens (2, 4, 30, 31) de formation d'image comprennent des moyens (2, 20) de charge destinés à charger ledit élément (1) porteur d'image, lesdits moyens (2, 20) de charge comprenant un élément de charge (2, 20) et des moyens (40) d'application de tension destinés à appliquer une tension à l'élément de charge (2, 20), lesdits moyens (2, 4, 30, 31) de formation d'image comprenant en outre des moyens (30, 31) destinés à former une image latente conformément à la formation d'une image sur la surface dudit élément (1) porteur d'image qui a été chargée électriquement par lesdits moyens (2, 20) de charge, et des moyens (4) de développement destinés à développer l'image latente.

5. Appareil selon la revendication 4, dans lequel lesdits moyens (4) de développement peuvent être mis en oeuvre pour effectuer un développement inverse afin de développer une image latente et lesdits moyens (40) d'application de tension peuvent être mis en oeuvre pour appliquer une tension audit élément (50, 60) de report qui est opposée en polarité à la tension établie par lesdits moyens (2, 20) de charge.

6. Appareil selon la revendication 4, dans lequel lesdits moyens (4) de développement peuvent être mis en oeuvre pour effectuer un développement sans inversion afin de développer l'image latente, ledit appareil comportant en outre des moyens (70) de décharge, disposés entre lesdits moyens de développement et lesdits moyens (50) de report, pour décharger électriquement ledit élément (1) porteur d'image avant un report.

7. Appareil selon la revendication 4, 5 ou 6, dans lequel les moyens (40) d'application de tension pour ledit élément (20) de charge et lesdits moyens (40) d'application de tension pour l'élément (50, 60) de report peuvent être mis en oeuvre en synchronisme.

8. Appareil selon l'une quelconque des revendications 4 à 7, dans lequel ledit élément (20) de charge est agencé pour entrer en contact avec ledit élément (1) porteur d'image afin de le charger.

9. Appareil selon la revendication 8, dans lequel lesdits moyens (40) d'application de tension peuvent être mis en action pour appliquer audit élément (20) de charge à la fois une tension continue et une tension alternative superposée.



10. Appareil selon l'une quelconque des revendications 7 à 9, dans lequel les moyens (40) d'application de tension pour l'élément de charge (2, 20) et les moyens (40) d'application de tension pour l'élément de report (50, 60) comprennent une source commune de tension.
11. Appareil selon la revendication 8, dans lequel ledit élément (20) de charge peut être mis en action pour fonctionner à la manière d'un élément de décharge pour décharger électriquement ledit élément (1) porteur d'image.
12. Appareil selon la revendication 11, dans lequel ledit élément (20) de décharge peut être mis en action pour effectuer une opération de décharge pour la surface dudit élément (1) porteur d'image au moins pendant un tour complet dudit élément (1) porteur d'image après l'achèvement de la formation d'une image et pendant lequel une tension alternative est appliquée par les moyens (40) d'application de tension pour l'élément (20) de charge.
13. Appareil selon la revendication 12, dans lequel les moyens (40) d'application de tension pour appliquer une tension alternative à l'élément (20) de charge et les moyens (40) d'application de tension pour appliquer une tension à l'élément (50, 60) de report peuvent être mis en action en synchronisme, et dans lequel la tension appliquée à l'élément (50, 60) de report est une tension redressée produite à partir de ladite tension alternative.
14. Appareil selon la revendication 1, dans lequel l'élément (1) porteur d'image est mobile et des images peuvent être formées sur celui-ci de façon répétitive, dans lequel l'appareil comporte un élément (20) de charge alimenté en une tension alternative variant cycliquement ou en une combinaison d'une tension alternative et d'une tension continue pour charger l'élément (1) porteur d'image avant la production d'une image et pour détruire simultanément la configuration de charge de toute image précédente.
15. Appareil selon l'une quelconque des revendications précédentes, dans lequel l'élément (50, 60) de report, au moins en partie, est en caoutchouc conducteur.
16. Appareil selon l'une quelconque des revendications précédentes, dans lequel l'élément (50, 60) de report est électriquement conducteur.
17. Appareil selon la revendication 16, dans lequel l'élément (50, 60) de report présente une résistance de 10^2 - 10^8 ohms par cm^2 de sa surface.
18. Appareil selon l'une quelconque des revendications précédentes, dans lequel ledit élément (1) porteur d'image comprend un photoconducteur organique.
19. Procédé de formation d'images comprenant les étapes qui consistent :
- à précharger la surface d'un élément (1) porteur d'image ;
 - à exposer une zone de la surface dudit élément (1) porteur d'image pour produire une image électrostatique ;
 - à développer ladite image électrostatique pour produire une image développée ;
 - à faire avancer un élément (P) de réception d'image entre ledit élément (1) porteur d'image et l'élément de report (50, 60) ; et
 - à appliquer une tension audit élément (50, 60) de report pour provoquer le report de ladite image développée dudit élément (1) porteur d'image sur ledit élément (P) de réception d'image ;
- lequel procédé est caractérisé en ce que :
- ledit élément (1) porteur d'image est agencé de façon à être en contact avec ledit élément (50, 60) de report et, dans l'application de ladite tension audit élément (50, 60) de report, la tension appliquée est maintenue inférieure à une tension continue minimale dudit élément (50, 60) de report pour laquelle une charge de la surface dudit élément (1) porteur d'image se produirait si aucun élément (P) de réception d'image ne passait entre les surfaces respectives dudit élément (50, 60) de report et dudit élément (1) porteur d'image.
20. Procédé selon la revendication 19, dans lequel :
- à la fois une tension continue et une tension alternative sont appliquées pour précharger la surface dudit élément (1) porteur d'image ; et
 - ensuite, l'application de ladite tension continue est arrêtée tandis que l'application de ladite tension alternative est maintenue, pendant au moins une rotation complète dudit élément (1) porteur d'image, pour permettre une décharge complète de ladite surface.
21. Procédé selon la revendication 20, dans lequel l'application d'une tension audit élément (50, 60) de report est arrêtée à partir d'un temps défini dans un intervalle de temps (T2) commençant avec la cessation de l'application de ladite tension continue et finissant avec la cessation de ladite tension alternative.
22. Procédé selon la revendication 21, dans lequel



ladite tension alternative et ladite tension appliquée audit élément (50, 60) de report cessent simultanément.

23. Procédé selon la revendication 22, dans lequel ladite tension appliquée audit élément (50, 60) de report est produite par le redressement de ladite tension alternative. 5

24. Procédé selon l'une quelconque des revendications 19 à 23, dans lequel :
une image développée non inversée est produite ; et 10

l'image développée est exposée pour décharger partiellement la surface dudit élément (1) porteur d'image afin de faciliter le report d'une image effectué ensuite. 15

25. Procédé selon l'une quelconque des revendications 19 à 23, dans lequel : 20

une image développée inversée est produite ; et ladite image développée est reportée sans exposition et décharge consécutive quelconques effectuées entre le développement et le report. 25

30

35

40

45

50

55

15