SUBSURFACE SAFETY VALVE FLAPPER

TECHNICAL FIELD

[0001] This invention relates to subsurface safety valves for deployment in hydrocarbon producing wells, particularly subsurface safety valves comprising flappers.

BACKGROUND

[0002] Typically, a hydrocarbon producing well will include a subsurface safety valve to seal off a section of production tubing in the event of an emergency, e.g., damage to the well head. This type of valve is usually activated from the surface using a hydraulic control system with control lines that run from the surface to the subsurface safety valve. The valve typically comprises a valve housing and a closure member used to seal the production tubing in the well bore. The closure member typically used is a flapper which is hingedly attached to the valve housing and rotatable throughout an arc of ninety degrees between an open and closed position. The control system uses hydraulic pressure to move a hollow tube, usually referred to as a flowtube, downwardly against the flapper and a return spring, thereby disposing the flapper in an open position such that hydrocarbons may flow in the production tubing. Once, the hydraulic pressure is lost in the system, the flow tube moves upwardly thereby allowing the return spring to bias the flapper in a closed position effectively sealing off from the surface the flow of hydrocarbons in the production tubing.

[0003] Once the flapper is in the closed position, formation pressure accumulates on the upstream side of the flapper. This increase in pressure causes a high pressure differential across the flapper making the opening of the flapper difficult. One manner to solve this problem is to incorporate an equalizing or bleed valve assembly in the flapper. Such an equalizing valve assembly typically comprises a plunger or like member, a spring, and hardware to fasten the spring and plunger to the flapper. The plunger, typically biased against the flapper by the spring, is displaced to allow the pressure differential to dissipate across the flapper thereby reducing the difficulty in disposing the flapper in an open position.

SUMMARY OF THE INVENTION

[0004] It now has become apparent that a need exists for a durable equalizing valve assembly which can withstand the extreme forces generated by the and on the flapper when it slams closed during use. The flapper is commonly exposed to extreme forces during closing. Those forces may damage the equalizing valve assembly components, especially the hardware used to fasten the equalizing valve assembly to the flapper.

[0005] The present invention is deemed to meet the foregoing need, amongst others, by providing in at least one embodiment, a flapper comprising a durable and efficient flapper valve assembly capable of dissipating a pressure differential across the flapper. In at least one embodiment of the present invention, the flapper valve assembly is designed to withstand high external forces created by the slamming of the flapper when closing by requiring no additional hardware to fasten the components of the flapper valve assembly to the flapper.

[0006] One embodiment of the present invention provides a flapper for use as a component of a safety valve designed for deployment in a well bore having well bore fluids. The flapper comprises a flapper body forming a flapper valve bore therethrough. The flapper body further forms a groove proximate to the flapper bore. The flapper also comprises a plunger member sized and configured to be received in the flapper valve bore, the plunger member comprising a first end portion and a second end portion. Additionally, the flapper comprises a leaf spring comprising a primary end portion and a secondary end portion, the primary end portion of the leaf spring detachably attached to the second end portion of the plunger member and unattached to the flapper body and the secondary end portion of the leaf spring being sized and configured to be received and retained in the groove and to bias the plunger member into the flapper valve bore. Forces exerted on the flapper body when rotating between an open state and a closed state during use of the safety valve urge at least a portion of the leaf spring into the groove. In this way, the components of the flapper maintain their structural relationship with one another despite being exposed to the forces associated with the repeated opening and closing of the safety valve during operation.

[0007] Another embodiment of this invention is a method for equalizing differential pressure across a safety valve deployed in a well bore having well bore fluids. The method comprises deploying the safety valve in the well bore. The safety valve comprises a flapper,

wherein the flapper comprises a flapper body forming a flapper valve bore therethrough. The flapper body further forms a groove proximate to the flapper bore. The method further comprises biasing a plunger member in the flapper valve bore by coupling the plunger member to a leaf spring comprising a primary end portion and a secondary end portion. The plunger member is sized and configured to be received in the flapper valve bore and further comprises a first end portion and a second end portion. The primary end portion of the leaf spring is coupled to the second end portion of the plunger member. The secondary end portion of the leaf spring is sized and configured to be received and retained in the groove. The method further comprises displacing the plunger member to allow fluid to flow from a portion of the well bore having higher pressure to a portion of the well bore having lower pressure. Displacing the plunger member causes the primary end portion of the leaf spring to rotate about the latitudinal axis of the flapper, whereby the pressure differential across the safety valve is equalized.

[0008] Still yet, another embodiment of the present invention provides a method for retaining a flapper valve in a flapper in a safety valve designed for deployment in a well bore. The method comprises providing a flapper valve bore in the flapper. The flapper valve bore extends through the flapper and the flapper further defines a groove extending distally from the flapper valve bore. The method further comprises biasing a plunger member into the flapper valve bore by coupling the plunger member to a leaf spring. The leaf spring is disposed in the groove and extends distally from the plunger member. The leaf spring is urged into the groove when forces are exerted on the flapper and thereby retains the plunger member in the flapper valve bore.

[0009] These and other features of this invention will be still further apparent from the ensuing description, drawings, and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] Fig. 1 is a cross sectional view of a subsurface safety valve, wherein the flapper is in a closed state consistent with one embodiment of the present invention.

[0011] Fig. 2 is a cross sectional view of a subsurface safety valve, wherein the flapper is in a open state consistent with one embodiment of the present invention.

[0012] Fig. 3 is a perspective view of a flapper consistent with one embodiment of the present invention.

[0013] Fig. 4 is a cross sectional view of a flapper body and a flapper valve consistent with one embodiment of the present invention.

[0014] Fig. 5 is a top plan view of a flapper consistent with one embodiment of the present invention.

[0015] Fig. 6 is a perspective view of a plunger member comprising a plurality of fluid pathways consistent with one embodiment of the present invention.

[0016] Fig. 7 is a cross-sectional view of a plunger member comprising a plunger member bore and a plurality of fluid pathways consistent with one embodiment of the present invention.

[0017] Fig. 8 is a top plan view of a plunger member comprising a plunger member bore and a plurality of fluid pathways consistent with one embodiment of the present invention

[0018] In each of the above figures, like numerals are used to refer to like or functionally like parts among the several figures.

FURTHER DETAILED DESCRIPTION OF THE INVENTION

[0019] Illustrative embodiments of the invention are described below as they might be employed in the construction and use of a subsurface safety valve flapper and methods according to the present invention. In the interest of clarity, not all features of an actual implementation are described in this specification. It will be of course appreciated that in the development of such an actual embodiment, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure.

[0020] Turning now to the figures, Figs. 1 and 2 illustrate a subsurface safety valve **10** consistent with at least one embodiment of the present invention. When deployed in a well bore (not shown), subsurface safety valve **10** is commonly incorporated into the production

tubing (not shown). Subsurface safety valve **10** includes a valve housing **12** comprising a first end portion **14** and a second end portion **16**. First end portion **14** of the housing **12** is threaded for attachment to an adjacent string of production tubing (not shown) and second end portion **16** of the housing **12** is threaded for attachment with an adjacent section of production tubing (not shown). The valve housing **12** further defines a bore **18** for fluid flow there through. The valve housing **12** further includes an enlarged central portion **20**, wherein an annular valve seat **22** is secured within the central portion **20**. As illustrated in Fig. 1, the subsurface safety valve **10** would function to inhibit fluid flow from the direction of the second end portion **16** to the first end portion **14** of the valve housing **12**. Thus, the second end portion **16** will be considered upstream to the first end portion **14**.

[0021] As illustrated in Figs. 1 and 2, subsurface safety valve **10** further comprises a flapper **24**, wherein the flapper **24** is hingedly secured to the valve seat **22** by hinge pin **26**. The flapper **24** may rotate about the hinge pin **26** in approximately a 90° range of motion, between an open state (shown in Fig. 2) and a closed state, as shown in Fig. 1. In the closed state, flapper **24** is in contact and seated on the valve seat **22**, thereby forming a sealing relationship with the valve seat **22**. A torsion spring (not shown) biases the flapper **24** in a closed state, as shown in Fig. 2. With the flapper **24** and valve seat **22** forming the sealing relationship as shown in Fig. 1, the subsurface safety valve **10** inhibits fluid flow from the upstream portion of the well bore to the downstream portion of the well bore. As illustrated, the flapper **24** further comprises a pressure equalizing assembly **28**, the structure and function of which will be discussed further below.

[0022] An actuation member **30**, which may be a conventional actuation tube or sleeve, is disposed within the housing bore **18** downstream of the valve seat **22** and may be shifted along the longitudinal axis of the housing bore **18**, typically by means of hydraulic pressure or shifting tools; however, actuation member **30** may be shifted by other means known in the art. Actuation member **30** is shifted between an upper position (as shown in Fig. 1) and a lower position (as shown in Fig. 2). Actuation member **30** comprises a lower end portion **32**, the lower end portion **32** may be substantially flat. Actuation member **30** is shifted to allow the flapper **24** to rotate between open and closed states depending on the position of the actuation member **30**.

[0023] Turning now to Figs. 3 through 5, the flapper **24** and pressure equalizing assembly **28** may be better understood. Flapper **24** comprises a flapper body **34**, wherein the flapper body **34** is curved. The flapper body **34** is a generally saddle-shaped disc, wherein the flapper body **34** is arcuately curved to provide a curvature that approximately matches the interior surface of the housing **12**. As shown in Figs. 3 and 4, the flapper body **34** arcuately curves away from a latitudinal axis of the flapper body **34** when viewed from the upstream face **38** of the flapper **24**. The flapper body **34** is curved in order to allow for a smaller outer diameter of the valve housing **12** while increasing the surface sealing contact between the flapper body **34** and the valve seat **22**. The flapper body **24** further forms a rounded radial perimeter **36** that is sized and configured to retain a sealing relationship with the valve seat **22** when the flapper **24** is in contact with the valve seat **22**. The flapper body **34** comprises an upstream face **38** and a downstream face **40**, the upstream face **38** receiving the fluid pressure from the upstream portion of the well bore when the flapper **24** is in a closed state. The downstream face **40** comprises contact portions (not shown), the contact portions sized and configured to be contacted by the actuation member **30** to facilitate the rotation of the flapper **24** between states. The contact portions may be substantially flat so that the contact portions may contact the lower end portion **32** of the actuation member **30** in a mating fashion. The flapper body **34** further forms at least one hinge component **42**, illustrated as a hinge, sized and configured for hinged attachment to the safety valve **10**, wherein the hinged component **42** extends radially from the flapper body.

[0024] As illustrated in Figs. 3 through 5, flapper body **34** further forms a flapper valve bore **44** therethrough, the location of the flapper valve bore **44** being within the contact portion of the downstream face **40** of the flapper **24**. Flapper body **34** further forms a groove **46** proximate to the flapper bore **44** in the upstream face **38** of the flapper **24**. Groove **46** extends distally from the flapper valve bore **44** toward the portion of the flapper body **34** directly opposing the hinged component **42**.

[0025] Flapper **24** further comprises a plunger member **48**, illustrated in Figs. 6 through 8 as a plunger, is sized and configured to be received in the flapper valve bore **44**. Plunger **48** is further sized and configured to shift within the flapper valve bore **44**; however, plunger **48** forms a sealing relationship with the flapper valve bore **44** when disposed within the valve

bore **44**. Plunger **48** comprises a first end portion **50** and a second end portion **52**, wherein the first end portion **50** of the plunger **48** protrudes above the downstream face **40** of the flapper **24**. The first end portion **50** of the plunger **48** may be substantially flat so that the substantially flat lower end portion **32** of the actuation member **30** may be in a mating fashion with the first end portion **50** of the plunger **48** when actuation member **30** is shifted and placed in contact with the first end portion **50** of the plunger **48**.

[0026] Plunger **48** further forms a plunger member bore **54** therethrough, as illustrated as a plunger bore in Figs. 7 and 8. Plunger bore **54** comprises a first end **56** and a second end **58**, wherein the first end **56** is located at the first end portion **50** of the plunger **48** and is in fluid communication with the upstream portion of the well bore. Plunger **48**, as illustrated, is cylindrical in form and further comprises a continuous sidewall **60**. Plunger **48** further forms at least one fluid pathway **62** in fluid communication with the plunger member bore **54**. Fluid pathway **62** extends from the plunger bore **54** to the sidewall **60** of the plunger **48**. Plunger bore **54** and fluid pathway **62** provide a fluid passageway **64** through the flapper valve bore **54** when the plunger **48** is disposed in the flapper valve bore **44** but is sufficiently displaced from the flapper valve bore **44** so that the fluid passageway **64** is in fluid communication with both an upstream side of the flapper **24** and a downstream side of the flapper **24**.

[0027] As shown in Figs. 3 through 5, flapper **24** further comprises a leaf spring **66**. As illustrated, leaf spring **66** extends distally from the flapper valve bore **44**. Leaf spring **66** comprises a primary end portion **68** and a secondary end portion **70**. The primary end portion **68** of the leaf spring **66** is detachably attached to the second end portion **52** of the plunger **48** and unattached to the flapper body **34** and the secondary end portion **70** of the leaf spring **66** is sized and configured to be received and retained in the groove **46** and to bias the plunger **48** into the flapper valve bore **44**. The primary end portion **68** of the leaf spring **66** may further define a leaf spring aperture **72**, wherein the second end portion **52** of the plunger **48** may be inserted through the leaf spring aperture **72** and mechanically coupled to the leaf spring **66**. The leaf spring **66** is received and retained in the groove **46** such that forces exerted on the flapper body **34** when rotating between an open state and a closed state during use of the safety valve **10** urge at least a portion of the leaf spring **66** into the groove **46**.

[0028] Plunger **48** is movably disposed within the flapper valve bore **44** between an open

position and a closed position. In the open position, fluid may flow through the fluid passageway **64** from the upstream portion of the well bore to the downstream portion of the well bore. In its normal state, plunger **48** is biased in the closed position by the leaf spring **66** such that the plunger **48** creates a sealing relationship with the flapper valve bore **44** so that fluid is unable to flow through the fluid passageway **64**. In the closed position, first end portion **50** of the plunger **48** extends above the contact portion (not shown) of the flapper body **34**.

[0029] In operation, the subsurface safety valve **10** is opened by moving the flapper **24** from the closed position illustrated in Fig. 1 to the open position illustrated in Fig. 2. This is accomplished by displacing the actuation member **30** from its upper position shown in Fig. 1 downward toward the upstream portion of the well bore until the lower end portion **32** of the actuation member **30** contacts the first end portion **50** of the plunger **48**. This contact urges the plunger **48** into an open position, thereby compressing the leaf spring **66**. Fluid from the upstream portion of the well bore may now flow to the downstream portion of the well bore. Thus, pressure across the flapper **24** is reduced or equalized. As the actuation member **30** further moves in the upstream direction towards its lower position, the actuation member **30** contacts the contact portions of the flapper body **34**, thereby bringing the actuation member **30** and contact portions into mating contact and allows the flapper **24** to be urged into an open position as the actuation member **30** travels to its lower position.

[0030] In order to close the subsurface safety valve **10**, the actuation member **30** is moved upwardly in the downstream direction towards the upper position of the actuation member **30**. As the actuation member **30** moves upward, the torsion spring (not shown) urges the flapper **24** towards its closed state. When the production tubing (not shown) incorporating the subsurface safety valve **10** contains fluid flowing at a high flow rate or under significant pressure, the flapper **24** may slam shut against the valve seat **22** with tremendous force. This force actually aids in retaining the components of the pressure equalizing assembly **28**, namely the leaf spring **66** and plunger **48**, disposed in the flapper body **34** by urging the leaf spring **66** into the groove **46** when such forces slam the flapper **24** against the valve seat **22**. By providing a groove **46** in the flapper body **34** and minimizing the amount of hardware in the pressure equalizing assembly **28**, it extremely unlikely that any component of the pressure

equalizing assembly **28** would become dislodged from the subsurface safety valve **10**.

[0031] One of ordinary skill in the art will understand that the components of the subsurface safety valve, including the flapper body and pressure equalizing assembly, may be made from high strength steel materials, composites or non-elastomeric materials.

[0032] Except as may be expressly otherwise indicated, the article "a" or "an" if and as used herein is not intended to limit, and should not be construed as limiting, the description or a claim to a single element to which the article refers. Rather, the article "a" or "an" if and as used herein is intended to cover one or more such elements, unless the text expressly indicates otherwise.

[0033] This invention is susceptible to considerable variation within the spirit and scope of the appended claims.

CLAIMS

1. A flapper for use as a component of a safety valve designed for deployment in a well bore having well bore fluids, the flapper comprising

a flapper body forming a flapper valve bore therethrough, the flapper body further forming a groove proximate to the flapper bore;

a plunger member sized and configured to be received in the flapper valve bore, the plunger member comprising a first end portion and a second end portion; and

a leaf spring comprising a primary end portion and a secondary end portion, the primary end portion of the leaf spring detachably attached to the second end portion of the plunger member and unattached to the flapper body and the secondary end portion of the leaf spring being sized and configured to be received and retained in the groove and to bias the plunger member into the flapper valve bore,

wherein forces exerted on the flapper body when rotating between an open state and a closed state during use of the safety valve urge at least a portion of the leaf spring into the groove.

2. A flapper according to claim 1 wherein the primary end portion of the leaf spring is mechanically coupled to the second end portion of the plunger member.

3. A flapper according to claim 1 wherein the primary end portion of the leaf spring further defines a leaf spring aperture, wherein the second end portion of the plunger member is inserted through the leaf spring aperture and mechanically coupled to the leaf spring.

4. A safety valve for deployment in a well bore having well bore fluids wherein the safety valve comprises a flapper in accordance with claim 1.

5. A flapper according to claim 1 wherein the flapper body is curved.

6. A flapper according to claim 1 wherein the flapper body further forms at least one hinge component sized and configured for hinged attachment to the safety valve.

7. A flapper according to claim 1 wherein at least a portion of the groove extends distally from the flapper valve bore.

8. A flapper according to claim 1 wherein at least a portion of the leaf spring extends distally from the flapper valve bore.

9. A flapper according to claim 1 wherein the plunger member further forms a plunger member bore therethrough.

10. A flapper according to claim 9 wherein the plunger member further forms at least one fluid pathway in fluid communication with the plunger member bore, the plunger member bore and fluid pathway providing at least one fluid passageway through the flapper valve bore when the plunger member is disposed in the flapper valve bore but is sufficiently displaced from the flapper valve bore so that the fluid passageway is in fluid communication with both an upstream side of the flapper body and a downstream side of the flapper body.

11. A method for equalizing differential pressure across a safety valve deployed in a well bore having well bore fluids, the method comprising

deploying the safety valve in the well bore, the safety valve comprising a flapper, wherein the flapper comprises a flapper body forming a flapper valve bore therethrough, the flapper body further forming a groove proximate to the flapper bore;

biasing a plunger member in the flapper valve bore by coupling the plunger member to a leaf spring comprising a primary end portion and a secondary end portion, the plunger member being sized and configured to be received in the flapper valve bore and further comprising a first end portion and a second end portion and the primary end portion of the leaf spring being coupled to the second end portion of the plunger member and the secondary end portion of the leaf spring being sized and configured to be received and retained in the groove; and

displacing the plunger member to allow fluid to flow from a portion of the well bore

having higher pressure to a portion of the well bore having lower pressure, wherein displacing the plunger member causes the primary end portion of the leaf spring to rotate about the latitudinal axis of the flapper,
whereby the pressure differential across the safety valve is equalized.

12. A method according to claim 11 wherein the plunger member forms a plunger member bore therethrough, the plunger member bore further forming at least one fluid pathway in fluid communication with the plunger member bore, the plunger member bore and fluid pathway providing at least one fluid passageway through the flapper valve bore when at least a portion of the plunger member is displaced from the flapper valve bore and the fluid passageway further allowing fluid to flow from the portion of the well bore having higher pressure to the portion of the well bore having lower pressure thereby equalizing the pressure across the flapper.

13. A method according to claim 11 further comprising the step of opening the flapper after the pressure differential has been equalized.

14. A method for retaining a flapper valve in a flapper in a safety valve designed for deployment in a well bore, the method comprising

providing a flapper valve bore in the flapper, the flapper valve bore extending through the flapper and the flapper further defining a groove extending distally from the flapper valve bore, and

biasing a plunger member into the flapper valve bore by coupling the plunger member to a leaf spring, the leaf spring disposed in the groove and extending distally from the plunger member,
whereby the leaf spring is urged into the groove when forces are exerted on the flapper thereby retaining the plunger member in the flapper valve bore.

15. A method according to claim 14 further comprising the step of deploying the safety valve in the well bore.