

Method For Carbonizing Carbon Dioxide and Application Thereof

Field of the Invention

The present invention relates to a method for carbonizing carbon dioxide, and more particularly, to a method for converting carbon dioxide into elemental carbon under room temperature and atmospheric condition, without requiring high external energy input.

Background of the Invention

Carbon dioxide (CO₂) is a major greenhouse gas produced by human activities, primarily through the combustion of fossil fuels, for instance, to run vehicles (petrol, diesel and kerosene), heat homes, businesses and power factories. The concentration of carbon dioxide in the earth's atmosphere has risen drastically in the past decades, which is considered as a major factor contributing to global warming.

Presently, there is no practical solution for CO₂ emission problem in industries. The process for removing CO₂ known in the art is carbon capture and storage (CCS) in which CO₂ is captured by for example chemicals such as monoethanolamine (MEA), compressed and buried underground. However, in this process, the storage problem for CO₂ needs to be solved. It is recognized that CO₂ emission is in the order of trillion tons annually, and storing such a huge amount of the gas CO₂ is costly and problematic. Another disadvantage of the CCS process is that the buried CO₂ cannot be reused.

There are other processes such as using chemical neutralization or absorption for the removal of CO₂, but disposal of final products from these processes is a crucial issue. Therefore, the above processes cannot be considered as practical solutions for the removal of CO₂.

The processes and systems in the prior art discussed above are not able to re-utilize the gas CO₂, and the disposal of final products thereof creates another issue.

To effectively remove CO₂, the invention provides a method that is capable of carbonizing CO₂ into black elemental carbon under room temperature and atmospheric conditions, which makes CO₂ a renewable energy. Consequently, the invention not only provides the most practical solution to the CO₂ emission problem without causing a harm to the atmosphere and the environments, but also paves the way for developing new energy sources, which has not been taught and suggested by any of the prior art reference documents.

Summary of the Invention

The present invention has been developed to fulfill the needs noted above and therefore has a principle object of the provision of a method for removing carbon dioxide from air or the flue gas as a result of the combustion of fossil fuels, biomass, or other industrial processes such as coal gasification processes, de-carbonation of limestone and the like, which do not cause harm to the environments.

Another object of the invention is to provide a method for removing carbon dioxide which requires no high energy input and thus is significantly more economical and convenient than the processes and systems in the prior art.

A yet further object of the invention is to provide a method for removing carbon dioxide and converting the final products as energy sources.

These and other objects and advantages of the invention are satisfied by providing a method for carbonizing carbon dioxide, comprising the step of contacting carbon dioxide with a solution of chelating agent or a solution of substance which exhibits chelating properties under dynamic conditions to generate oxygen and carbon particles. Recovering carbon particles may be performed by any means known in the art, for example filtration or settling processes.

In preferred embodiments of the invention, the chelating agent is phosphate-based solutions selected from the group consisting of Na_3PO_4 , Na_2HPO_4 , K_3PO_4 , K_2HPO_4 or their mixtures with carbonate-based solution. The chelating agent may also be selected from carboxylates or amines such as ethylenediaminetetraacetic acid (EDTA), diethylenetriaminepentaacetic acid (DTPA), propylenediaminetetraacetic acid (PDTA), nitrilotriacetic acid (NTA) or ethylenediaminedisuccinate (EDDS) etc.

The solution of chelating agent or the solution of substance which exhibits chelating properties may have a pH value of 3 to 14, preferably 10 to 13. The solution of chelating agent or the solution of substance which exhibits chelating properties may be present at a concentration of 0.2 to 75% by weight, preferably 15 to 30% by weight.

The contact between the gas carbon dioxide and the solution may be performed under basic condition, preferably at the pH value of 8 to 14, if the chelating agent or the substance which exhibits chelating properties in water is alkaline. It has been found by the inventor that, in that case, if the solution has a concentration of 2-50% and a pH of 8-14, the carbon particles of nanometer magnitude may be generated.

The contact between the gas carbon dioxide and the solution may also be performed under acidic condition, preferably at the pH value of 2 to 6, if the chelating agent or the substance which exhibits chelating properties in water is acidic. It has been found by the inventor that, in that case, if the solution has a concentration of 0.5-10% and a pH of 3-5, the carbon particles of nanometer magnitude may be generated.

According to the invention, the dynamic conditions may be created or induced by actions selected from cavitations, compression, expansion, venturi, orifice, linear or spiral spray, jets, screen, mist spraying or bubbling.

Carbon dioxide may contact with the solution of chelating agent or the solution of substance which exhibits chelating properties in a counter flow, co-current flow, or cross flow direction.

It has been found that, if the solution of chelating agent or the solution of substance which exhibits chelating properties is subjected to a pulsed electromagnetic wave treatment, more elemental carbon particles can be produced. In this regard, the electromagnetic wave treatment may be applied by use of a device for generating an electromagnetic field which has a time varying low frequency. The electromagnetic wave may have a frequency in the range of 500Hz to 5MHz.

To reactivate and maintain the chelating properties of the solution of the method, the solution of chelating agent or the solution of substance which exhibits chelating properties may be regenerated. The regeneration may be carried out by addition of an alkaline solution into the solution, electrolyzing the solution, subjecting the solution to pulsating wave electrolysis, electrostatic charge cloud reactivation, or any combination thereof.

If necessary, the contacting step of the method can be repeated for one or more times.

Another aspect of the invention relates to use of carbon dioxide or carbonate-based compounds as a source for producing carbon and oxygen, wherein naturally occurring carbon dioxide or carbon dioxide generated from the carbonate-based compounds are subjected to the method according to the invention.

In contrast to the processes and systems available in the prior art, the method of the invention for carbonizing carbon dioxide is capable of reducing carbon dioxide into its elemental state. Therefore, there is no need for disposal of final products and considering storage of CO₂.

The most advantage of the invention is the generation of elemental carbon and oxygen which can be recovered and reused again for combustion. This improves drastically the energy production efficiency for any carbon-based fuels. With such a recovery of energy, all carbonate-based substances such as minerals, limestone, dolomites or the like, including bicarbonates and carbonates present in the seawater or freshwater can be treated as an energy source. When their carbonate contents are converted into CO₂ by acid treatment, the gas CO₂ produced is then used for conversion into elemental carbon and oxygen. A further advantage of the invention is that the method of the invention can result in generation of a large amount of nano carbon particles.

In addition to the elemental carbon produced in the method of the invention, the oxygen

gas produced is also another valuable product for many practical industrial applications.

Since the method of the invention can result in the generation of a large amount of nano carbon particles, the invention is also a good process for nano carbon production.

5 The objects, characteristics, advantages and technical effects of the invention will be further elaborated in the following description of the concepts and structures of the invention with reference to the accompanying drawings. The drawings illustrate the invention by way of examples without limitation to the invention in any manner.

Brief Description of the Drawings

10 Fig. 1 is a schematic diagram showing a method constructed according to a first embodiment of the invention.

Fig. 2 is a schematic diagram showing a method constructed according to a second embodiment of the invention.

15 Fig. 3 is a chart showing the correlation of the removal efficiency of carbon dioxide to the pH value of Na_3PO_4 solution.

Detailed Description of the Invention

While this invention is illustrated and described in preferred embodiments, the invention may be produced in many different configurations, sizes, forms and materials.

20 Referring now to the drawings, Fig. 1 illustrates a schematic diagram of the method constructed consistent with a first preferred embodiment of the present invention. In this embodiment, 20% by weight of Na_3PO_4 aqueous solution is used as the chelating agent that is in contact with CO_2 . Other substances having good chelating property are possible for use in the invention. For example, carboxylates, phosphates and amines including
25 ethylenediaminetetraacetic acid (EDTA) are typical chelating agents. It should be note that different chelating agents has different operating pH range and their optimum range may be determined on site to suit the actual application condition and constraint. In general, the contact between the gas carbon dioxide and the solution may be performed under basic condition, preferably at the pH value of 8 to 14, if the chelating agent or the substance which exhibits
30 chelating properties in water is alkaline; the contact between the gas carbon dioxide and the solution may also be performed under acidic condition, preferably at the pH value of 2 to 6, if the chelating agent or the substance which exhibits chelating properties in water is acidic. For example, the phosphate based agent will operate at high alkaline level whereas EDTA is able

to operate even at acidic condition. In addition, the acidic chelating agent may operate under basic condition in the method of the invention, for example, sodium hydroxide may be added into the EDTA solution to bring the pH thereof to as high as 13 where the EDTA is still able to capture the carbon.

5 In particular, the gas CO₂ 200 enters a spray tower 100 via a gas inlet 110 located at the bottom of the spray tower 100 and passes upward. The Na₃PO₄ solution 300 is stored in a tank 400 and fed into the upper part of the spray tower 100 by a circulating pump 500. Although Fig. 1 illustrates a nozzle for the simplicity, it should be understood that many nozzles 130 are placed across the spray tower 100 at different heights to spray the Na₃PO₄ solution 300 downward to come into contact with carbon dioxide rising upward from the gas inlet 110. As can be seen, carbon dioxide 200 is contacted with the Na₃PO₄ solution 300 in a counter flow direction. It would be noted that the Na₃PO₄ solution 300 can be fed in a co-current flow or cross flow direction relative to the flow of carbon dioxide.

15 In the spray tower 100, the gas CO₂ is reduced drastically with the generation of fine carbon particles and oxygen. The results reveal that the conversation rate of CO₂ into elemental carbon may vary from 10% to 70% depending on the number of stages applied in the method. The carbon particles are found in the contacted Na₃PO₄ solution 350, and come out of the spray tower 100 with the contacted Na₃PO₄ solution 350 and enter into the tank 400. The gas after the Na₃PO₄ treatment exits via a gas outlet 120 on the top of the spray tower 100 and is collected.


25 The carbon containing Na₃PO₄ solution 350 is transported to a carbon collector 600 for collection of elemental carbon particles. The carbon collector 600 may be a separator of any type that allows the separation of the carbon particles 250 from the Na₃PO₄ solution, for example, a filter or a decanter. The separated Na₃PO₄ solution 380 is then transported back to the tank 400 for circulating use.

Typically, the pH of the Na₃PO₄ solution is in the range of 8 – 14, preferably 10 -12. The basic conditions are necessary for the effective carbonization of the invention, when Na₃PO₄ is used as the chelating agent. In this embodiment, the Na₃PO₄ solution is selected to ensure the pH of the solution at a high pH level to reach the desired pH range for better CO₂ reduction. If the pH of the solution is not high enough, it may be corrected by other alkaline solution to increase the pH of the solution. It has been observed that not all CO₂ will be converted into elemental carbon, and side reactions take place, for example, a portion of CO₂ will be converted into carbonic acid, eventually causing the solution in the spray tower to become more acidic. This will reduce the pH of the solution and the carbon capture efficiency and thereby reducing the reacting sites created by Na₃PO₄, with a result of decreased rate of the CO₂ removal. Thus, the pH of the Na₃PO₄ solution can be used as an indicator for controlling the pH hence the overall CO₂ removal efficiency.

In order to ensure the high CO₂ removal and conversion rate, the pH of the solution flowing in the spray tower 100 shall be maintained at a higher level. In this case, the Na₃PO₄ solution is basified to the desirable high pH by regeneration through addition of an alkaline solution such as NaOH or Na₃PO₄ into the Na₃PO₄ solution, electrolyzing the Na₃PO₄ solution, subjecting the Na₃PO₄ solution to pulsating wave electrolysis, electrostatic charge separation, or any combination thereof. In this way, the OH⁻ ions are introduced into the Na₃PO₄ solution to correct or maintain the pH to/at its original pH level. The electrolysis or the charge separation can be either carried out via side stream or in tank or inline electrolysis. The cathode and anode used in the electrolysis methods may be enclosed with or without the ions membrane or ion barrier materials for increasing the OH⁻ ions in the main bulk solution.

In the prior art, the standard reaction for CO₂ in contact with Na₃PO₄ is to produce sodium carbonate, and such reaction takes place under equilibrium and non-dynamic conditions where CO₂ cannot be broken down into black elemental carbon. As opposed to the prior art, CO₂ and the Na₃PO₄ solution in the method of the invention are under dynamic motion conditions. Such motion of the solution and the gas can be created by any means known in the art, for example induced by cavitations, compression, expansion, venturi, orifice, linear or spiral spray, jets, screen or mist spraying, bubbling or other forms of actions. It is possible that one of the solution and the gas is in stationary condition.

It is believed that, in the method of the invention, the Na₃PO₄ solution serves as a chelating agent and also acts as a catalyst rather than as a reactant to remove and capture the CO₂ under dynamic conditions, for instance, under the spray or bubbling/cavitations effect. Here, the main chemical reactions in the spray tower 100 occur as follows:



These two reactions can both take place simultaneously. It has been observed that higher pH of the solution favors reaction (a) and lower pH favors reaction (b). Fig. 3 illustrates the correlation of the removal efficiency of carbon dioxide to the pH value of Na₃PO₄ solution. As illustrated, at high pH level, such as pH >12, reaction (a) produces more carbon particle in the process which can be collected and also there is proportionate increase of O₂ by volume after the Na₃PO₄ treatment. At low pH level, such as 8~9, both C⁴⁺ and O²⁻ ions exist in the solution, less carbon is collected and less oxygen increase is measured.

The spraying of the Na₃PO₄ solution in the spray tower enables to create a good contact for the CO₂ gas reduction to take place. The spray rate is relating to the tower diameter, nozzle design and the rated value of the nozzles to ensure the good contact between the solution and the gas. The flow rate of the Na₃PO₄ solution will then be sized according to these hardware and gas/solution contact requirements.

The concentration of the Na₃PO₄ solution is a second factor that affects the CO₂ removal.

For a typical flue gas with CO₂ content of 2.5 - 16%, the concentration of the Na₃PO₄ solution of 3 up to 75% can be used. The higher the concentration of the Na₃PO₄ solution, the more efficient recovery of elemental carbon particles. However, this has to take into account the cost of the Na₃PO₄ added and the concentration of CO₂ in the flue gas. With the addition of 3 to 75% of the Na₃PO₄ solution, its pH value will vary from 8 -14 approximately at the start. The concentration of the Na₃PO₄ solution used in the method of the invention is preferably in the range 2% to 50% by weight, preferably 15 to 30% by weight. With 20% of the Na₃PO₄ solution, the CO₂ removal rate can be as high as 80% in a cavitations column.

The size of elemental carbon produced in the method of the invention is affected by the solution concentration and pH. In the case that the Na₃PO₄ solution has a high concentration, carbons of larger particle size are obtained; in the case that the Na₃PO₄ solution has a low concentration especially at a lower pH, carbons of finer particle size, for instance, in the nano scale will be collected. In this embodiment, the carbon particles of nanometer magnitude are found in the contacted Na₃PO₄ solution 350, when in the Na₃PO₄ solution 300 is present at a concentration of 2-50%, and has a pH of 8-14.

It is surprisingly observed that the Na₃PO₄ solution, after being subjected to a treatment of electromagnetic field including pulsated electromagnetic wave ranging from ultra low frequency wave to ultra violet light, would increase the removal of CO₂, and carbon particles of nano size to carbon particles of visible large micron size (which may vary from 50 micrometer to below 100 nanometer) are seen to be precipitated. The size of carbon particles and the rate of precipitation can be controlled by the concentration of the Na₃PO₄ solution and/or the charging electromagnetic wave. The wave forms, frequency, strength, pulsating frequency will affect the precipitation rate. The electromagnetic wave frequency applied to the Na₃PO₄ solution would typically be between 500Hz – 5MHz. The electromagnetic waveform strength (i.e. amplitude) would result in high excitation of the Na₃PO₄ solution to reach a resonance response, and accordingly the precipitation mechanism would reach a resonant level to enhance the conversion of CO₂.

Therefore, a device (not shown) for generating an electromagnetic field which has a time varying frequency may be placed in the Na₃PO₄ solution tank 400 to energize the Na₃PO₄ solution. The device may consists of a coil wrapped around a piece of pipe. The coil is connected to a separate panel from the Na₃PO₄ solution 300 by applying a time varying low frequency electromagnetic field to the solution surrounding the device. The details of the device for generating the electromagnetic wave may make reference to the PCT application no. PCT/SG2006/000218. The energized Na₃PO₄ solution is sprayed downward to directly contact with the gas CO₂ rising upward from the bottom of the spray tower 100. Alternatively, an electromagnetic wave generator (not shown) in the form of emitters connected to the driver card directly or via an inductor coil may be placed inside the pipeline between the spray tower 100 and the tank 400 to apply the electromagnetic wave to the Na₃PO₄ solution flowing

therethrough.

To provide better efficiency of the conversion of CO₂ into carbon, multiple stages of the spray tower may be used. The multiple stages of the tower can be provided in a single tower, or separate vessels arranged in horizontal relation, each dedicated to a specific stage or set of stages, may be used.

Instead of using the spray tower 100, a bubbling column can be used in the method of the invention. Fig. 2 illustrates a schematic diagram showing the method of the invention using the bubbling column. As illustrated, the gas CO₂ 200 enters the bubble column 700 via a gas inlet 710 located at the bottom thereof. The Na₃PO₄ solution 300 is stored in the column 700. A diffuser 730 is arranged at the bottom of the interior of the column 700 to continuously cause a turbulent stream to enable an optimum contact between the gas CO₂ and the Na₃PO₄ solution 300 for the generation of the carbon particles. Like the first embodiment discussed above, the carbon particles are carried in the Na₃PO₄ solution 350 that flows out at the bottom of the column 700. The gas after the Na₃PO₄ treatment exits via a gas outlet 720 on the top of the bubble column 700 and is collected.

The carbon containing Na₃PO₄ solution 350 is directly transported to a carbon collector 600 for collection of elemental carbon particles. Likewise, the carbon collector 600 may be a filter or decanter that allows the separation of the carbon particles 250 from the Na₃PO₄ solution. The separated Na₃PO₄ solution 380 is then transported back to the bubbling column 700 for circulating use.

Obviously, the invention is characterized in that CO₂ is removed by reduction to its elemental state under normal room temperature and atmosphere, with the generation of carbon particles and the gas oxygen. The method of the invention requires no high external energy input for the removal of the gas CO₂. It is believed that the chelating agent solution with strong chelating including those substances which exhibit chelating properties, high pKa constant and strong buffer capability, such as Na₃PO₄, K₃PO₄, K₂HPO₄, Na₂HPO₄, EDTA or the like, has a catalytic function to lower the energy required for CO₂ breaking as well as capturing the elemental carbon in the solution. Simultaneously, the dynamic motion of the solution, such as bubbling or spraying actions, helps to release the media internal energy, thereby causing the CO₂ carbonization to take place in the solution at normal room temp, atmospheric condition.

In the conventional processes for removing CO₂, for example, using NaOH for removing CO₂, a large amount of NaOH is required and the disposal of the final products is also an issue. While according to the invention, the majority of the gas CO₂ is converted into elemental carbon and oxygen, and no chemical is used and the disposal of the final products does not exist in the invention. More importantly, the final products of the invention, carbon and oxygen, can be recovered. Therefore, CO₂ can be treated as a renewable energy.

Based on the method of the invention, the gas CO₂ which occurs naturally or is produced chemically, or carbonate-based compounds such as minerals, limestone, dolomites and the like all can serve as an energy source to recover oxygen and carbon. For example, if carbonate minerals are taken as an energy source, then seawater may be electrolyzed by a separator
5 such as membrane. The acid produced electrolytically can be used to treat the carbonate minerals to generate CO₂, which is then treated by the method of the invention to recover carbon and oxygen. And if concentrated CO₂ is obtained from the CO₂ capturing methods such as MEA amine method, then high contents of carbon and oxygen would be obtained by the method of the invention.

10 Thus, the present invention provides a method which continuously and effectively removes the greenhouse gas CO₂. By the re-generation of the chelating agent solution, the method of the invention is sustained to be continual. The invention is significantly more economical and convenient and does not cause harm to the environments. When compared with the processes and systems in the prior art, the invention exhibits a novel and unique feature that elemental
15 carbon and oxygen are generated as final products and can be recovered as an energy source. The invention not only solves the storage problem associated with the CO₂ capturing technologies, but also eliminates the need of using chemicals required in the prior processes and the need of disposal of final products.

Having sufficiently described the nature of the present invention according to some
20 preferred embodiments, the invention, however, should not be limited to the structures and functions of the embodiments and drawings. It is stated that insofar as its basic principle is not altered, changed or modified it may be subjected to variations of detail. Numerous variations and modifications that are easily obtainable by means of the skilled person's common knowledge without departing from the scope of the invention should fall into the scope of this
25 invention.

What is claimed is:

1. A method for carbonizing carbon dioxide, comprising the step of contacting carbon dioxide with a solution of chelating agent or a solution of substance which exhibits chelating properties under dynamic conditions to generate oxygen and carbon particles.

5 2. The method according to claim 1, wherein the chelating agent is phosphate-based solutions, carboxylates, or amines.

3. The method according to claim 2, wherein the chelating agent is selected from the group consisting of Na_3PO_4 , Na_2HPO_4 , K_3PO_4 , K_2HPO_4 , and/or their mixtures with carbonate-based solution.

10 4. The method according to claim 2, wherein the cheating agent is selected from the group consisting of ethylenediaminetetraacetic acid (EDTA), diethylenetriaminepentaacetic acid (DTPA), propylenediaminetetraacetic acid (PDPA), nitrilotriacetic acid (NTA) or ethylenediaminedisuccinate (EDDS).

15 5. The method according to claim 1, wherein the solution of chelating agent or the solution of substance which exhibits chelating properties has a pH value of 3 to 14.

6. The method according to claim 5, wherein the contact is performed under basic condition, preferably at the pH value of 8 to 14, if the chelating agent or the substance which exhibits chelating properties in water is alkaline.

20 7. The method according to claim 6, wherein the solution has a concentration of 2-50% and a pH of 8-14, resulting in the generation of carbon particles of nanometer magnitude.

8. The method according to claim 5, wherein the contact is performed under acidic condition, preferably at the pH value of 2 to 6, if the chelating agent or the substance which exhibits chelating properties in water is acidic.

25 9. The method according to claim 8, wherein the solution has a concentration of 0.5-10% and a pH of 3-5, resulting in the generation of carbon particles of nanometer magnitude.

10. The method according to claim 1, wherein the solution of chelating agent or the solution of substance which exhibits chelating properties is present at a concentration of 0.2 to 75% by weight.

11. The method according to claim 10, wherein the concentration is 15 to 30% by weight.

30 12. The method according to claim 1, wherein the dynamic conditions are created by actions selected from cavitations, compression, expansion, venturi, orifice, linear or spiral spray, jets, screen, mist spraying or bubbling.

13. The method according to claim 1, wherein carbon dioxide contacts with the solution of chelating agent or the solution of substance which exhibits chelating properties in a counter flow, co-current flow, or cross flow direction.

5 14. The method according to claim 1, wherein the solution of chelating agent or the solution of substance which exhibits chelating properties is subjected to a pulsed electromagnetic wave treatment.

15. The method according to claim 14, wherein the electromagnetic wave treatment is applied by use of a device for generating an electromagnetic field which has a time varying low frequency.

10 16. The method according to claim 14 or 15, wherein the electromagnetic wave has a frequency in the range of 500Hz to 5MHz.

17. The method according to claim 1, further comprising a step of recovering the carbon particles and collecting oxygen.

15 18. The method according to claim 1, further comprising a step of regenerating the solution of chelating agent or the solution of substance which exhibits chelating properties to reactivate and maintain the chelating properties of the solution.

19. The method according to claim 18, wherein the regeneration is carried out by addition of an alkaline solution into the solution, electrolyzing the solution, subjecting the solution to pulsating wave electrolysis, electrostatic charge cloud reactivation, or any combination thereof.

20 20. The method according to any one of claims 1 to 19, wherein the contacting step is repeated for one or more times.

25 21. Use of carbon dioxide or carbonate-based compounds as a source for producing carbon and oxygen, wherein naturally occurring carbon dioxide or carbon dioxide generated from the carbonate-based compounds are subjected to the method according to any one of claims 1 to 20.

22. Use according to claim 21, wherein the carbonate-based compounds are selected from the group consisting of bicarbonates, carbonates, carbonate minerals, limestone, and dolomites.