

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B29D 22/00, B65D 25/42	A1	(11) International Publication Number: WO 97/27043 (43) International Publication Date: 31 July 1997 (31.07.97)
(21) International Application Number: PCT/US97/01137 (22) International Filing Date: 23 January 1997 (23.01.97) (30) Priority Data: 60/010,455 23 January 1996 (23.01.96) US 60/034,633 3 January 1997 (03.01.97) US (71)(72) Applicant and Inventor: REDMOND, Sanford [US/US]; Sanford Redmond Inc., 780 East 134 Street, Bronx, NY 10454 (US). (74) Agents: PAULSON, Robert, E. et al.; Morgan & Finnegan, L.L.P., 345 Park Avenue, New York, NY 10154 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: RECLOSABLE DISPENSER PACKAGE, RECLOSABLE OUTLET FORMING STRUCTURE AND METHOD AND APPARATUS FOR MAKING SAME		
(57) Abstract An aperture forming structure includes a break away tip member (634) of thermoformable plastic. The break away tip includes a hollow protrusion extending from a surface. The intersection of the hollow protrusion and the surface is a fault line (636). Rupturing of the fault line creates an aperture for dispensing the contents of the package. A cap (620) may be integrally formed with the aperture forming structure and detached for protecting the hollow protrusion or for closing the aperture. The aperture forming structure can be made by heating a relatively stiff substantially flat thermoformable sheet of and then stretching the sheet to create a first and a second hollow protrusion in tiered configuration. A rupture line is placed at the intersection of the first and the second protrusions. The sheet may be attached to a pouch or containment member formed from a flexible sheet which contains any flowable substance. 		