[CLAIMS]

1. A method for optimizing efficiency of a transport provider, comprising:

receiving, by a processor, a first departure time of a vehicle, which is administered by the transport provider, at a first location;

receiving, by the processor, a second departure time of the vehicle at a second location which is located after the first location;

determining, by the processor, a difference between the first departure time and the second departure time; and

updating, by the processer, a current schedule to provide an updated schedule in response to the determination of the difference, the updated schedule indicating an updated estimated arrival time of the vehicle at a location after the second location.

2. The method according to claim 1, wherein the step of updating the current schedule to provide the updated schedule comprises:

updating, by the processor, an estimated first departure time of at least one other vehicle, to provide an updated estimated first departure time, the at least one other vehicle being one which is administered by the transport provider and the estimated first departure time of at least one other vehicle being one at which the at least one other vehicle is expected to depart from the first location.

3. The method according to claim 2, further comprising:

receiving, by the processor, a first departure time of the at least one other vehicle, the first departure time of the at least one other vehicle being one at which the at least one other vehicle departs from the first location.

4. The method according to claim 3, further comprising:

determining, by the processor, a difference between the updated estimated first departure time of the at least one other vehicle and the recorded first departure time of the at least one other vehicle, the difference being a control measure data.

5. The method according to claim 4, wherein the current schedule is updated to provide the updated schedule in response to the determination of the control measure data.

6. The method according to claim 5, further comprising optimizing, by the processor, a headway between the vehicle and the at least one other vehicle in response to the updated schedule.

7. The method according to claim 6, wherein the step of optimizing the headway comprises:

receiving, by the processor, predetermined data relevant to at least the vehicle; and

optimizing, by the processor, the headway in response to the step of receiving of the predetermined data.

8. The method according to any one of claims 2 to 7, wherein the at least one other vehicle is one that is in transit.

9. The method according to any one of claims 1 to 8, wherein the step of updating the current schedule to provide the updated schedule comprises:

receiving, by the processor, speed information relating to the vehicle,

wherein the current schedule is updated to provide the updated schedule in response to the step of receiving the speed information relating to the vehicle.

10. An apparatus for optimizing efficiency of a transport provider, the apparatus comprising:

means for receiving a first departure time of a vehicle which is administered by the transport provider at a first location;

means for receiving a second departure time of the vehicle at a second location which is located after the first location;

means for determining a difference between the first departure time and the second departure time; and

means for updating a current schedule to provide an updated schedule in response to the determination of the difference, the updated schedule indicating an

updated estimated arrival time of the vehicle at a location after the second location.