

COUNTERCURRENT CONTACTING DEVICES

Cross Reference To Related Applications

This application is based on United States Non-Provisional Application No. 16/281,351, filed February 21, 2019, United States Non-Provisional Application No. 16/712,995, filed
5 December 13, 2019, and United States Non-Provisional Application No. 16/744,174, filed January 15, 2020. The priorities of the foregoing applications are hereby claimed and their disclosures incorporated herein by reference.

Technical Field

The present invention relates generally to the countercurrent contacting of fluids and, more
10 particularly to devices for the countercurrent contacting of a solid phase and a liquid phase or a liquid and a vapor phase and a method of manufacturing the countercurrent contacting device.

Background Art

Contacting devices in the form of structured packings are used in various applications to cause blending or fluidization of multi-component mixtures flowing in countercurrent relationship
15 within mass transfer columns, as well as to facilitate the chemical reaction, heat transfer and/or mass transfer of the fluid streams. Multiple contacting devices are typically stacked in end-to-end relationship within a region of a column through which a solid phase and a liquid phase or a liquid phase and a vapor phase are flowing in countercurrent relationship. These contacting devices are often employed in connection with fluidized beds used in petroleum, chemical,
20 combustion, and other types of processes to promote vigorous mixing and intimate contact of fluid streams and solid particles within a vessel. This intimate contacting can be used to achieve efficient heat transfer, mass transfer and/or chemical reaction between the fluid streams, solid particles, and/or fluids coated on or entrained with the solid particles. An example of a fluidized bed involving countercurrent flow of fluid streams and solid particles is found in certain types
25 of strippers and regenerators used in fluid catalytic cracking or FCC systems.

One of these types of contact devices is disclosed in U.S. Patent No. 6,224,833 assigned to Koch-Glitsch, Inc. and is marketed as KFBE fluidized bed structured packing. The contact device uses two or more grids of blade-like crossing elements that are arranged to intersect with each other at a preselected angle and to also be positioned at an angle to the longitudinal

axis of the column or vessel. The crossing elements in each grid are spaced apart a distance corresponding to the width of the crossing elements of the intersecting grid so that the crossing elements of the intersecting grids are interleaved with and are in sideways contact with each other at crossing points. These contacting crossing elements are typically individual elements
5 that must be held in place and then welded together at the crossing points to secure them together.

The construction of the intersecting grids of the contacting devices by welding together the individual contacting crossing elements is a time-consuming and labor-intensive process. U.S. Patent No. 5,435,061 discloses one approach to simplifying the construction process of
10 contacting devices used as static mixers by using a metal casting process to form portions or subassemblies of the static mixers. The subassemblies are then joined together to form the static mixing device. While the number of welds required to construct the static mixer is reduced in this process, a need remains for a process of constructing contacting devices that increases the strength of the contacting devices by reducing the number of welds, but which also does not
15 require the casting of subassemblies.

Summary of Invention

In one aspect, the present invention is directed to a contacting device for the countercurrent contacting of a solid and a liquid phase or a liquid and a vapor phase, the contacting device comprising: a first grid formed of a first set of spaced-apart and parallel-extending deflector
20 blades; a second grid formed of a second set of spaced-apart and parallel-extending deflector blades that are interleaved with and cross the first set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the first and second set each having opposite ends and opposite side edges, the side edges having portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross; and
25 apertures formed in the deflector blades of the first and/or second sets of deflector blades and directional tabs associated with the apertures.

In another aspect, the present invention is directed to a contacting device subassembly for the countercurrent contacting of a solid and liquid phase or a liquid and vapor phase, the contacting device subassembly comprising: a first grid formed of a first set of spaced-apart and parallel-
30 extending deflector blades; a second grid formed of a second set of spaced-apart and parallel-extending deflector blades that are interleaved with and cross the first set of deflector blades at

a preselected angle, the deflector blades in the first and second sets each having opposed ends and side edges; and a transverse strip formed by uncut portions of the side edges of adjacent ones of the deflector blades and located where the deflector blades cross and/or adjacent each of the opposite ends, wherein if the transverse strip is located where the deflector blades cross, the deflector blades of the first and/or second sets of deflector blades include apertures and directional tabs associated with the apertures.

In a further aspect, the invention is directed to a contacting device subassembly for the countercurrent contacting of a solid and liquid phase or a liquid and vapor phase, the contacting device subassembly comprising: a first grid formed of a first set of spaced-apart, parallel-extending, planar deflector blades; a second grid formed of a second set of spaced-apart, parallel-extending, planar deflector blades that are interleaved with and cross the first set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the first and second sets each having opposed ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes; a third grid formed of a third set of spaced-apart, parallel-extending, planar deflector blades; and a fourth grid formed of a fourth set of spaced apart, parallel-extending, planar deflector blades that are interleaved with and cross the third set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the third and fourth sets each having opposed ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes that are parallel to each other, and apertures formed in the deflector blades of the first and/or second sets of deflector blades and directional tabs associated with the apertures. One of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades. One of the ends in each

of the deflector blades in the second set is spaced apart from and aligned with one of the ends in each of the deflector blades in the fourth set. The first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

5 In a further aspect, the invention is directed to a contacting device comprising at least two of the contacting device subassemblies in which the interconnected uncut ends of the deflector blades in the first and third sets in one of the contacting devices are joined to said spaced apart and aligned ends of the deflector blades in the second and fourth sets in an adjacent one of the contacting device subassemblies.

10 In a still further aspect, the invention is directed to a method of making a contacting device, comprising the steps of: cutting and bending one or more sheets of material to form a plurality of contacting device subassemblies; and joining adjacent ones of the contacting device subassemblies together by joining the uncut ends of the deflector blades in the first and third sets in one of the adjacent contacting devices to the spaced apart and aligned ends of the deflector blades in the second and fourth sets in the other one of the adjacent contacting devices
15 to form the contacting device.

Brief Description of Drawings

Fig. 1 is a side perspective view of a contacting device having intersecting grids of deflector blades and constructed according to an embodiment of the present invention and shown in a fragmentary portion of a column.

20 Fig. 2 is a side elevation view of the contacting device and column shown in Fig. 1.

Fig. 3 is a top plan view of the contacting device and column shown in Figs. 1 and 2.

Fig. 4 is a side perspective view of one embodiment of a subassembly of the contacting device.

Fig. 5 is a side perspective view of the subassembly of the contacting device taken from an opposite side from the view shown in Fig. 4.

25 Fig. 6 is an end elevation view of two of the contacting device subassemblies prior to being joined together to form the contacting device.

Fig. 7 is a side perspective view of a second embodiment of the contacting device subassembly that incorporates apertures in deflector blades.

Fig. 8 is a front elevation view of a blank with a series of fold and cut lines that may be used to form a contacting device.

5 Fig. 9 is a perspective view of the blank shown in Fig. 8.

Fig. 10 is a side perspective view of a third embodiment of the contacting device subassembly that includes apertures and directional tabs in the deflector blades.

Fig. 11 is an edge elevation view of the third embodiment of the contacting device subassembly.

10 Fig. 12 is a side perspective view of a fourth embodiment of a contacting device subassembly that includes apertures and directional tabs in the deflector blades.

Fig. 13 is an edge elevation view of the fourth embodiment of the contacting device subassembly.

15 Fig. 14 is a side perspective view of a fifth embodiment of a contacting device subassembly that includes apertures and directional tabs in the deflector blades.

Fig. 15 is an edge elevation view of the fifth embodiment of the contacting device subassembly.

Fig. 16 is a side perspective view of a sixth embodiment of a contacting device subassembly that includes apertures and directional tabs in the deflector blades.

20 Fig. 17 is an edge elevation view of the sixth embodiment of the contacting device subassembly.

Fig. 18 is a side perspective view of a seventh embodiment of a contacting device subassembly that includes apertures and directional tabs in the deflector blades.

Fig. 19 is a side elevation view of the seventh embodiment of the contacting device subassembly.

25 Fig. 20 is an edge elevation view of the seventh embodiment of the contacting device subassembly.

Fig. 21 is a fragmentary edge elevation view of one deflector blade of the seventh embodiment of the contacting device subassembly taken along line 21-21 of Fig. 19 in the direction of the arrows and shown on an enlarged scale.

Fig. 22 is a side perspective view of an eighth embodiment of a contacting device subassembly
5 that includes multiple directional tabs associated with each aperture in the deflector blades.

Fig. 23 is a side perspective view of a ninth embodiment of a contacting device subassembly that includes apertures and directional tabs formed in side edges of the deflector blades.

Fig. 24 is a side perspective view of a tenth embodiment of a contacting device subassembly that includes apertures and directional tabs formed in both side edges of the deflector blades.

10 Fig. 25 is a side perspective view of an eleventh embodiment of a contacting device subassembly.

Fig. 26 is a side perspective view of a contacting device formed using multiple contact device subassemblies of Fig. 25.

Fig. 27 is a side perspective view of a tenth embodiment of a contacting device subassembly
15 that includes apertures and directional tabs formed in the deflector blades of the contacting device subassembly shown in Fig. 25.

Fig. 28 is a side perspective view of an eleventh embodiment of a contacting device subassembly that includes apertures and directional tabs formed in the deflector blades of the contacting device subassembly shown in Fig. 25.

20 Fig. 29 is a side perspective view of a twelfth embodiment of a contacting device subassembly that includes transverse strips formed by uncut portions of the side edges of adjacent ones of the deflector blade and located where the adjacent deflector blades cross and at their opposed ends.

Fig. 30 is a side perspective view of a thirteenth embodiment of a contacting device
25 subassembly similar to that shown in Fig. 29, but showing segments of the deflector blades having the shape of isosceles trapezoids rather than rectangles.

Description of Embodiments

Turning now to the drawings in greater detail and initially to Figs. 1-3, one embodiment of a contacting device is designated generally by the numeral 10 and is shown within a cylindrical column 12 through which different phase streams are intended to flow in countercurrent relationship for intimate contact to achieve efficient heat transfer, mass transfer and/or chemical reaction between the phase components. The different phase streams may include a solid phase and a liquid phase or a liquid phase and a vapor phase. The contacting device 10 fills a cross section of the column 12. Although only a single contacting device 10 is illustrated, multiple contacting devices 10 may be stacked in end-to-end relationship within the column 12, with adjacent ones of the contacting devices 10 aligned with or rotated with respect to each other about a longitudinal center axis of the column 12.

Each of the contacting devices 10 comprises a number of subassemblies 13 of paired intersecting grids 14 and 16 that are comprised of crossing elements in the form of spaced-apart and parallel deflector blades 18 and 20, respectively. The paired grids 14 and 16, and the individual deflector blades 18 and 20, cross each other at an included angle that may in one embodiment be within the range of 45 to 135 degrees and in another embodiment be within the range of 60 to 120 degrees. The grids 14 and 16 and deflector blades 18 and 20 are also positioned at an angle, which is normally one-half of the included angle, with respect to the longitudinal center axis of the column 12.

The deflector blades 18 in each of the grids 14 are interleaved with and cross the deflector blades 16 in each of the paired intersecting grids 16. The deflector blades 18 and 20 may be in the form of rectangular strips or other trapezoidal shapes, except that the deflector blades 18 and 20 that are positioned nearest the inner surface of the column 12 are shaped to conform to the shape of the inner surface of the column 12. The deflector blades 18 may be planar and the deflector blades 20 may have two planar segments 20a and 20b that are positioned in offset planes by a bent portion 20c. The offset planes may be parallel to each other.

Each of the deflector blades 18 within each grid 14 has opposed ends 22 and 24 and opposed side edges 26 and 28. Each of the deflector blades 20 within each grid 16 likewise have opposed ends 30 and 32 and opposed side edges 34 and 36. The side edges 26, 28 and 34, 36 of deflector blades 18 and 20, respectively, include uncut portions that join adjacent ones of the interleaved deflector blades 18 and 20 along a transverse strip 38 where the deflector blades 18 and 20

cross each other. This transverse strip 38 creates a strong integral connection between adjacent ones of the deflector blades 18 and 20 that extends across the entire width of each grid 14 and 16 and eliminates the need to position and then weld or otherwise join together individual ones of the deflector blades 18 and 20. The side edges 26, 28 and 34, 36 include cut portions that
 5 extend from the uncut portions to the opposed ends 22, 24 and 30, 32 of the deflector blades 18 and 20, respectively.

The bent portion 20c that places the segments 20a, 20b of the deflector blade 20 in the offset planes may be in the form of an S-shaped bend 40 that incorporates the transverse strip 38. As can be seen in Fig. 3, the S-shaped bend 40 shortens the longitudinal length of the deflector
 10 blades 20 in relation to the longitudinal length of the deflector blades 18, thereby creating slit-like openings 42 between the ends 30, 32 of adjacent deflector blades 18 in the solid surface axial projection of the contacting device 10. These openings 42 and the S-shaped bend 40 in the deflector blades 20 are believed to facilitate mixing of the fluid streams when they are flowing through the contacting device 10.

15 In one embodiment, in each pair of intersecting grids 14 and 16, the end 24 of each one of the deflector blades 18 is uncut and is joined to a similarly uncut end 22 of one of the deflector blades 18 in another one of the intersecting pairs of grids 14 and 16 along a reverse bend 44 that aligns one of the pairs of intersecting grids 14 and 16 with another one of the pairs of intersecting grids 14 and 16 to form a larger contacting device subassembly 46 as shown in
 20 Figs. 4 and 5. In another embodiment, the end 24 of only some of the deflector blades 18 is uncut and is joined to a similarly uncut end 22 of one of the deflector blades 18 in another one of the intersecting pairs of grids 14 and 16 along the reverse bend 44 to form the contacting device subassembly 46.

The interconnected uncut ends 24 and 22 of the deflector blades 18 creates a strong integral
 25 connection that eliminates the need to position and then weld together the ends 24 and 22 of individual deflector blades 18 during assembly of the contacting device 10. Each deflector blade 18 is shown as having one cut end 22 or 24. In another embodiment the cut end 22 or 24 is replaced by an uncut end 22 or 24 that is then connected to an uncut end 22 or 24 of the deflector blades 18 in a further one of the intersecting pairs of grids 14 and 16 along another
 30 one of the reverse bends 44 so that three of the intersecting pairs of grids 14 and 16 are aligned with each other. Additional intersecting pairs of grids 14 and 16 can be joined in this manner.

In one embodiment of the contacting device subassembly 46, the end 32 of each deflector blade 20 in the grid 16 is spaced from the end 30 of the longitudinally-aligned deflector blade 20 in the adjacent grid 16 to create a gap 48. As illustrated in Fig. 6, the gap 48 may be sized to receive at least some of the reverse bend 44 at the uncut ends 22, 24 of the deflector blades 18
 5 in another of the contacting device subassemblies 46 so that the ends 32, 30 of the deflector blades 20 may be welded or otherwise secured to the uncut ends 22, 24 of the deflector blades 18 to join the two contacting device subassemblies 46 together to form at least part of the assembled contacting device 10. Additional contacting devices subassemblies 46 can be joined together in this manner.

10 As shown in Figs. 7 and 10-24, in some embodiments of the paired grids 14 and 16 of the deflector blades 18 and 20 used in the construction of the contacting device 10, some or all of the deflector blades 18 and/or some or all of the deflector blades 20 may include apertures 50 that allow portions of the fluid streams to pass through the deflector blades 18 and/or 20 to facilitate mixing of the fluid streams when flowing countercurrently through the assembled
 15 contacting device 10.

In other embodiments of the paired grids 14 and 16, as shown in Figs. 10-24, some or all of the deflector blades 18 and/or some or all of the deflector blades 20 may include a plurality of directional tabs 56, each of which is positioned in overlying relationship to an aperture 58 formed in the deflector blade 18 and/or 20. The apertures 58 function like the previously-
 20 described apertures 50 to allow portions of the fluid streams to pass through the deflector blades 18 and/or 20 to facilitate mixing of the fluid streams, while the directional tabs 56 further facilitate mixing of the fluid streams by either facilitating entry of the fluid stream into the associated apertures 58 and/or by redirecting the fluid stream as it exits from the associated apertures 58. The directional tabs 56 in some embodiments, such as shown in Figs. 10, 11 and
 25 16-24, may be oriented such that they extend upwardly from the plane of the associated deflector blades 18 and/or 20. In other embodiments, such as shown in Figs. 12 and 13, the directional tabs 56 may be oriented so that they extend downwardly from the plane of the associated deflector blades 18 and/or 20. In still other embodiments, such as shown in Figs. 14 and 15, some directional tabs 56 may extend downwardly while other directional tabs 56 extend
 30 upwardly on the same deflector blades 18 and/or 20.

In general, when the directional tabs 56 are extending upwardly, they facilitate redirecting fluid streams that are descending along the upper surfaces of the deflector blades 18 and/or 20 into and then through the associated apertures 58 to return the fluid streams to open zones where the desired intermixing with the ascending fluid stream may occur. When the directional tabs 56 are extending downwardly, they facilitate redirection of fluid streams that are ascending along the undersurfaces of the deflector blades 18 and/or 20 into and through the associated apertures 58 to return the fluid streams to the open zones to facilitate the desired intermixing with the descending fluids streams.

The size, shape, number and positioning of the directional tabs 56 and the apertures 58 in the deflector blades 18 and/or 20 can be varied to suit particular applications. In some embodiments, such as shown in Figs. 10-17 and 23, the directional tabs 56 and the apertures 58 may be of square or rectangular shape. In other embodiments as shown in Fig. 24, the directional tabs 56 and apertures 58 may be of triangular shape. In still other embodiments, such as shown in Figs. 18-21, the directional tabs 56 may be of a dome-shaped construction while the apertures 58 are of square, rectangular, circular or other shape. In further embodiments as shown in Fig. 22, multiple directional tabs 56 may be associated with a single one of the apertures 58. In the embodiment of the paired grids 14 and 16 shown in Fig. 22, the directional tabs 56 are triangular in shape and extend upwardly along the perimeter of the rectangular aperture 58. In other variations, the triangular directional tabs 56 may extend downwardly along the perimeter of the rectangular apertures 58 or some of the triangular directional tabs 56 may extend upwardly while others extend downwardly. The rectangular apertures 58 are shown in Fig. 22 extending at oblique angles to the longitudinal center line of the deflector blades 18 and 20.

In the embodiments of the paired grids 14 and 16 of deflector blades 18 and 20 shown in Figs. 10-17 and 22-24, each directional tab 56 is constructed by cutting slits in the deflector blade 18 or 20 to form all but one edge of the directional tab 56 and then bending the directional tab 56 out of the plane of the deflector blade 18 or 20 to form the associated aperture 58. The directional tab 56 remains connected to the deflector blade 18 or 20 along its uncut edge 60 and extends at a preselected angle to the plane of the deflector blade 18 or 20. The preselected angle can be varied depending upon the particular application in which the contacting device 10 is intended to be used. In some embodiments, the preselected angle may be in the range of

5 to 65 degrees, while in other embodiments the preselected angle may be in the range of 10 to 45 degrees.

In other embodiments of the paired grids 14 and 16, each directional tab 56 may be formed separately from the associated aperture 58 by welding or otherwise securing a separate
 5 directional tab 56 to the deflector blade 18 or 20 in spaced and at least partially covering relationship to the aperture 58, such as shown in Figs. 18-21. Using a separate directional tab 56 in this fashion allows greater flexibility in the sizing and shaping of the directional tab 56 in relationship to the associated aperture 58.

The directional tabs 56 and apertures 58 may be centrally positioned on the longitudinal center
 10 lines of the deflector blades 18 and/or 20 as shown in Figs. 10-15 and 18-21, or they may be offset from the longitudinal center lines such as shown in Figs. 16 and 17 where adjacent ones of the directional tabs 56 and apertures 58 are arranged in a staggered fashion in relation to the longitudinal center lines. In other variations, the directional tabs 56 and apertures 58 may be positioned at the side edges 26, 28, 34, 36 of the deflector blades 18 and/or 20 as shown in
 15 Figs. 23 and 24 or the apertures 58 may extend obliquely to the longitudinal center lines as shown in Fig. 22.

It will also be appreciated that the paired grids 14 and 16 of deflector blades 18 and 20 containing the directional tabs 56 and apertures 58 may be of various constructions. For example, the deflector blades 18 and 20 of the paired grids 14 and 16 shown in Figs. 10-21 are
 20 as previously described, while the deflector blades 18 and 20 of the paired grids 14 and 16 shown in Figs. 22-24 lack some of the described features. For example, the deflector blades 20 in those embodiments lack the S-shaped bend 40 and the ends 24 of the deflector blades 18 are not uncut and joined to the uncut ends 24 of other deflector blades 18 in another one of the intersecting pairs of grids 14 and 16 along a reverse bend 44.

Turning now to Figs. 8 and 9, a blank 52 in the form of a planar sheet of a material, such as a
 25 metal or an alloy, from which one of the contacting device subassemblies 46 is formed is illustrated. The blank 52 has been cut to form the cut ends 22, 24 and cut portions of the sides 26, 28 of the deflector blades 18, as well as the cut ends 30, 32 and the cut portions of the sides 34, 36 of the deflector blades 20. The S-shaped bends 40 to be formed in the deflector blades
 30 20 and the reverse bends 44 to be formed between the ends 24 and 22 of longitudinally-adjacent deflector blades 18 are shown by broken lines. After cutting the planar sheet of material to form

the blank 52, the contacting device subassembly 46 is then formed by bending the blank 52 at the locations of the S-shaped bends 40 and the reverse bends 44. Because side-ways adjacent ones of the deflector blades 18 and 20 are integrally joined together at the uncut portions of their sides 26, 28 and 34, 36 along the transverse strip 38 and the longitudinally-adjacent ones of the deflector blades 18 are integrally joined together at their uncut ends 22, 24 along the reverse bend 44, the contacting device subassembly 46 is formed as a one-piece element without any need for welding together of separate deflector blades. This results in a high-strength contacting device subassembly 46 that can be fabricated more quickly and less expensively than would otherwise be required if the deflector blades 18 and 20 were required to be welded together. Similarly, the contacting device 10 can be quickly assembled from the contacting device subassemblies 46 with a minimum of welding required.

Turning now to Fig. 25, the interleaved and crossing deflector blades 18 and 20 in the paired grids 14 and 16 of the subassembly 46 shown in that figure are constructed so that one of the transverse strips 38 is formed by uncut portions of the sides edges 26, 28 and 34, 36 positioned adjacent the ends 22 and 30 of the deflector blades 18 and 20, respectively, and another one of the transverse strips 38 is formed by uncut portions of the sides edges 26, 28 and 34, 36 positioned adjacent the opposed ends 24 and 32 of the deflector blades 18 and 20, respectively. These transverse strips 38 create a strong integral connection between sideways-adjacent ones of the deflector blades 18 and 20 that extends across the entire width of each grid 14 and 16 and eliminates the need to position and then weld or otherwise join together individual ones of the deflector blades 18 and 20 in the grid 14 and in the grid 16.

The side edges 26, 28 and 34, 36 of the deflector blades 18 and 20 include cut portions that extend between the uncut portions to allow the deflector blades 18 and 20 to be bent into their interleaved and crossing arrangement. Each of the deflector blades 18 and 20 includes a central crossing segment 60 and end segments 62 that are connected to opposed ends of the central crossing segment 60 by reverse bends 64. In one embodiment, each of the reverse bends 64 may be formed as a single curvilinear bent portion of the deflector blade 18 or 20. In another embodiment as shown in Fig. 25, each of the reverse bends 64 may be in the form of two spaced-apart bends 66 with a planar segment 68 positioned between the bends 66 to facilitate the joinder of adjacent ones of the paired grids 14 and 16 to form the contacting device 10 shown in Fig. 26.

As can be seen in Fig. 26, the planar segments 68 of the deflector blades 18 and 20 in each of the paired grids 14 and 16 is received between the planar segments 68 of the deflector blades 18 and 20 in the adjacent paired grids 14 and 16. The side edges 26, 28 and 34, 36 along the planar segments 68 provide a larger surface area along which the planar segments 68 of the adjacent paired grids 14 and 16 may be more securely joined together during assembly of the contacting device from the individual subassemblies 13 of paired crossing grids 14 and 16. While the deflector blades 18 and 20 illustrated in Figs. 25 and 26 are not shown with apertures and associated directional tabs in order to facilitate an understanding of the arrangement of the deflector blades 18 and 20 themselves, it is to be understood that apertures as well as associated directional tabs, including any of those described and/or shown in other figures of the drawings herein, may be used with the deflector blades 18 and 20.

For example, in the embodiment of the subassembly 46 shown in Fig 27, directional tabs 56 and associated apertures 58 are provided in the central crossing segments 60 and end segments 62 of each of the deflector blades 18 and 20 and are centered on the longitudinal center lines of the deflector blades 18 and 20. Two of the apertures 58 are positioned in spaced apart relationship in each of the central crossing segments 60 and two directional tabs 56 are associated with each of those apertures 58. One of the directional tabs 56 extends upwardly along one edge of the aperture 58 and the other directional tab 56 extends downwardly from a opposite edge of the aperture 58.

As another example, in the embodiment of the subassembly 46 shown in Fig. 28, three of the apertures 58 and paired directional tabs 56 are provided in each central crossing segment 60 and a single aperture 58 and associated directional tab 56 is provided in each end segment 62 of each of the deflector blades 18 and 20 and are centered on the longitudinal center lines of the deflector blades 18 and 20. Apertures 58 and associated directional tabs 56 are also provided at the side edges 26, 28, 34, 36 of the deflector blades 18 and 20. Similar arrangements of apertures 58 and associated directional tabs 56 that are used in the subassembly 46 shown in Fig. 28 may also be incorporated into other arrangements of the deflector blades 18 and 20, such as the arrangements of deflector blades 18 and 20 shown in the subassemblies 46 shown in Figs. 4-6, or can be used in place of the apertures 58 and directional tabs 56 in the subassemblies 46 shown in Figs. 22-24.

While the embodiments of the contacting device subassemblies 46 shown in Figs. 25-27 have transverse strips 38 formed adjacent the ends 22 and 30 of the deflector blades 18 and 20 and adjacent the opposite ends 24 and 32 of the deflector blades 18 and 20, a third transverse strip 38 may be formed by uncut portions of the side edges 26, 28 and 34, 36 of the central crossing segments 60 of the deflector blades 18 and 20, as illustrated in Fig. 29, to provide greater rigidity to the contacting device subassembly 46. To accommodate the third transverse strip 38 in the central crossing segments 60, a pair of spaced apart bends 70 and a planar segment 72 positioned between the bends 70 are provided in the central crossing segments 60 at the location of the uncut portions of the side edges 26, 28 and 34, 36 of the central crossing segments 60 of the deflector blades 18 and 20. Although the deflector blades 18 and 20 are shown without directional tabs and apertures to facilitate an understanding of the arrangement of the deflector blades 18 and 20 themselves, it is to be understood that apertures as well as associated directional tabs, including any of those described and/or shown in other figures of the drawings herein, may be used with the deflector blades 18 and 20.

As previously referenced, the deflector blades 18 and 20 may have trapezoidal shapes other than rectangular. For example, as shown in the contacting device subassembly shown in Fig. 30, the portions of the deflector blades 18 and 20 that extend between the rectangular planar segments 68 and the transverse strips 38 may be in the form of isosceles trapezoids. The converging sides edges 26, 28 and 24, 26 of these isosceles trapezoidal portions of the deflector blades 18 and 20 in the direction of fluid flow are believed to facilitate removal of the fluid from the deflector blades 18 and 20 and mixing with the fluid flowing in the opposite direction. Again, directional tabs and apertures are not shown to facilitate an understanding of the arrangement of the deflector blades 18 and 20 themselves, but it is to be understood that apertures as well as associated directional tabs, including any of those described and/or shown in other figures of the drawings herein, may be used with the deflector blades 18 and 20.

From the foregoing, it will be seen that this invention is one well adapted to attain all the ends and objectives hereinabove set forth together with other advantages that are inherent to the structure.

It will be understood that certain features and subcombinations are of utility and may be employed without reference to other features and subcombinations. This is contemplated by and is within the scope of the invention.

Since many possible embodiments may be made of the invention without departing from the scope thereof, it is to be understood that all matter herein set forth or shown in the accompanying drawings is to be interpreted as illustrative and not in a limiting sense.

CLAIMS

[Claim 1] A contacting device subassembly for the countercurrent contacting of a solid and liquid phase or a liquid and vapor phase, said contacting device subassembly comprising:

5 a first grid formed of a first set of spaced-apart and parallel-extending deflector blades;
a second grid formed of a second set of spaced-apart and parallel-extending deflector blades that are interleaved with and cross the first set of deflector blades at a preselected angle, the deflector blades in the first and second sets each having opposed ends and side edges;

10 a third grid formed of a third set of spaced-apart and parallel-extending deflector blades;
and

a fourth grid formed of a fourth set of spaced apart and parallel-extending deflector blades that are interleaved with and cross the third set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the third and fourth sets each having opposed ends and side edges, the side edges having uncut portions that join the adjacent ones
15 of the interleaved deflector blades along a transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes,

20 wherein one of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades; and

a transverse strip formed by uncut portions of the side edges of adjacent ones of the deflector blades and located where the deflector blades cross,

25 wherein the transverse strip is located where the deflector blades cross, the deflector blades of the first and/or second sets of deflector blades include apertures and directional tabs associated with the apertures,

30 wherein the side edges of the deflector blades include cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes.

[Claim 2] The contacting device subassembly of claim 1, wherein the directional tabs have an uncut edge connecting the directional tabs to the deflector blades of the first and/or second sets of deflector blades.

5 [Claim 3] The contacting device subassembly of claim 1, wherein the directional tabs are welded to the deflector blades of the first and/or second sets of deflector blades in spaced and at least partially covering relationship to the apertures.

10 [Claim 4] The contacting device subassembly of claim 1, wherein the directional tabs extend upwardly or downwardly at an angle in the range of 5 to 65 degrees from a plane of the deflector blades in the first and/or second sets of deflector blades.

15 [Claim 5] The contacting device subassembly of claim 1, wherein the offset planes of the segments of the deflector blades in the second set are parallel to each other and the offset planes of the segments of the deflector blades in the fourth set are parallel to each other.

20 [Claim 6] The contacting device subassembly of claim 5, wherein one of the ends in each of the deflector blades in the second set is spaced apart from and aligned with one of the ends in each of the deflector blades in the fourth set.

[Claim 7] The contacting device subassembly of claim 5, wherein the first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

25 [Claim 8] The contacting device subassembly of claim 1, wherein the cut portions of the side edges joining the adjacent ones of the deflector blades in the first, second, third and fourth sets are each linear.

30 [Claim 9] The contacting device subassembly of claim 5, wherein the first and second grids cross at an included angle within the range of 45 to 135 degrees and the third and fourth grids cross at an included angled within the range of 45 to 135 degrees.

[Claim 10] The contacting device subassembly of claim 5, wherein said one of the ends of each of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend.

- 5 [Claim 11] A contacting device subassembly for the countercurrent contacting of a solid and liquid phase or a liquid and vapor phase, said contacting device subassembly comprising:
- a first grid formed of a first set of spaced-apart, parallel-extending, planar deflector blades;
 - a second grid formed of a second set of spaced-apart, parallel-extending, planar
10 deflector blades that are interleaved with and cross the first set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the first and second sets each having opposed ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a
15 transverse strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes;
 - a third grid formed of a third set of spaced-apart, parallel-extending, planar deflector blades;
 - 20 a fourth grid formed of a fourth set of spaced apart, parallel-extending, planar deflector blades that are interleaved with and cross the third set of deflector blades at an included angle within the range of 45 to 135 degrees, adjacent ones of the interleaved deflector blades in the third and fourth sets each having opposed ends and linear side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along a transverse
25 strip where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes that are parallel to each other; and
 - apertures formed in the deflector blades of the first and/or second sets of deflector
30 blades and directional tabs associated with the apertures,
 - wherein one of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along

a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades,

wherein one of the ends in each of the deflector blades in the second set is spaced apart from and aligned with one of the ends in each of the deflector blades in the fourth set,

5 wherein the first, second, third and fourth grids have a least one side shaped to conform to a curved longitudinal plane.

[Claim 12] A contacting device for the countercurrent contacting of a solid and a liquid phase or a liquid and a vapor phase, said contacting device comprising:

10 a first grid formed of a first set of spaced-apart and parallel-extending deflector blades;
a second grid formed of a second set of spaced-apart and parallel-extending deflector blades that are interleaved with and cross the first set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the first and second set each having opposite ends and opposite side edges, the side edges having portions that join the adjacent ones of the
15 interleaved deflector blades along a transverse strip where the deflector blades cross;

a third grid formed of a third set of spaced-apart and parallel-extending deflector blades;
a fourth grid formed of a fourth set of spaced apart and parallel-extending deflector blades that are interleaved with and cross the third set of deflector blades at a preselected angle, adjacent ones of the interleaved deflector blades in the third and fourth sets each having
20 opposed ends and side edges, the side edges having uncut portions that join the adjacent ones of the interleaved deflector blades along another one of the transverse strips where the deflector blades cross and cut portions that extend from the uncut portions to the opposed ends of the deflector blades, the deflector blades in the fourth grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes; and

25 apertures formed in the deflector blades of the first and/or second sets of deflector blades and directional tabs associated with the apertures,

wherein the side edge portions that join the adjacent ones of the interleaved deflector blades along the transverse strip where the deflector blades cross are uncut and wherein cut portions extend from the uncut portions to the opposite ends of the deflector blades, the
30 deflector blades in the second grid each having a bent portion that places segments of the deflector blade on opposite sides of the uncut portion in offset planes, and

wherein one of the ends in at least some of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend that aligns the first and second grids of deflector blades with the third and fourth grids of deflector blades.

5

[Claim 13] The contacting device of claim 12, wherein the directional tabs associated with some of the apertures extend upwardly from deflector blades of the first and/or second sets of deflector blades and the directional tabs associated with others of the apertures extend downwardly from deflector blades of the first and/or second sets of deflector blades.

10

[Claim 14] The contacting device of claim 12, wherein said one of the ends of each of the deflector blades in the first set is uncut and is interconnected with an uncut one of the ends of the deflector blades in the third set along a reverse bend.