



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 13/15	A1	(11) International Publication Number: WO 97/17923 (43) International Publication Date: 22 May 1997 (22.05.97)
<p>(21) International Application Number: ☒ PCT/US96/17001</p> <p>(22) International Filing Date: ☒ 22 October 1996 (22.10.96)</p> <p>(30) Priority Data: 95117922.5 ☒ 14 November 1995 (14.11.95) ☒ EP</p> <p>(34) Countries for which the regional or international application was filed: BE et al.</p> <p>(71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): PALUMBO, Gianfranco [IT/DE]; Georgenfeld 7, D-61352 Bad Homburg (DE). SCHMIDT, Mattias [DE/DE]; Altkoenigweg 3, D-65510 Idstein (DE). PLISCHKE, Manfred [DE/DE]; Ahornweg 18, D-61449 Steinbach (DE). MEYER, Wolfgang [DE/DE]; Gustav-Stresemann-Strasse 5, D-65439 Florsheim (DE).</p> <p>(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: DISPOSABLE ABSORBENT ARTICLES HAVING REDUCED SURFACE WETNESS</p> <p>(57) Abstract</p> <p>A disposable absorbent article comprising a backsheet, a topsheet, a fluid acquisition/distribution region and at least one fluid storage region, said article having a total product acquisition performance of more than 3.75 ml/sec in the first gush and more than 0.5 ml/sec in the fourth gush and an in bag stack height of less than 9.9 mm, characterised in that said topsheet allows to retain no more than 0.25 g of fluid as measured by the topsheet-on-acquisition-material-wetness test, and that said acquisition/distribution region has a drip capacity of at least 5.0 grams of fluid per gram of material.</p>		