(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110657 A2

(51) International Patent Classification[7]: B08B 3/12

(21) International Application Number:
PCT/EP2004/051020

(22) International Filing Date: 3 June 2004 (03.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/478,308 12 June 2003 (12.06.2003) US

(71) Applicant *(for all designated States except US)*: **SEZ AG** [AT/AT]; Draubodenweg 29, A-9500 Villach (AT).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **FERRELL, Gary W.** [US/US]; 5084 La Honda Road, San Gregorio, California 94074 (US). **SCHIPPER, John F.** [US/US]; 3133 Flowers, Palo Alto, California 94306 (US). **RATRA, Jagjit S.** [US/US]; 1454 Inwood Court, Campbell, California 95008 (US).

(74) Agent: **KONTRUS, Gerhard**; c/o SEZ AG, Draubodenweg 29, A-9500 Villach (AT).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US*

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(48) Date of publication of this corrected version:
31 March 2005

(15) Information about Correction:
see PCT Gazette No. 13/2005 of 31 March 2005, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: UNIFORM CAVITATION FOR PARTICLE REMOVAL

(57) Abstract: Systems and methods for promoting a substantially uniform cavitation field. With system (100) including a diaphragm (109) dividing a container (103), a second energy pulse corresponding to a first energy pulse arising from collapse of a cavity C is produced and is used to determine whether to adjust a corresponding transducer 121-k. In system (16), a cavity creating unit (11), including an assembly of transducers 15-i, is moveable from a test liquid to a particle removal (PR) liquid after transducer testing. In another system, a sensor plate (170) having an array of sensors 171-j provides a virtual wafer. A substantially uniform field of cavitation may be maintained by a cavity enhancement liquid, or adjustment of transducer energy. Mechanisms of holding an object produce substantially uniform cavitation. Opposed transducers in a container having monotonically decreasing and/or increasing cavitation density produce substantially uniform cavitation density.

WO 2004/110657 A2