

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 December 2006 (07.12.2006)

PCT

(10) International Publication Number  
**WO 2006/130415 A1**

(51) International Patent Classification:

**G01F 1/84** (2006.01) **G01N 9/00** (2006.01)

(21) International Application Number:

PCT/US2006/020188

(22) International Filing Date: 24 May 2006 (24.05.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/685,739 27 May 2005 (27.05.2005) US

(71) Applicant (for all designated States except US): **MICRO MOTION, INC.** [US/US]; 7070 Winchester Circle, Boulder, Colorado 80301 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DUFFILL, Graeme, Ralph** [GB/US]; 9742 North 117th Way, Scottsdale, Arizona 85259 (US). **BELL, Mark, James** [US/US]; 15710 W. 66th Place, Arvada, Colorado 80007 (US). **MCANALLY, Craig, B.** [US/US]; 594 East 131st

Way, Thornton, Colorado 80241 (US). **MAGINNIS, Richard, L.** [US/US]; 410 Whitetail Cricle, Lafayette, Colorado 80026 (US).


(74) Agents: **JANSEN, Gregg, L.** et al.; SETTER OLLILA LLC, 2060 Broadway, Suite 300, Boulder, Colorado 80302 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: METHODS AND METER ELECTRONICS FOR RAPIDLY DETECTING A NON-UNIFORMITY OF A MATERIAL FLOWING THROUGH A CORIOLIS FLOWMETER



(57) Abstract: Meter electronics (20) and methods for detecting a flow anomaly in a flow material flowing through a flow meter (5) are provided. The meter electronics (20) includes an interface (201) for receiving a vibrational response of the flow material, with the vibrational response including at least a first sensor signal and a second sensor signal, and a processing system (203) in communication with the interface (201). The processing system (203) is configured to receive the vibrational response from the interface (201), generate a ninety degree phase shift from the first sensor signal and generate at least one flow characteristic using at least the first sensor signal and the ninety degree phase shift, compare the at least one flow characteristic to at least one anomaly profile, detect a shift in the vibrational response if the at least one flow characteristic falls within the anomaly profile, and indicate an anomaly condition as a result of the detecting.

WO 2006/130415 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*