

DESCRIPTION**MOBILE STATION****TECHNICAL FIELD**

5 [0001]

The present invention relates to a mobile station provided with a first protocol function (AS function) corresponding to a first protocol (AS: Access Stratum) terminated between the mobile station and a radio base station and a second protocol function
10 (NAS function) corresponding to a second protocol (NAS: Non Access Stratum) terminated between the mobile station and a mobile switching center.

BACKGROUND ART

15 [0002]

With reference to Fig. 7, a re-connection process in a mobile communication system of the LTE (Long Term Evolution) scheme will be explained.

[0003]

20 As illustrated in Fig. 7, in step S501, when a mobile station UE detects a quality deterioration of a radio link (specifically, an RRC connection) established with a radio base station eNB1, the mobile station UE activates a timer T310.

[0004]

25 In step S502, when the quality deterioration of the radio link is not recovered before the timer T310 expires, then the mobile station UE detects a failure in the radio link (RLF: Radio Link Failure) and activates a timer T311.

[0005]

During a time that the timer T311 is activated, the mobile station UE performs a cell selection process. And, when a specific cell is discovered, the mobile station UE attempts to establish a radio link with a radio base station that manages the specific cell. At this time, when a "UE Context" of the mobile station UE is managed in the specific cell, then the establishment of the radio link is successful.

[0006]

In step S503, when the specific cell is not discovered during a time that the timer T311 is activated, when the "UE Context" of the mobile station UE is not managed in the discovered cell, or when an inter-RAT cell is discovered during a time that the timer T311 is activated, then the mobile station UE is transitioned to an idle state (RRC_Idle state).

[0007]

Thereafter, in step 504, the mobile station UE starts camping on a cell under the control of a radio base station eNB2.

[0008]

In step S505, the mobile switching center MME does not know that the mobile station UE has started the camping on the cell under the control of the radio base station eNB2, and therefore, the mobile switching center MME transmits downlink data destined to the mobile station UE, to a radio base station eNB1. Therefore, the downlink data destined to the mobile station UE is lost without reaching the mobile station UE.

[0009]

In step S507, the radio base station eNB1 releases an S1 connection with the mobile switching center MME for the mobile station UE, because there is no response, within a predetermined

period from the mobile station UE, to an uplink synchronization request signal transmitted to the mobile station UE in step S506.

[0010]

In step S508, the mobile switching center MME transmits a
5 paging signal to the mobile station UE.

[0011]

In step S509, in response to the received paging signal, the mobile station UE establishes a radio link with the radio base station eNB2 by transmitting a service request to the mobile
10 switching center MME.

[0012]

In step S510, the radio base station eNB2 transmits downlink data via the radio link established in step S509.

15 **SUMMARY OF THE INVENTION**

PROBLEMS TO BE SOLVED BY THE INVENTION

[0013]

However, the conventional mobile communication system has a problem in that the network cannot detect the transition of a
20 state of the mobile station UE (transition from an RRC_Connected state to an RRC_Idle state) resulting from the RLF, until the downlink data is generated, and the downlink data generated in this period is lost without reaching the mobile station UE.

[0014]

25 The conventional mobile communication system has another problem that the mobile station is configured to perform a re-connection process after receiving the paging signal from the mobile switching center MME when the mobile station UE is transitioned to the RRC_Idle state resulting from the RLF, and thus,

it takes time for the radio link (U plane) to recover.

[0015]

Therefore, the present invention is intended to overcome the above-described problem. An object of the present invention
5 is to provide a mobile station capable of making it difficult for downlink data to be lost even if the mobile station UE is transitioned to an idle state resulting from RLF.

MEANS FOR SOLVING THE PROBLEM

10 [0016]

A first aspect of the present invention is summarized as a mobile station including: a first protocol function corresponding to a first protocol terminated between the mobile station and a radio base station; and a second protocol function
15 corresponding to a second protocol terminated between the mobile station and a mobile switching center, wherein the first protocol function is configured to notify, when detecting a failure in a radio link established with the radio base station, or when discovering a cell subject to a location registration by a cell
20 selection process, the second protocol function of the detection; and the second protocol function is configured to transmit, in response to the notification, a location registration request signal to the mobile switching center.

[0017]

25 In the first aspect of the present invention, the location registration request signal can include a flag requesting a recovery of the radio link.

[0018]

In the first aspect of the present invention, the second

protocol function can be configured to transmit the location registration request signal, after an elapse of a predetermined period from receiving the notification, or during a time that the predetermined period elapses from receiving the notification.

5 [0019]

In the first aspect of the present invention, the second protocol function can be configured to determine whether to transmit the location registration request signal, based on a type of communications performed via the radio link in which the failure
10 has been detected.

[0020]

A second aspect of the present invention is summarized as a mobile station including: a first protocol function corresponding to a first protocol terminated between the mobile
15 station and a radio base station; and a second protocol function corresponding to a second protocol terminated between the mobile station and a mobile switching center, wherein the first protocol function is configured to transition to an idle state after an elapse of a first predetermined period after the failure in the
20 radio link established with the radio base station is detected; and the second protocol function is configured to transmit a location registration request signal to the mobile switching center, after a second predetermined period elapses after data is transmitted last, or during a time that the second predetermined
25 period elapses after data is transmitted last.

[0021]

In the second aspect of the present invention, the second predetermined period can be configured to be measured by the first protocol function or the second protocol function.

EFFECT OF THE INVENTION

[0022]

As explained above, according to the present invention, it
5 is possible to provide a mobile station capable of making it
difficult for downlink data to be lost even if the mobile station
UE is transitioned to an idle state resulting from RLF.

BRIEF DESCRIPTION OF THE DRAWINGS

10 [0023]

[Fig. 1] Fig. 1 is an overall configuration diagram of a
mobile communication system according to a first embodiment of the
present invention.

[Fig. 2] Fig. 2 is a functional block diagram of a mobile
15 station according to the first embodiment of the present invention.

[Fig. 3] Fig. 3 is a diagram explaining an operation of the
mobile communication system according to the first embodiment of
the present invention.

[Fig. 4] Fig. 4 is a diagram explaining an operation of the
20 mobile communication system according to the first embodiment of
the present invention.

[Fig. 5] Fig. 5 is a functional block diagram of a mobile
station according to a first modified example of the present
invention.

25 [Fig. 6] Fig. 6 is a functional block diagram of a mobile
station according to a second modification of the present
invention.

[Fig. 7] Fig. 7 is a diagram explaining an operation of a
conventional mobile communication system of the LTE scheme.

BEST MODES FOR CARRYING OUT THE INVENTION

[0024]

(Mobile communication system according to a first embodiment of
5 the present invention)

With reference to Fig. 1 through Fig. 4, a mobile communication system according to a first embodiment of the present invention will be explained.

[0025]

10 As illustrated in Fig. 1, the mobile communication system according to the embodiment is a mobile communication system of the LTE scheme, and includes: a mobile switching center MME; a radio base station eNB1/eNB2; and a mobile station UE.

[0026]

15 As illustrated in Fig. 2, the mobile station UE according to the embodiment includes: an AS function (first protocol function) corresponding to an AS (first protocol) terminated between the mobile station UE and the radio base station eNB; and an NAS function (second protocol function) corresponding to an NAS
20 (second protocol) terminated between the mobile station UE and the mobile switching center MME.

[0027]

The AS function includes a monitor unit 11 and a notification unit 12.

25 [0028]

The monitor unit 11 is configured to monitor the generation of a failure (RLF) in a radio link (for example, an RRC connection) established with the radio base station eNB1 and broadcast information including a location registration area.

[0029]

The notification unit 12 is configured to notify, to the NAS function, the detection of the failure (RLF) in the radio link (for example, an RRC connection) established with the radio base station eNB1, when the failure is detected.

[0030]

Alternately, when a cell subject to location registration is discovered based on the location registration area included in the received broadcast information, the notification unit 12 is configured to notify the NAS function of the discovery, in a cell selection process.

[0031]

The NAS function includes a location registration processing unit 21, a timer 22, and a service request transmission unit 23.

15 [0032]

The location registration processing unit 21 is configured to transmit a location registration request signal (TAU: Tracking Area Update) to the mobile switching center MME, when the notification indicating that the RLF has been detected is received from the AS function, or when the cell subject to the location registration is discovered in the cell selection process and there is no uplink data to be transmitted.

[0033]

In this case, the location registration request signal may be configured to include a flag (Active Flag) requesting a recovery of the radio link.

[0034]

The location registration processing unit 21 may also be configured to transmit the location registration request signal,

after an elapse of a predetermined period from receiving the above-described notification.

[0035]

The location registration processing unit 21 may also be
5 configured to transmit the location registration request signal,
during a time that the predetermined period elapses from receiving
the above-described notification.

[0036]

The predetermined period is configured to be measured by
10 a timer 22. The predetermined time may be a time autonomously
generated by the mobile station UE, a time notified from the network,
or a time obtained by multiplying the time notified from the network
by a random number. The predetermined time may be configured to
differ depending on each mobile station UE or each group of the
15 mobile stations UE.

[0037]

The service request transmission unit 23 is configured to
transmit a service request signal (Service Request) to the mobile
switching center MME, when the notification indicating that the
20 RLF is detected is received from the AS function and there is the
uplink data to be transmitted.

[0038]

The service request signal is a signal used in the
re-connection process by the mobile station UE, i.e., a signal
25 requesting an establishment of the radio link (RRC connection) with
the radio base station eNB2.

[0039]

Hereinafter, with reference to Fig. 3 and Fig. 4, an
operation of the mobile communication system according to the

embodiment will be explained.

[0040]

Firstly, a first operation of the mobile communication system according to the embodiment will be described with reference
5 to Fig. 3.

[0041]

As illustrated in Fig. 3, in step S101, the AS function of the mobile station UE activates a timer T310, when the quality deterioration of the radio link (RRC connection) established with
10 the radio base station eNB1 is detected.

[0042]

In step S102, when the quality deterioration of the radio link is not recovered before the timer T310 expires, then the AS function of the mobile station UE detects the RLF and activates
15 a timer T311.

[0043]

During a time that the timer T311 is activated, the AS function of the mobile station UE performs a cell selection process. And, when a specific cell is discovered, then the AS function of
20 the mobile station UE attempts to establish a radio link with the radio base station managing the specific cell.

[0044]

In step S103, when the specific cell is not discovered during a time that the timer T311 is activated, when the "UE Context" of
25 the mobile station UE is not managed in the discovered cell, or when an inter-RAT cell is discovered during a time that the timer T311 is activated, then the AS function of the mobile station UE is transitioned to an idle state (RRC_Idle state).

[0045]

In this case, the AS function of the mobile station UE notifies the NAS function of the mobile station UE that the RLF is detected. Alternately, the AS function of the mobile machine
5 may notify the NAS function of the mobile station UE that the cell subject to the location registration is discovered by the cell selection process.

[0046]

Thereafter, in step S104, the AS function of the mobile
10 station UE starts a camping on a cell under the control of the radio base station eNB2.

[0047]

In step S105, the NAS function of the mobile station UE transmits the location registration request signal to the mobile
15 switching center MME, after a predetermined period elapses after receiving the above-described notification.

[0048]

In step S106, the mobile switching center MME releases an S1 connection with the radio base station eNB1 for the mobile
20 station UE. And, when there is the uplink data to be transmitted, the mobile switching center MME transmits the paging signal to the mobile station UE in step S107.

[0049]

In step S108, in response to the received paging signal,
25 the NAS function of the mobile station UE establishes a radio link with the radio base station eNB2, by transmitting a service request to the mobile switching center MME.

[0050]

In step S109, the radio base station eNB2 transmits downlink

data via the radio link established in step S108.

[0051]

Secondly, the first operation of the mobile communication system according to the embodiment will be described with reference
5 to Fig. 4.

[0052]

As illustrated in Fig. 4, the operations from steps S201 to S204 are identical to those from steps S101 to S104 illustrated in Fig. 3.

10 [0053]

In step S205, the NAS function of the mobile station UE transmits the location registration request signal including a flag (Active Flag) requesting a recovery of the radio link, to the mobile switching center MME, after a predetermined period elapses
15 after receiving the above-described notification.

[0054]

In step S206, the mobile switching center MME releases the S1 connection with the radio base station eNB1 for the mobile station UE, and establishes the S1 connection with the radio base
20 station eNB2 for the mobile station UE. Moreover, the radio link is established between the radio base station eNB2 and the mobile station UE.

[0055]

In step S207, the radio base station eNB2 transmits downlink
25 data via the radio link established in step S206.

[0056]

(Operation and Effect of the mobile communication system according to the first embodiment of the present invention)

According to the embodiment-based mobile communication

system, when the AS function of the mobile station UE detects the RLF, the AS function of the mobile station UE is configured to notify the NAS function of the detection, and according to the notification, the NAS function of the mobile station UE is configured to transmit the location registration request signal to the mobile switching center MME. Thus, it is possible to reduce a time required for the mobile station UE to recover from the idle state, and it is possible to make it difficult for downlink data to be lost.

10 [0057]

Moreover, according to the embodiment-based mobile communication system, the NAS function of the mobile station UE is configured to transmit the location registration request signal, after waiting for a predetermined time assigned to each mobile station UE after receiving the above-described notification, and thus, it is possible to avoid a situation where the transmission of the location registration request signal is congested at the tunnel exit, etc.

[0058]

20 Furthermore, according to embodiment-based mobile communication system, the NAS function of the mobile station UE is configured to transmit the location registration request signal within a predetermined time assigned to each mobile station UE, after receiving the above-described notification, and thus, it is possible to avoid a situation where the transmission of the location registration request signal is congested at the tunnel exit, etc., by not allowing the location registration signal to be transmitted by, for example, setting a setting value to 0 (zero).

[0059]

(First Modified Example)

With reference to Fig. 5, a mobile communication system according to a first modified example of the present invention will
5 be described while focusing on the difference in the mobile communication system according to the above-described first embodiment.

[0060]

As illustrated in Fig. 5, the AS function of the mobile
10 station UE includes the notification unit 12, a transmission unit 13, and a timer 14. In this case, the AS function is configured to transition to an idle state, after an elapse of a first predetermined period after the failure (RLF) in the radio link established with the radio base station eNB is detected.

15 [0061]

The transmission unit 13 is configured to transmit the uplink data.

[0062]

The notification unit 12 is configured to monitor a time
20 at which the uplink data is transmitted by the transmission unit 13, and to notify, to the NAS function, the transmission time of the uplink data.

[0063]

The notification unit 12 is configured to notify, after a
25 second predetermined period elapses after the data is transmitted last, the NAS function that the second predetermined period elapses after the data is transmitted last. In such a case, the timer 14 may be configured to measure the second predetermined period.

[0064]

The NAS function of the mobile station UE includes a location registration processing unit 21, and a timer 22.

[0065]

5 The location registration processing unit 21 is configured to transmit the location registration request signal to the mobile switching center MME, after the second predetermined period elapses after the data is transmitted last.

[0066]

10 In this case, the timer 22 included in the NAS function is configured to measure the second predetermined period, and the location registration processing unit 21 may be configured to transmit, when the timer expires, the location registration request signal to the mobile switching center MME, determining that
15 the second predetermined period elapses after the data is transmitted last.

[0067]

Alternately, the timer 14 included in the AS function is configured to measure the second predetermined period, and the
20 location registration processing unit 21 may be configured to transmit the location registration request signal to the mobile switching center MME, when the location registration processing unit 21 has received the notification that the second predetermined period elapses from the AS function after the data is transmitted
25 last.

[0068]

(Second Modified Example)

With reference to Fig. 6, a mobile communication system according to a second modified example of the present invention

will be described while focusing on the difference in the mobile communication system according to the above-described first embodiment.

[0069]

5 As illustrated in Fig. 6, the configuration of the mobile station UE according to the second modified example is identical to that of the mobile station UE according to the above-described first embodiment except that a communication state management unit 24 is provided as the NAS function.

10 [0070]

 The communication state management unit 24 is configured to manage a type of communications performed via each radio link. In this case, when the type of communications is managed, QoS of the communication may be managed, or information indicating
15 whether the current service is a real time service may be managed.

[0071]

 The location registration processing unit 21 is configured to determine whether or not to transmit the location registration request signal, based on the type of communications performed via
20 the radio link in which the failure has been detected by the AS function.

[0072]

 For example, the location registration processing unit 21 is configured to transmit the location registration request signal
25 when the type of communications performed via the radio link in which the failure has been detected by the AS function is a specific communication, and not to transmit the location registration request signal when the type of communications is other than a specific communication.

[0073]

(Third Modified Example)

The location registration processing unit 21 may be configured to transmit the location registration request signal
5 (RAU: Routing Area Update, LAU: Local Area Update) to the cell under the control of a discovered mobile communication system of the WCDMA scheme, when the cell under the control of the mobile communication system of the LTE scheme is not discovered in the cell selection process.

10 [0074]

In this case, the location registration processing unit 21 may be configured to transmit the location registration request signal to the cell under the control of the discovered mobile communication system of the WCDMA scheme, even if an "ISR (Idle
15 state Signaling Reduction)" is applied.

[0075]

The operation of the above-described mobile station UE or radio base station eNB or mobile switching center MME may be implemented by a hardware, may also be implemented by a software
20 module executed by a processor, and may further be implemented by the combination of the both.

[0076]

The software module may be arranged in a storing medium of an arbitrary format such as RAM(Random Access Memory), a flash
25 memory, ROM(Read Only Memory), EPROM(Erasable Programmable ROM), EEPROM(Electronically Erasable and Programmable ROM), a register, a hard disk, a removable disk, and CD-ROM.

[0077]

Such a storing medium is connected to the processor so that the processor can write and read information into and from the storing medium. Such a storing medium may also be accumulated in the processor. Such a storing medium and processor may be arranged
5 in ASIC. Such ASIC may be arranged in the mobile station UE or the radio base station eNB or the mobile switching center MME. As a discrete component, such a storing medium and processor may be arranged in the mobile station UE or the radio base station eNB or the mobile switching center MME.

10 [0078]

Thus, the present invention has been explained in detail by using the above-described embodiments; however, it is obvious that for persons skilled in the art, the present invention is not limited to the embodiments explained herein. The present
15 invention can be implemented as a corrected, modified mode without departing from the gist and the scope of the present invention defined by the claims. Therefore, the description of the specification is intended for explaining the example only and does not impose any limited meaning to the present invention.

CLAIMS**[Claim 1]**

A mobile station comprising:

5 a first protocol function corresponding to a first protocol terminated between the mobile station and a radio base station; and

a second protocol function corresponding to a second protocol terminated between the mobile station and a mobile
10 switching center, wherein

the first protocol function is configured to activate a first timer, when a quality deterioration of a radio link established with the radio base station is detected;

the first protocol function is configured to detect a failure
15 in the radio link and to activate a second timer, when the quality deterioration of the radio link is not recovered before the first timer expires;

the first protocol function is configured to transition to an idle state, when an inter-RAT cell is discovered during a time
20 that the second timer is activated, and to notify, to the second protocol function, the failure; and

the second protocol function is configured to transmit, in response to the notification, a location registration request signal to a mobile switching center in a radio communication system
25 to which the inter-RAT cell belongs.

[Claim 2]

The mobile station according to claim 1, wherein

the second protocol function is configured to transmit, even

if an ISR is applied, the location registration request signal in response to the notification.

[Claim 3]

- 5 The mobile station according to claim 1, wherein
 the first protocol function is an AS function corresponding
to an AS that serves as the first protocol; and
 the second protocol function is an NAS function
corresponding to an NAS that serves as the second protocol.