METHODS AND APPARATUS FOR WIRELESS COMMUNICATIONS INCLUDING DIRECT PAGING IN COMBINATION WITH HOPPED DATA SIGNALING

FIELD

[0001] Various embodiments relate to wireless communications methods and apparatus and, more particularly, to wireless communications methods and apparatus which support direct peer device paging in combination with hopped data communications via an intermediary node.

BACKGROUND

[0002] One approach used to support multi-hop communications is for each node in the system to periodically broadcast a routing table identifying other nodes with which it can have a direct connection for the communication of data. In such a system a node can learn from an adjacent node's routing table that a route exists for it to communicate data with a more distance node by using the adjacent node as an intermediary.

[0003] One problem with this approach is that the cost associated with each node having to periodically communicating its routing table can be large from both an air link resource usage perspective and a power consumption perspective. The amount of air link resources required to be dedicated for conveying the broadcast routing tables can represent a relatively high level of overhead signaling, thus limiting the amount of air link resources available for traffic data signaling. In applications where the communications devices which are broadcasting routing tables are battery powered devices, power consumption can also be an issue of concern. For example, a battery powered portable wireless device, which may infrequently have a need to transmit traffic, in such a system, would tend to drain its battery by having to periodically broadcast its routing table so that other devices could benefit.

[0004] In view of the above discussion, there are a need for new and improved methods and apparatus for supporting multi-hop data signaling. Methods and apparatus that support peer discovery and multi-hop routing, yet tend to conserve battery power would be beneficial. Methods and apparatus for supporting multi-hop data signaling that do not require a proactive broadcast of a routing table would also be beneficial.

SUMMARY

[0005] Wireless communications devices in a regional network, e.g., an ad-hoc peer to peer network, discover one another via presence indicator signals which are broadcast from each device and recovered directly by other devices in the vicinity. A wireless terminal monitors for and detects presence indicator signals, updating and maintaining a list of devices currently in its vicinity with which it may seek to establish communications. A first communications device seeking to establish communications with a second communications device, currently on its list, sends a paging signal directly to the second communications device. Then, the first communications device monitors for a paging response signal from the second communications device. In response to a received paging response signal from the second device, the first communications device transmits data units, directed to the second communications device, to a third communications device which is acting as an intermediary or hop point in the data unit routing. The power levels used for the data unit signal is, in some embodiments, controlled to be lower than the power level used for the transmitted paging signal.

[0006] In various embodiments, a presence indicator signal is a lightweight signal, which communicates a small amount of information, which is sufficient for device discovery but is not sufficient by itself to determine a multi-hop route or set-up a multi-hop routing table corresponding to the device which transmitted the presence indicator signal. In some embodiments, the presence indicator signal conveys only an identifier corresponding to the device which transmitted the presence indicator signal. In some other embodiments, the presence indicator signal also conveys a limited amount of additional information including one or more of: a device type indicator, information identifying device functionality, and information used to interpret the content of the presence indicator signal. By restricting the amount of information conveyed in the presence indicator signal, air link resources and power are conserved over an approach which requires each communications device to periodically broadcast its routing table.

[0007] Following discovery operations, direct paging between devices is used, as needed, to open up a larger data channel used for sending a user data packet. The user data packet may be, and sometimes is, communicated indirectly between the two devices which exchanged direct paging signals, the data being communicated via an

intermediary node. Thus the power level used for transmitting the data signals, which typically consume a larger amount of the air link resources, can be lower than the power level for paging signals, if an intermediary node is available for relaying data, thus conserving power and lowering interference levels.

[0008] An exemplary method of operating a first communications device to communicate with a second communications device comprises: transmitting a paging signal directly to said second communications device over an airlink; and transmitting data, directed to said second communications device, to a third communications device. An exemplary first communications device, in accordance with some embodiments, comprises: a paging signal generation module for generating a paging signal directed to said second communications device; a hopped route data signal generation module for generating data units directed to said second communications device to be communicated via a third communications device; and a wireless transmitter module for transmitting said paging signal directly to said second communications device over an airlink and for transmitting data units, directed to said second communications device, to said third communications device. In one example, the first communications device and second communications device are in a region including the third communications device, e.g., the first second and third communications devices are located in the same region and are part of an ad-hoc peer to peer communications network.

[0009] While various embodiments have been discussed in the summary above, it should be appreciated that not necessarily all embodiments include the same features and some of the features described above are not necessary but can be desirable in some embodiments. Numerous additional features, embodiments and benefits of various embodiments are discussed in the detailed description which follows.

BRIEF DESCRIPTION OF THE FIGURES

[0010] Figure 1 is a drawing of an exemplary peer to peer communications network, e.g., an ad-hoc peer to peer communications network in a local region, in accordance with one exemplary embodiment.

[0011] Figure 2 is a drawing of an exemplary communications device, e.g., a peer to peer communications device, in accordance with an exemplary embodiment.

[0012] Figure 3 is a flowchart of an exemplary method of operating a first communications device, e.g., a first peer to peer communications device, to communicate with a second peer to peer communications device.

[0013] Figure 4 is a drawing illustrating an exemplary communications network and exemplary signaling in accordance with one exemplary embodiment.

DETAILED DESCRIPTION

[0014] Figure 1 is a drawing of an exemplary peer to peer communications network 100, e.g., an ad-hoc peer to peer communications network in a local region, in accordance with one exemplary embodiment. Exemplary communications network 100 includes a plurality of peer to peer wireless communications devices (device 1 102, device 2 104, device 3 106, device 4, 108, ..., device N 110). The wireless communications devices (102, 104, 106, 108, ...110) support presence indicator signaling for peer discovery, direct paging signaling between peers, and data transmissions between peers with routing which may, and sometimes does include multiple hops. Thus a first peer to peer device discovers another peer to peer device in its local vicinity via direct signaling and sends a page directly to the second device, yet the first communications device may, and sometimes does, send data, e.g., user data in a peer to peer traffic segment to the second device via an intermediary, e.g., a third node. Some of the peer to peer communications devices, e.g., device 4 108, also include a wired interface, which couples the peer to peer communications device to other nodes and/or the Internet, in addition to a wireless communications interface. Some of the peer to peer communications devices are mobile communications devices, e.g., handheld mobile communications devices.

[0015] Figure 2 is a drawing of an exemplary communications device 200, e.g., a mobile node supporting peer to peer communications, in accordance with an exemplary embodiment. Exemplary communications device 200 is, e.g., any of the communications devices (102, 104, 106, 108, 110) of network 100 of Figure 1.

[0016] Exemplary communications device 200 includes wireless receiver module 202, wireless transmitter module 204, a processor 206, user I/O devices 208, and memory 210 coupled together via a bus 212 over which the various elements may interchange data and information. In some embodiments, device 200 also includes an I/O interface 207 coupled to bus 212, e.g., a wired interface, via which communications

device 200 may be coupled to a backhaul network including other network nodes, a cellular network, and/or the Internet.

[0017] Memory 210 includes routines 218 and data/information 220. The processor 206, e.g., a CPU, executes the routines 218 and uses the data/information 220 in memory 210 to control the operation of the communications device 200 and implement methods, e.g., a method in accordance with flowchart 400 of Figure 3 or in accordance with the signaling flow described in Figure 4.

[0018] Routines 218 include a communications routine 222 and wireless terminal control routines 224. The communications routine 222 implements the various communications protocols used by the communications device 200. The wireless terminal control routines 224 include a paging signal generation module 226, a hopped route data signal generation module 228, a peer discovery module 230, a paging response signal processing module 232, a data transmission approval module 234, a transmission power control module 236, a communications peer updating module 238, and a routing information recovery module 240.

[0019] Data/information 220 includes received presence indication signals (received presence indicator signal 1 242, ..., received presence indicator signal N 244), a maintained list of identified peer communications devices in the vicinity 246, a generated paging signal 248, a received paging response signal 250, a paging response determination 252, recovered routing information 254, generated data units 256, and power level information 258. The power level information 258 includes presence signal level information 260, paging signal level information 262 and data unit signal level information 264.

[0020] Wireless receiver module 202, e.g., an OFDM receiver, is coupled to receive antenna 214 via which the communications device 200 receives signals from other communications devices in the region. Received signals include presence indicator signals, paging response signals, and routing information signals. Wireless receiver module 202 is for receiving, prior to receiving a paging signal, a presence indicator signal communicated over an airlink directly from a second communications device. Wireless receiver module 202 is also for receiving, following transmission of a paging signal, and prior to transmitting data, a paging response signal, which is in response to the paging signal, over an airlink directly from the second device. Wireless receiver module 202 is also for receiving a signal from a third communications device,

prior to transmitting data , directed to said second communications device, to said third communications device, e.g., the signal from the third communications device being a routing information signal. The second communications device is, e.g., a peer communications device with which communications device 200 exchanges direct paging signals, while the third communications device is an intermediary node, used by communications device 200 and the second communications device to communicate data between device 200 and the second device.

[0021] Wireless transmitter module 204, e.g., an OFDM transmitter, is coupled to transmit antenna 216 via which the communications device 200 transmits signals to other communications devices in the region. In some embodiments, the same antenna is used for the receiver and the transmitter. Transmitted signals include paging signals and data unit signals. Wireless transmitter module 204 transmits paging signals directly to a second communications device over an airlink and transmits data units directed to the second communications device to a third communications device. Thus paging signaling is direct, while traffic data signaling may be, and sometimes is, indirect signaling including multiple hops. The data units may include user data, e.g., peer to peer traffic data conveying text, audio, and/or image data.

[0022] Paging signal generation module 226 is for generating a paging signal directed to a second communications device. Hopped route data signal generation module 228 is for generating data units, e.g., packets, directed to a second communications device to be communicated via a third communications device. The data units are, e.g., packets of peer to peer traffic data conveying user data such as voice, image and/or text data.

[0023] Peer discovery module 230 is for determining a source of a received data indicator signal, e.g., determining whether a received data indicator signal is from the second communications device. Thus peer discovery module 230 identifies the source of the received indicator signal, e.g., by a decoding operation which correlates signal characteristic information, e.g., tone used, or recovered bits with a mapping to a specific wireless terminal. Paging response signal processing module 232 processes a received paging response signal and determines if the received paging response signal represents a positive response to a previously transmitted paging signal from device 200. Data transmission approval module 234 controls the transmission of data to a second device to proceed in response to a received paging response signal.

[0024] Transmission power control module 236, using power level information 258, in some embodiments, controls the transmitter module 204 to transmit a paging signal at a higher power level per information bit than the power level per information bit used for transmitting data units. Transmission power control module 236, using power level information 258, in some embodiments, controls the transmitter module 204 to transmit a paging signal at a higher total power level than the total power level used for transmitting data units.

[0025] Communications peer updating module 238 updates a list of devices with which device 200 can communicate based on the received presence indicator signals. In some embodiments, a presence indicator signal is a signal which communicates an identifier corresponding to another device, e.g., a second device. In various embodiments, the presence indicator signal is a lightweight signal used for discovery, and the indicator signal by itself is not sufficient to determine multi-hop routing or set-up a multi-hop routing table. In some embodiments, a presence indicator signal communicates only an identifier used to identify corresponding to the device which transmitted the presence indicator signal. In some embodiments, the presence indicator signal communicates information in a set of information consisting of one or more of the following: i) one or more identifiers corresponding to the device which transmitted the presence indicator signal, ii) information indicating the type of the device which transmitted the presence indicator signal, iii) functionality supported by the device which transmitted the presence indicator signal, and iv) information used to interpret the content of the presence indicator signal. In various embodiments, the information used to interpret the content of the presence indicator signal may include, e.g., flags indicating how to process content, information indicating the number of fields in a message, information indicating the number of bits in each field, and/or a message type indicator.

[0026] Routing information recovery module 240 recovers a signal including information from a third device indicating that the third device can act as an intermediary between device 200 and a second communications device for the communication of data. In some embodiments, the signal from the third communications device includes an identifier corresponding to the third device.

[0027] Received presence indicator signals (242, 244) represent signals which are received by wireless receiver module 202 and processed by peer discovery module

230. List of identified peer communications devices in vicinity 246 is a list being maintained and updated by peer discovery module 230 which identifies devices with which communications device 200 can seek to establish a page. List 246 includes peer devices corresponding to detected presence indicator signals (242, 244).

[0028] Generated paging signal 248 is an output of paging signal generation module 228, is a direct paging signal, and is transmitted by wireless transmitter module 204. Received paging response signal 250 is a signal received, by wireless receiver module 202 and processed by paging response signal processing module 232. Paging response determination 252 is a determination performed by paging response signal processing module 232, e.g., determining if a positive response to the paging signal 248 was received. In some embodiments, a detected paging response signal from the device to which the page was directed indicates a positive response, and the lack of a page response signal indicates a negative response. In some embodiments, there is a predetermined relationship between the air link resource on which the page was transmitted and the air link resource corresponding to the page response signal. In some such embodiments, a page response signal does not include a device identifier corresponding to the device which transmitted the page response signal.

[0029] Recovered routing information 254 includes information recovered from a received routing information signal received by wireless receiver module 202 and processed by routing information recovery module 240. Generated data units 256 is an output of hopped route data signal generation module 228. Generated data units 256 is, e.g., a peer to peer traffic signal conveying user data directed to a second communications device, which device 200 has previously paged and previously received a positive page response, but transmitted by wireless transmitter module 204 to a third device which is to act as intermediary hop point in delivery of the traffic data to the second device.

[0030] Power level information 258 includes information used by transmission power level control module 236 to control the wireless transmitter device 204 to transmit different types of signals at different power levels. In some embodiments, the presence signal level information 260 and the data unit signal level information 264 indicates that the presence level signal is to be transmitted at a higher power level per information bit than the transmit power level per information bit for a data unit signal. In some embodiments, the paging signal level information 262 and the data unit signal

level information 264 indicates that the paging level signal is to be communicated at a higher power level per information bit than the power level per information bit for a data unit signal. In some embodiments, the presence signal level information 260 and the data unit signal level information 264 indicate that the presence level signal is to be transmitted at a higher total power level than the total power level for a data unit signal. In some embodiments, the paging signal level information 262 and the data unit signal level information 264 indicates that the paging level signal is to be transmitted at a higher total power level than the total power level for a data unit signal. In some embodiments, the presence signal level information 260 and the data unit signal level information 264 indicates that the presence level signal is to be transmitted at a higher power level per air link resource unit than the transmit power level per air link resource unit for a data unit signal. In some embodiments, the paging signal level information 262 and the data unit signal level information 264 indicates that the paging level signal is to be communicated at a higher power level per air link resource unit than the power level per air link resource unit for a data unit signal. In some embodiments, the air link resource unit is an OFDM tone-symbol, representing one tone for one OFDM symbol transmission time interval.

[0031] Figure 3 is flowchart 400 of an exemplary method of operating a first communications device, e.g., a first peer to peer communications device, with a second communications device, e.g., a second peer to peer communications device. The first and second communications devices are in a region with a third communications device, e.g., a third peer to peer communications device. Operation of the exemplary method starts in step 402 where the first communications device is powered on and initialized. Operation proceeds from start step 402 to step 404.

[0032] In step 404 the communications device monitors for the presence of indicator signals from other communications devices in the region. During the monitoring the first communications device may, and sometimes does, perform sub-step 406 in which the first communications device receives a presence indicator signal communicated directly over an airlink from a second communications device. In some embodiments, the presence indicator is a signal which communicates an identifier corresponding to the second device. In some such embodiments, the presence indicator signal is a signal which communicates only an identifier corresponding to the second device. In various embodiments, the presence indicator signal communicates

information in a set of information consisting of: i) one or more identifiers corresponding to the second communications device; (ii) information indicating the type of the second communications device; (iii) functionality supported by the second communications device; and (iv) information used to interpret the content of the presence indicator signal. Information used to interpret the content of the presence indicator signal may include, e.g., flags indicating how to process content, information indicating the number of fields in the message, information indicating the number of bits in each filed, information indicating a message type indicator, etc. Operation proceeds from step 404 to step 408.

[0033] In step 408, the communications device determines whether or not a presence indicator signal was received from the second device and proceeds as a function of whether or not the presence indicator signal was received. If a presence indicator signal was not received from the second device, then operation proceeds from step 408 back to step 404, e.g., to perform monitoring for presence indicator signals during the next interval during which presence indicator signals are communicated. However, if a presence indicator signal was received from the second device, then operation proceeds from step 408 to step 410.

[0034] In step 410, the first communications device updates a list of devices with which said first communications device can communicate based on the received presence indicator signal. Then, in step 412 the first communications device decides if it seeks to transmit traffic to the second device. If it does not wish to transmit traffic to the second device, operation proceeds from step 412 back to step 404, e.g. to perform monitoring for presence indicator signals during the next interval during which presence indicator signals are communicated. However, if the first communications device seeks to transmit traffic to the second device, then operation proceeds from step 412 to step 414.

[0035] In step 414 the first communications device transmits a paging signal directly to said second communications device over an airlink. Then, in step 416 the first communications device monitors to receive a paging response signal from the second device. During the monitoring, sub-step 418 may be, and sometimes is, performed. In sub-step 418 the first communications device receives a paging response signal over an airlink directly from the second communications device. Operation proceeds from step 416 to step 418.

[0036] If in step 420, the first communications device determines that a paging response signal was not received from the second communications device, then operation proceeds from step 420 to step 404. However, if a paging response signal, e.g., a positive response signal in response to the request of transmitted signal of step 414, was received from the second communications, then operation proceeds from step 420 to step 422. In step 422 the first communications device monitors for signals from other communications devices. In some embodiments, step 422 may, and sometimes does include sub-step 424. In sub-step 424 the first communications device receives a signal from a third communications device, e.g., a routing information signal identifying that the third communications device can route traffic signals to the second communications device. In some embodiments, the signal from the third communications device includes an identifier corresponding to the third device. Operation proceeds from step 422 to step 426.

[0037] In step 426, the first communications device transmits data, directed to the second communications device, to the third communications device. In various embodiments, the transmitted data includes user data. For example, the user data is data corresponding to voice, image, and/or a file and is communicated in a peer to peer traffic channel segment. In some embodiments, the transmitted paging signal of step 414 is transmitted at a higher per tone average power level than is the data transmitted in step 426. In some embodiments, the transmitted paging signal of step 414 is transmitted at a higher power level per information bit than the power level per information bit that the data transmitted in step 426 is transmitted at. In some embodiments, the transmitted paging signal of step 414 is transmitted at a higher total power level than the total power level that the data transmitted in step 426 is transmitted at. Operation proceeds from step 426 to step 404, where the first communications device monitors for presence indicator signals, e.g., during a subsequent interval used to communicate presence indicator signals.

[0038] Figure 4 is a drawing 500 illustrating an exemplary communications network and exemplary signaling in accordance with one exemplary embodiment. The exemplary communications network includes first, second and third communications devices (502, 504 and 506), e.g., peer to peer communications devices, which are situated in a region such that the third device 504 is located between the first and second devices (502, 506). In this example, the devices (502, 504, 506) in the network follow a

recurring timing structure which includes a discovery interval 501, a paging interval 503, and a traffic interval 505. Devices (502, 504, 506) are, e.g., devices in accordance with device 200 of Figure 200 and/or devices devices which implement the method of flowchart 400 of Figure 3.

[0039] During the discovery interval 501 the device generate and transmit presence indicator broadcast signals. For example, second communications device generates and transmits a device 2 presence indicator broadcast signal 510 as indicated by box 508. Similarly first communications device 502 generates and transmits a device 1 presence indicator broadcast signal 514, and third communications device 504 generates and transmits a device 3 presence indicator broadcast signal 516.

[0040] First communications device 502 receives device 2 presence indicator signal 510 and device 3 presence indicator signal 516 as indicated by block 512. Similarly, second communications device 506 receives device 1 presence indicator signal 514 and device 3 presence indicator signal 516, and third communications device 504 receives device 1 presence indicator signal 514 and device 2 presence indicator signal 510.

[0041] In response to the received presence indicator signals, first communications device 502 updates a list identifying devices present with which the first device may communicate, as indicated by box 518. The first communications device decides that it would like to communicate traffic signals with the second communications device 506 and thus generates and transmits a paging signal 522 to the second communications device 506 during the paging interval 503 as indicated by block 520. The second communications device 506 receives the paging signal 522 as indicated by block 524, and decides to generate and transmit a paging response signal 528, e.g., a positive acknowledgement to the paging request as indicated by block 526. First communications device 502 receives the paging response signal 528 as indicated by block 530, which allows the first communications device 502 to proceed with communication of traffic to the second communications device 506.

[0042] The third communications device 504 generates and transmits a routing information signal 534 to the first communications device 502 as indicated by block 532. The routing information signal is, e.g., a signal indicating that third communications device is available to serve as an intermediary for the routing of traffic packets between the first communications device 502 and the second communications

device 506. The routing information signal 534 is received by first communications device 502 as indicated by block 536. The first communications device 502 uses the routing information in determining routing for traffic signals directed to the second communications device 506. In this example, the first communications device 502 decides to transmit traffic information intended to be delivered to the second communications device 506 to the third communications device 504, which is available to serve as an intermediary. Thus the first communications device 502 generates and transmits traffic signal 540, directed to the second device 506, to the third communications device 504, as indicated by block 538. The third communications device 504 receives traffic signal 540, processes the signal 540 and retransmits the traffic information as traffic signal 543, as indicated by block 542. The second communications device 506 receives the traffic signal 543 and recovers the traffic data/information which was communicated by first communications device 502, as indicated by clock 544.

[0043] The techniques of various embodiments may be implemented using software, hardware and/or a combination of software and hardware. Various embodiments are directed to apparatus, e.g., mobile nodes such as mobile terminals, base stations, communications system. Various embodiments are also directed to methods, e.g., method of controlling and/or operating mobile nodes, base stations and/or communications systems, e.g., hosts. Various embodiments are also directed to machine, e.g., computer, readable medium, e.g., ROM, RAM, CDs, hard discs, etc., which include machine readable instructions for controlling a machine to implement one or more steps of a method.

[0044] In various embodiments nodes described herein are implemented using one or more modules to perform the steps corresponding to one or more methods, for example, signal processing, message generation and/or transmission steps. Thus, in some embodiments various features are implemented using modules. Such modules may be implemented using software, hardware or a combination of software and hardware. Many of the above described methods or method steps can be implemented using machine executable instructions, such as software, included in a machine readable medium such as a memory device, e.g., RAM, floppy disk, etc. to control a machine, e.g., general purpose computer with or without additional hardware, to implement all or portions of the above described methods, e.g., in one or more nodes. Accordingly,

among other things, various embodiments are directed to a machine-readable medium including or otherwise embodying machine executable instructions for causing a machine, e.g., processor and associated hardware, to perform one or more of the steps of the above-described method(s). Some embodiments are directed to a device, e.g., communications device, including a processor configured to implement one, multiple or all of the steps of one or more methods of the invention.

[0045] In some embodiments, the processor or processors, e.g., CPUs, of one or more devices, e.g., communications devices such as access nodes and/or wireless terminals, are configured to perform the steps of the methods described as being performed by the communications device. The configuration of the processor may be achieved by using one or more modules, e.g., software modules, to control processor configuration and/or by including hardware in the processor, e.g., hardware modules, to perform the recited steps and/or control processor configuration. Accordingly, some but not all embodiments are directed to a device, e.g., communications device, with a processor which includes a module corresponding to each of the steps of the various described methods performed by the device in which the processor is included. In some but not all embodiments a device, e.g., communications device, includes a module corresponding to each of the steps of the various described methods performed by the device in which the processor is included. The modules may be implemented using software and/or hardware.

[0046] Some embodiments are directed to a computer program product comprising a computer-readable medium comprising code for causing a computer, or multiple computers, to implement various functions, steps, acts and/or operations, e.g. one or more steps described above. Depending on the embodiment, the computer program product can, and sometimes does, include different code for each step to be performed. Thus, the computer program product may, and sometimes does, include code for each individual step of a method, e.g., a method of controlling a communications device or node. The code may be in the form of machine, e.g., computer, executable instructions stored on a computer-readable medium such as a RAM (Random Access Memory), ROM (Read Only Memory) or other type of storage device. In addition to being directed to a computer program product, some embodiments are directed to a processor configured to implement one or more of the various functions, steps, acts and/or operations of one or more methods described

above. Accordingly, some embodiments are directed to a processor, e.g., CPU, configured to implement some or all of the steps of the methods described herein. The processor may be for use in, e.g., a communications device or other device described in the present application.

[0047] While described in the context of an OFDM system, at least some of the methods and apparatus of various embodiments are applicable to a wide range of communications systems including many non-OFDM and/or non-cellular systems.

[0048] Numerous additional variations on the methods and apparatus of the various embodiments described above will be apparent to those skilled in the art in view of the above description. Such variations are to be considered within the scope. The methods and apparatus may be, and in various embodiments are, used with CDMA, orthogonal frequency division multiplexing (OFDM), and/or various other types of communications techniques which may be used to provide wireless communications links between access nodes and mobile nodes. In some embodiments the access nodes are implemented as base stations which establish communications links with mobile nodes using OFDM and/or CDMA. In various embodiments the mobile nodes are implemented as notebook computers, personal data assistants (PDAs), or other portable devices including receiver/transmitter circuits and logic and/or routines, for implementing the methods.

CLAIMS

1. A method performed by a first communications device to communicate with a second communications device, said first and second communications device being in a region including a third communications device, the method comprising:

transmitting a paging signal to said second communications device over an airlink; and

transmitting data, to be directed to said second communications device via said third communications device, to said third communications device.

2. The method of claim 1, wherein said data includes user data.

3. The method of claim 1, further comprising:

receiving, prior to transmitting said paging signal, a presence indicator communicated over the airlink directly from the second communications device.

4. The method of claim 3, further comprising:

receiving, following transmission of said paging signal and prior to transmitting said data, a paging response signal, which is in response to said paging signal, over the airlink directly from the second device.

5. The method of claim 4, wherein said step of transmitting data directed to said second device is performed in response to receiving said paging response signal.

6. The method of claim 3, wherein said paging signal is transmitted at a higher power level per information bit than said data.

7. The method of claim 3, wherein said paging signal is transmitted at a higher total power level than said data.

8. The method of claim 6, wherein said presence indicator is a signal which communicates an identifier corresponding to the second device.

9. The method of claim 8, wherein said presence indicator signal communicates only said identifier.

10. The method of claim 8, wherein said presence indicator signal communicates information in a set of information consisting of one or more of the following: i) one or more identifiers corresponding to said second communications device; ii) information indicating the type of the second device; iii) functionality supported by the second device; and iv) information used to interpret the content of the presence indicator signal.

11. The method of claim 8, further comprising:

updating a list of devices with which said first communications device can communicate based on the received presence signal.

12. The method of claim 8, further comprising:

receiving a signal from the third communications device prior to said step of transmitting data, directed to said second communications device, to said third communications device.

13. The method of claim 12, wherein said signal from the third communications

device includes an identifier corresponding to the third device.

14. A first communications device for communicating with a second communications device, said first and second communications device being in a region including a third communications device and said third communicates device acting as an intermediary node between said first and second communications devices for the communication of data, the first communications device comprising:

a paging signal generation module for generating a paging signal directed to said second communications device;

a hopped route data signal generation module for generating data units directed to said second communications device to be communicated via a third communications device; and

a wireless transmitter module for transmitting said paging signal directly to said second communications device over an airlink and for transmitting data units, directed to said second communications device, to said third communications device.

15. The first communications device of claim 14, wherein said data units include user data.

16. The first communications device of claim 14, further comprising:

a wireless receiver module for receiving, prior to transmitting said paging signal, a presence indicator communicated over the airlink directly from the second communications device; and

a peer discovery module for determining if a received presence indicator signal is from the second communications device.

17. The first communications device of claim 16, wherein said wireless receiver module is also for receiving, following transmission of said paging signal and prior to transmitting said data, a paging response signal, which is in response to said paging signal, over the airlink directly from the second device, the first communications device further comprising:

a paging response signal processing module for processing a received paging response signal and determining if a received paging response signal represents a positive response to the transmitted paging signal.

18. The first communications device of claim 17, further comprising:

a data transmission approval module for controlling the transmission of data directed to said second device to proceed in response to a received paging response signal.

19. The first communications device of claim 16, further comprising:

a transmission power control module for controlling said transmitter module to transmit said paging signal at a higher power level per information bit than said data units.

20. The first communications device of claim 16, further comprising:

a transmission power control module for controlling said transmitter module to transmit said paging signal at a higher total power level than said data units.

21. The first communications device of claim 19, wherein said presence indicator is a signal which communicates an identifier corresponding to the second device.

22. The first communications device of claim 21, wherein said presence indicator signal communicates only said identifier.

23. The first communications device of claim 21, wherein said presence indicator signal communicates information in a set of information consisting of one or more of the following: i) one or more identifiers corresponding to said second communications device; ii) information indicating the type of the second device; iii) functionality supported by the second device; and iv) information used to interpret the content of the presence indicator signal.

24. The first communications device of claim 21, further comprising:

a communications peer updating module for updating a list of devices with which said first communications device can communicate based on the received presence signal.

25. The first communications device of claim 21, wherein said wireless receiver is also for: receiving a signal from the third communications device prior to said step of transmitting data, directed to said second communications device, to said third communications device, the first communications device further comprising:

a routing information recovery module for recovering information from the third device indicating that the third communicates device can act as an intermediary between the first and second communications devices for the communication of data.

26. The first communications device of claim 25, wherein said signal from the third

communications device includes an identifier corresponding to the third device.

27. A first communications device for communicating with a second communications device, said first and second communications device being in a region including a third communications device and said third communicates device acting as an intermediary node between said first and second communications devices for the communication of data, the first communications device comprising:

paging signal generation means for generating a paging signal directed to said second communications device;

hopped route data signal generation means for generating data units directed to said second communications device to be communicated via a third communications device; and

wireless transmitter means for transmitting said paging signal directly to said second communications device over an airlink and for transmitting data units, directed to said second communications device, to said third communications device.

28. The first communications device of claim 27, wherein said data units include user data.

29. The first communications device of claim 27, further comprising:

wireless receiver means for receiving, prior to transmitting said paging signal, a presence indicator communicated over the airlink directly from the second communications device; and

peer discovery means for determining if a received presence indicator signal is from the second communications device.

30. The first communications device of claim 29, wherein said wireless receiver means is also for receiving, following transmission of said paging signal and prior to transmitting said data, a paging response signal, which is in response to said paging signal, over the airlink directly from the second device, the first communications device further comprising:

paging response signal processing means for processing a received paging response signal and determining if a received paging response signal represents a positive response to the transmitted paging signal.

31. A computer readable medium comprising:

code for causing a processor in a first communications device to control the first communications device to transmit a paging signal directly to a second communications device over an airlink, said first and second communications device being in a region including a third communications device and said third communicates device acting as an intermediary node between said first and second communications devices for the communication of data; and

code for causing the processor to control said first communications device to transmit data, directed to said second communications device, to said third communications device.

32. The computer readable medium of claim 31, wherein said data includes user data.

33. The computer readable medium of claim 31, wherein the computer-readable

medium further comprises:

code for causing the processor in the first communications device to receive, prior to transmitting said paging signal, a presence indicator communicated over the airlink directly from the second communications device.

34. The computer readable medium of claim 33, wherein the computer readable medium further comprises:

code for causing the processor in the first communications device to receive, following transmission of said paging signal and prior to transmitting said data, a paging response signal, which is in response to said paging signal, over the airlink directly from the second device.

35. An apparatus comprising:

a processor for use in a first communications device, the processor being configured to:

transmit a paging signal directly to a second communications device over an airlink, said first and second communications devices being in a region including a third communications device and said third communicates device acting as an intermediary node between said first and second communications devices for the communication of data; and

transmit data, directed to said second communications device, to said third communications device.

36. The apparatus of claim 35, wherein said data includes user data.

37. The apparatus of claim 35, wherein the processor is further configured to:

receive, prior to transmitting said paging signal, a presence indicator communicated over the airlink directly from the second communications device.

38. The apparatus of claim 37, wherein the processor is further configured to:

receive, following transmission of said paging signal and prior to transmitting said data, a paging response signal, which is in response to said paging signal, over the airlink directly from the second device.