

Specification of the Patent of Invention for: **"COOLING COMPRESSOR CONTROL SYSTEM AND METHOD"**

The present invention relates to a system and a method that enable one to control the stopping (braking) behavior of a reciprocating compressor.

DESCRIPTION OF THE PRIOR ART

Hermetic compressor of reciprocating type comprise rod-crank-and-piston type with reciprocating movement and are widely used in the cooling-equipment, household and commercial industry.

Reciprocating compressors may be of the fixed-capacity type, wherein the control of two fixed-velocity states (ON/OFF) is carried out upon turning on the compressor at a maximum temperature and turning off the compressor at a minimum temperature, or varying-capacity compressors, wherein the control is carried out by some electromechanical device or electronic circuit, capable of responding to a programming dependent upon variables to be controlled on the cooling equipment, as for instance the inner temperature of the compartments, wherein the compressor acts in reciprocating operation cycles at varying velocities and stop.

During the periods of operation, the reciprocating compressors are responsible for circulating the cooling gas through the cooling circuit, the rod-crank-and-piston mechanism being responsible for carrying out cyclic movements in which the piston raises the gas pressure during its advance and the cooling gas applied a contrary stress onto the mechanism and to the turning axle. This stress on the piston and the consequent reaction on the mechanism and turning axle varies significantly throughout a turn of the turning axle, the variation being directly proportional to the values of cooling-gas pressure (the greater the difference between the pressures of evaporation and of condensation of the cooling circuit, the greater it is).

Thus, with cooling equipment that uses reciprocating compressors, at the moments when the compressor is turned off the mechanism still turns due to the inertia of the assembly, mainly the inertia of the motor rotor, which imposes the turning movement. The inertia movement causes a jolt

during the stopping of the compressor due to a contrary impulse on the piston, caused by the different in pressure of the gas. The impulse is caused by the abrupt stopping of the axle or by the turning movement in an opposite direction at the last turn of the axle because the piston is not capable of overcoming the pressure. Thus, the gas is compressed and uncompressed in an alternating movement, which may cause problems to the reciprocating compressor.

Because of this, the stopping jolt is typical in reciprocating compressors for cooling. Generally, one designs suspension-spring systems inside the compressor, which support the whole assembly, so as to absorb impulses and attenuate them, and not cause problems, such as spring breaks or stopping noises due to shocks between parts. The greater the difference in pressure under which the compressor is operating, the greater the stopping impulses will be.

One of the engineering solutions to the jolt problem when the compressor is stopping is a balanced design of the suspension springs. The main function of the suspension springs is to attenuate the transmission of the vibrations generated during the normal operation in the pumping system due to the reciprocating movement of the piston, thus preventing these vibrations from passing on to the outer compressor body and, as a result, to the cooler, which causes noises. In this way, the springs should then be soft enough to attenuate the normal-functioning vibration, besides absorbing the stopping impulse. On the other hand, the springs should not be designed to be excessively soft to the point of allowing a long displacement of the assembly during this stopping impulse, since this may cause shocks at the mechanical stops, raising noises. Similarly, the design should be adopted so as not to cause excessive stress on the springs to the point of causing fatigue or breakage thereof.

It is possible to note that the stopping jolt is more intense on compressors that operate with greater differences in pressure and on compressors that have smaller inner mass of their components. Besides, factors linked to the pressure condition and to the assembly mass make it difficult to

design the suspension springs, and the more one wants to attenuate the normal-operation vibration the higher this project will be, especially in operation at low rotations. Because of this, one encounters even more severe contour conditions, which are difficult to be met.

5 In designs where there are severe pressure conditions, optimization of the assembly weight and the need to reduce considerably the vibration level in low-rotation operation, the solution to the spring design may not meet all the desired conditions.

10 Another example of a technique that controls the deceleration of a motor can be seen in the north-american document US 5,986,419. This document applies a braking torque for deceleration of the mechanical assembly, but only after detecting that the turn velocity is below a velocity level. Since this velocity level is null ($v=0$), the braking torque is only applied if the motor is rotating at the wrong direction, which is a completely different problem and solution.

OBJECTIVES OF THE INVENTION

 Therefore, it is a first objective of this invention to provide a system and a method for reducing the rigidity of the springs of the suspension system, thus minimizing the vibration level during normal operation.

20 It is another objective of this invention to provide a system and a method that are capable of reducing the demand for robustness of the suspension system, maintaining the level of reliability and useful life of the springs, by preventing breakage thereof.

25 A further objective of this invention is to provide a system and a method that are capable of enabling the compressor to operate in conditions of high difference in pressure, under which it can be turned off without undesired impacts and noises being generated.

BRIEF DESCRIPTION OF THE INVENTION

30 The objectives of the invention are achieved by means of a reciprocating compressor comprising at least one mechanical assembly, which includes at least one compression mechanism and one motor; and at least one electronic control; the electronic control is configured to detect a turn ve-

locity of the compression mechanism and to apply a braking torque to the mechanical assembly during the stopping process of the compressor after detecting that the turn velocity is below a predefined velocity value, the braking torque being initiated at a next moment after a compression stroke has been completed; and the braking torque being configured for gradual deceleration of the turn velocity such that the turn velocity of the compression mechanism has zero value at the moment when the new compression stroke is about to begin.

Additionally, the objectives are achieved by a reciprocating compressor control method, comprising the steps of:

(a) detecting a turn velocity of a mechanical assembly that comprises at least the compression mechanism and one motor;

(b) comparing the turn velocity with a predefined velocity value; and

(c) applying a braking torque for deceleration of the mechanical assembly during the stopping process of the compressor after detecting that the turn velocity is below a predefined velocity value, the braking torque (36) being initiated at a next moment (35) after a compression stroke has been completed;

wherein step (c) is configured to cause gradual deceleration of the turn velocity so that the turn velocity of the compression mechanism has zero value at the moment when a new compression stroke is about to begin.

The objectives are further achieved by a cooling compressors control system, the system comprising at least: one electronic control; and one reciprocating compressor comprising at least one mechanical assembly, which includes at least one compression mechanism and one motor; wherein the electronic control is configured to detect a turn velocity of the compression mechanism and to apply a braking torque to the mechanical assembly during the stopping process of the compressor after detecting that the turn velocity is below a predefined velocity value, the braking torque being initiated at a next moment after a compression stroke has been completed; the braking torque being configured for gradual deceleration of the turn velocity

such that the turn velocity of the compression mechanism has zero value at the moment when the new compression stroke is about to begin.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The present invention will now be described in greater detail with reference to the following figures:

Figure 1 - representation of a cooling system;

Figure 2 - representation of the control of a compressor, as well as the main subsystems inside the compressor;

10 Figure 3 - representation of details of the mechanical subsystem of a reciprocating compressor;

Figure 4 - representation of the compression process and of the velocity of the axle of a compressor;

15 Figure 5 - representation of the compression process and of the velocity of the axle of a compressor during the start according to the state of the art; and

Figure 6 - representation of the compression process and of the velocity of the axle of a compressor during the start according to the present invention.

DETAILED DESCRIPTION OF THE FIGURES AND OF THE INVENTION

20 As represented in figure 1, a cooling system comprises a reciprocating compressor 3, which is fed by an electric power network 1 and has an electronic controller 2 capable of controlling the operation of a reciprocating compressor 3. The reciprocating compressor 3 drives a cooling gas in a gas-circulation closed circuit 18, creating a cooling-gas flow 78 inside this
25 circuit, directing the gas to a condenser 5. After the condenser 5, the cooling gas goes through a flow-cooling device 6, which may be, for instance, a capillary tube. Then, the gas is led to an evaporator 4 and later returns to the reciprocating compressor 3, restarting the gas-circulation circuit.

30 Figure 2 illustrates a focus in subsystems inside the reciprocating compressor, the reciprocating compressor 3 being formed by a housing 17, suspension springs 11 that are responsible for damping the mechanical vibration generated by the movement of a mechanical assembly 12, formed by

the motor 9 and the compression mechanisms 8, which are interconnected mechanically by the axle 10 that transmits torque and rotary motion.

The mechanical vibrations generated by the compression mechanism 8, due to the unbalancing and torque variation, are filtered by the suspension springs 11. For this reason, the suspension springs 11 are projected so as to have a low elasticity coefficient (that is, as soft as possible), in order to increase the effectiveness of vibration filtration. However, this design increases the amplitude of the oscillation transient and displacement of the mechanical assembly 12 during the stop of the reciprocating compressor 3, if the suspension springs 11 are made to soft, being capable of causing mechanical shocks between the mechanical assembly 12 (drive and compression) against the housing 17 of the reciprocating compressor 3, generating acoustic noise and possible fatigues or breaks of the suspension springs 11.

Figure 3 shows the compression mechanism 8, which comprises a turning axle 10, to which the rod 16 is coupled. The rod 16 modifies the rotary motion of the turning axle 10 during the reciprocating motion, which drives a piston 15 to move inside a cylinder 13, causing the compressed gas to circulate through a valve plate 14. This mechanism compresses the gas, so that high differences in pressure and high reaction torque peaks are generated. The rotary motion of the turning axle 10 is kept by its own inertia, its average velocity being maintained by the production of torque by the motor 9.

Figure 4 presents an operation torque 20, generated by the motor 9, which encounters a reaction torque 21 of the compression mechanism 8, configured to cause a variation of a turning velocity 23 of the turning axle 10 of the reciprocating compressor 3. This turning velocity 23 of the turning axle 10 varies throughout a compression cycle/stroke, which begins at the lower dead point of the piston 15, generally when the turn angle is zero, reaching the maximum compression and the maximum reaction torque 21 generally at a lower angle close to 180 degrees of turn, thus causing deceleration of the axle.

As can be seen in figure 5, during the stopping process of the reciprocating compressor 3 according to the state of the art, at the stopping

moment 22 when the motor 9 stops generating operation torque 20, the compression mechanism 8 continues its inertia movement fed by the kinetic energy stored on the turning axle 10, the turn velocity 23 of the turning axle 10 decreasing gradually with every compression stroke that is completed, extracting kinetic energy from the turning mass axle 10, until the impulse moment 24, when, due to the very reduced rotation of the turning axle there is not sufficient energy to complete the compression stroke.

Thus, the turning axle 10 loses turn velocity 23 quickly, that is, a high deceleration (rpm/s) takes place, which causes a reverse impulse in the compression mechanism 8 at the impulse moment 24. The deceleration of the compression mechanism 8 in a very short period of time drives the whole mechanical assembly 12 and may cause the turning axle 10 to turn in the opposition direction. The kinetic energy of the turning axle 10 depends on the rotation (squared) and on the inertia of the turning axle 10. The reverse impulse that takes place at the abrupt stop causes a strong impulse on the mechanical assembly 12 and, in this way, causes a large displacement and possible mechanical shock between mechanical assembly 12 and housing 17, thus causing noise and fatigue of the suspension springs 11.

Figure 6, in reversed way, shows a graph according to the present invention, which shows the solution of the problems indicated, wherein, during the stopping process of the reciprocating compressor 3, at the braking moment 32 when the motor 9 stops generating operation torque, the compression mechanism 8 continues its inertia movement fed by the kinetic energy stored on the turning axle 10, the turn velocity 23 of the turning axle 10 decreasing gradually until the rotation of the turning axle 10 will be lower than a predefined velocity value 34. When the electronic controller 2 detects that the rotation of the turning axle 10 reaches the predefined velocity value 34, at the following moment 35 the electronic controller 2 applies a braking torque 36 in the opposite direction to the turn of the compression mechanism 8.

Preferably, this detection is made by the electronic control 2, which detects the time between the changes of rotor position. As can be seen in figures 5 and 6, the period of stroke of the piston (0° to 360°) varies

in an inversely proportional way with respect to the velocity. In this way, the electronic control 2 can be configured to detect the period which the compression mechanism 8 needs to carry out its movement (from 0° to 360°) and compare such a period with a maximum reference time. This maximum reference time is related with the period which the compression mechanism 8 needs to carry out its movement at the predefined velocity value 34. In this way, one can state that the braking torque 36 is applied when the rotation velocity of the turning axle 10 is below a predefined velocity value 34 that is predefined by the electronic control 2. In the preferred embodiments of the present invention, the braking torque 36 is generally applied when the reaction torque 31 goes through one of its maximum values (peaks), to facilitate the braking by using the inertia of the motor 9, which is already under deceleration. The most relevant aspects of this braking torque 36 are its intensity, which depends on the level of current that will circulate through the windings of the motor 9, and its duration, which may go from the moment when it reaches the predefined velocity value 34 until complete stop of the motor 9.

The application of the braking torque 36 may be made in various ways. Preferably one employs the methods of adding a resistance between the windings of the motor 9, which causes the current generated by the movement of the motor 9 to circulate in a closed circuit and generates a torque contrary to the motion (which may also be carried out by means of a PWM modulation of the inverter that controls the motor 9), or the application of a current contrary to that applied to the motor 9 when it is in operation.

This following 35 following the predefined velocity value 34 comprises much of the last turn of the turning axle 10, beginning a braking period 37 of the turning axle 10. In this way, one prevents the last compression stroke from taking place, thus preventing also a strong reverse impulse on the compression mechanism 8. In this way, the deceleration of the turning axle 10 takes place and is distributed throughout the last turn in a controlled manner, resulting in a deceleration value (rpm/s) that is substantially lower than the one observed in the present-day art. In order for this event to take place, the predefined rotation velocity value 34 of the turning axle 10 should

preferably be sufficient for the kinetic energy stored on the turning axle 10 of the reciprocating compression 3 to be capable of completing a complete compression stroke, thus preventing the sudden deceleration and jolt of the compression mechanism 8.

5 Thus, the present invention enables the suspension springs 11 of the mechanism 12 to be designed so as to have low elasticity coefficient, being very effective to filter vibration, and still prevents shocks of the mechanical assembly 12 with the housing 17 of the reciprocating compressor 3. Besides, the present invention prevents high displacement of this mechanical
10 assembly 12 during the stopping transient, minimizing the mechanical stress and fatigue caused to the suspension springs 11.

 Therefore, the present invention defines a system and a method that reduces significantly (or even eliminates) jolts on the mechanical assembly of the compressor during its stop, by means of controlled deceleration of
15 the rod-crank-and-piston assembly throughout the last turn of the turning axle, this preventing the piston from decelerating abruptly during the last incomplete gas compression stroke and also preventing the production of a high impulse with torque.

 A preferred example of embodiment having been described, one
20 should understand that the scope of the present invention embraces other possible variants, being limited only by the contents of the accompanying claims, which include the possible equivalents.

CLAIMS

1. A reciprocating compressor (3) comprising at least one mechanical assembly (12), which includes

- at least one compression mechanism (8) and one motor (9);

5 and

- at least one electronic control (2);

characterized in that the electronic control (2) is configured to detect a turn velocity (23) of the compression mechanism (8) and to apply a braking torque (36) to the mechanical assembly (12) during the stopping process of the compressor after detecting that the turn velocity (23) is below a predefined velocity value (34), the braking torque (36) being initiated at a next moment (35) after a compression stroke has been completed; and

- the braking torque (36) being configured for gradual deceleration of the turn velocity (23) such that the turn velocity (23) of the compression mechanism (8) has zero value at the moment when the new compression stroke is about to begin.

2. A reciprocating compressor according to claim 1, **characterized in that** the electronic control (2) detects the period that the compression mechanism (8) needs to carry out its movement and compares such a period with a maximum reference time, the maximum reference time being related with the period which the compression mechanism (8) needs to carry out its movement at the predefined velocity value (34).

3. A reciprocating compressor according to claim 1 or 2, **characterized in that** the predefined velocity value (34) is configured to guarantee that the inertia of the mechanical assembly (12) will be capable of carrying out a complete compression stroke.

4. A reciprocating compressor according to claim 1, **characterized in that** the application of the braking torque (36) is finished at the moment when a new compression stroke is about to begin.

5. A reciprocating compressor according to claim 1, characterized in that the braking torque (36) has a direction opposite that of the turn velocity (23).

6. A reciprocating compressor control method, **characterized by**

comprising the steps of:

- (a) detecting a turn velocity (23) of a mechanical assembly (12) that comprises at least the compression mechanism (8) and one motor (9);
- 5 (b) comparing the turn velocity (23) with a predefined velocity value (34); and
- (c) applying a braking torque (36) for deceleration of the mechanical assembly (12) during the stopping process of the compressor after detecting that the turn velocity (23) is below a predefined velocity value
- 10 (34), the braking torque (36) being initiated at a next moment (35) after a compression stroke has been completed;

wherein step (c) is configured to cause gradual deceleration of the turn velocity (23) so that the turn velocity (23) of the compression mechanism (8) has zero value at the moment when a new compression stroke is

15 about to begin.

7. A method according to claim 6, **characterized in that** the step (a) detects the period which the compression mechanism (8) needs to carry out its movement and the step (b) compares such a period with a maximum reference time related with the period which the compression mechanism (8)

20 needs to carry out its movement at the predefined velocity value (34).

8. A method according to claim 6 or 7, **characterized in that** the predefined velocity value (34) guarantees that the inertia of the mechanical assembly (12) will be capable to carry out a complete compression value.

9. A method according to claim 6, **characterized in that** the step

25 (c) is finished at the moment when the compression stroke is about to initiate.

10. A method according to claim 6, **characterized in that** the step (c) is carried out by applying a torque contrary to the turn velocity (23).

11. Cooling compressors control system, the system comprising at least:

- 30 - one electronic control (2); and
- one reciprocating compressor (3) comprising at least one mechanical assembly (12), which includes at least one compression mechanism

(8) and one motor (9);

- the control system being **characterized in that** the electronic control (2) is configured to detect a turn velocity (23) of the compression mechanism (8) and to apply a braking torque (36) to the mechanical assembly (12) during the stopping process of the compressor after detecting that the turn velocity (23) is below a predefined velocity value (34), the braking torque (36) being initiated at a next moment (35) after a compression stroke has been completed;

- the braking torque (36) being configured for gradual deceleration of the turn velocity (23) such that the turn velocity (23) of the compression mechanism (8) has zero value at the moment when the new compression stroke is about to begin.

12. A system according to claim 11, **characterized in that** the electronic control (2) detects the period that the compression mechanism (8) needs to carry out its movement and compares such a period with a maximum reference time, the maximum reference time being related with the period which the compression mechanism (8) needs to carry out its movement at the predetermined velocity value (34).

13. A system according to claim 11 or 12, **characterized in that** the predefined velocity value (34) is configured to guarantee that the inertia of the mechanical assembly (12) will be capable of carrying out a complete compression stroke.

14. A system according to claim 11, **characterized in that** the application of the braking torque (36) is finished at the moment when a new compression stroke is about to begin.

15. A system according to claim 11, **characterized in that** the braking torque (36) is configured for gradual deceleration of the turn velocity (23).

16. A system according to claim 11, **characterized in that** the braking torque (36) has a direction opposite that of the turn velocity (23).