

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 October 2002 (31.10.2002)

PCT

(10) International Publication Number
WO 02/086036 A1

(51) International Patent Classification⁷: **C10M 157/00**,
157/04 // (C10M 157/00, 143:10, 145:14, 145:16) (C10M
157/04, 145:14, 145:16, 149:04, 149:06, 149:10), C10N
20:04, 40:08

(74) Agents: **SHOLD, David, M.** et al.; The Lubrizol Corpo-
ration, 29400 Lakeland Boulevard, Wickliffe, OH 44092
(US).

(21) International Application Number: PCT/US02/10906

(22) International Filing Date: 4 April 2002 (04.04.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/285,377 20 April 2001 (20.04.2001) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.

(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(71) Applicant (*for all designated States except US*): **THE LU-
BRIZOL CORPORATION** [US/US]; 29400 Lakeland
Boulevard, Wickliffe, OH 44092 (US).

Published:
— with international search report

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **GAPINSKI, Richard,
E.** [US/US]; 7316 Hopkins Road, Mentor, OH 44060 (US).

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: ALL-WEATHER TRACTOR HYDRAULIC FLUID USING A MIXTURE OF VISCOSITY MODIFIER TYPES TO MEET SHEAR-STABLE MULTIGRADE VISCOSITY REQUIREMENTS

(57) Abstract: A composition of the following components: an oil of lubricating viscosity; a polymethacrylate viscosity modifier; an ester of a maleic acid/styrene copolymer; and optionally, an additive package that imparts to the fluid the capacity to meet bench and dynamometer tests specified by an equipment manufacturer, is suitable for use as a functional fluid such as a tractor hydraulic fluid, under a wide variety of climatic conditions.



WO 02/086036 A1