

Description

This invention relates to apparatus and a method for monitoring the diagnostic output of a computer-based system, and more particularly to such apparatus for use with a computer-based elevator controller possessing enhanced diagnostic capability.

As computer-based systems advance in sophistication and proliferate in number, associated service problems increase in novelty and number as well. Elevators provide a representative example. In the prior art, elevator problems that exist at the time a service technician requests this information can be extracted by an Operator's Maintenance Tool (OMT), as disclosed in U.S. Patent No. 4,561,093 to Doane et al. With the OMT, a user must either ask the elevator controller for the diagnostic status, or command the elevator to operate in an attempt to duplicate and identify the problem. This works well for simplistic elevator control problems. However, for more complex elevator problems, it is often required to install a complex and expensive logic state analyzer on the computer-based elevator controller to diagnose the aforementioned problems. However, the analyzer must be operated by a person knowledgeable with the control software of the elevator controller. Normally, this is not the elevator service technician.

To solve this problem, enhanced elevator diagnostics was developed. Commonly-owned U.S. Patent No. 4,750,591 to Coste et al. discloses a method and apparatus for monitoring an elevator by utilizing signals available within the elevator itself to determine the identity of an elevator car operating state. That art is predicated on the fact that an elevator car normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states. As a result, selected message signals are provided in the presence of state transitions to either normal or abnormal operating states. These selected message signals are intended to be transmitted to external monitoring apparatus at the elevator site.

Objects of the invention include extracting and recording enhanced diagnostic information from a computer-based elevator controller and conveying the diagnostic information to interested personnel in a meaningful way.

According to the present invention there is provided;

apparatus for use with an elevator system having at least one car, comprising:

for each elevator car, signal processing means for monitoring the states of a plurality of two-state parameter signals indicative of a corresponding plurality of elevator parameters, said signal processing means determining the identity of an elevator operating state for an elevator car which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states by detecting the satisfaction of a transition criterion defining a transition from an immediately preceding operating state or to an immediately succeeding operating state by detecting the parameter signal state or states, alone or in combination, of one or more sensed parameter signals defining the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the chain or to an abnormal operating state, and for providing selected message signals in the presence of corresponding selected transitions;

for each elevator car, an event buffer, responsive to a selected number of the latest to occur of selected parameter signal state changes, for storing state change signals indicative of said latest parameter signal state changes, said event buffer being responsive to said selected message signals for providing related buffer message signals corresponding to said stored state change signals;

for each elevator car, communication means, responsive to said selected message signals provided by said signal processing means, for transmission thereof, and responsive to said buffer message signals provided by said event buffer, for transmission thereof;

characterized by:

monitor communication means, responsive to each of said elevator car communication means, for decoding said transmitted selected message signals and providing decoded signals indicative thereof, and for decoding said transmitted buffer message signals and providing decoded signals indicative thereof;

user input means for providing signals indicative of parameter limit values corresponding to parameter value transition criterion for said plurality of parameters monitored by each one of said elevator car signal processing means;

display means responsive to said monitor signal processing means;

monitor signal processing means, responsive to said monitor communication means, for providing signals indicative of said decoded selected message signals to said display means for display in a predetermined form, and for providing signals indicative of said decoded buffer message signals to said display means for display in a predetermined form, said monitor signal processing means being responsive to said user input means for providing signals indicative of said parameter limit value signals to said display means for display in a predetermined form, and for providing said signals indicative of said parameter limit

value signals to said monitor communication means for transmission.

Furthermore the object of the invention is solved by the features of the method according to claim 5.

Other objects, features, and advantages of the present invention will become more apparent in light of the following detailed description of exemplary embodiments thereof, as illustrated in the accompanying drawings.

Fig. 1 illustrates a computer of the invention connected, by means of a serial communication link, to eight computer-based, elevator controllers, each of which has enhanced diagnostic capability.

Fig. 2 is a block diagram of the computer of Fig. 1.

Fig. 3 illustrates a computer screen for display of a plurality of typical elevator parameters.

Fig. 4 illustrates a computer screen for display of an exemplary main menu for the monitoring program.

Fig. 5 illustrates a computer screen of the typical contents of an elevator controller event buffer as a result of an alarm or alert condition.

Fig. 6 illustrates a computer screen associated with an alarm display along with an optional detailed description of the alarm and the possible causes for it.

Fig. 7 illustrates a computer screen associated with typical elevator performance data collected during polling of the elevator controller.

In Fig. 1, a computer 10 is connected by means of a serial communication link 12 to eight computer-based, elevator controllers 14-21. The computer 10 is typically an International Business Machine Corporation (IBM) laptop personal computer or one of a number of other manufacturer's computers similar to that of IBM (i.e., IBM "clones"). The communication link 12 is typically that of the well-known RS422 industry standard.

Each elevator controller 14-21 contains software that controls the operation of the elevator car and also implements enhanced elevator diagnostics as disclosed in the aforementioned commonly-owned U.S. Patent No. 4,750,591 to Coste et al. There, a method and apparatus for monitoring an elevator is disclosed in which the elevator car is modeled as operating in a closed loop chain of normal operating states. The controller monitors the states of a plurality of two-state parameter signals, each signal being indicative of one of a corresponding plurality of elevator parameters. The identity of a car operating state is determined by detecting the satisfaction of a criterion defining a transition either from an immediately preceding operating state or to an immediately succeeding operating state. The transition detection is accomplished by detecting the parameter signal state or states, alone or in combination, of one or more of the sensed parameter signals that define the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the sequence of states or to an abnormal operating state. The elevator controller provides selected message signals in the presence of corresponding selected transitions. A selected number of the most recent to occur of certain parameter signal state changes are stored in an event buffer and provided as part of the selected message signals.

As a result of the monitoring of elevator operation, the controller software records significant parameter signal state changes and analyzes these changes for indication of performance data, alarms, and alerts. Such analysis provides error recognition by comparing actual event sequences to predefined valid event sequences that are normal to elevator control. Deviations from the pre-defined sequences invoke the alarm condition, alert condition, and some system usage accounting messages. Other system usage accounting messages are integral to normal event sequences. Performance data consists of data such as number of runs and number of door operations. An alarm message is associated with certain shutdown conditions where a passenger may be trapped in the car. An alert message is an indication that the elevator is operating below performance standards.

Also provided as a part of alarms and alerts are the contents of an event buffer, located inside the controller, that stores the last one hundred or so significant events (i.e., significant parameter signal state changes) leading up to the reported alarm or alert condition. The storing of the last one hundred events monitored is particularly advantageous for trouble shooting purposes.

Monitoring an elevator car according to an operating state model together with storing the most recent of selected event occurrences provides a powerful method of diagnosing elevator problems.

In an exemplary embodiment of the aforementioned Coste et al patent, the monitoring of an elevator system according to the state machine model is accomplished by a computer-based elevator controller. Once transition-significant parameter signals are detected and recorded by the controller, they are analyzed for the presence of significant events such as alarm conditions, sub-standard performance conditions (alerts), and system usage performance conditions. Diagnostic messages indicative of these conditions are then communicated outside of the particular controller to the computer 10 for manifestation to elevator personnel. Communication of diagnostic messages indicative of problem conditions to an external computer provides an improved method of troubleshooting computer-based elevator controllers.

Fig. 2 is a block diagram of the computer of Fig. 1. The communication link 12 connecting the elevator controllers 14-21 together is also connected to communication means 25 inside the computer 10. The communication means 25 are typically implemented with readily-available dedicated digital line driver and receiver integrated circuits marketed by well-known companies such as Texas Instruments or Motorola. The communications means 25 are used to receive the messages indicative of enhanced elevator diagnostic information transmitted over the communication line 12 from any one of the elevator controllers 14-21. Once received, the communication means 25 decodes the message signals and provides signals indicative of the decoded messages to a central processing unit (CPU) 27. The CPU is typically implemented with any well-known microprocessor integrated circuit (IC), such as the Intel Model 80188 microprocessor, together with optional support ICs (e.g., interrupt controller, direct memory access controller, etc.).

Table III of the aforementioned Coste et al patent, incorporated herein as Table I, lists exemplary messages transmitted to the computer 10 in response to the diagnosis of certain elevator conditions. For example, assume a typical sequence of elevator operating states (reference Fig. 4(a) of the the aforementioned Coste et al patent) where the elevator car has stopped at a landing, the doors are closed, and a door open command has been received by the elevator controller. The reception of the door open command transitions the elevator controller software to proceed from a no door open command state (S0) to a state (S1) where the doors are opening and the door fully closed parameter signal is off. The next normal operating state (S2) is that of the condition where the doors are partially open and are continuing to open in response to the door open command. Once the doors are fully open, a transition is made to a state (S3) indicative of the doors being fully open and the elevator controller is anticipating a door close command.

25

30

35

40

45

50

55

TABLE 1

SHUTDOWN MESSAGES (TYPE 01)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
1	Trapped passenger	Committable landing	Car at landing	Car stall protect	REM state	Safe
2	Trapped passenger malfunction doors	Committable landing	Car at landing	Car stall protect	REM state	Safe
3	Stalled car	Committable landing	Car at landing	Car stall protect	REM state	Safe
4	Stalled car malfunction doors	Committable landing	Car at landing	Car stall protect	REM state	Safe
5	Stalled car door stuck	Committable landing	Car at landing	Car stall protect	REM state	Safe

TABLE I

SHUTDOWN MESSAGES (TYPE 01)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
6-10	Condition resolved back in service	Committable landing	Car at landing	Car stall protect	REM state	Safe
11	Back in service by power cycled	TSK000	INT000	STR000, STR001	LST000, LST001	STACK POINTER
12	Car not responding	Committable landing	Car at landing	Car stall protect	REM state	Safe
13	Trapped passenger car not responding	Committable landing	Car at landing	Car stall protect	REM state	Safe

TABLE I

SHUTDOWN MESSAGES (TYPE 01)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
14	Frequent safety chain failures	Committable landing	Car at landing	Car stall protect	REM state	Safe
15	Frequent door open failures	Committable landing	Car at landing	Car stall protect	REM state	Safe
16	ECS not running (generated by external computer)	Committable landing	Car at landing	Car stall protect	REM state	Safe
17	REM buffer overrun	Committable landing	Car at landing	Car stall protect	REM state	Safe
18	Operator interrupt	Committable landing	Car at landing	Car stall protect	REM state	Safe

TABLE I

MAINTENANCE MESSAGES (TYPE 02)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
1	Deceleration time limit exceeded	Number of occurrences	Limit	Last failure time	Landing of last occurrence	
2	Excessive nudges	Number of occurrences	Number of nudges	Number door operations	Limit	
3	Door close time limit	Number of occurrences	Limit	Last failure time	Landing of last occurrence	
4	Excessive nudges exceeded	Number of occurrences	Number of nudges	Number door operations	Limit	
5	Rear close time limit exceeded	Number of occurrences	Limit	Last failure time	Landing of last occurrence	

TABLE I

MAINTENANCE MESSAGES (TYPE 02)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
6	Run time between landings exceeded	Number of occurrences	Limit	Last failure time	First landing	Second landing
28	High pit oil	Number of occurrences				
29	Spare					
30	Door open time limit exceeded	Number of occurrences	Limit	Last failure time	Landing of last occurrence	
31	Rear open time limit exceeded	Number of occurrences	Limit	Last failure time	Landing of last occurrence	

TABLE 1

MAINTENANCE MESSAGES (TYPE 02)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
32	Failure of doors to open detected	Number of occurrences	Landing of last occurrence	REM state	Emergency stop	
33	Failure of rear doors to open detected	Number of occurrences	Landing of last occurrence	REM state	Emergency stop	
34	Malfunction door switches	Number of occurrences	Landing of last occurrence	REM state	Emergency stop	
35	Spare					
36	Rear lock bounce	Number of occurrence	Landing of last occurrence			

TABLE I

MAINTENANCE MESSAGES (TYPE 02)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
37	Front lock bounce	Number of occurrences	Landing of last occurrence			
38	Safety chain break	Number of occurrences	Landing of last occurrence			
39	Run aborted	Number of occurrences	Landing of last occurrence	REM state	Emergency stop	Motion detected
40	Invalid change in committable position	Number of occurrences	Landing of last occurrences			
41	Invalid inductor sequence	Number of occurrences	Landing of last occurrence	REM state		

TABLE I

PERFORMANCE DATA (TYPE 03)

SUB-TYPE	DEFINITION	DATA WORD 1	DATA WORD 2	DATA WORD 3	DATA WORD 4	DATA WORD 5
1	Front door information	Front door operations	Front door reversals	Front door nudges	Front door close exceedances	
2	Rear door/ information	Rear door operations	Rear door reversals	Rear door nudges	Rear door close exceedances	Number of runs
3	Run information	Demand minutes	Running minutes	Relevels		
4	For electronic	Empty runs up	Empty runs down	Partial runs up	Partial runs down	
5	For electronic	Full runs up	Full runs down			

Upon receiving a door close command, a transition is made to a state (S4) in which the doors are partially open and are closing in response to the close command. Once the doors are fully closed and no door open command is present, a transition is made to a corresponding state (S5). Then, when a door open command is received, a transition is made to the state (S1) in which the door open command has been received and the door fully closed parameter signal is off. This closed loop sequence of normal car door

operating states is the expected sequence for a normally operating elevator car.

Connected with certain ones of the state transitions are output functions performed by the elevator controller. For example, upon the transition from state S0 to state S1, a timer, implemented either in hardware or software, would have been started. Then, from the time the door open command is received in state S0, through intermediary states S1 and S2, until the time the door fully open condition is sensed in state S3, the timer is in operation. Once state S3 is reached, the timer value is compared to a preselected time limit for door opening. If the time limit is exceeded, then the elevator controller sends a selected maintenance request message over the communication link 12 to the communication means 25 inside the computer 10. For the particular situation just described, maintenance message sub-type number thirty (reference Table I) is sent. Also, additional data words are transmitted, such as the number of occurrences of this particular time limit exceedence along with information that describes the current time limit that the actual limit was compared against by the elevator controller, the last time that a failure occurred, and the landing of the last occurrence of a time limit exceedence. These transmitted data words indicative of enhanced elevator diagnostics are then processed by the CPU 27 either for display on a computer display 29 or for a hard copy printout generated by an externally-connected printer 32. For a laptop-type personal computer, the display 29 is typically implemented as an eighty-column by twenty-five-line character matrix using liquid crystal display technology. The printer 32 is connected by a communications link 34 to the communication means 25. The protocol used for printer communications is typically either that of the well-known RS232 serial type or that of the well-known Centronics parallel communications protocol. The printer can be that of a wide variety of well-known types (e.g., dot matrix, laser, etc.) made by a number of well-known manufacturers (Okidata, Epson, Toshiba, etc.). The data words transmitted over the communication link 12 from any elevator controller can also be stored in storage means 36 for future manipulation and reference. The storage means 36 are typically comprised of several types of electronic storage media: volatile random access memory (RAM) for temporary storage and manipulation by the CPU 27; magnetic storage in the form of floppy disk for non-volatile, transportable storage; magnetic hard disk storage for non-volatile, high-volume storage.

Normally, the apparatus of the present invention is intended to be used either during system installation, for periodic evaluation, or for problem site analysis. A typical operating sequence is as follows: elevator maintenance personnel physically locate the computer 10 and, optionally, the printer 32 in the elevator machine room, or in close proximity thereto. The computer 10 is connected to up to eight computer-based elevator controllers 14-21 by way of the communication link 12. Typically, an IBM laptop personal computer is supplied with at least one communication port implementing the RS232 protocol, and at least one communication port implementing the Centronics parallel protocol. The optional printer 32 connects directly to either a Centronics parallel port or to one of the RS232 serial ports on the IBM computer 10. Since typically RS422 protocol electronics are not supplied on an IBM personal computer, a commonly available RS232-to-RS422 adapter is plugged into one of the RS232 ports on the IBM computer, and the RS422 cable implementing the RS422 communication link 12 is plugged into the adapter.

Once the computer and printer are connected to the elevator controllers, the software program that controls the operation of the computer 10 is loaded into the computer 10. Typically, the software is provided on a floppy disk which is placed into the system floppy disk drive (i.e., the "A" drive) on the IBM computer 10. Also, a data floppy disk is loaded into a second disk drive (i.e., the "B" drive) on the IBM computer 10. Electrical power is then applied to the computer 10 and printer 32.

After powerup, the software offers the user a choice between a configuration program or a monitoring program. The configuration program is normally run when it is desired to enter the parameters of the elevator installation, or if the user is unsure of the configurations on file, or if it is desired to edit a configuration file. The monitoring program is normally run when the configuration file for the particular elevator installation has been established and the user desires to extract information from any connected elevator controllers. All display of data to the user for subsequent interpretation and/or interaction is presented by way of the display 29.

The type of information normally entered when running the configuration program includes the site name, building number, number of cars, and the machine number of each car. This information is entered by the user using keystroke entries made on a keyboard 38 of the IBM computer 10.

Another feature of the configuration program is that, in the aforementioned door open/close sequence example, the current door open time limit, that the actual door opening time limit is compared against, is one of a plurality of predetermined parameter limit values that can be selected by the user. The user can choose to modify default values for the limits of a number of typical elevator operational parameters, as listed in Table II along with the corresponding parameter definitions. The chosen default values are entered interactively by the user using the keyboard 38 and display 29. Fig. 3 illustrates an exemplary computer

screen containing a plurality of typical elevator parameters listed in Table II. The parameters which the user can set the current values of are enclosed in rectangles. The particular elevator controller uses the current values in determining certain elevator status conditions. These values are communicated by the computer 10 over the communication link 12 to the particular elevator controller when the monitoring program is entered.

Once the system configuration is complete, the monitoring program is entered wherein the enhanced elevator diagnostic information can be extracted from any of the computer-based elevator controllers 14-21 connected to the computer 10. The information is normally communicated to the computer at five hundred millisecond intervals. This transmission rate is strictly exemplary.

TABLE II

5	<u>Parameter</u>	<u>Definition</u>
10	POR Message Enable	If enabled, an alarm is generated whenever car is powered up.
15	Event Buffer with Alert	If you enter "Y", the program will save the event buffer associated with each alert generated.
20	Nudge Threshold	Maximum allowable number of consecutive runs in which nudging is initiated. If this number is exceeded, a front door or rear door alert is generated.
30	Excessive Door Close Cycles	Maximum allowable number of instances of excessive door close time. If this number is exceeded, a front door or rear door alert is generated.
35	Alert Threshold	Maximum allowable number of occurrences of any one alert. If this number is exceeded, an alarm is generated.
45	One-Floor Run	Maximum time allowed for Time monitored one-floor run from "start landing" to "end landing". If time exceeds given value, an alert will be generated.
50		
55		

TABLE II

<u>Parameter</u>	<u>Definition</u>
One-Floor Run Start Landing	Start landing for monitored one-floor run.
One-Floor Run End Landing	End landing for monitored one-floor run.
F Door Close	Maximum time allowed for the front doors to close. If actual time exceeds this limit, the Excessive Front Door Close counter is incremented.
R Door Close	Maximum time allowed for the rear doors to close. If actual time exceeds this limit, the Excessive Rear Door Close counter is incremented.
F Door Open	Maximum time allowed for the front doors to open. If actual time exceeds this limit, an alert is generated.
R Door Open	Maximum time allowed for the rear doors to open. If actual time exceeds this limit, an alert is generated.

TABLE II

<u>Parameter</u>	<u>Definition</u>
Emergency Button	Maximum time allowed for "No Car Response" if the in-car Emergency Stop button is pushed when initial problem is detected.
Group Comm	Maximum time allowed from Delay detection of a group communication failure, until failure is cleared. If trouble is not cleared within the timer limit, an alarm is generated.

After entering the monitoring program, a main menu appears on the display screen 29, as illustrated in Fig. 4. This menu lists the options available to the operator for extracting, recording, or conveying enhanced elevator diagnostic data. The software for the computer 10 is designed such that most selections are entered with single keystrokes. For example, upon initially entering the monitoring program, the user typically depresses the function key "F1" in order to select, from a list that appears on the screen, the desired site configuration file developed hereinbefore in the configuration program. This single keystroke entry facilitates ease of operation.

After the user has chosen the proper site configuration file, program operation is returned to the main menu. At this point, the user typically extracts data from an elevator controller by one of two methods: if the currently stored historical data in the elevator controller may be of some value in diagnosing a reported problem (e.g., due to an elevator malfunction reported by building personnel), then the user selects "F3" in order to poll the elevator control system (ECS) for such information; if the meaning of the data is unknown (of no interest), then the user selects "F2" in order to "flush" (erase) data from the controller. After selecting the flush option, the user can either save the flushed data on the floppy disk portion of the storage means 36 for future interpretation or the data can be discarded. Also in the flush option, the number of alarm or alert conditions received for each elevator car controller from which data is flushed is indicated on the display 29.

If it is desired to poll the system for current data (i.e., real time operation), the user should first flush the elevator controller of stored data and then begin polling the controller for current data. As a result of the polling operation, the screen displays the various operational functions (e.g., mode, motion, status of emergency button, car position, group status, etc.) of the polled elevator car, and will indicate whether alarms or alerts exist for the car. Data transmitted from an elevator controller to the computer 10 during the polling operation is saved in the storage means 36 for further interpretation, if desired.

The elevator controller communicates the contents of the controller event buffer to the computer 10 if the result of either the polling or flush operations indicate alarm or alert conditions. Fig. 5 illustrates a computer screen of the typical contents of a controller event buffer as a result of an alarm or alert condition. Listed are the latest to occur state changes of a number of typical elevator parameters that are monitored by the elevator controller.

Once the contents of the elevator controller have been either flushed or polled and subsequently saved in the storage means 36, the user is presented with several options for viewing the resulting saved data. By selecting option "F5" from the main menu, the user can display the various types of information transmitted by an elevator controller to the computer 10. For example, either alarms, alerts, and event buffers or, alternatively, performance data can be displayed on the display 29, or routed to the printer 32 for a hard copy printout. The computer screen (Fig. 5) illustrating event buffer contents associated with resultant alarm

or alert conditions has been discussed hereinbefore. However, it is also possible to display the contents of the event buffer regardless of the presence of alarms or alerts. This saves time in that it allows one event buffer for one car controller to be displayed without first performing either the flush or poll procedure and paging through the resulting event buffers for the data associated with each car controller.

As a second option, the user can display alarms or alerts together with corresponding causes for either the alarm or alert. Fig. 6 illustrates a computer screen associated with an alarm display along with an optional detailed description of the alarm and the possible causes for it. The display for the alert condition is similar.

Also, the user can display elevator performance data collected during polling. Performance data associated with any elevator car is normally saved at the end of the polling session. Fig. 7 illustrates a computer screen associated with typical elevator performance data collected during polling of the elevator controller. As with alarms, alerts, and event buffers, performance data can also be printed out.

The software which controls the primary computer functions of communicating with the elevator controllers 14-21 over the communication link 12, communicating with the printer 32 via either an RS232 serial interface of a Centronics parallel interface, interacting with the user via the keyboard 38, storing the signals indicative of enhanced elevator diagnostic information in memory 36, and processing the display screens of the display 29 is implemented in a well-known manner that should be readily apparent to those skilled in the art in light of the teachings presented herein. A manufacturer such as IBM makes available to the public information regarding the interfacing with the computer's disk operating system (DOS) software for performing functions such as those enumerated above. The computer software that interfaces with the IBM DOS can be written in a designer's choice of a variety of commonly-available computer languages (e.g., Pascal, C, Assembler, etc.) made available either by IBM itself or one of a variety of third-party vendors.

Although the present invention has been described in detail in connection with the method and apparatus for monitoring an elevator as embodied in a computer-based elevator controller and disclosed in the aforementioned Coste et al patent, it is to be understood that the present invention can be utilized in any type of elevator system which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states, which system determines the identity of an operating state by detecting the satisfaction of a criterion defining a transition from an immediately preceding operating state or to an immediately succeeding operating state by detecting the system parameter signal state or states, alone or in combination, of one or more sensed system parameter signals defining the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the chain or to an abnormal operating state, and which system provides selected message signals in the presence of corresponding selected transitions.

As described, the communication link between the computer 10 and a plurality of elevator controllers 14-21 is implemented with the well-known RS422 communications protocol. However, any serial or parallel communications protocol can be used; the choice of protocol depends on criteria such as the physical environment and communication interfaces available on the system controllers and computers. Also, an IBM laptop personal computer is used to extract, record and convey the enhanced elevator diagnostic information from eight elevator controllers. However, any number of elevator controllers can be interconnected to any one of a number of well-known types of commercially available computers. Also, it is possible for one skilled in the art to design and build the apparatus of the present invention using commonly-available electronic components, or even custom-designed components such as gate arrays or programmable logic devices.

Although the invention has been illustrated and described with respect to exemplary embodiments thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions and additions may be made therein and thereto, without departing from the scope of the invention.

Claims

1. Apparatus for use with an elevator system having at least one car, comprising:

for each elevator car, signal processing means (14-21) for monitoring the states of a plurality of two-state parameter signals indicative of a corresponding plurality of elevator parameters, said signal processing means (14-21) determining the identity of an elevator operating state for an elevator car which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states by detecting the satisfaction of a transition criterion defining a transition from an immediately preceding operating state or to an immediately succeeding operating state by detecting



or alert conditions has been discussed hereinbefore. However, it is also possible to display the contents of the event buffer regardless of the presence of alarms or alerts. This saves time in that it allows one event buffer for one car controller to be displayed without first performing either the flush or poll procedure and paging through the resulting event buffers for the data associated with each car controller.

5 As a second option, the user can display alarms or alerts together with corresponding causes for either the alarm or alert. Fig. 6 illustrates a computer screen associated with an alarm display along with an optional detailed description of the alarm and the possible causes for it. The display for the alert condition is similar.

10 Also, the user can display elevator performance data collected during polling. Performance data associated with any elevator car is normally saved at the end of the polling session. Fig. 7 illustrates a computer screen associated with typical elevator performance data collected during polling of the elevator controller. As with alarms, alerts, and event buffers, performance data can also be printed out.

15 The software which controls the primary computer functions of communicating with the elevator controllers 14-21 over the communication link 12, communicating with the printer 32 via either an RS232 serial interface of a Centronics parallel interface, interacting with the user via the keyboard 38, storing the signals indicative of enhanced elevator diagnostic information in memory 36, and processing the display screens of the display 29 is implemented in a well-known manner that should be readily apparent to those skilled in the art in light of the teachings presented herein. A manufacturer such as IBM makes available to the public information regarding the interfacing with the computer's disk operating system (DOS) software
20 for performing functions such as those enumerated above. The computer software that interfaces with the IBM DOS can be written in a designer's choice of a variety of commonly-available computer languages (e.g., Pascal, C, Assembler, etc.) made available either by IBM itself or one of a variety of third-party vendors.

25 Although the present invention has been described in detail in connection with the method and apparatus for monitoring an elevator as embodied in a computer-based elevator controller and disclosed in the aforementioned Coste et al patent, it is to be understood that the present invention can be utilized in any type of elevator system which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states, which system determines the identity of an operating state by detecting the satisfaction of a criterion defining a transition from an immediately preceding
30 operating state or to an immediately succeeding operating state by detecting the system parameter signal state or states, alone or in combination, of one or more sensed system parameter signals defining the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the chain or to an abnormal operating state, and which system provides selected message signals in the presence of corresponding selected transitions.

35 As described, the communication link between the computer 10 and a plurality of elevator controllers 14-21 is implemented with the well-known RS422 communications protocol. However, any serial or parallel communications protocol can be used; the choice of protocol depends on criteria such as the physical environment and communication interfaces available on the system controllers and computers. Also, an IBM laptop personal computer is used to extract, record and convey the enhanced elevator diagnostic
40 information from eight elevator controllers. However, any number of elevator controllers can be interconnected to any one of a number of well-known types of commercially available computers. Also, it is possible for one skilled in the art to design and build the apparatus of the present invention using commonly-available electronic components, or even custom-designed components such as gate arrays or programmable logic devices.

45 Although the invention has been illustrated and described with respect to exemplary embodiments thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions and additions may be made therein and thereto, without departing from the scope of the invention.

50 Claims

1. Apparatus for use with an elevator system having at least one car, comprising:

55 for each elevator car, signal processing means (14-21) for monitoring the states of a plurality of two-state parameter signals indicative of a corresponding plurality of elevator parameters, said signal processing means (14-21) determining the identity of an elevator operating state for an elevator car which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states by detecting the satisfaction of a transition criterion defining a transition from an immediately preceding operating state or to an immediately succeeding operating state by detecting



the parameter signal state or states, alone or in combination, of one or more sensed parameter signals defining the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the chain or to an abnormal operating state, and for providing selected message signals in the presence of corresponding selected transitions;

5 for each elevator car, an event buffer (14-21), responsive to a selected number of the latest to occur of selected parameter signal state changes, for storing state change signals indicative of said latest parameter signal state changes, said event buffer being responsive to said selected message signals for providing related buffer message signals corresponding to said stored state change signals;

10 for each elevator car, communication means (14-21), responsive to said selected message signals provided by said signal processing means, for transmission thereof, and responsive to said buffer message signals provided by said event buffer, for transmission thereof; characterized by:

15 monitor communication means (25), responsive to each of said elevator car communication means (14-21), for decoding said transmitted selected message signals and providing decoded signals indicative thereof, and for decoding said transmitted buffer message signals and providing decoded signals indicative thereof;

user input means (38), for providing signals indicative of parameter limit values corresponding to parameter value transition criterion for said plurality of parameters monitored by each one of said elevator car signal processing means

20 display means (29), responsive to monitor signal processing means (27,36);

25 monitor signal processing means (27,36), responsive to said monitor communication means (25), for providing signals indicative of said decoded selected message signals to said display means (29), for display in a predetermined form, and for providing signals indicative of said decoded buffer message signals to said display means (29), for display in a predetermined form, said monitor signal processing means (27,36) being responsive to said user input means (38) for providing signals indicative of said parameter limit value signals to said display means (29) for display in a predetermined form, and for providing said signals indicative of said parameter limit value signals to said monitor communication means (25) for transmission.

30 2. The apparatus of claim 1, wherein said user input means (38) comprises means for providing keyboard input of said plurality of signals indicative of parameter limit values corresponding to parameter value transition criterion for said plurality of parameters monitored by each one of said elevator car signal processing means (14-21).

35 3. The apparatus of claim 1 or 2, wherein said monitor signal processing means (14-21) comprises means, responsive to said monitor communication means (25), for storing signals indicative of said decoded selected message signals and for storing signals indicative of said decoded buffer message signals.

40 4. The apparatus of claim 1, 2 or 3 wherein said monitor communication means (25) comprises means, responsive to said monitor signal processing means (14-21), for providing signals indicative of said selected message signals to a hardcopy printout device (32) for printout in a predetermined form, and for providing signals indicative of said buffer message signals to a hardcopy printout device (32) for printout in a predetermined form.

45 5. A method of monitoring the diagnostic signal output of an elevator controller of an elevator system which normally operates sequentially from state to state in a closed loop sequential chain of linked normal operating states, which system determines the identity of an operating state by detecting the satisfaction of a criterion defining a transition from an immediately preceding operating state or to an immediately succeeding operating state by detecting the system parameter signal state or states, alone or in combination, of one or more sensed system parameter signals defining the satisfied transition criterion, each criterion indicating either a transition to a normal operating state in the chain or to an abnormal operating state, and which system provides selected message signals in the presence of corresponding selected transitions,

55 said method comprising:

providing signals indicative of parameter limit values corresponding to a parameter value transition criterion for each of the one or more selected elevator parameter signals monitored by the controller;

displaying visually signals indicative of said parameter limit value signals in a predetermined form;



communicating said signals indicative of said parameter limit value signals to the elevator controller;
 providing signals indicative of said selected message signals;
 displaying visually said signals indicative of said selected message signals in a predetermined
 5 form;
 providing signals indicative of said event signals; and
 displaying visually said signals indicative of said event signals in a predetermined form.

6. The method of claim 5 further comprising:
 10 inputting by keyboard (38) a desired value of each of said signals indicative of parameter limit values.

Patentansprüche

- 15 1. Vorrichtung zur Verwendung bei einer mindestens eine Kabine aufweisenden Aufzugsanlage, umfassend:
 für jede Aufzugskabine vorgesehene Signalverarbeitungsmittel (14-21) zum Überwachen der Zustände
 mehrerer zwei Zustände aufweisender Parametersignale, die eine entsprechende Mehrzahl von Aufzug-
 parametern angeben, wobei die Signalverarbeitungsmittel (14-21) die Identität eines Aufzug-Betriebszu-
 20 stands für eine Aufzugskabine festlegen, die normalerweise sequentiell von Zustand zu Zustand in einer
 sequentiellen, eine geschlossene Schleife bildenden Kette von miteinander verbundenen Normalbe-
 triebszuständen arbeitet, indem die Erfüllung eines Übergangskriteriums festgestellt wird, welches
 einen Übergang von einem unmittelbar vorausgehenden Betriebszustand oder in einen unmittelbar
 nachfolgenden Betriebszustand definiert, indem der Parametersignal-Zustand oder die
 25 Parametersignale-Zustände von einem oder mehreren gelesenen Parametersignalen, die das erfüllte
 Übergangskriterium definieren, allein oder in Kombination erfaßt werden, wobei jedes Kriterium entwe-
 der einen Übergang in einen Normalbetriebszustand in der Kette oder in einen abnormalen Betriebszu-
 stand anzeigt, und um ausgewählte Nachrichtensignale bei Vorhandensein der entsprechenden ausge-
 wählten Übergänge zu schaffen;
 einen für jede Aufzugskabine vorgesehenen Ereignispuffer (14-21), der auf eine ausgewählte Anzahl von
 30 zuletzt aufgetretenen ausgewählten Parametersignal-Zustandsänderungen anspricht, um Zustandsände-
 rungssignale zu speichern, die kennzeichnend sind für die genannten letzten Parametersignal-Zu-
 standsänderungen, wobei der Ereignispuffer auf die ausgewählten Nachrichtensignale anspricht, um
 den gespeicherten Zustandsänderungssignalen entsprechende zugehörige Puffernachrichtensignale
 bereitzustellen;
 35 für jede Aufzugskabine vorgesehene Kommunikationsmittel (14-21), die auf die von der Signalverarbei-
 tungseinrichtung bereitgestellten ausgewählten Nachrichtensignale ansprechen, um sie zu übertragen,
 und die auf die von dem Ereignispuffer bereitgestellten Puffernachrichtensignale ansprechen, um sie zu
 übertragen,
 gekennzeichnet durch:
 40 Überwachungs-Kommunikationsmittel (25), die auf jedes der Aufzugskabinen-Kommunikationsmittel (14-
 21) ansprechen, um die übertragenen ausgewählten Nachrichtensignale zu decodieren und dafür
 kennzeichnende decodierte Signale bereitzustellen und um die übertragenen Puffernachrichtensignale
 zu decodieren und dafür kennzeichnende decodierte Signale bereitzustellen;
 Benutzer-Eingabemittel (38) zum Bereitstellen von Signalen, die kennzeichnend sind für Parameter-
 45 grenzwerte entsprechend dem Parameterwert-Übergangskriterium für die Parameter, die von jedem
 einzelnen der Aufzugskabinen-Signalverarbeitungsmittel überwacht werden;
 eine auf eine Überwachungssignal-Verarbeitungseinrichtung (27,36) ansprechende Anzeigeeinrichtung
 (29);
 eine Überwachungssignal-Verarbeitungseinrichtung (27, 36), die auf die Überwachungs-Kommunika-
 50 tionsmittel (25) ansprechen, um Signale für die Anzeigeeinrichtung (29) bereitzustellen, die kennzeich-
 nend sind für die decodierten ausgewählten Nachrichtensignale, damit diese in einer vorbestimmten
 Form angezeigt werden, und um Signale an die Anzeigeeinrichtung (29) zu liefern, die kennzeichnend
 sind für die decodierten Puffernachrichtensignale, um sie in einer vorbestimmten Form anzuzeigen,
 wobei die Überwachungssignal-Verarbeitungseinrichtung (27, 36) auf die Benutzer-Eingabeeinrichtung
 55 (38) anspricht, um für die Anzeigeeinrichtung (29) Signale bereitzustellen, welche die Parameter-
 Grenzwertsignale kennzeichnen, damit diese in einer vorbestimmten Form angezeigt werden, und um
 die für die Parameter-Grenzwertsignale kennzeichnenden Signale der Überwachungs-Kommunikations-
 einrichtung (25) für die Übertragung bereitzustellen.



2. Vorrichtung nach Anspruch 1, bei der die Benutzer-Eingabeeinrichtung (38) Mittel aufweist zur Schaffung einer Tastatur-Eingabe der mehreren Signale, die kennzeichnend sind für Parameter-Grenzwerte, entsprechend dem Parameterwert-Übergangskriterium für die Mehrzahl von Parametern, die durch jedes der Aufzugkabinen-Signalverarbeitungsmittel (14-21) überwacht werden.

3. Vorrichtung nach Anspruch 1 oder 2, bei der die Überwachungssignal-Verarbeitungsmittel (14-21) eine auf die Überwachungs-Kommunikationseinrichtung (25) ansprechende Einrichtung aufweisen, um Signale zu speichern, die kennzeichnend sind für die decodierten ausgewählten Nachrichtensignale, und um Signale zu speichern, die kennzeichnend sind für die decodierten Puffernachrichtensignale.

4. Vorrichtung nach Anspruch 1, 2 oder 3, bei der die Überwachungs-Kommunikationseinrichtung (25) eine auf die Überwachungssignal-Verarbeitungseinrichtung (14-21) ansprechende Einrichtung aufweist, um einem Hartkopie-Druckgerät (32) für die ausgewählten Nachrichtensignale kennzeichnende Signale für einen Ausdruck in einer vorbestimmten Form anzubieten, und um dem Hartkopie-Druckgerät (32) für den Ausdruck in vorbestimmter Form Signale anzubieten, die kennzeichnend sind für die Puffernachrichtensignale.

5. Verfahren zum Überwachen der Diagnosesignalausgabe einer Aufzugsteuerung einer Aufzuganlage, die normalerweise sequentiell von Zustand zu Zustand in einer eine geschlossene Schleife bildenden sequentiellen Kette von miteinander verbundenen Normalbetriebszuständen arbeitet, wobei das System die Identität eines Betriebszustands dadurch feststellt, daß es die Erfüllung eines Kriteriums erfaßt, welches einen Übergang von einem unmittelbar vorausgehenden Betriebszustand oder in einen unmittelbar nachfolgenden Betriebszustand definiert, indem der Systemparametersignalzustand oder die Systemparameterzustände von einem oder mehreren, das erfüllte Übergangskriterium definierenden Systemparametersignalen allein oder in Kombination erfaßt werden, wobei jedes Kriterium entweder einen Übergang in einen Normalbetriebszustand innerhalb der Kette oder in einen abnormalen Betriebszustand angibt, und wobei das System ausgewählte Nachrichtensignale bei Vorhandensein der entsprechenden ausgewählten Übergänge bereitstellt, umfassend:

Bereitstellen von Signalen, die kennzeichnend sind für Parametergrenzwerte entsprechend einem Parameterwert-Übergangskriterium für jedes von dem einen oder den mehreren ausgewählten Aufzugparametersignalen, die von der Steuerung überwacht werden;

visuelles Anzeigen von für die Parametergrenzwertsignale kennzeichnenden Signalen in einer vorbestimmten Form;

Übermitteln der für die Parametergrenzwertsignale kennzeichnenden Signale zu der Aufzugsteuerung;

Bereitstellen von Signalen, die kennzeichnend sind für die ausgewählten Nachrichtensignale;

visuelles Anzeigen der für die ausgewählten Nachrichtensignale kennzeichnenden Signale in einer vorbestimmten Form;

Bereitstellen von Signalen, die kennzeichnend sind für die Ereignissignale; und

visuelles Darstellen von für die Ereignissignale kennzeichnenden Signale in einer vorbestimmten Form.

6. Verfahren nach Anspruch 5, weiterhin umfassend:

Eingeben eines gewünschten Wertes für jedes der für Parametergrenzwerte kennzeichnenden Signale über eine Tastatur (38).

45 Revendications

1. Appareil destiné à être utilisé avec un système d'ascenseurs ayant au moins une cabine, qui comprend :

pour chaque cabine d'ascenseur, des moyens de traitement de signaux (14 à 21) destinés à surveiller les états d'une pluralité de signaux paramètres à deux états, indicatifs d'une pluralité correspondante de paramètres de l'ascenseur, lesdits moyens de traitement des signaux (14 à 21) déterminant l'identité d'un état de fonctionnement de l'ascenseur pour une cabine d'ascenseur qui, normalement, opère séquentiellement d'état en état en une chaîne séquentielle, d'états de fonctionnement normaux liés les uns aux autres, en boucle fermée, en détectant la satisfaction d'un critère de transition qui définit une transition partant d'un état de fonctionnement immédiatement précédent ou aboutissant à un état de fonctionnement immédiatement suivant par la détection d'un ou plusieurs signaux de paramètres détectés seuls ou en combinaison qui définissent le critère de transition satisfait, chaque critère indiquant, une transition qui aboutit soit à un état de fonctionnement normal



inclus dans la chaîne, soit à un état de fonctionnement anormal, et fournissant des signaux messages sélectionnés en présence de transitions sélectionnées correspondantes ;

pour chaque cabine d'ascenseur, un tampon d'événements (14 à 21) qui répond à un nombre sélectionné de changements d'états de signaux de paramètres sélectionnés qui sont les derniers à se produire, pour mémoriser des signaux de changements d'états indicatifs desdits derniers changements d'états de signaux de paramètres, ledit tampon d'événements répondant auxdits signaux de messages sélectionnés en fournissant des signaux de changement d'état mémorisés,

pour chaque cabine d'ascenseur, des moyens de communication (14 à 21) qui répondent auxdits signaux de messages sélectionnés fournis par lesdits moyens de traitement de signaux, pour les transmettre, et qui répondent à des signaux de messages de tampon fournis par ledit tampon d'événements, pour leur transmission ;
caractérisé par :

des moyens de communication de moniteur (25), qui répondent à chacun desdits moyens de communication (14 à 21) de la cabine d'ascenseur, en décodant lesdits signaux de messages sélectionnés transmis, en fournissant des signaux décodés indicatifs de ces signaux de messages, en décodant lesdits signaux de messages de tampon transmis et en fournissant des signaux décodés indicatifs de ces derniers ;

des moyens d'entrée d'utilisateur (38) servant à fournir des signaux indicatifs de valeurs limites de paramètres qui correspondent à des critères de transition de valeurs de paramètres pour ladite pluralité de paramètres surveillés par chacun desdits moyens de traitement de signaux de cabines d'ascenseurs ;

des moyens d'affichage (29) qui répondent à des moyens de traitement de signaux de moniteur (27, 36) ;

des moyens de traitement de signaux de moniteur (27, 36) qui répondent auxdits moyens de communication de moniteur (25) en fournissant des signaux indicatifs desdits signaux de messages sélectionnés décodés auxdits moyens d'affichage (29) pour les afficher dans une forme prédéterminée, et en fournissant des signaux indicatifs desdits signaux messages de tampon décodés auxdits moyens d'affichage (29) pour les afficher dans une forme prédéterminée, lesdits moyens de traitement de signaux de moniteur (27, 36) répondant auxdits moyens d'entrée d'utilisateur (38) en fournissant des signaux indicatifs desdits signaux de valeurs limites des paramètres auxdits moyens d'affichage (29) pour les afficher dans une forme prédéterminée, et pour fournir lesdits signaux indicatifs desdits signaux de valeurs limites des paramètres auxdits moyens de communication de moniteur (25) pour leur transmission.

2. Appareil selon la revendication 1, dans lequel lesdits moyens d'entrée d'utilisateur (38) comprennent des moyens formant entrée de clavier pour ladite pluralité de signaux indicatifs de valeurs limites de paramètres qui correspondent à un critère de transition de valeur de paramètre pour ladite pluralité de paramètres surveillés par chacun des moyens de traitement de signaux (14 à 21) des cabines d'ascenseurs.
3. Appareil selon la revendication 1 ou 2, caractérisé en ce que lesdits moyens de traitement des signaux de moniteur (14 à 21) comprennent des moyens qui répondent auxdits moyens de communication de moniteur (25) en mémorisant des signaux indicatifs desdits signaux de messages sélectionnés décodés et en mémorisant des signaux indicatifs desdits signaux de messages de tampon décodés.
4. Dispositif selon la revendication 1, 2 ou 3, dans lequel lesdits moyens de communication de moniteur (25) comprennent des moyens qui répondent auxdits moyens de traitement de signaux de moniteur (14 à 21) en fournissant des signaux indicatifs desdits signaux de messages sélectionnés à un dispositif d'impression sur copie matérielle (32) pour exécuter l'impression dans une forme prédéterminée, et en fournissant des signaux indicatifs desdits signaux de messages de tampon au dispositif d'impression sur copie matérielle (32) pour exécuter l'impression dans une forme prédéterminée.
5. Procédé de surveillance de la sortie de signal de diagnostic d'un contrôleur d'ascenseurs d'un système d'ascenseurs qui, normalement, opère séquentiellement d'état à état en une chaîne séquentielle en boucle fermée d'états de fonctionnement normaux liés les uns aux autres, lequel système détermine l'identité d'un système de fonctionnement en détectant la satisfaction d'un critère définissant une transition partant d'un état de fonctionnement immédiatement précédent ou aboutissant à un état de fonctionnement immédiatement suivant par la détection d'un ou plusieurs signaux de paramètres de



système détecté, seul ou en combinaison, qui définissent le critère de transition satisfait, chaque critère indiquant, soit une transition aboutissant à un état de fonctionnement normal inclus dans la chaîne, soit une transition aboutissant à un état de fonctionnement anormal, lequel système fournit des signaux de messages sélectionnés en présence de transitions sélectionnées correspondantes,

5 ledit procédé consistant à :

 fournir des signaux indicatifs de valeurs limites de paramètres qui correspondent à un critère de transition de valeur de paramètre pour chacun des signaux de paramètres sélectionnés de l'ascenseur surveillés par le contrôleur ;

10 afficher visuellement des signaux indicatifs desdits signaux de valeurs limites de paramètres dans une forme prédéterminée ;

 communiquer lesdits signaux indicatifs desdits signaux de valeurs limites de paramètres au contrôleur de l'ascenseur ;

 fournir des signaux indicatifs desdits signaux de messages sélectionnés ;

15 afficher visuellement lesdits signaux indicatifs desdits signaux de messages sélectionnés dans une forme prédéterminée ;

 fournir des signaux indicatifs desdits signaux d'évènements ; et

 afficher visuellement lesdits signaux indicatifs desdits signaux d'évènements dans une forme prédéterminée.

20 6. Procédé selon la revendication 5, consistant en outre à :

 entrer au moyen du clavier (38) une valeur désirée de chacun desdits signaux indicatifs des valeurs limites des paramètres.

25

30

35

40

45

50

55