

present invention comprises a connector housing having a bottom surface and a top surface located in opposed relation to the bottom surface, and contacts to be disposed in the connector housing and having time  
5 portions located at the bottom surface to be mounted on a printed circuit board and contact portions adjacent to the top surface for engaging with contacts in a matable connector. The cap housing for the electrical connector has a plurality of integral cap portions for removably  
10 mounting on the connector housing and covering the top surface and the contact portions of the electrical connector to be disposed in the cap housing.

A second cap housing for an electrical connector to achieve the above features is a cap housing for an  
15 electrical connector having a mating portion near the top surface to mate with a matable connector, and contacts disposed in the mating portion for engagement with contacts in the matable connector, the cap housing for the electrical connector being mounted on the  
20 electrical connector to cover the mating portion with the bottom surface facing the circuit board. It features the provision of engaging projections to engage with the contacts of the electrical connector when mounted thereon.

Also, a third cap housing for an electrical connector according to the present invention to achieve the above features is mounted on an electrical connector to cover a mating portion near the top surface for  
mating with a matable connector and to be mounted with  
30 the bottom surface facing a circuit board. The cap housing for the electrical connector features the provision of not only a first cap portion at one side to cover a mating portion of an electrical connector having a male type mating portion but also a second cap portion  
35 to cover a mating portion of an electrical connector having a female type mating portion.

The invention is a cap housing for mounting electrical connectors thereto for protecting contact

portions of electrical contacts secured in connector housings and for positioning the tine portions of the electrical contacts onto circuit boards so that the tine portions can be soldered to the circuit boards, wherein  
5 the cap housing includes cap portions for receiving mating sections of the connector housings containing the contact portions with the mounting sections of the connector housings containing the tine portions for positioning on a circuit board, and engaging members of  
10 the cap portions for engaging the electrical connectors thereby maintaining the electrical connectors on the cap portions.

Embodiments of the invention will now be described by way of example in accordance with the following  
15 description with reference to the accompanying drawings in which:

FIGURE 1 is an isometric exploded view of a simplified version of a first embodiment of a cap housing and electrical connectors according to the  
20 present invention.

FIGURE 2 is a view similar to FIG. 1 showing the cap housing and connectors in an assembled condition.

FIGURE 3 is an end view of the assembly of FIG. 2.

FIGURES 4 to 7 are top plan, side, bottom and end  
25 views respectively of a first embodiment of the cap housing of FIGS. 1 to 3.

FIGURE 8 is a cross-sectional view of the cap housing of FIGS. 4 to 7 taken along line 8-8 of FIG. 5.

FIGURES 9 and 10 are top plan and side views of an  
30 electrical connector for mounting to the cap housing of FIGS. 4 to 8.

FIGURE 11 is a top plan view of the cap housing of FIG. 4 having the electrical connector of FIGS. 9 and 10 mounted thereto.

35 FIGURES 12 and 13 are side and end views, respectively, of FIG. 11.

FIGURE 14 is a top plan view of a second embodiment of the cap housing of the present invention.

FIGURES 15 to 17 are side, bottom and end views of the cap housing of FIG. 14.

FIGURE 18 is a cross-sectional view of the cap housing of FIGS. 14 to 17 taken along line 18-18 of FIG. 15.

FIGURE 19 is a top plan view of an electrical connector for mounting to the cap housing of FIG. 14.

FIGURE 20 is a side view of FIG. 19.

FIGURE 21 is a top plan view of the cap housing of FIG. 14 having the electrical connectors of FIG. 19 and 20 mounted thereto.

FIGURES 22 and 23 are side and end views, respectively, of the assembly of FIG. 21.

FIGURE 24 is a part top plan view of a third embodiment of the cap housing of the present invention mounted to a male electrical connector.

FIGURES 25 and 26 are side and end views, respectively, of the assembly of FIG. 24.

FIGURE 27 is a cross-sectional view of the assembly of FIG. 24 taken along line 27-27 thereof.

FIGURE 28 is a cross-sectional view of the cap housing of FIG. 24 taken along line 28-28 thereof.

FIGURE 29 is a top plan view of a fourth embodiment of the cap housing of the invention mounted to a female electrical connector.

FIGURES 30 and 31 are side and end views, respectively, of the assembly of FIG. 29.

FIGURE 32 is a cross-sectional view of the assembly of FIG. 29 taken along line 32-32 thereof.

FIGURE 33 is a cross-sectional view of the cap housing of FIG. 29 taken along line 33-33 thereof.

FIGURE 34 is a part magnified view of the cap housing of FIG. 33 in engagement with a contact of the connector of FIG. 29.

FIGURE 35 is a top plan view of a fifth embodiment of the cap housing of the invention mounted to a male electrical connector.

FIGURES 36 and 37 are side and end views, respectively, of the cap housing of FIG. 35.

FIGURE 38 is a cross-sectional view of the assembly of FIG. 35 taken along line 38-38 thereof.

5       FIGURE 39 is a view similar to FIG. 38 of the cap housing of FIG. 35 mounted to a female electrical connector.

      The particular cap housing 10 for electrical connectors is formed with a pair of parallel cap portions 12,14 which are integrally made by molding from, for example, a suitable plastic material with ribs 16,18 intercoupling them at both ends. The cap portions 12,14 are designed to be removably mounted on connector housing 20,22 of respective electrical connectors. When the cap portions 12,14 are mounted on the housings 20,22, the top surfaces 20a,22a of the housings 20,22 as well as contact portions 24 of electrical contacts are covered as best shown in FIG. 3. As a result, when mounting on a circuit board (not shown) or transporting the electrical connectors having the housings 20,22, the top surfaces 20a,22a of the housings 20,22 and the contact portions 24 of the contacts are protected by the cap housing 10 for the electrical connectors, thereby keeping any dust or other foreign material away from the contact portions 24 of the contacts. Furthermore, the two cap portions 12,14 of the cap housing 10 hold a pair of electrical connectors simultaneously for mounting on a circuit board or transportation. It is to be noted here that the above description is made regarding the cap housing 10 for electrical connectors which is formed with a pair of parallel cap portions 12,14; however, more than two cap portions may be formed. Also, the two cap portions 12,14 may be arranged in a V-shape or three cap portions may be arranged integrally in a U-shape depending on the particular arrangement of how the electrical connectors are to be mounted on a circuit board.

Reference is now made to FIGS. 4 through 13 to describe the first embodiment of the cap housing for electrical connector according to the present invention.

Shown in FIGS. 4 through 13 is the cap housing 30 for electrical connectors. The cap housing 30 comprises two parallel cap portions 40,60 which are formed integrally and formed with ribs 32 at both ends. Additionally, both cap portions 40,60 are coupled together with additional ribs 34 for better alignment of the cap portions 40,60 and preventing the cap portions from warping.

Best seen in FIG. 6, each cap portion 40,60 is formed with an upper wall 42,62 and sidewalls 44,64 to define grooves 46,66 which constitute spaces surrounded by these walls in which an electrical connector 80 is received (see FIGS. 9 and 10). Alignment plates 36 (FIGS. 5 through 8) are formed at both ends of the cap portions 40,60 at center portions of the ribs 32 for alignment of the electrical connectors 80 by abutting sidewalls of the housing of electrical connectors 80 (see FIG. 13) against side surfaces 36a of the alignment plates 36, thereby preventing any misalignment of the electrical connector 80 when retained in the cap housing 30. At both end portions of outer surfaces 44a,64a of the sidewalls 44,64 of each cap portion 40, 60 resilient arms 48,68 are located for engagement with the electrical connectors 80 to maintain them on the cap portions. The arms 48,68 are formed with projections 48a,68a (FIGS. 6 through 8) projecting inwardly from the free ends thereof. The projections 48a,68a enter openings 86a in a ground plate 86 on the housing of the electrical connectors 80 (see FIGS. 12 and 13). Note that holes 49,69 are formed in the upper wall 42,62 of each cap portion 40,60 (FIG. 4) for inserting and extracting core pins (not shown).

FIGS. 9 and 10 show the electrical connector to be secured in the cap housing 30. The electrical connector 80 is provided with a housing 82 and a large number of

electrical contacts 84 are disposed in the housing 82. The housing 82 is formed with a plurality of projections 82a at the sidewalls designed to enter the openings 86a in the ground plate 86 which is secured on the sidewall of the housing 82. As described above, the projections 48a, 68a of the arms 48, 68 are designed to enter the two openings 86a at both ends among many openings 86a in the ground plate 86. Also, the housing 82 has a bottom surface 88 facing a circuit board (not shown) and a top surface 90 at an opposite location to the bottom surface. Each contact 84 has a tine portion 84a at each side of the bottom surface 88 to be engaged with a solder pad on a circuit board and a contact portion 84b located along each side of the housing 82 defining a mating section for engagement with a mating contact (not shown).

FIGS. 11 through 13 show electrical connectors 80 retained in the cap housing 30. As described above, electrical connectors 80 are received in the grooves 46, 66 in the cap housing 30 which are firmly and removably retained in the cap housing 30 by the projections 48a, 68a of the arms 48, 68 engagingly entering the openings 86a in the ground plate 86. In the manner, the cap housing 30 not only secures the housings 82 of the electrical connectors 80 therein but also covers and protects the top surface 90 of the housing 82 and the contact portions 84b of the contacts 84. As a result, the contact portions 84b are kept clean from flux and the like which may otherwise attach thereto when the tine portions 84a are soldered to a circuit board, thereby establishing excellent electrical engagement with matable contacts. Also, the contact portions 84b are kept clean and protected during transportation of the electrical connectors 80. Additionally, two electrical connectors 80 can be mounted on a circuit board or transported simultaneously by holding them in the two cap portions 30, 40 of the cap housing 30. It is to be noted that the particular cap

housing 30 described above has two parallel cap portions 40,60 but may have more than two cap portions. Also, the two cap portions 46,60 may be disposed in a V-shape or three cap portions may be disposed in a U-shape depending on particular arrangements of the electrical connectors to be mounted on a circuit board.

Reference will now be made to FIGS. 14 through 23 to describe a second embodiment of the cap housing for electrical connectors according to the present invention.

FIGS. 14 through 18 show the cap housing 130 which is formed with two parallel cap portions 140,160 integrally formed by being coupled at both ends by ribs 132. The cap portions 140,160 are further coupled together by ribs 134 for preventing the cap housing 130 from warping.

Each cap portion 140,160 comprises a protrusion 143,163 including a bottom wall 142,162, and sidewalls 144,164 to define spaces or recesses 146,166 (FIGS. 17, 18 and 21). There are formed alignment plates 136 at center portions of the ribs 132. Sidewalls of the housings of the electrical connectors 180 (see FIG. 23) abut against the side surfaces 136a of the alignment plates 136, thereby preventing misalignment of the electrical connectors 180 mounted onto the cap housing 130. Resilient arms 148,168 are formed at both ends of the external side surfaces 144a, 164a of the sidewalls 144, 146 for engaging against a ground plate 186 (see FIG. 23). The arms 148,168 are formed with projections 148a,168a at the ends thereof extending inwardly for engaging the ground plate 186, thereby removably retaining the cap housing 130 onto the housing of the electrical connector 180 by the projections. Note that the ground plate 186 is formed with holes 182a to receive the projections 148a,168a therein for holding the housing of the electrical connector 180 onto the cap housing. Note that there are formed openings 149,169 (FIG. 14) in the sidewalls 144,166 of each cap portion

140,160 for insertion and removal of a core pins (not shown).

FIGS. 19 and 20 show electrical connector 180 to be mounted onto the cap housing 130 as shown in FIG. 16.

5 The electrical connector 180 includes a housing 182 and a large number of electrical contacts 184 disposed in the housing 182. A groove 183 is formed at the center portion of the housing 182 in the longitudinal direction for matingly receiving protrusions 143,163 of the cap  
10 housing 130. There are a plurality of projections 182a on the sidewall of the housing 182 to be engagingly received in openings 186a in the ground plates 186 which is secured on the sidewall of the housing 182. The housing 182 has a bottom surface 188 facing a circuit  
15 board (not shown) and a top surface 190 at an opposite location to the bottom surface 188. Each contact 184 has a tine portion 184a located at the bottom surface 188 to be engaged with a solder pad on circuit board and a contact portion 184b along a surface of groove 183 for  
20 engagement with a matable contact (not shown).

FIGS. 21 through 23 show the electrical connector 180 secured to the cap housing 130. As described hereinbefore, the protrusions 143,163 of the cap housing 130 are snapped in the grooves 183 of the electrical  
25 connectors 180 while the arms 148,168 engage the ground plate 186 with projections 148a,168a being disposed in holes 182a of ground plate 186, thereby removably mounting the cap housing 130 onto the housings 182 of the electrical connectors 180. This particular way of  
30 securing the cap housing 130 onto the housings 182 of the electrical connectors 180 covers for protection purposes the top surfaces 190 of the housings 182 and the contact portions 184b of the contacts 184. As a  
result, flux or any foreign material is kept away from  
35 the contact portions 184b during a soldering operation of the tine portions 184a to a circuit board, thereby assuring excellent electrical contact with matable contacts. Also, the contact portions 184b are dust free

during transportation of the electrical connectors 180. Moreover, a pair of the electrical connectors 180 are simultaneously held in the two cap portions 140,160 in the cap housing 130 for convenience of mounting on a circuit board or transportation. The two parallel cap portions 140, 160 are formed in the particular cap housing 130 just described herein. However, it is to be noted that more than two cap portions may be provided and two cap portions 140,160 may be disposed in a V-shape or three cap portions may be disposed integrally in a U-shape depending on the particular arrangement of such electrical connectors on a circuit board.

Now reference is made to FIGS. 24 through 28 to describe a third embodiment of the cap housing according to the present invention.

In this particular embodiment, the cap housing according to the present invention is designed for mounting to a male type electrical connector.

As apparent from FIGS. 24 through 27, a cap portion 310 of the cap housing 300 is adapted to be mounted on a male type electrical connector 380 to cover a mating portion 385 near the top surface 382 thereof.

Electrical contacts 383 are secured in the mating portion 385 of the male type electrical connector 380 with contact portions 384 of the contacts 383 adapted to make electrical contact with contact portions of respective contacts in a matable connector (not shown) when the mating portion 385 of the male type electrical connector 380 is mated with a complementary mating portion of the matable connector. As best shown in FIG. 28, the cap portion 310 of the cap housing 300 is formed with a recess 311 having sidewalls 312 formed with engaging projections 313. The engaging projections 313 are adapted to engage the contacts 383 of the male type electrical connector 380 when it is mounted on the cap housing 300. In this particular embodiment, the engaging projections 313 are not externally located because the male type electrical connector 380 engages

inside the cap portion 310 in the cap housing 300. Also, they are not easily disengaged once the cap housing 300 is mounted on the male type electrical connector. Additionally, provision of the engaging projections 313 inside the cap portion 310 contributes to minimize the size of the cap housing as compared to the case where the engaging members such as resilient latch members 48,68 with an electrical connector are provided on the outer surfaces 44a,64a of the sidewalls 44,64 of the cap portions 40,60 as shown in FIGS. 4 through 8.

When the cap housing 300 is mounted on the electrical connector 380 as mentioned above, the portions 386 at the bottom surface 388 opposite to the top surface 382 of the male type electrical connector 380 are soldered to a circuit board (not shown) for mounting the electrical connector 380 at a predetermined location on the circuit board.

In the particular embodiment, engagement of the engaging projections 313 in the cap housing 300 with a plurality of electrical contacts 383 disposed in the male type electrical connector 380 eliminates strict requirements for proper alignment between the male type electrical connector 380 and the cap housing 300, thereby improving the operational characteristics of placing the connectors onto a circuit board and protecting the contact portions 384 in the same manner as in the other embodiments.

Furthermore, the cap housing 300 in this particular embodiment is formed with a vacuum pick-up surface 340 at the top thereof for convenience of transportation and alignment of the cap housing 300 by a conventional automatic machine having a vacuum pick-up nozzle.

Reference is now made to FIGS. 29 through 34 to describe a fourth embodiment of the cap housing according to the present invention.

As shown in FIGS. 29 through 32, a cap portion 410 of the cap housing 400 is adapted to be mounted on a

female type electrical connector 480 to cover its mating portion 485 near the top surface 482 thereof. Disposed in the mating portion 485 of the female type electrical connector 480 are electrical contacts 483 having contact portions 484 adapted to electrically engage respective contacts in a matable connector (not shown) when the matable portion 485 of the female type electrical connector 480 is mated with a complementary mating portion of the matable connector. As best shown in FIGS. 33 and 34, the cap portion 410 of the cap housing 400 is formed with a projection 411 to be received in the female type electrical connector 480. Formed at the tips of the sidewalls 412 of the protrusion 411 are resilient arms or engaging members 420 to engage the contacts 483 of the female type electrical connector 480. Also, formed near the tips of the resilient engaging members 420 are engaging projections 413 which engage the contacts 483 at points 484 of the female type electrical connector 480 when the cap housing 400 is mounted on the female type electrical connector 480. In this particular embodiment, the cap housing 400 and the female type electrical connector 480 are engaged inside the cap portion 410 of the cap housing 400, the engaging projections 413 have no external interference, thereby assuring that the cap housing is not easily removed from the female type electrical connector once mounted thereto. Additionally, since the engaging projections are formed inside the cap portion 410, the entire cap housing can be made compact because of the same reason as the cap housing 300 and the male type electrical connector described above.

The cap housing 400 is mounted on the female type electrical connector 480 in the above manner and the tine portions 486 at the bottom surface 488 opposite to the top surface 482 of the female type electrical connector 480 are soldered onto a circuit board (not shown) for mounting the female type electrical connector 480 at a predetermined location on the circuit board.

Also, in this particular embodiment, the engaging projections 413 formed on the cap housing 400 engage a large number of electrical contacts 483 disposed in rows in the female type electrical connector 480, thereby  
5 eliminating strict accuracy requirements for alignment when engaging the female type electrical connector 480. This improves the operational characteristics as pointed out above in regard to cap housing 300.

It is also noted that the cap housing 400 in this  
10 particular embodiment features the use of vacuum pick-up surface 440 on the top surface. A vacuum nozzle of an automatic vacuum pick-up machine may be attached to the vacuum pick-up surface 440 for precisely placing of the cap housing 400 onto a circuit board and to protect the  
15 contact portions during shipment of the connectors mounted onto the cap housing.

Additionally, the cap housing 400 has openings 450 at upper portions thereof for preventing the cap housing 400 from warping or deforming due to internal stress  
20 during the molding process of the cap housing.

Referring now to FIGS. 35 through 39, a fifth embodiment of the cap housing according to the present invention will be described.

As apparent from FIGS. 35 through 39, the fifth  
25 embodiment of the cap housing 500 according to the present invention is formed with a first cap portion 511 at one surface 501 and a second cap portion 512 at the opposite surface 502. The first cap portion 511 is adapted via a groove 515 to cover a male type mating  
30 portion 585 containing contact portions 584 of the electrical contacts 583 to the top surface 582 of the male type electrical connector 580 while the second cap portion 512 is adapted to cover a female type mounting  
portion 685 containing contact portions 684 of the  
35 electrical contacts 683 to the top surface 682 of the female type electrical connector 680.

Note that the mating portion 585 of the male type electrical connector 580 and the mating portion 685 of

the female type electrical connector 680 are designed to mate with each other.

As best shown in FIGS. 35 and 38, when the cap housing 500 is mounted on the male type electrical connector 580, the tine portions 586 formed at the bottom surface 588 of the male type electrical connector 580 may be soldered onto a circuit board (not shown) for mounting the male type electrical connector 580 at a predetermined location on the circuit board.

Electrical connector 580 is held onto cap portion 511 via projections 513 which engage contact portions 584; whereas electrical connector 680 is held onto cap portion 512 via the frictional engagement of contact portions 684 with the walls of protrusion 514 of cap portion 512.

The above particular configuration of the fifth embodiment of the cap housing 500 provides both functions as the cap housing for both male type and female type electrical connectors using a single cap housing. Also, the production cost can be reduced because a single cap housing can be used easily as a cap housing for both male type and female type electrical connectors.

As understood from the above description, the first and second embodiments of the cap housing for electrical connectors according to the present invention features a plurality of integrally formed cap portions for covering a top surface of a connector housing as well as a mating portion containing contact portions of electrical contacts. This arrangement helps to protect the top surface of the housing and the mating portion and contact portions of the contacts covered by the cap housing during mounting on a circuit board or transportation of the electrical connectors, thereby protecting the contact portions of the contacts from collecting flux, dust, etc. Additionally, since a plurality of cap portions of the first embodiment of the cap housing is integrally formed, a plurality of

electrical connectors can be simultaneously mounted on a circuit board or transported. Such plurality of electrical connectors are properly aligned with each other.

- 5           Additionally, in the third embodiment of the cap housing according to the present invention, the cap portion in the cap housing is formed with engaging projections which has no substantial external interference, thereby making it difficult to be
- 10           disengaged from the electrical connector. Also, such particular configuration having the engaging portions inside the cap housing helps reduce the size of the cap housing as a whole.

- Furthermore, in the fourth and fifth embodiments of
- 15           the cap housing according to the present invention, a first cap portion for a male type electrical connector is formed in one surface, while a second cap portion for a female type electrical connector is formed in the opposite surface. As a result, the cap housing can be
- 20           used commonly for both male type and female type electrical connectors, which has various manufacturing advantages and helps to reduce production cost.

WHAT IS CLAIMED IS:

1. A cap housing for mounting electrical connectors thereto for protecting contact portions of electrical contacts secured in connector housings and for positioning the tine portions of the electrical contacts onto circuit boards so that the tine portions can be soldered to the circuit boards, characterized in that:

said cap housing (30,130,300,400,500) includes cap portions (40,60,140,160,310,410,511,512) for receiving mating sections of the connector housings containing the contact portions (84b,184b,384,484,584,684) with the mounting sections of the connector housings containing the tine portions (84a,184a,386,486,586,686) for positioning on a circuit board, and engaging members (48,68,148,168,313,421,513,514) of the cap portions for engaging the electrical connectors thereby maintaining the electrical connectors on the cap portions.

2. A cap housing as claimed in claim 1, wherein the cap portions (40,60,310,511,512) have a groove (46,66,311,515) therein in which the mating sections are received.

3. A cap housing as claimed in claim 1, wherein the cap portions (140,160,410,512) include protrusions (143,163,411,514) onto which the mating sections engage.

4. A cap housing as claimed in claim 1, wherein the engaging members (48,68,148,168,420) are resilient arms.

5. A cap housing as claimed in claim 5, wherein the resilient arms have projections (48a,68a,148a,168a) that are disposed in holes (86a,186a) of a ground plate (86,186) on a side of the connector housings (82,182).

6. A cap housing as claimed in claim 4, wherein the resilient arms (420) have projections (413) that engage the contact portions (484) of the electrical contacts (483).

This Sheet Has Been Replaced





WO 97/12426

PCT/US96/15560

7. A cap housing as claimed in claim 1, wherein the engaging members (313,513) are projections that engage the contact portions (384,584) of the electrical contacts (383,583).

5 8. A cap housing as claimed in claim 1, wherein alignment plates (36,136) are located between the cap portions (40,60,140,160) and against which the connector housings (82,182) engage.

10 9. A cap housing as claimed in claim 1, wherein a top surface (340,440) of the cap housing (300,400) is planar for engagement by a vacuum nozzle of a connector-positioning device.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN  
REPLACED