

TITLE

Lockable Snap-Clip Fastener

CROSS-REFERENCES TO RELATED APPLICATIONS

5 This Application claims priority on prior filed U.S. Provisional Application number 61/533,104, filed 9 September 2011 and as a continuing application of prior filed U.S. Non-provisional Application 13/439,034, filed 4 April 2012 and incorporates both prior Applications by reference in their entirety.

10 TECHNICAL FIELD

 The present invention relates to the field of fasteners and more particularly relates to a lockable snap-clip fastener.

BACKGROUND ART

15 The present invention is a lockable snap clip that comprises fewer parts than prior art snap clips and uses them in a simple arrangement which makes the snap clip of the present invention advantageous over the prior art.

 The present invention represents a departure from the prior art in that the snap clip of the present invention allows for a lockable snap clip which is
20 simple and intuitive to use that will remain in either a locked or unlocked configuration until the user desires to switch from one to the other.

DISCLOSURE OF THE INVENTION

 In view of the foregoing disadvantages inherent in the known types of
25 snap-clip fasteners, this invention provides a lockable snap-clip fastener. As

such, the present invention's general purpose is to provide a new and improved lockable snap-clip fastener that is easy and intuitive to use, uses few component parts and is economical to manufacture.

To accomplish these objectives, the snap-clip fastener according to the present invention comprises two jaw members joint at a pivot and biased by a spring in a closed position. A locking bar passes through one jaw member and slides underneath an end of the spring. The bar may pass to one side or the other of the jaw member through which it passes and is held in position by the spring. In one position, the bar blocks passage of the other jaw member, while it allows passage in the other position.

The more important features of the invention have thus been outlined in order that the more detailed description that follows may be better understood and in order that the present contribution to the art may better be appreciated. Additional features of the invention will be described hereinafter and will form the subject matter of the claims that follow.

Many objects of this invention will appear from the following description and appended claims, reference being made to the accompanying drawings forming a part of this specification wherein like reference characters designate corresponding parts in the several views.

Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also it is to be understood that the phraseology and terminology employed

herein are for the purpose of description and should not be regarded as limiting.

As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

10 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of a fastener depicting the best mode of the present invention.

Figure 2 is an alternate perspective view of the fastener of FIG. 1.

Figure 3 is an exploded view of the fastener of FIG. 1.

15 Figure 4 is an alternate exploded view of the fastener of FIG. 1.

Figure 5 is a plan view of the fastener of FIG. 1, unlocked.

Figure 6 is a sectional view of the fastener of FIG. 4, taken along line A-A.

Figure 7 is a sectional view of the fastener of FIG. 4, taken along line B-B.

Figure 8 is a plan view of the fastener of FIG. 1, locked.

20 Figure 9 is a sectional view of the fastener of FIG. 4, taken along line C-C.

Figure 10 is a sectional view of the fastener of FIG. 4, taken along line D-D.

Figure 11 is an alternate perspective view of the fastener of FIG. 1.

25 Figure 12 is a perspective view of the fastener of FIG. 1 in use on either end of a sling.

Figure 13 is a perspective view of the fastener of FIG. 1, attached to a mounting loop.

BEST MODE FOR CARRYING OUT THE INVENTION

With reference now to the drawings, the preferred embodiment of the locking snap-clip fastener is herein described. It should be noted that the articles “a”, “an”, and “the”, as used in this specification, include plural referents unless the content clearly dictates otherwise.

The following reference numerals are used to indicate the following components of the displayed preferred embodiment:

- 10 8 - connection hardware;
- 10 - fastener;
- 12 - mandible;
- 13 - spring;
- 14 - maxilla;
- 15 15 - roll pin;
- 16 - lock bar;
- 18 - sling;
- 22 - stop;
- 24 - distal tab;
- 20 26 - hooked tooth;
- 28 - lever;
- 40 - cradle;
- 42 - pivot hole;
- 43 - floor;
- 25 44 - channel;

- 45 - tooth;
- 46 - back ridge;
- 48 -attachment bar;
- 62 - first tapered end;
- 5 64 - ridge;
- 66 - off-center vertical notch;
- 68 -second tapered end.

With reference to FIGS. 1 and 2, two jaw bodies, a mandible 12 and a maxilla 14, form the fastener 10. Maxilla 14 cradles mandible 12. The mandible 12 and maxilla 14 pivot relative to each other about a roll pin 15 and are biased in a closed position by torsion spring 13. Lock bar 16 passes through a middle portion of the maxilla 14 and may selectively impede movement of the mandible 12 relative thereto. This impediment allows the fastener 10 to be locked in an immovable position at the will of the user.

15 Figures 3 and 4 depict the components of the fastener in greater detail. The mandible 12 features a hooked tooth 26 on one end and a lever 28 on the other. Two distal tabs 24 are located on either side of the mandible 12, roughly one third of the length of the mandible 12 from a terminal end of the lever 28. Tabs 24 both feature coaxial through holes. A stop 22 is located on one side of the mandible 12 underneath the lever 28 and behind one tab 24. 20 The maxilla 14 features a cradle 40 which interfaces with the hooked tooth 26. Cradle 40 features a floor 43 and two sides, which each terminate in a tooth 45, with space defined between each tooth 45 and the floor 43. Maxilla 14 also features an attachment bar 48 opposite the cradle. The attachment bar 48 25 defines a hind end of the maxilla 14. Two pivot holes 42 are provided in

opposite walls of the maxilla 14, such that, when properly positioned, the holes in the tabs 24 are coaxial with the pivot holes 42. A roll pin 15 or similar structure is therein inserted to join the mandible 12 and maxilla 14 and serve as a pivot bar about which the jaw bodies respectively pivot. Torsion spring 13 is positioned about the roll pin 15, between the tabs 24, and is anchored with one arm in a slot on a back ridge 46 of the maxilla 14 (FIG. 11). The torsion spring 13 biases the jaw bodies in a closed position.

The locking bar 16 passes through a channel 44 behind the pivot holes 42 in the maxilla 14. The locking bar features two tapered ends 62, 68, an off-center vertical notch 66 and a ridge 64 residing in a similarly off-center horizontal notch. Together, ridge 64 and the horizontal notch form two detents on either side of the ridge 64. When in position, the horizontal notch resides underneath the end of the spring 13 anchored in the back ridge 46. The interplay between these pieces is shown in a better view in FIG. 8.

In use, shown in FIGS. 5-10, the locking bar 16 is pushed to one side or the other. In an open position, shown in FIGS. 5-7, stop 22 is positioned over the notch 66, thereby allowing relative movement between the mandible 12 and maxilla 14. Spring 13 resides in an outer edge detent of the ridge 64 in the horizontal notch. Spring pressure biases the spring 13 against the locking bar 16 and maintains the locking bar's position. To lock the fastener, shown in FIGS. 8-10, a user presses the exposed tapered end of the locking bar 16 until enough force is applied to the spring 13 to cause it to jump ridge 64 and settle on its other side's detent. In this position, stop 22 is not positioned over vertical notch 66, but rather over a solid portion of the locking bar 16. This then prevents the mandible 12 and maxilla 14 from pivoting and opening the

fastener. The locking bar 16 of the fastener then requires positive pressure from the user to switch from one position to another and remains in that position until the user consciously desires to change.

This fastener 10 may be used in many different functions, such as the
5 sling 18 shown in FIG. 12. In any setting, a strap may be secured about attachment bar 48 in any of the known, conventional means or through any means later discovered. In use, shown in FIG. 13, the fastener 10 is opened by unlocking it and depressing the lever 28 to separate the mandible 12 from the maxilla 14. A piece of connection hardware 8, such as a ring or bar, is
10 positioned between the teeth 45 and floor 43 of the maxilla jaw 14 and the lever 28 released, thereby closing the hooked tooth 26 around the connection hardware. The fastener 10 is then locked as described above.

Although the present invention has been described with reference to preferred embodiments, numerous modifications and variations can be made
15 and still the result will come within the scope of the invention. No limitation with respect to the specific embodiments disclosed herein is intended or should be inferred.

INDUSTRIAL APPLICABILITY

The present invention is capable of being produced in industry and being
20 used as an aid in portage and other fields where carrying or fastening an object to another object is required. This Application illustrates the invention as being in use with a sling; however, the invention is capable of use with other objects, most notably straps and packs, where temporary but secure fastening of two objects is required. The attachment bar 48 is an example means by which the
25 present invention is connected to the target object, in this case a sling. It

should be readily appreciated that different attachment means may be utilized for different types of objects and different purposes. The present invention may be manufactured from any appropriate material, metals and plastics being considered ideal for durability and economical construction.

Claims:

1. A clip fastener comprising:
 - a. two hingedly opposable jaws, both jaws being biased into a closed position;
 - b. a lock bar;
 - 5 c. a stop tab, extending from one jaw proximate the lock bar, the lock bar proximate the stop tab and situated within a channel in one of the jaws and capable of transverse slidable motion therethrough, the lock bar further comprising:
 - i. a vertical notch located off center of the lock bar;
 - 10 ii. a horizontal notch located off center on an opposite side of the vertical notch; and
 - iii. a ridge residing within the horizontal notch such that two detents are formed by the ridge and an interior of the horizontal notch; and
 - d. a spring with at least one end;
- 15 wherein, opening and closing the jaws defines a path of travel for the stop tab, the lock bar residing within the path of travel, and the at least one end of the spring resides within the horizontal notch of the lock bar such that upon moving the lock bar into open and closed positions the ridge of the lock bar may be selectably located upon either side of the end of the spring thereby selectively positioning the vertical notch in the path of travel and allowing passage of the stop tab and associated relative pivoting movement
 - 20 of the jaws when the lock bar is in an open position.
2. A combination comprising a fastener having two pivotable jaws, a torsion spring providing pivoting bias for said jaws and a stop tab located on one of the jaws, and a
 - 25 locking mechanism for the fastener, the locking mechanism comprising:
 - a. a transverse bar, slidable through one of the pivotable jaws into, selectably, an open position and a closed position;
 - b. a ridge residing off-center on a top side of the transverse bar in a manner to interface with a lower arm of the torsion spring; and
 - 30 c. a vertical notch located oppositely off-center from the ridge on the

transverse bar; wherein
the stop tab located on one of the jaws is arranged to interface with the
transverse bar when the transverse bar is in the closed position and to interface
with the notch when the transverse bar is in the open position.

5

3. The combination of claim 2, wherein the ridge resides in a horizontal notch on the
transverse bar.

4. The combination of claim 3, wherein the ridge interfaces with an end of the torsion
spring such that, when the transverse bar is in an open position, the ridge is on one side
of the end of the spring and, when the transverse bar is in a closed position, the ridge is
on another side of the end of the torsion spring.

5. The combination of claim 2, wherein the ridge interfaces with an end of the torsion
spring such that, when the transverse bar is in an open position, the ridge is on one side
of the end of the spring and, when the transverse bar is in a closed position, the ridge is
on another side of the end of the torsion spring.

6. A clip fastener comprising:

- 20 a. a mandible jaw, the mandible jaw further comprising:
- i. a hind lever end;
 - ii. a two distal tabs, one on either side of the mandible jaw and each having
a hole such that the holes are coaxial;
 - iii. a stop tab positioned between one of the distal tabs and the hind lever;

25 and

 - iv. a forward hooked tooth; and
- b. a maxilla jaw, the maxilla jaw further comprising:
- i. a rear transverse bar extending from a jaw body;
 - ii. a back ridge forward of the transverse bar;

- iii. a transverse lock channel having an open top and being forward of the back ridge; and
 - iv. a forward cradle comprising a floor and two side walls, the side walls each having a tooth spaced apart from the floor and one
 - 5 orifice such that the orifices are diametrically opposite each other;
 - c. a pivot bar, being inserted through the orifices of the maxilla jaw and the holes in the distal tabs of the mandible jaw;
 - d. a spring situated about the pivot bar and anchored on the back ridge, positioned to bias the jaws in a closed relationship; and
 - 10 e. a lock bar, situated within the lock channel of the maxilla and capable of slidable motion therethrough, the lock bar further comprising:
 - i. a vertical notch located off center of the lock bar;
 - ii. a horizontal notch located on an upper half of the lock bar and off center on an opposite side of the vertical notch; and
 - 15 iii. a ridge residing within the horizontal notch such that two detents are formed by the ridge and an interior of the horizontal notch;
- wherein, horizontal notch of the lock bar resides under an end of the spring anchored upon the back ridge of the maxilla jaw such that upon moving the lock bar into open and closed positions the ridge of the lock bar being selectably located upon either side
- 20 of the end of the spring and the stop tab will be over the lock bar when the lock bar is in a closed position and the stop tab will be positioned over the vertical notch in a manner that will allow passage of the stop tab and associated relative pivoting movement of the jaws when the lock bar is in an open position.