

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099511 A2

(51) International Patent Classification⁷: **E02F**
(21) International Application Number:
PCT/US2004/011266
(22) International Filing Date: 29 April 2004 (29.04.2004)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
10/425,934 30 April 2003 (30.04.2003) US
10/824,490 15 April 2004 (15.04.2004) US

(71) Applicant (for all designated States except US): **ESCO CORPORATION** [US/US]; 2141 N.W. 25th Avenue, Portland, OR 97210 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BRISCOE, Terry, L.** [US/US]; 11399 NW Ride Road, Portland, OR 97229 (US).

(74) Agent: **SCHAD, Steven, P.**; Banner & Witcoff, Ltd., 1001 G Street, N.W., Eleventh floor, Washington, DC 20001-4597 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **RELEASABLE COUPLING ASSEMBLY**

(57) Abstract: A lock that includes a wedge that is used to releasably secure separable components of an assembly together. The wedge can be used with a spool. The wedge and spool are threadedly coupled together to drive the wedge into and out of an opening in the assembly without hammering or prying. The direct coupling of the wedge and spool eliminates the need for bolts, washers, nuts and other hardware so as to minimize the number of parts. As a result, the lock is inexpensive to make, easy to use, and unlikely to become inoperative because of lost or broken parts or due to fines or other difficulties encountered in harsh digging environments. Further, the wedge can be driven into the assembly to provide the degree of tightness necessary for the intended operation and/or to re-tighten the assembly after incurring wear during use. A latch assembly is preferably provided to securely hold the wedge in place and avoid an undesired loss of parts during use.



WO 2004/099511 A2