

WATER SUPPLY CONTROL METHOD AND APPARATUS, CLOTHES TREATMENT DEVICE, AND STORAGE MEDIUM

ABSTRACT

A water loading control method and apparatus, a clothes treatment device (100), and a storage medium. The method comprises: executing a first water loading process and a second water loading process on the basis of a clothes treatment instruction, wherein the first water loading process is executed before and/or after the second water loading process, the first water loading process comprises loading water into a clothes accommodating apparatus (101) of the clothes treatment device (100) by means of a first water supply pipeline (103), the first water supply pipeline (103) is in communication with the clothes accommodating apparatus (101) by means of an air outlet channel (105) of the clothes treatment device (100), a filter screen (106) for filtering air flow during drying is arranged in the air outlet channel (105), the second water loading process comprises loading water into the clothes accommodating apparatus (101) by means of a second water supply pipeline (107), and the second water supply pipeline (107) is in communication with the clothes accommodating apparatus (101) by means of a detergent box (102) of the clothes treatment device (100). Cleaning the filter screen (106) before and/or after clothes treatment indicated by the clothes treatment instruction is executed can increase the ventilation area of the filter screen (106) to improve the ventilation performance of the filter screen (106) during the execution of the clothes treatment instruction, thereby improving the drying effect.

Fig 7.