

DESCRIPTIONWOUND IRRIGATION DEVICE AND METHOD5 Cross-Reference to a Related Application

This application claims the benefit of provisional patent application Serial No. 60/504,767, filed September 22, 2003, which is hereby incorporated by reference in its entirety.

10 Background of the Invention

In the management and treatment of a wound there are three primary objectives: (1) prevention of infection, (2) preservation and/or restoration of function, and (3) preservation and/or restoration of cosmetic appearance. The most important of these objectives is the prevention of infection. Success in the prevention of infection directly affects the healing process and the degree to which the other two objectives, function and cosmetic appearance, can be preserved and/or restored.

15 It is known that the number of bacteria, rather than bacterial type, is a critical determinant of whether a wound becomes infected. Experimental evidence suggests that a critical level of bacteria is approximately 10^5 organisms per gram of tissue. Below this level, wounds heal; at levels greater than 10^5 bacteria per gram of tissue, wounds often become infected. All traumatic wounds are contaminated by the time the wound is presented to a medical care facility for treatment (Dire, Daniel I. [1990] "A comparison of Wound Irrigation Solutions Used in the Emergency Department," *Annals of Emergency Medicine* 19(6):704-708). Dirty wounds, or those which have not been

20 treated within six hours, are likely to be contaminated with bacteria at levels that are higher than the critical level. Reducing the number of bacteria in and around the wound is a recognized and accepted means for avoiding infection and expediting wound healing.

25 Different procedures of wound management have been developed to help decrease the level of bacteria present in a wound, *i.e.*, reduce the incidence of infection. The cleansing of a wound and the site surrounding the wound to remove blood clots, debris,

30 dirt, or other foreign materials that can introduce contaminants, including pathogenic

microorganisms, is critical in reducing levels of bacteria in and around the wound. There are numerous wound cleansing procedures presently used by healthcare professionals such as debridement, excision and irrigation. See, for example, Sinkinson, Craig Alan, ed. (1989) "Maximizing A Wound's Potential For Healing," *Emergency Medicine Reports* 10(11):83-89; Lammers, Richard L. (1991) "Soft Tissue Procedures: Principles of Wound Management," in *Clinical Procedures in Emergency Medicine*, Roberts and Hedges, eds., 2nd Ed., W.B. Saunders Company, pp. 515-521; Cracroft, Davis (1987) "Minor Lacerations and Abrasions," *Emergency Medicine: A Comprehensive Review*, Kravis and Warner, eds., 2nd ed., Aspen Publishing Co., pp. 107-110; and Mulliken, John B. (1984) "Management of Wounds," in *Emergency Medicine*, May ed., John Wiley & Sons, pp. 283-286.

Irrigation is the most commonly used procedure for cleansing of open contaminated wounds. Irrigation involves the application of sterile solutions or fluids to wounds to remove loose devitalized tissue, bacterial inoculum, blood clots, loose debris, and foreign bodies proximate to and within the depths of the wound. The two critical components of any effective wound irrigation method and/or device are: (1) the application of an adequate volume of sterile irrigation solution to the wound, and (2) the use of sufficient pressure applied in an effective dispersal pattern in the delivery of the solution to effectively remove contaminants. Regarding volume, the amount of irrigation solution required will depend upon the type of wound and the level of contamination. Injuries which can introduce a high amount of bacteria into a wound (such as puncture wounds and bites) may require 1 liter or more of irrigation solution. See Mulliken, 1989. Regarding pressure, it has been demonstrated that stream pressure of a minimum of 4 pounds per square inch (psi) (and, preferably, 7 psi) is required to effectively flush or remove contaminants from a wound. See, for example, Rodeheaver GT. Wound Cleaning, Wound Irrigation, Wound Disinfection, In: Krasner D., Kane D. Chronic Wound Care. 2nd ed. Wayne, P.A.: Health Management Publications; 1997, pp 97-108; and Bergstrom N., Bennett, M.A., Carlson, C.E. *et al.* Treatment of Pressure Ulcers. Clinical Guideline No. 15. AHCPR Publication No. 95-0652. Rockville, MD. Department of Health and Human Services. Public Health Services, Agency of Health Care Policy and Research; December 1994.

Irrigation pressure in excess of desired limits (*e.g.*, 25 psi or greater) may actually drive bacteria and particulate matter deeper into the wound and thereby defeat the purpose of the irrigation process. High-pressure irrigation may also cause damage to healthy tissue and impede the tissue's defenses and retard healing. Thus, effective wound
5 irrigation requires the use and application of adequate volumes of irrigation solution delivered to the wound in an effective dispersal pattern at appropriate pressures.

Bulb syringes or gravity flow irrigation devices deliver fluid at low pressures and as such are ineffective in ridding wounds of small particulate matter or in sufficiently reducing wound bacterial counts. Irrigation by bulb syringe exerts a pressure of about
10 0.05 psi, which does not reduce the number of bacteria or particulate contaminants enough to prevent infection. The flow rate of irrigation fluid delivered through intravenous (IV) tubing can be enhanced by inflation of a blood pressure cuff around a collapsible plastic IV bag. This method is cumbersome and provides considerably less irrigation pressure than can be delivered by a plunger-type syringe.

The plunger-type syringe is the most common irrigation device currently used. Its use involves filling the barrel of the syringe with sterile irrigation solution and depressing the plunger to generate and apply a single pressurized stream of solution in and around the wound to dislodge and rinse away contaminants. This device has two notable disadvantages: (1) an extremely limited reservoir of irrigation fluid (typically a syringe
20 with a 35 cc-capacity barrel), and (2) it is limited to dispersal and application of a single concentrated stream of solution to the wound. Consequently, in most cases, the syringe must be repeatedly refilled in order to apply sufficient quantities of irrigation solution to a wound. This is time-consuming and cumbersome to do while attempting to maintain a sterile field. In an attempt to address this limitation, a device has been developed that
25 involves a system consisting of a syringe and IV tubing with a valve system that attaches to a bottle of saline to provide a ready means of refilling the syringe barrel. (Travenol pressure irrigation set, code no. 2D2113, or irriget, Ackrad Laboratories, Garwood, NJ). Additionally, U.S. Patent No. 4,357,937 describes a disposable, manually operable medical irrigation device which is adapted for providing selective volume and stream
30 intensity in liquid flow from a plurality of syringes. These devices do not adequately

address the disadvantages of using syringes for irrigation as discussed above and are not commonly used in clinical practice due to their complexity of use and cost.

The amount of hydraulic pressure that can be delivered with a plunger-type syringe varies with the force exerted on the plunger of the syringe and with the internal diameter of the attached needle. Plunger-type syringe devices that deliver moderate pressure employ either a 19 gauge needle attached to a 35 cc syringe, which creates hydraulic pressure in the range of 7-8 psi, or a 30 ml syringe fitted with a 19 gauge needle which typically creates about 7 psi irrigation pressure. A 22 gauge needle attached to a 12 cc syringe, delivers a pressure of about 13 psi. Such pressures have been proven effective in wound irrigation, but, as stated above, such devices apply only a single concentrated stream of solution to the wound. In addition, these described devices hold less than adequate volumes of irrigation solution and therefore require repeated refilling which is time consuming and cumbersome.

U.S. Patent No. 5,071,104 describes a wound irrigation apparatus and process for cleansing wounds which includes a pressure bladder, *e.g.*, a blood pressure cuff, disposed proximate a reservoir holding a cleaning solution. The device in the '104 patent also includes a flexible tubular conduit for transmitting the solution from the reservoir to a single nozzle. The conduit and reservoir form a two-part system which is time consuming to set up, inconvenient to use, and costly.

U.S. Patent No. 5,133,701 describes a disposable pressurized wound irrigation device which has a pressurized chamber for providing a force upon the reservoir such that a single liquid stream of cleansing solution is expelled from the device at a constant pressure. A propellant is used in evacuating the cleanser contents of the device. This invention requires a propellant and involves a relatively elaborate manufacturing and filling process which is labor intensive and requires specialized machinery. This device is also inconvenient to use and costly.

More recently, an advantageous wound irrigation system has been developed whereby a dispersed stream of irrigation fluid is easily and effectively applied to wounds.

This system is described at, for example, U.S. Patent Nos. 5,830,197 and 6,468,253 and International Patent Applications WO 00/15279 and WO 02/007799. Although the use of the dispersed stream was highly advantageous, it has now been determined that the shape

and size of the nozzles delivering the irrigation fluid can be improved to give even better results.

The subject invention successfully addresses the above described disadvantages associated with the previously known devices and methods, and provides certain attributes and advantages which have not been realized by these known devices.

Brief Summary of the Invention

The subject invention provides novel, inexpensive, and highly effective methods and devices for convenient and effective wound irrigation. In one embodiment the subject invention provides a discharge means for a reservoir housing containing irrigation solution wherein the discharge means has one or more specifically designed nozzles through which a sufficient volume of the irrigation solution can pass at an appropriate pressure for effective wound irrigation.

In a preferred embodiment, the device has a plurality of nozzles that are specifically designed to reduce the pressure loss as the irrigation fluid leaves the reservoir housing. There are two elements of the design that are particularly important — the shape of the nozzle and the length of the nozzle. Preferably, the nozzle is elongated and comprises a venturi shaped passageway.

In a preferred embodiment, the reservoir housing, upon which a discharge means is either permanently or detachably affixed, is compressible (*e.g.*, plastic bottles in which saline solutions are presently available). The operator (*i.e.*, medical or health care professional or other person) using the subject device and providing wound irrigation therapy can easily compress the reservoir housing to force the irrigation solution through the nozzle(s) of the discharge means under sufficient pressure to dislodge dirt, debris, or other particles, including microorganisms, *e.g.*, pathogenic bacteria.

Specifically exemplified herein is the use of a plurality of elongated nozzles to achieve the desired dispersal, pressure, and volume of the stream of irrigation solution.

The subject invention provides an easy to use, economical wound irrigation system that is capable of delivering adequate volumes of irrigation solution (without refilling the reservoir) in a dispersed stream under sufficient pressure to effectively cleanse the wound, thereby reducing the incidence of infection.

In a further embodiment, the subject invention provides a laceration tray that has items conveniently provided for treating wounds.

In yet another embodiment, the subject invention provides a sterile product for use in an operating room.

5 In yet another embodiment, the subject invention provides a pressurized irrigation assembly comprising: irrigation solution; a reservoir housing that contains the irrigation solution; a discharge means having one or more specifically designed nozzles through which a sufficient volume of the irrigation solution can pass at an appropriate pressure; and a means for creating pressure for the generation of one or more dispersed streams
10 through the nozzle(s) to irrigate damaged tissue.

The subject invention allows the operator to, without assistance, easily direct and control the application of irrigation solution with one hand, leaving the other hand free for other activities, such as separation of the wound to further facilitate irrigation.

15 Brief Summary of the Figures

Figure 1 shows the subject wound irrigation device that includes a compressible reservoir housing, and a discharge means that has a plurality of nozzles for directing a pressurized stream of irrigation solution to a wound.

20 **Figure 2** shows an embodiment of the subject wound irrigation device with a protective cover.

Figure 3 shows one embodiment of the subject wound irrigation device.

Figure 4 shows elongated nozzles of the subject invention.

Figure 5 shows a specific embodiment of the subject invention.

25 **Figure 6** shows a venturi shaped nozzle of the subject invention.

Detailed Description of the Invention

The subject invention provides novel, convenient, inexpensive, and effective wound irrigation devices that comprise, in a preferred embodiment, a reservoir housing and a discharge means having one or more nozzles for irrigation of a wound. The subject
30 invention also provides methods of use for the device.

The materials and methods of the subject invention make it possible to conveniently and easily apply a stream of irrigation fluid to a wound with the stream having an appropriate volume, pressure, and dispersal pattern. Under optimal circumstances, the wound irrigation devices and methods of the subject invention are utilized by trained emergency medical technicians; however, because of the simplicity and convenience of the devices of the subject invention, they can be used to greatly enhance the effectiveness of wound irrigation regardless of the training level of the operator performing the irrigation.

In a preferred embodiment, the nozzle(s) of the current invention are specifically designed to reduce the pressure loss as the irrigation fluid leaves the reservoir housing. There are two elements of the design that are particularly important — the shape of the nozzle and the length of the nozzle. Preferably, the nozzle is elongated and comprises a venturi shaped passageway.

In a preferred embodiment, each nozzle acts a jet through which irrigation fluid is forced, under pressure, to achieve velocities and pressures appropriate for efficient wound (including eye) irrigation. The nozzles are designed to reduce friction and turbulence and facilitate achieving sufficient irrigation pressures with minimal operator effort.

In accordance with the subject invention, it has been determined that an elongated nozzle is preferred. As used herein, reference to the “nozzle” refers to a passage 98 that delivers a stream of irrigation fluid from the inside to the outside of a reservoir housing. In accordance with the subject invention, the nozzle is preferably longer than about 0.005 inches (from inlet port 102 to outlet port 96). More preferably, the nozzle is longer than about 0.01 inches. Also, it has been determined that it is preferable for the nozzle to be less than about 0.50 inches. More preferably, the nozzle is less than about 0.3 inches. Even more preferably, the nozzle is about 0.2 inches long.

In certain embodiments of the invention, the nozzle is a “shaped” nozzle defined by a venturi shaped passageway (see Figures 5 and 6). As used herein, the “venturi shaped passageway” extends the length of the nozzle and is defined by a cylindrical bore 98 that narrows as it approaches the outlet port 96. The venturi shaped passageway of the nozzle limits the generation of turbulence in the irrigation fluid as it passes through the nozzle(s) during the operation of the wound irrigation device of the subject invention.

Therefore, fluid passing through the nozzle experiences laminar flow (or at least a reduction in turbulence) as it passes through and exits the nozzle. Thus, as used herein, reference to the “venturi shaped passageway” refers to a nozzle with a passageway where the cross-sectional area of the inlet port **102** is greater than the cross-sectional area at or near the outlet port **96** and the turbulence through the nozzle is less than the turbulence of a nozzle of the same or similar size but having a “squared-off” inlet port and/or constant diameter passageway. This venture shaped nozzle has been found to be particularly advantageous for achieving desired irrigation fluid pressures and velocities according to the subject invention.

The nozzle passage area **98** is preferably defined by a funnel shape having a portion with a curved surface, where the nozzle cross-section decreases from an upstream wider end **102** to the downstream end **96**.

Figure 5 shows a specific embodiment of the elongated, shaped nozzles of the subject invention. In Figure 5 the conical shaped nozzle is 0.2 inches long (from inlet port to outlet port).

In another embodiment, the elongated nozzles of the invention have nozzle passageways that are defined by a cylindrical shape with straight walls that lack the curving conical shape.

As would be appreciated by a person skilled in the art having the benefit of the current disclosure, the nozzles of the subject invention can be formed within the material of the discharge means. Thus, if the discharge means is formed of plastic that is sufficiently thick, then the nozzles may simply pass through the material of the discharge means. Alternatively, the nozzles may extend from either side of the discharge means. Such an embodiment is shown in Figures 3-5.

Figure 1 shows an embodiment of the subject invention wherein the device comprises a squeezable reservoir housing having a wall **60** that forms a reservoir that can contain therein an irrigation material (such as wound-cleaning material). The reservoir can preferably hold a liquid solution (for example, sterile saline) as the wound cleansing solution for irrigating, and thereby removing particles or other contaminants from a wound. The reservoir housing has a mouth **62**, which communicates the reservoir to the

outside of the housing. Disposed over the reservoir housing mouth, and affixed to the reservoir housing mouth is a discharge means **80, 100**.

Another embodiment of the subject invention includes a reservoir housing comprising an inlet port and fitting for attaching tubing for delivery of pressurized gas to the reservoir. Pressure sources generally available in hospitals, emergency rooms, and other medical clinics or facilities provide a pressure of 0-55 pounds per square inch (PSI). The reservoir can be attached by, for example, a flexible tube to the pressure source connector and to a fitting provided on the reservoir housing of the subject device.

In certain embodiments, the discharge means is detachably affixed to the reservoir housing mouth. In such embodiments, the reservoir mouth can include connecting means such as threads, snap fits, grooves, or other mechanical connection configurations for operably connecting the reservoir housing mouth to the discharge means.

The wall of the reservoir housing can be made or molded from any material that is preferably rigid enough to stand upright when the reservoir is filled with irrigation solution. In a typical embodiment, the reservoir housing is formed by a molded plastic, which is pliable enough so that the wall of the reservoir housing can be squeezed or compressed by hand to exert pressure on the contents of the reservoir. The preferred embodiment comprises a plastic material that is pliable enough to squeeze by hand and which also has sufficient resilience to return to its original shape when no longer compressed or squeezed.

The horizontal cross-sectional shape of the reservoir housing can be circular, square, rectangular, or other geometric shapes as desired or as already available. The walls can be tapering toward one end or the other. Alternatively, other shapes can be made for the reservoir housing according to and adapted for a particular use. For example, part of the reservoir housing wall can be slightly rounded as in a general hourglass shape and/or can be molded for ergonomics to easily fit a hand or otherwise to facilitate handling or compressing the reservoir housing. The reservoir formed by the housing of the subject invention can typically hold a volume of about 100 ml to 1000 ml, preferably about 250 ml to about 750 ml and most preferably about 500 ml. Advantageously, with manual compression, the device and method of the subject invention can deliver 500 ml of irrigation fluid in less than 30 seconds and, typically, in

15 to 25 seconds. The fluid is delivered at about 4 to 20 psi. Lower pressures can be used for irrigating eye wounds. For irrigation of wounds in or around the eye, a pressure of about 1 psi to about 5 psi is preferred.

Further, in a preferred embodiment, the reservoir housing comprises at one end a neck portion formed at the mouth of the reservoir housing. The neck portion of the reservoir housing is generally at least slightly smaller in cross sectional area than the reservoir housing. The reservoir housing neck is preferably integrally molded with the reservoir housing, but can be formed or molded separately and affixed to the mouth of the reservoir housing. The material used for the neck portion of the reservoir housing can be the same as the material used to make the reservoir housing cylinder. Alternatively, the neck portion can be a different material, for example, a more rigid or sturdy material than the compressible material forming the reservoir housing wall. For example, the material used to make the neck portion can be a metal or a hard plastic, or the like.

With reservoir housing embodiments that include a neck portion, the discharge means is typically disposed over and affixed to the neck portion. In a related embodiment, the neck portion of the reservoir housing can include a connecting means for detachably affixing a discharge means thereto. The connecting means can include threads, latches, grooves, or other mechanical connection configurations for operably connecting the neck portion to the discharge means. The connecting means can be on the outer face of the neck portion, forming a male connecting end, or can be on the inner face forming a female connecting end of the neck portion.

In a preferred embodiment, the discharge means has a plurality of elongated nozzles 70 whereby the irrigation solution in the reservoir passes through in a pressurized and directional manner. A backsplash shield 90 can also be provided either with the reservoir housing or with the discharge means.

The back-splash protective shield protects the health care professional (or other user) from back-splash of human and or animal body fluids that are mixed with and splashed from the wound when the wound is contacted by the discharged irrigation solution.

As described herein, a critical feature of the subject invention is the unique design of the nozzles that enable easy and convenient creation of a dispersed stream of irrigation

solution having the appropriate volume, pressure and dispersal pattern to obtain effective wound irrigation.

As used herein, reference to a “dispersed” stream of solution means that the area from which the stream emanates, or the area which it contacts, is larger than that which can be achieved using a typical syringe for irrigation. A typical syringe, as is well known in the art can be, for example, a 16 or 18 gauge syringe. In one embodiment, the dispersed stream can be achieved using multiple nozzles. The nozzles can be presented in a variety of patterns on a discharge means, such as a circular or square pattern.

The discharge means with nozzles is a particularly advantageous feature of the invention. The discharge means can be, for example, a flat or domed disc of approximately the same size as the opening of the reservoir housing. In one embodiment, the discharge means has a plurality of nozzles.

In certain embodiments, the discharge means is designed with connecting means that are threads or grooves, which allow for complementary attachment to currently available irrigation solution bottles. Thus, the discharge means of the subject invention can be interchangeable, when desired, with the screw-cap that is provided with an irrigation solution bottle as are available. The screw-top design of the discharge means provides the operator with the option of using the reservoir housing with the nozzles of the invention or to threadably remove the discharge means and pour out or change the irrigation solution.

Each of the nozzles of the discharge means can be of any desirable size, preferably less than one-eighth inch in diameter and having a size between about a 10 gauge hypodermic needle and about a 30 gauge needle, and most preferably having a size ranging from that of a 16 gauge needle to a 25 gauge needle. Specific dimensions and shapes are shown in Figure 5. The outlet port 96 may have, for example, an inner diameter of about 0.02 to about 0.07 inches. For the venturi shaped nozzle (Figure 6), the diameter of the inlet port 102 (proximal to the reservoir) can be, for example, from about 0.05 to about 0.30 inches, or more.

Each of the nozzles can be the same size or the nozzles can be different sizes and shapes. The different sizes of nozzles allow for the liquid to be expelled from the discharge means at different pressures. For example, the 16 gauge nozzle allows for a

stream having about 6 psi pressure when the device is squeezed by the normal adult; the 25 gauge nozzle provides a pressure of up to about 20 psi from each nozzle.

5 The shaped nozzles of the invention have the added advantage when compared to other nozzles in that little or no release of irrigation material is permitted without pressure being applied to the irrigation material. For example, if a reservoir housing with shaped nozzles is tipped onto its side or even held upside-down with gravitational pull on the irrigation material through the discharge means, there will be little or no release of irrigation material through the shaped nozzles.

10 As shown in Figure 2, one embodiment of the subject invention also includes a removable or partially detachable protective cap 92, which is placed over the discharge means to protect the nozzles and contents of the reservoir from contamination or premature discharge or leakage. The protective cap can be attached with an element 94 that is removable. Such elements 94 include fasteners, non-permanent adhesives, and the like.

15 In a preferred embodiment, the discharge means 70 comprises four nozzles. Additionally, to discharge the irrigation solution at appropriate pressure, the diameter of the nozzles 74 can be about 0.02 to 0.07 inches in diameter.

The irrigation solution used can be water, saline, or a balanced salt solution. The solution is preferably sterile and at the discretion of the user or manufacturer of the irrigation solution can additionally comprise an antibacterial and/or antifungal component. The device can be sterilized by known sterilization techniques, including boiling, autoclaving, gas sterilization and the like, either separately or together with the reservoir housing.

20 Buffered Ringer's solution or commercially available balanced salt solution (*e.g.*, Tis-U-Sol or Physio-Sol) are physiologically compatible and are commonly used in wound irrigation procedures.

The antiseptic agents most commonly used in wound care at present include:

25 Povidone-iodine solution (Betadine preparation)-iodine added to the carrier polyvinylpyrrolidone (PVP), a water-soluble organic complex; this combination is called an iodophor. Standard solutions of Betadine preparation are 10 per cent.

30

Povidone-iodine surgical scrub (Betadine scrub)-the iodophor PVP-I and an anionic detergent (pH 4.5).

pHisoHex-an emulsion of an anionic detergent, entsulfon, lanolin cholesterols, petrolatum, and hexachlorophene (pH 5.5).

5 Hi-Bi-clens-chlorhexidine gluconate plus a sudsing base (pH 5.1 to 6.5).

Tincture of green soap-potassium oleate, isopropanol, potassium coconut oil, soap.

Dakin's solution 0.2 per cent solution hypochlorite solution.

Hydrogen peroxide-an oxidizing agent.

10 Benzalkonium chloride (Zephiran)-a quaternary ammonium compound that works as a cationic surface active agent.

Nonionic surfactants-Pluronic F-68 (Shur-Clens) and Poloxamer-188 (Pharma Clens)-agents that have no antimicrobial activity (pH 7.1).

15 From the description of the device herein above, a method of using the subject device would readily be understood and adaptable by those persons having ordinary skill in the art. The reservoir housing is filled with a desired irrigation solution. The irrigation solution is sterilized before or after filling. The reservoir housing and contents can be stored in a sterile environment, *e.g.*, sterile packaging which is opened immediately prior to use. In a preferred use, the protective shield is removed, then the reservoir housing can
20 be directed towards the wound and squeezed or compressed to expel or discharge the solution in the desired direction, and at the desired pressure to effect irrigation of a wound to remove contaminants or debris. See also the Example 2, provided below.

It would also be understood that the described discharge means can be packaged separately from the reservoir housing. The discharge means is packaged in a sterile
25 environment. In a preferred use of the embodiment wherein the discharge means is provided separately from the reservoir housing, the cap of a readily available, squeezable irrigation bottle containing a sterile irrigation solution, *e.g.*, normal saline, is replaced with the subject discharge means. The bottle, now having the subject discharge means attached or engaged thereto, can be used as described herein.

30 In one embodiment, the discharge means is provided in a sterile laceration tray. According to the subject invention, the laceration tray has, in addition to a discharge

means or entire irrigation bottle of the subject invention, other items conveniently provided for treating wounds. Contemplated items that can be included in a laceration tray include, but are not limited to, needle holders (*i.e.*, 5" floor-grade smooth); scissors (*i.e.*, 4.5" floor-grade straight Iris scissors); hemostats (*i.e.*, 5" floor-grade curved mosquito hemostat); forceps (*i.e.*, floor-grade tissue forceps with 1x2 teeth); cups (*i.e.*, 2 oz. medicine cups); syringes (*i.e.*, 10cc Luer Lock syringe); needles (*i.e.*, 25 gauge x 5/8" needle; 27 gauge x 1.5" needle; 18 gauge x 1.5" needle); dressings (*i.e.*, gauze dressings); drapes (*i.e.*, polylined fenestrated drapes); and towels (*i.e.*, absorbent towels).

Another embodiment of the invention provides a pressurized irrigation assembly to provide automated dispersal of irrigation solution. The pressurized irrigation assembly can comprise: irrigation solution; a reservoir housing that contains the irrigation solution; a discharge means having a plurality of specifically designed nozzles through which a sufficient volume of the irrigation solution can pass at an appropriate pressure; a means for creating irrigation solution pressure for the generation of a plurality of dispersed streams through the nozzles to irrigate damaged tissue.

A variety of pressure means have been developed to enable automatic (as opposed to manual) transfer of irrigation solution from a reservoir housing to damaged tissue. For example, U.S. Patent No. 6,574,527 to Henniges *et al.* describes a hand held irrigator that can be attached to the mouth of a reservoir housing irrigation solution. Various other apparatus that enable the automatic transfer of irrigation solution from a reservoir housing to damaged tissue include, but are not limited to, U.S. Patent Nos. 6,751,813; 6,746,419; 6,106,494; 5,484,402; 5,470,305; 5,269,750; and 5,046,486.

In one embodiment of the invention, the pressure means is a hand-held device similar to the irrigator disclosed in U.S. Patent No. 6,754,527. The hand held device has a tip and a supply end. Irrigation solution from the reservoir housing is provided to the supply end of the pressure means and is eventually discharged from the tip of the pressure means. Affixed to the tip is a discharge means of the invention, which can be detachably affixed to the tip. The hand held device further comprises a pump for regulating the rate of irrigation solution discharge and a motor for actuating the pump. In certain embodiments, the motor is a battery operated motor.

In a method of use, where a reservoir housing 60 having discharge means 70 affixed thereto is provided, a protective cap 92 is first removed from the backsplash shield 90. The discharge means 70 is directed towards the wound, and the reservoir housing 60 is compressed, discharging the irrigation solution through the discharge means 70. The solution can be discharged at a range of pressures of about 4 - 20 lbs/in², with a preferred pressure of about 7 psi.

The reservoir housing 60 can be compressed manually or via other mechanical means. For example, the operator may compress the reservoir housing using either one hand or two hands, to provide increased pressure (*i.e.*, 16 psi). Alternatively, a pressure means can be activated to generate a dispersed stream of irrigation solution through the discharge means.

In another method of use, where a reservoir housing 60 and discharge means 70 are provided separately, a protective cap 92 is removed from the mouth or neck portion of the reservoir housing. The discharge means is then affixed to the mouth or neck portion of the reservoir housing via complementary connecting means. After the discharge means is affixed to the reservoir housing, the discharge means is directed towards the wound or eye, and the reservoir housing is compressed to discharge a dispersed stream of irrigation solution through the nozzles of the discharge means.

Significantly, it is known that more force is required to rid the wound of particles with a small surface area (*e.g.*, bacteria) than to remove particles with a large surface area (*e.g.*, dirt, sand, or vegetation). Minimum recommended volumes of irrigation solution vary, but for a moderately sized potentially contaminated wound, for example a laceration 3-6 cm long and less than 2 cm deep, at least 200 to 500 ml, or more should be used. Greater volumes, on the order of one to two liters, may be required for larger or heavily contaminated wounds. Irrigation should continue at least until all visible, loose particulate matter has been removed.

Following are examples that illustrate procedures for practicing the invention. These examples should not be construed as limiting.

Example 1 — Preferred Nozzle Designs

Performance of nozzle designs with regard to pressure, flow rate and dynamic pressure, were compared.

5 In one test, a squeeze bottle with inlet fitting and pressurized reservoir was set up on its side and filled. A flow meter was placed between the squeeze bottle and the reservoir. A test pressure range of 2-7 psi was applied to each nozzle design and the flow rate was recorded for each test pressure (1 psi increments).

The shaped nozzle design (defined by a venturi shaped passageway) created greater flow than the sharp edged, non-shaped nozzle at the same fluid pressure.

10 For a pressure test, a fulcrum and scale were set-up in front of the horizontally mounted irrigation device. The pressure to the nozzles was varied from 2 to 7 psi and the force was recorded at each 1 psi increment.

The shaped nozzle produces between 70% - 200% more force than the sharp-edged nozzle.

15 At 4 psi the calculations show 25.7 and 19.2 grams of force for the shaped and non-shaped nozzles, respectively.

Thus, the discharge means with 4-venturi shaped nozzles produces more force and more flow per squeeze on the irrigation bottle than the discharge means with 4 non-shaped nozzles.

20

Example 2 — Methods of Wound Irrigation

When a patient presents a wound to a medical or other health care professional skilled in the art, that medical professional assesses the extent of the injury sustained by the patient, including all other life threatening injuries. Appropriate action regarding these life threatening injuries is performed and a history is recorded. All wounds are covered to minimize further contamination until the actual repair process begins.

25 For examination of the wound, it is assumed that a medical professional would have performed a detailed evaluation of the extent of tissue injury, including but not limited to: anatomical area considerations, depth of the wound, type of injury, e.g., crash injury, puncture wound, bites, missiles, cuts with sharp objects, or the like. Included in this examination would be a determination of the type(s) of contamination, time elapsed

30

between the occurrence of the injury to presentation, gross contamination of a wound, and other medical factors associated with an increase incidence of infection (for example, diabetics, AIDS patients, and chemotherapeutics patients).

5 The wound and surrounding tissue, at the option of the health care professional, could be anesthetized using topical, local, or general anesthetics before the wound-cleansing method begins.

10 In one embodiment, the subject device has a discharge means affixed to a reservoir housing as described with a protective shield covering the discharge means. The health care professional using the subject device would remove the protective shield to expose the discharge means. The subject device can be held in either hand as preferred by the user. Normally, it would be held in the dominant hand in a bottle-holding fashion. This allows the medical care professional to gently open the wound if needed, with the opposite hand, preferably protected by a sterile glove, to expose the depths of the wound.

15 Once the depths of the wound have been exposed, the end of the reservoir housing having the discharge means affixed thereto is directed towards the wound. Manual or mechanically produced pressure is applied to the reservoir housing to expel the irrigation solution through the nozzles of the discharge means. The wound should be irrigated in this fashion until all visible evidence of contamination has been removed. A potentially contaminated wound of any size should be irrigated with a minimum of 200-300 ml of irrigation solution. Heavily contaminated or larger wounds may require 2-3 liters of irrigation solution. The health care professional could vary the angle of the discharged irrigation solution from the discharge means in reference to the wound to further assist with the dislodgement of contaminants. This variation in the angle will also decrease or increase the amount of back-splash. Thus it would be important to irrigate in a manner that decreases the back-splash. Minimizing back-splash is achieved by irrigation at acute angles to the plane of the wound.

25 Following an initial irrigation of the wound, a re-examination of the wound should be undertaken. The wound should be explored to its base to ascertain that no visible foreign bodies or contaminants remain. If foreign bodies or contaminants are found, the irrigation process should be repeated followed by a re-examination. This may continue for several cycles.

Once irrigation has been completed, *i.e.*, no visible contaminants remain, the damaged tissue would be repaired in a standard accepted fashion.

Irrigation of skin wounds such as cuts, scrapes, punctures, abrasions, *etc.* are particular well-suited for irrigation according to the subject invention.

5

It should be understood that the example and embodiment described herein is for illustrative purposes only and that various modifications or changes in light thereof will be suggested to persons skilled in the art and are to be included within the spirit and purview of this application and the scope of the appended claims.

In the Claims

I claim

1. A device for wound irrigation wherein said device comprises a reservoir housing containing a sterile wound irrigation solution, and wherein said reservoir housing is attached to a discharge means having at least one nozzle through which the wound irrigation solution can exit the reservoir housing, wherein said nozzle has a cross-sectional area that decreases from the inlet port of the nozzle (proximal to the reservoir housing) to the outlet port (distal to the reservoir housing) such that the nozzle forms a venturi passageway.
2. The device, according to claim 1, wherein the nozzle has a length from the inlet port to the outlet port of between about 0.005 and 0.50 inches.
3. The device, according to claim 2, wherein the nozzle has a length of between about 0.01 and 0.3 inches.
4. The device, according to claim 1, wherein the inner diameter of the outlet port is between about 0.02 and 0.07 and the inner diameter of the inlet port is between about 0.05 and 0.30 inches.
5. The device, according to claim 1, further comprising a backslash shield.
6. The device, according to claim 1, wherein the reservoir housing is made from a compressible material.
7. The device, according to claim 6, wherein the reservoir housing is made from plastic.

8. The device, according to claim 1, wherein the reservoir housing is generally in the shape of a cylinder having an ergonomic shape with curved sides such that the cross-sectional area of the cylinder varies along the length of the cylinder.

9. The device, according to claim 1, further comprising means for pressurizing the reservoir housing.

10. The device, according to claim 8, wherein the means for pressurizing the reservoir housing is battery operated.

11. The device, according to claim 1, having a plurality of nozzles.

12. The device, according to claim 11, having 4 nozzles.

13. The device, according to claim 1, which creates a dispersed stream of irrigation fluid when the irrigation fluid leaves the device under pressure.

14. The device, according to claim 1, which has approximately 500 ml of irrigation solution.

15. The device, according to claim 14, wherein, when the device is placed on its side, fluid does not exit the nozzles.

16. The device, according to claim 1, which is sterile and enclosed within wrapper that maintains sterility until the wrapper is opened.

17. A tray conveniently providing items for use in treating wounds wherein said tray comprises at least one of the following:

a) a discharge means that can be attached to a bottle containing wound irrigation solution; or

b) a bottle containing a wound irrigation solution,
and wherein said tray further comprises at least one item selected from the group consisting of:

needle holders; scissors; hemostats; forceps; cups; syringes; needles; dressings; drapes; and towels.

18. A method for irrigating a wound, said method comprising the following steps:

(a) providing a device for wound irrigation wherein said device comprises a reservoir housing containing a sterile wound irrigation solution, and wherein said reservoir housing is attached to a discharge means having at least one nozzle through which the wound irrigation solution can exit the reservoir housing, wherein said nozzle has a cross-sectional area that decreases from the inlet port of the nozzle (proximal to the reservoir housing) to the outlet port (distal to the reservoir housing) such that the nozzle forms a venturi passageway;

(b) directing the discharge means and reservoir housing so as to discharge the wound-irrigation solution toward a wound; and

(c) discharging said wound-irrigation solution from said reservoir housing and through said nozzle, or nozzles, to produce a stream of wound-irrigation solution directed at the wound.

19. The method, according to claim 18, wherein said wound-irrigation solution is discharged from said device, at a pressure between about 4 psi and about 20 psi.

20. The method, according to claim 18, wherein said discharge means has a plurality of nozzles.

21. The method, according to claim 20, wherein said discharge means has 4 nozzles.

22. The method, according to claim 18, wherein the inner diameter of the outlet port of the nozzle, or nozzles, is between about 0.02 and about 0.07 inches.

23. The method, according to claim 18, wherein the inner diameter of said inlet port(s) is between about 0.05 and 0.30 inches.

24. The method, according to claim 18, wherein said discharge means is detachably engaged to said reservoir housing.

25. The method, according to claim 18, wherein said device comprises a backsplash shield.

26. The method, according to claim 18, wherein the nozzle has a length of between about 0.01 and 0.50 inches.

27. The method, according to claim 18, wherein the irrigation fluid leaving the device creates a dispersed stream of fluid.

28. The method, according to claim 18, wherein about 500 ml of fluid is administered in about 15 to 30 seconds.

29. The method, according to claim 18, wherein the wound is in or around the eye and the irrigation fluid is administered at a pressure of from about 1 psi to 5 psi.

30. A discharge means that can be attached to a reservoir housing that contains an irrigation fluid, where said discharge means has at least one nozzle through which the wound irrigation solution can exit the reservoir housing, wherein said nozzle has a cross-sectional area that decreases from the inlet port of the nozzle (proximal to the reservoir housing) to the outlet port (distal to the reservoir housing) such that the nozzle forms a venturi passageway.