

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)


PCT

(10) International Publication Number
WO 2004/053465 A2

- (51) International Patent Classification⁷: **G01N 15/14**, B01L 3/00, G01P 13/00 (74) Agents: **DEHLINGER, Peter, J.** et al.; Perkins Coie LLP, P.O. Box 2168, Menlo Park, CA 94026 (US).
- (21) International Application Number: PCT/US2003/039069 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 9 December 2003 (09.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/431,872 9 December 2002 (09.12.2002) US
60/511,798 16 October 2003 (16.10.2003) US
10/705,162 6 November 2003 (06.11.2003) US
- (71) Applicant: **ADVANCED FLUIDIX LABORATORIES, LLC** [US/US]; 888 Peepsight Court, Incline Village, NV 89451 (US).
- (72) Inventors: **ARAVANIS, Alexander, M.**; 268 Swain Way, Palo Alto, CA 94304 (US). **PYLE, Jason, L.**; 1240 College Avenue, Palo Alto, CA 94306 (US).
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: MALE FERTILITY ASSAY METHOD AND DEVICE



(57) Abstract: A method and device for assaying sperm motility in a forward direction and density of active sperm in a semen sample are disclosed. The device includes a microfluidics structure having a sample reservoir, a downstream collection region and a microchannel extending therebetween. The microchannel is dimensioned to confine sample sperm to single-direction movement within the channel, such that sperm in a semen sample placed in the sample reservoir enter and migrate along the microchannel toward and into the collection region. Also included is a detector for detecting the presence of labeled sperm in the microchannel or collection region, and an electronics unit operatively connected to the detector for (i) receiving detector signals, (ii) based on the detector signals received, determining sperm motility and density in the sperm sample, and (iii) displaying information related to sperm motility and density.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.