

Process for dehumidifying moist gas mixtures

The invention relates to a process for dehumidifying a moist gas mixture. The invention further relates to an apparatus for dehumidifying a moist gas mixture and to the use of said apparatus in the process according to the invention.

5

Background of the invention

Dehumidification of moist gas mixtures is necessary in a multitude of technical fields.

For instance ventilation and air conditioning of buildings or vehicles generally necessitates not only cooling but also dehumidification of the air since the air to be cooled is often so humid that during
10 cooling to the desired temperature the temperature falls below the dew point temperature. Hence in conventional air conditioning systems dehumidification of the air accounts for a large part of the electricity consumption.

The electricity consumption of air conditioning systems for buildings is reduced by dehumidifying the air by adsorption or absorption of water with a drying medium and subsequently regenerating
15 the water-laden drying medium by heating to a temperature at which the water is desorbed again. Compared to adsorption on a solid absorbent, the advantage of absorption in a liquid absorption medium is that drying of air can be performed with reduced equipment complexity and with less drying medium and that regeneration of the water-laden drying medium using solar heat is easier to carry out.

20 A further technical field where dehumidifying of moist gas mixtures is employed is the field of absorption chillers (principle described in WO 2014/079675 A1; according to the invention “absorption chiller” is used synonymously with “absorption heat pump”). Here, the damp gas mixture is formed during evaporation of water under low pressure. The water vapour thus formed needs to be removed from the moist gas mixture so that said mixture may then be returned to the
25 water evaporation to pass through a new cycle. Here too, absorption in a liquid absorption medium is favoured over adsorption on a solid adsorption medium.

Finally, dehumidification of moist gas mixtures is also important in the field of natural gas extraction, as described in DE 10 2010 004 779 A1 for example.

Examples of materials incorporated in air or natural gas dehumidifying plants and in chillers include
30 titanium, copper and noble metals. Components based on aluminium too are installed in air dehumidifying plants. Compared to alternative materials such as titanium, copper or stainless steel, aluminium has the advantage that it has a higher thermal conductivity. It is additionally easier to process, lighter and cheaper. Hence in automobile manufacture in particular air conditioning systems made of aluminium are preferred over other materials.

35 The aqueous solutions of lithium bromide, lithium chloride or calcium chloride hitherto employed as liquid absorption media in commercial air conditioning systems have the disadvantage that they are corrosive towards the materials of construction typically employed in air conditioning systems and

that they thus necessitate the use of expensive specific materials of construction. This problem is encountered particularly for aluminium. These solutions can additionally cause problems due to salt crystallizing out of the absorption medium.

Y. Luo et al., Appl. Thermal Eng. 31 (2011) 2772-2777 proposes using the ionic liquid 1-ethyl-3-methylimidazolium tetrafluoroborate in place of an aqueous solution of lithium bromide for drying of
5 air. However, this ionic liquid has the disadvantage of only poor absorption capability.

Y. Luo et al., Solar Energy 86 (2012) 2718-2724 proposes using the ionic liquids 1,3-dimethylimidazolium acetate as an alternative to 1-ethyl-3-methylimidazolium tetrafluoroborate for drying of air. However, 1,3-dimethylimidazolium acetate is not stable and decomposes to a not
10 inconsiderable extent during desorption.

This problem is also encountered for the ionic liquids proposed in US 2011/0247494 A1, paragraph [0145]. This document proposes using trimethylammonium acetate or 1-ethyl-3-methylimidazolium acetate as liquid drying agent in place of aqueous lithium chloride solution. Example 3 compares water uptake from moist air for a series of further ionic liquids.

15 CN 102335545 A describes aqueous solutions of ionic liquids that do not suffer from the abovementioned problems as absorption media for air dehumidification. The absorption media are reported to be noncorrosive toward steel. Ionic liquids described are, inter alia, 1,3-dimethylimidazolium dimethylphosphate, 1-ethyl-3-methylimidazolium dimethylphosphate and 1-butyl-3-methylimidazolium dimethylphosphate. However, CN 102335545 A is chiefly concerned
20 with steel-based air dehumidifiers. Yet this material is disadvantageous compared to aluminium for the abovementioned reasons. Additionally the heat transfer achieved with the ionic liquids cited in CN 102335545 A, which is important for efficient air dehumidification, was relatively low.

Yet, heat transfer is an important parameter which must be accounted for when choosing absorption media. Thus, in the field of air dehumidification absorption media which ensure a
25 particularly good heat transfer between themselves and further constituents of an air dehumidifier are particularly readily employable. In air dehumidifiers in which metallic components (for example aluminium) are employed this heat transfer takes place at least partially between the absorption media and metallic surfaces.


The present invention accordingly has for its object to provide absorption media that ensure
30 improved heat transfer compared with prior art absorption media when used in aluminium-based air conditioning systems, air dehumidifiers, absorption chillers etc.

Absorption media have now been found which, surprisingly, fulfil this object.

Detailed description of the invention

35 The present invention accordingly relates in a first aspect to a process for dehumidifying a moist gas mixture **G**, in particular moist air, in an apparatus **V**₁, comprising the steps of:

- (a) contacting the moist gas mixture **G** with a liquid absorption medium **A**_{VE} comprising a mixture of at least one trialkyl phosphate of the structure (I) with



and at least one salt **S** selected from the group consisting of Q^+A^- , $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, $(\text{Q}^+)_2\text{R}^2\text{OPO}_3^{2-}$, $\text{Q}^+\text{M}^+\text{R}^3\text{OPO}_3^{2-}$,

5 wherein the liquid absorption medium **A_{VE}** at least partially absorbs water from the moist gas mixture **G**,

to obtain a liquid absorption medium **A_{VE1}** having an elevated water content compared to the liquid absorption medium **A_{VE}** and a gas mixture **G₁** having a relatively low water content compared to the moist gas mixture **G**,

10 (b) at least partially removing water from the liquid absorption medium **A_{VE1}** to obtain a liquid absorption medium **A_{VE2}** having a relatively low water content compared to the liquid absorption medium **A_{VE1}**,

wherein the apparatus **V₁** at least partially comprises a surface made of an aluminium material of construction **O_{Al}** and in the apparatus **V₁** at least one of the liquid absorption media selected from the group consisting of **A_{VE}**, **A_{VE1}**, **A_{VE2}** contacts the surface made of an aluminium material of construction **O_{Al}** via at least one contact surface,
15 characterized in that

Q^+ is a dialkylimidazolium cation in which, in particular, the alkyl groups each independently of one another have 1 to 10 carbon atoms,

20 wherein A^- is an anion selected from the group consisting of R^*COO^- , $\text{R}'\text{SO}_3^-$, HSO_4^- , $\text{R}''\text{SO}_4^-$, wherein R^* , R' , R'' , R^{A} , R^{B} , R^{C} , are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

wherein R^1 , R^2 , R^3 are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

and wherein M^+ is an alkali metal ion, preferably Li^+ , K^+ or Na^+ , more preferably K^+ or Na^+ .

25 The gas mixture **G** is not subject particularly restricted. "Moist" is to be understood as meaning in the context of the invention "comprising water, in particular water vapour". "Dehumidifying" is to be understood as meaning at least partially removing water.

"At least partially" is to be understood as meaning in the context of the invention "partially or completely".

30 "Moist gas mixture **G**" is accordingly to be understood as meaning in the context of the invention that the gas mixture **G** comprises water, preferably water vapour ("water vapour" is to be understood as meaning water in the gaseous physical state), and that its composition is otherwise

not particularly restricted. The water content of this moist gas mixture is not particularly restricted and is in particular from 0.01 vol% to 99.99 vol% ("vol%" indicates the volume of water vapour based on the overall volume of moist gas mixture **G**). The composition of the moist gas **G** may otherwise vary depending on the application of the process according to the invention. The moist gas mixture **G** is in particular selected from moist natural gas, moist air (this may be moist indoor air or the moist air resulting from evaporation of water in absorption chillers), preferably moist air. For moist natural gas the water content is in particular from 0.01 vol% to 15.00 vol%, for moist air said content is in particular from 0.01 vol% to 15.00 vol% in the case of moist indoor air or in particular from 95.00 vol% to 99.99 vol% which is the preferred range when moist air resulting from evaporation of water in absorption chillers is concerned.

The process according to the invention is carried out in an apparatus **V₁** which at least partially comprises a surface made of an aluminium material of construction **O_{Al}** (in the context of the invention **O_{Al}** is short for "surface made of an aluminium material of construction") and in which at least one of the liquid absorption media selected from the group consisting of **A_{VE}**, **A_{VE1}**, **A_{VE2}** contacts the surface made of an aluminium material of construction **O_{Al}** via at least one contact surface.

It is in particular possible to employ an apparatus **V₁** having the following components:

- (i) at least one water absorption unit **W_{abs1}** set up for contacting the moist gas mixture with the liquid absorption medium **A_{VE}**,
- (ii) at least one water desorption unit **W_{des1}** which comprises a heat exchanger **W_{x1}** and is set up for at least partially removing water from a liquid absorption medium **A_{VE}**,
- (iii) and a circuit **U₁** which connects the water absorption unit **W_{abs1}** with the water desorption unit **W_{des1}** and by means of which the liquid absorption medium **A_{VE}** may be circulated.

The water absorption unit **W_{abs1}** is the component in which step a) of the process according to the invention in particular is carried out. Employable as water absorption unit **W_{abs1}** are in particular the water absorbers known to those skilled in the art. Said absorbers are based on the principle of increasing the surface area of the liquid absorption medium **A_{VE}** and simultaneously achieving the longest possible residence time of the liquid absorption medium **A_{VE}** in the water absorber during absorption of water. It is in particular possible here to employ water absorbers selected from the group of: packed beds, spray columns, falling-films, bubble columns, tray columns, wet scrubbers (for example Venturi scrubbers), stirred tanks and combinations of these absorbers. It is particularly preferable to employ as water absorbers falling-films, in particular shell and tube falling-films. The water absorption unit **W_{abs1}** may in particular also comprise an additional heat exchanger **W_{z1}** set up such that the liquid absorption medium **A_{VE}** is coolable.

The water desorption unit **W_{des1}** which comprises a heat exchanger **W_{x1}** is the unit in which step b) of the process according to the invention in particular is carried out. The water desorption unit **W_{des1}** is based on the principle of supplying heat to the water-laden liquid absorption medium **A_{VE}** (in particular **A_{VE1}**), increasing the surface area of the water-laden liquid absorption medium **A_{VE}** (in

particular A_{VE1}) and simultaneously achieving the longest possible residence time of the water-laden liquid absorption medium A_{VE} (in particular A_{VE1}) in the water desorption unit.


Employable as water desorption unit W_{des1} comprising a heat exchanger W_{x1} are in particular the combinations of heat exchanger and water desorber known to those skilled in the art, in particular horizontal tube evaporators having an upstream heat exchanger, in particular shell and tube heat exchangers, plate and frame heat exchangers. In addition the water desorption unit W_{des1} comprising a heat exchanger W_{x1} may also be a water desorber having an integrated heat exchanger. Such water desorbers having an integrated heat exchanger are in particular climbing film evaporators, long tube vertical evaporators, short tube vertical evaporators, forced circulation evaporators, agitated thin film evaporators. It is particularly preferable to employ as water desorption unit W_{des1} falling-films, in particular shell and tube falling-films.

Circuit U_1 in particular passes A_{VE1} from step a) of the process according to the invention from the water absorption unit W_{abs1} to the water desorption unit W_{des1} and more preferably - in particular when the process according to the invention is carried out in continuous fashion - additionally passes A_{VE2} from step b) of the process according to the invention from the water absorption unit W_{des1} to the water desorption unit W_{abs1} .

The circuit U_1 is in particular a conduit, in particular selected from the group consisting of tube, hose.

In a further preferred embodiment the circuit U_1 also comprises a pump.


A first step of the process according to the invention comprises contacting the moist gas mixture G with a liquid absorption medium A_{VE} comprising a mixture of at least one trialkyl phosphate of the structure (I) with



and at least one salt S selected from the group consisting of Q^+A^- , $Q^+(R^1O)_2PO_2^-$, $(Q^+)_2R^2OPO_3^{2-}$, $Q^+M^+R^3OPO_3^{2-}$. The contacting may be effected in any way known to those skilled in the art, in particular in a water absorption unit W_{abs1} . The contacting causes the absorption medium A_{VE} to at least partially absorb moisture, i.e. water, from the moist gas stream G to afford a liquid absorption medium A_{VE1} having an elevated water content compared to the liquid absorption medium A_{VE} and a gas mixture G_1 having a relatively low water content compared to the moist gas mixture G .

It is preferable to cool the absorption medium A_{VE} during contacting of the moist gas mixture G in order that as much moisture as possible is absorbed from the moist gas mixture G . This may be achieved, for example, via an additional heat exchanger W_{z1} in the water absorption unit W_{abs1} . The temperature of the absorption medium A_{VE} during contacting of the moist gas mixture G is thus preferably in the range of from 2°C to 100°C, preferably from 3°C to 80°C, more preferably from 4°C to 50°C, most preferably from 5°C to 30°C.

The absorption medium **A_{VE}** comprises a mixture of at least one trialkyl phosphate of the structure (I) with



and at least one salt **S** selected from the group consisting of Q^+A^- , $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, $(\text{Q}^+)_2\text{R}^2\text{OPO}_3^{2-}$,
 5 $\text{Q}^+\text{M}^+\text{R}^3\text{OPO}_3^{2-}$,

wherein Q^+ is a 1,3-dialkylimidazolium cation in which in particular the alkyl groups each independently of one another have 1 to 10 carbon atoms,

wherein A^- is an anion selected from the group consisting of R^*COO^- , $\text{R}'\text{SO}_3^-$, HSO_4^- , $\text{R}''\text{SO}_4^-$,
 wherein R^* , R' , R'' , R^{A} , R^{B} , R^{C} , are each independently of one another an alkyl group, in particular
 10 having 1 to 10 carbon atoms,

wherein R^1 , R^2 , R^3 are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

and wherein M^+ is an alkali metal ion, preferably Li^+ , K^+ or Na^+ , yet more preferably K^+ or Na^+ .

In a preferred embodiment of the process according to the invention the salt **S** is selected from the
 15 group consisting of Q^+A^- , $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, and Q^+ is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 6, preferably 1 or 4, more preferably 1 or 2 carbon atoms, and A^- is an anion selected from the group consisting of R^*COO^- , $\text{R}'\text{SO}_3^-$, $\text{R}''\text{SO}_4^-$, wherein R^* , R^1 , R' , R'' , R^{A} , R^{B} , R^{C} are each independently of one another an alkyl group having 1 to 6, preferably 1 to 4, more preferably 1 or 2, carbon atoms.

20 In a more preferred embodiment of the process according to the invention, the salt **S** has the general formula $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, and Q^+ is a dialkylimidazolium cation in which the alkyl groups are each independently of one another methyl or ethyl, and R^1 , R^{A} , R^{B} , R^{C} are each independently of one another methyl or ethyl.

In a yet more preferred embodiment of the process according to the invention, the salt **S** has the
 25 general formula $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, and Q^+ is selected from the group consisting of 1,3-dimethylimidazolium, 1,3-diethylimidazolium, 1-ethyl-3-methylimidazolium; R^{A} , R^{B} , R^{C} , R^1 is methyl or ethyl.

It is moreover particularly preferable in all of the aforementioned embodiments of the process according to the invention when R^{A} , R^{B} , R^{C} are independently of one another selected from methyl,
 30 ethyl; yet more preferably $\text{R}^{\text{A}} = \text{R}^{\text{B}} = \text{R}^{\text{C}} = \text{methyl}$ or $\text{R}^{\text{A}} = \text{R}^{\text{B}} = \text{R}^{\text{C}} = \text{ethyl}$; particularly preferably $\text{R}^{\text{A}} = \text{R}^{\text{B}} = \text{R}^{\text{C}} = \text{ethyl}$.

This is because it has now been found that, surprisingly, imidazolium salts with at least one ethyl group have a particularly small contact angle and thus ensure particularly good surface wetting.

This results in a relatively large contact area, thus also in fewer nonwetted spaces and thus in improved heat transfer inside the apparatus **V₁** and thus also in a particularly efficient process.

The liquid absorption medium **A_{VE}** may, in the process according to the invention, be employed in the form of the pure mixture of the trialkyl phosphates of the structure **(I)** and the salts **S**.

5 Alternatively and more preferably in the process according to the invention, the liquid absorption medium **A_{VE}** is an aqueous solution in which, in particular, the total weight of all trialkyl phosphates of structure **(I)** and all salts **S** is in the range from 65 wt% to 95 wt% based on the total weight of the aqueous solution. It is yet more preferable when the total weight of all trialkyl phosphates of structure **(I)** and all salts **S** in **A_{VE}** is in the range from 70 wt% to 90 wt% based on the total weight
10 of the aqueous solution, yet more preferably in the range from 75 wt% to 87 wt%.

In the process according to the invention the ratio of all trialkyl phosphates of structure **(I)** to the salts **S** in the absorption medium **A_{VE}** is not further restricted. However, it is preferable to employ in the process according to the invention an absorption medium **A_{VE}** in which the ratio of the total weight of all trialkyl phosphates of structure **(I)** to the total weight of all salts **S** is in the range 1 :
15 9999 to 1 : 9, more preferably 1 : 9999 to 1 : 99, yet more preferably 1 : 9999 to 1 : 999.

The gas mixture **G₁** obtained in the first step of the process according to the invention and having a relatively low water content compared to the moist gas mixture **G** then represents the dehumidified gas stream which, depending on the application, can be returned to living or working spaces in the form of dehumidified air or in the case of natural gas can be supplied to power generation.

20 The absorption medium **A_{VE1}** obtained in the first step of the process according to the invention has an elevated water content compared to the liquid absorption medium **A_{VE}**. It will be appreciated that **A_{VE1}**, in terms of the trialkyl phosphates of structure **(I)** comprised in it and of the salts **S** comprised in it, is identical to **A_{VE}** and is preferably distinguished therefrom only by the water content.

A second step of the process according to the invention comprises at least partially removing water
25 from the liquid absorption medium **A_{VE1}** to obtain a liquid absorption medium **A_{VE2}** having a relatively low water content compared to the liquid absorption medium **A_{VE1}**. This additionally comprises supplying heat in particular to the liquid absorption medium **A_{VE1}**. The supply of heat and the at least partial removal may be effected in any way known to those skilled in the art, in particular in a water desorption unit **W_{des1}** comprising a heat exchanger **W_{x1}**. The at least partial
30 removal of water from the liquid absorption medium **A_{VE1}** affords a liquid absorption medium **A_{VE2}** having a relatively low water content compared to the liquid absorption medium **A_{VE1}**.

It will be appreciated that the liquid absorption medium **A_{VE2}**, in terms of the trialkyl phosphates of structure **(I)** comprised in it and of the salts **S** comprised in it, is identical to **A_{VE1}** and is preferably distinguished therefrom only by the water content.

35 An essential feature of the process according to the invention is that the apparatus **V₁** at least partially comprises a surface made of an aluminium material of construction **O_{Al}** (in the context of the invention **O_{Al}** is an abbreviation for "surface made of an aluminium material of construction").

An aluminium material of construction in the context of the present invention is to be understood as meaning both unalloyed aluminium and aluminium alloys where in particular the mass fraction of

aluminium is greater than the mass fraction of every other element. The aluminium material of construction is preferably unalloyed aluminium.

Unalloyed aluminium is in particular aluminium having a purity of > 80 wt%, more preferably > 85 wt%, yet more preferably > 90 wt%, yet still more preferably > 95 wt%, yet still more preferably > 98 wt%. It is in particular highest purity aluminium having a purity of > 99.0 wt%, more preferably > 99.5 wt%, more preferably > 99.9 wt%.

Aluminium alloys comprise in addition to the aluminium in particular at least one alloying metal selected from the group consisting of magnesium, manganese, silicon, zinc, lead, copper, titanium, iron, more preferably selected from the group consisting of magnesium, manganese, silicon, zinc, lead, copper, titanium. The aluminium material of construction may then in particular be in the form of a wrought alloy or of a cast alloy.

A further essential feature of the process according to the invention is that in the apparatus V_1 at least one of the liquid absorption media selected from the group consisting of A_{VE} , A_{VE1} , A_{VE2} contacts the surface made of an aluminium material of construction O_{Al} via at least one contact surface. This is to be understood as meaning that at this contact surface the liquid absorption medium A_{VE} in question, A_{VE1} or A_{VE2} , is in direct contact with the surface made of an aluminium material of construction O_{Al} . In the context of the present invention "in direct contact" is to be understood as meaning "wetting". It will be appreciated that the liquid absorption medium selected from the group consisting of A_{VE} , A_{VE1} , A_{VE2} and the aluminium comprised in the contact surface are thus in direct contact. The aluminium comprised in the contact surface is not particularly restricted and is in particular selected from the group consisting of elemental aluminium or aluminium compounds such as in particular passivated aluminium (where passivated aluminium is to be understood as meaning in particular aluminium oxide).

In the embodiment according to the invention in which an apparatus V_1 is employed and comprises the following components:

- (i) at least one water absorption unit W_{abs1} set up for contacting the moist gas mixture with the liquid absorption medium A_{VE} ,
- (ii) at least one water desorption unit W_{des1} which comprises a heat exchanger W_{x1} and is set up for at least partially removing water from a liquid absorption medium A_{VE} ,
- (iii) and a circuit U_1 which connects the water absorption unit W_{abs1} with the water desorption unit W_{des1} and by means of which the liquid absorption medium A_{VE} may be circulated,

the contact surface at which the liquid absorption medium selected from the group consisting of A_{VE} , A_{VE1} , A_{VE2} contacts the surface made of an aluminium material of construction O_{Al} , is disposed in particular in at least one of the components selected from the group water absorption unit W_{abs1} , water desorption unit W_{des1} , circuit U_1 , preferably in at least one of the components selected from the group water absorption unit W_{abs1} , water desorption unit W_{des1} .

This is because it has now been found that, surprisingly, the mixtures of at least one trialkyl phosphate of structure (I) and at least one salt S according to the invention show particularly good


wetting of aluminium materials of construction, thus ensure particularly good heat transfer and are thus particularly suitable as liquid absorption media in the apparatus **V**₁ having a surface made of an aluminium material of construction **O**_{Al}, in which one of the absorption media selected from the group consisting of **A**_{VE}, **A**_{VE1}, **A**_{VE2} is in direct contact with the surface made of an aluminium material of construction **O**_{Al}.

In a further preferred embodiment the process according to the invention is carried out in continuous fashion. This is to be understood as meaning in particular that following step b) the steps a) and b) are performed at least one more time and that the liquid absorption medium **A**_{VE} employed in the steps a) additionally performed in each case is at least partially the liquid absorption medium **A**_{VE2} obtained from the step b) performed immediately beforehand, i.e. in particular the water content of the liquid absorption medium **A**_{VE} employed in the step a) additionally performed in each case and of the liquid absorption medium **A**_{VE2} from the immediately preceding step b) is identical.

It is more preferable when this embodiment comprises heating liquid absorption medium **A**_{VE1} with heat from liquid absorption medium **A**_{VE2}. This may be carried out in an additional heat exchanger **W**_{y1}, in particular selected from the group consisting of shell and tube heat exchangers and plate and frame heat exchangers. This makes it possible to carry out the process according to the invention in a particularly energy efficient fashion.

The invention also relates in a further aspect to an apparatus **V**₂ for dehumidifying a moist gas mixture, in particular moist air, comprising the components

- (i) a liquid absorption medium **A**_{VO} comprising a mixture of at least one trialkyl phosphate of the structure (I) with



- and at least one salt **S** selected from the group consisting of Q^+A^- , $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, $(\text{Q}^+)_2\text{R}^2\text{OPO}_3^{2-}$, $\text{Q}^+\text{M}^+\text{R}^3\text{OPO}_3^{2-}$,

- (iii) at least one water absorption unit **W**_{abs2} set up for contacting the moist gas mixture with the liquid absorption medium **A**_{VO},
- (iv) at least one water desorption unit **W**_{des2} which comprises a heat exchanger **W**_{x2} and is set up for at least partially removing water from a liquid absorption medium **A**_{VO},
- (v) and a circuit **U**₂ which connects the water absorption unit **W**_{abs2} with the water desorption unit **W**_{des2} and by means of which the liquid absorption medium **A**_{VO} may be circulated,

wherein at least one of the components water absorption unit **W**_{abs2}, water desorption unit **W**_{des2}, circuit **U**₂ at least partially comprises a surface made of an aluminium material of construction **O**_{Al}, and

wherein disposed in the apparatus **V₂** is at least one contact surface at which the liquid absorption medium **A_{Vo}** contacts the surface made of an aluminium material of construction **O_{Al}**,

characterized in that

- 5 **Q⁺** is a dialkylimidazolium cation in which, in particular, the alkyl groups each independently of one another have 1 to 10 carbon atoms,


wherein **A⁻** is an anion selected from the group consisting of **R^{*}COO⁻**, **R'SO₃⁻**, **HSO₄⁻**, **R"SO₄⁻**, wherein **R^{*}**, **R'**, **R"**, **R^A**, **R^B**, **R^C**, are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

- 10 wherein **R¹**, **R²**, **R³** are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

and wherein **M⁺** is an alkali metal ion, preferably **Li⁺**, **K⁺** or **Na⁺**, more preferably **K⁺** or **Na⁺**.

The apparatus according to the invention **V₂** is suitable for dehumidifying a moist gas mixture, in particular moist air. Said apparatus comprises the following components:

- 15 As a first component the apparatus **V₂** according to the invention comprises a liquid absorption medium **A_{Vo}** which comprises a mixture of at least one trialkyl phosphate of structure **(I)** where



- and at least one salt **S** selected from the group consisting of **Q⁺A⁻**, **Q⁺(R¹O)₂PO₂⁻**, **(Q⁺)₂R²OPO₃²⁻**, **Q⁺M⁺R³OPO₃²⁻**, **Q⁺** is a dialkylimidazolium cation in which in particular the alkyl groups each
- 20 independently of one another have 1 to 10 carbon atoms,

wherein **A⁻** is an anion selected from the group consisting of **R^{*}COO⁻**, **R'SO₃⁻**, **HSO₄⁻**, **R"SO₄⁻**, wherein **R^{*}**, **R'**, **R"**, **R^A**, **R^B**, **R^C**, are each independently of one another an alkyl group, in particular having 1 to 10 carbon atoms,

- wherein **R¹**, **R²**, **R³** are each independently of one another an alkyl group, in particular having 1 to
- 25 10 carbon atoms,

and wherein **M⁺** is an alkali metal ion, preferably **Li⁺**, **K⁺** or **Na⁺**, yet more preferably **K⁺** or **Na⁺**.

- In a preferred embodiment of the apparatus **V₂** according to the invention in the absorption medium **A_{Vo}** the salt **S** is selected from the group consisting of **Q⁺A⁻**, **Q⁺(R¹O)₂PO₂⁻**, and **Q⁺** is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 6,
- 30 preferably 1 or 4, more preferably 1 or 2 carbon atoms, and **A⁻** is an anion selected from the group consisting of **R^{*}COO⁻**, **R'SO₃⁻**, **R"SO₄⁻**, wherein **R^{*}**, **R¹**, **R'**, **R"**, **R^A**, **R^B**, **R^C** are each independently of one another an alkyl group having 1 to 6, preferably 1 to 4, more preferably 1 or 2, carbon atoms.

In a more preferred embodiment of the apparatus **V₂** according to the invention in the absorption medium **A_{vo}** the salt **S** has the general formula $Q^+(R^1O)_2PO_2^-$, and Q^+ is a dialkylimidazolium cation in which the alkyl groups are each independently of one another methyl or ethyl, and R^1 , R^A , R^B , R^C are each independently of one another methyl or ethyl.

- 5 In a yet more preferred embodiment of the apparatus **V₂** according to the invention in the absorption medium **A_{vo}** the salt **S** has the general formula $Q^+(R^1O)_2PO_2^-$, and Q^+ is selected from the group consisting of 1,3-dimethylimidazolium, 1,3-diethylimidazolium, 1-ethyl-3-methylimidazolium; R^A , R^B , R^C , R^1 is methyl or ethyl.

- 10 It is moreover particularly preferable in all of the aforementioned embodiments of the apparatus **V₂** according to the invention when in the absorption medium **A_{vo}** R^A , R^B , R^C are independently of one another selected from methyl, ethyl; yet more preferably $R^A = R^B = R^C = \text{methyl}$ or $R^A = R^B = R^C = \text{ethyl}$; particularly preferably $R^A = R^B = R^C = \text{ethyl}$.

- This is because it has now been found that, surprisingly, imidazolium salts where $R = \text{ethyl}$ group have a particularly small contact angle and thus ensure particularly good surface wetting. This results in a relatively large contact area, thus also in fewer nonwetted spaces and thus in improved heat transfer inside the apparatus **V₂**.

- The liquid absorption medium **A_{ve}** may be employed in the apparatus **V₂** according to the invention in the form of the pure mixture of the trialkyl phosphates of the structure (I) and the salts **S**. Alternatively and more preferably in the apparatus **V₂** according to the invention the liquid absorption medium **A_{vo}** is an aqueous solution in which, in particular, the total weight of all trialkyl phosphates of structure (I) and all salts **S** is in the range from 65 wt% to 95 wt% based on the total weight of the aqueous solution. It is yet more preferable when the total weight of all trialkyl phosphates of structure (I) and all salts **S** in **A_{vo}** is in the range 70 wt% to 90 wt% based on the total weight of the aqueous solution, yet more preferably in the range 75 wt% to 87 wt%.

- 25 In the apparatus **V₂** according to the invention the ratio of all trialkyl phosphates of structure (I) to the salts **S** in the absorption medium **A_{vo}** is not further restricted. However, it is preferable to employ in the apparatus **V₂** according to the invention an absorption medium **A_{vo}** in which the ratio of the total weight of all trialkyl phosphates of structure (I) to the total weight of all salts **S** is in the range 1 : 9999 to 1 : 9, more preferably 1 : 9999 to 1 : 99, yet more preferably 1 : 9999 to 1 : 999.

- 30 As a second component the apparatus **V₂** according to the invention comprises a water absorption unit **W_{abs2}** set up for contacting the moist gas mixture with the liquid absorption medium **A_{vo}**. The water absorption unit **W_{abs2}** may in particular comprise an additional heat exchanger **W_{z2}** set up such that the liquid absorption medium **A_{vo}** is coolable. Employable as such a water absorption unit **W_{abs2}** are in particular the water absorbers known to those skilled in the art. Said absorbers are based on the principle of increasing the surface area of the liquid absorption medium **A_{vo}** and simultaneously achieving the longest possible residence time of the liquid absorption medium **A_{vo}** in the water absorber during absorption of water. It is in particular possible here to employ water absorbers selected from the group of: packed beds, spray columns, falling-films, bubble columns, tray columns, wet scrubbers (for example Venturi scrubbers), stirred tanks and combinations of

these absorbers. It is particularly preferable to employ as water absorbers falling-films, in particular shell and tube falling-films.

As a third component the apparatus V_2 according to the invention comprises a water desorption unit W_{des2} which comprises a heat exchanger W_{x2} and is set up for at least partially removing water from the liquid absorption medium A_{VO} . Employable therefor are in particular the combinations of heat exchanger and water desorber known to those skilled in the art. The water desorption unit W_{des2} is based on the principle of supplying heat to the liquid absorption medium A_{VO} , increasing the surface area of the liquid absorption medium A_{VO} and simultaneously achieving the longest possible residence time of the liquid absorption medium A_{VO} in the water desorption unit.

Employable as water desorption unit W_{des2} comprising a heat exchanger W_{x1} are in particular the combinations of heat exchanger and water desorber known to those skilled in the art, in particular horizontal tube evaporators having an upstream heat exchanger, in particular shell and tube heat exchangers, plate and frame heat exchangers. In addition the water desorption unit W_{des2} comprising a heat exchanger W_{x2} may also be a water desorber having an integrated heat exchanger. Such water desorbers having an integrated heat exchanger are in particular climbing film evaporators, long tube vertical evaporators, short tube vertical evaporators, forced circulation evaporators, agitated thin film evaporators. It is particularly preferable to employ as water desorption unit W_{des2} falling-films, in particular shell and tube falling-films.

As a fourth component the apparatus V_2 according to the invention comprises a circuit U_2 which connects the water absorption unit W_{abs2} with the water desorption unit W_{des2} and by means of which the liquid absorption medium A_{VO} may be circulated. The circuit U_2 is preferably a conduit, more preferably selected from the group consisting of tube, hose. In a further preferred embodiment the circuit U_2 also comprises a pump.

An essential feature of the apparatus V_2 according to the invention is that said apparatus at least partially comprises a surface made of an aluminium material of construction O_{Al} (in the context of the invention O_{Al} is an abbreviation for "surface made of an aluminium material of construction").

An aluminium material of construction in the context of the present invention is to be understood as meaning both unalloyed aluminium and aluminium alloys where in particular the mass fraction of aluminium is greater than the mass fraction of every other element. The aluminium material of construction is preferably unalloyed aluminium.

Unalloyed aluminium is in particular highest purity aluminium having a purity of > 99.0 wt%, more preferably > 99.9 wt%.

Aluminium alloys comprise in addition to the aluminium in particular at least one alloying metal selected from the group consisting of magnesium, manganese, silicon, zinc, lead, copper, titanium, iron, more preferably selected from the group consisting of magnesium, manganese, silicon, zinc, lead, copper, titanium. The aluminium material of construction may then in particular be in the form of a wrought alloy or of a cast alloy.

A further essential feature of the apparatus V_2 according to the invention is that disposed in said apparatus is a contact surface at which the liquid absorption medium A_{VO} contacts the surface

made of an aluminium material of construction O_{Al} . This is to be understood as meaning that at this contact surface the liquid absorption medium A_{VO} is in direct contact with the surface made of an aluminium material of construction O_{Al} . In the context of the present invention "in direct contact" is to be understood as meaning "wetting". It will be appreciated that the liquid absorption medium A_{VO} and the aluminium comprised in the contact surface are thus in direct contact. The aluminium comprised in the contact surface is not particularly restricted and is in particular selected from the group consisting of elemental aluminium or aluminium compounds such as in particular passivated aluminium (where passivated aluminium is to be understood as meaning in particular aluminium oxide).

- 5
- 10 In a preferred embodiment the apparatus V_2 comprises a further heat exchanger W_{y2} (additional to the heat exchanger W_{x2} comprised in the water desorption unit W_{des2}). The heat exchanger W_{y2} is set up such that liquid absorption medium A_{VO} sent from the water absorption unit W_{abs2} to the water desorption unit W_{des2} is suppliable with heat from liquid absorption medium A_{VO} , said medium being conducted away from the water desorption unit W_{des2} . This can be ensured by employing as
- 15 heat exchanger W_{y2} in particular a heat exchanger selected from shell and tube heat exchangers, plate and frame heat exchangers.

In a further preferred embodiment the apparatus V_2 is part of an absorption heat pump. This absorption heat pump then comprises as further components a condenser, an evaporator and a coolant, wherein the coolant is water.

- 20 The condenser is in particular connected to the water desorption unit W_{des2} via a conduit and is set up for condensing water at least partially removed from the liquid absorption medium A_{VO} in the water desorption unit W_{des2} . The condenser preferably also comprises a cooling water circuit.

- The evaporator is in particular connected to the condenser via a conduit (which may comprise a throttling means) and connected to the water absorption unit W_{abs2} via a further conduit and is set
- 25 up for evaporating condensed water from the condenser. The evaporator preferably also comprises a pressure of < 1 bar, more preferably < 0.1 bar, to permit evaporation of the condensed water at the lowest possible temperatures. The evaporator may further preferably additionally comprise an apparatus from which heat may be drawn and so that the condensed water may be evaporated (for example a coolant conduit in which coolant is passed into the space in which water is evaporated).

- 30 The Figures 1 and 2 elucidated hereinbelow show preferred embodiments of the process according to the invention and the apparatus according to the invention.

Figure 1 (abbreviated to "Fig. 1") shows an embodiment of the apparatus V_2/V_1 according to the invention.

- The apparatus V_2 shown in Figure 1 comprises a water absorption unit W_{abs2} <103> (with optional
- 35 additional heat exchanger W_{z2} <104>) to which a conduit <101> leads and from which a conduit <102> leads away, a water desorption unit W_{des2} which comprises a heat exchanger W_{x2} <108> and a water desorber <109> and to which conduit <111> leads and from which conduits <110>, <112> and <113> lead away, and a circuit U_2 formed from conduits <106>, <111> and <113> or <106>, <111>, <112> and <105> (in each case optionally with conduit <114>). The apparatus in

Figure 1 may also optionally comprise a further heat exchanger W_{y2} <107> to which conduits <106> and <112> lead and from which conduits <105> and <111> lead away. In addition the apparatus also comprises a liquid absorption medium A_{v0} . Said medium is disposed in one or more of the abovementioned components water absorption unit W_{abs2} , water desorption unit W_{des2} , circuit U_2 . Water absorption unit W_{abs2} <103> may optionally also comprise an additional heat exchanger W_{z2} <104>. Apparatus V_2 , in particular at least one of the components selected from the group consisting of water absorption unit W_{abs2} , water desorption unit W_{des2} , circuit U_2 , at least partially comprises a surface made of an aluminium material of construction O_{Al} and there is at least one contact surface at which the liquid absorption medium A_{v0} contacts the surface made of an aluminium material of construction O_{Al} . Optionally circuit U_2 may also additionally comprise a pump for conveying the liquid absorption medium.

Apparatus V_1 corresponds to apparatus V_2 without absorption medium A_{v0} , wherein in the figure description for Figure 1 and Figure 2 the terms U_2 , W_{abs2} , W_{des2} , W_{x2} , W_{y2} , W_{z2} are to be replaced by U_1 , W_{abs1} , W_{des1} , W_{x1} , W_{y1} , and W_{z1} respectively.

The process according to the invention will now be illustratively described with reference to apparatus V_1 using Figure 1:

A stream of moist gas mixture G (said stream may be moist air, moist natural gas or moist gas mixture originating from the evaporator of an absorption chiller - see also Figure 2 with regard to this option) is supplied via conduit <101> to a water absorption unit W_{abs1} <103> and contacted there with the liquid absorption medium A_{vE} supplied to the water absorption unit W_{abs1} <103> via the conduit <105> or via the conduit <113>. The water absorption unit W_{abs1} <103> may be any of the water absorbers cited hereinabove for W_{abs1} , in particular a falling-film. Contacting, in the water absorption unit W_{abs1} <103>, gas mixture G supplied via conduit <101> with the liquid absorption medium A_{vE} supplied via the conduit <105> or via the conduit <113> affords a liquid absorption medium A_{vE1} having an elevated water content compared to the liquid absorption medium A_{vE} and a stream of a gas mixture G_1 discharged via the conduit <102>, G_1 having a relatively low water content compared to the moist gas mixture G . Depending on the application G_1 is in particular dehumidified air or dehumidified natural gas. The water absorption unit W_{abs1} <103> may optionally also comprise an additional heat exchanger W_{z1} <104>. Preferably via the conduits <106>, <111> and the heat exchanger W_{y1} <107> (or, when heat exchanger W_{y1} <107> is not employed, via conduits <106>, <111> and <114>) the liquid absorption medium A_{vE1} is then passed to the water desorption unit W_{des1} composed of the heat exchanger W_{x1} <108> and the water desorber <109>. The water-laden liquid absorption medium A_{vE1} may additionally be supplied with heat in the optional heat exchanger W_{y1} <107>. The at least partial removal of water from liquid absorption medium A_{vE1} is then carried out in the water desorber <109> to afford a liquid absorption medium A_{vE2} having a relatively low water content compared to the liquid absorption A_{vE1} . The water removed is then discharged from the water desorber <109> as liquid or vapour, preferably as vapour, via conduit <110>. The liquid absorption medium A_{vE2} is then discharged from the water desorber <109> and returned to the water absorption unit W_{abs1} <103>. This may either be carried out directly, i.e. via the conduit <113> which is shown in dashed form in Figure 1. Alternatively and

preferably the liquid absorption medium A_{VE2} may also be supplied via the conduit <112> to the optional heat exchanger W_{y1} <107> in which the liquid absorption medium A_{VE1} supplied via conduit <106> to the optional heat exchanger W_{y1} <107> is supplied with heat from the liquid absorption medium A_{VE2} supplied via conduit <112> to the optional heat exchanger W_{y1} <107>.

- 5 Once the concentrated liquid absorption medium A_{VE2} has been supplied to the water absorption unit W_{abs1} via conduit <105> or <113> said medium is reused as A_{VE} for at least partially dehumidifying the gas stream in a new cycle. It is essential to the invention that in this process the apparatus according to Figure 1, preferably at least one of the components selected from the group consisting of water absorption unit W_{abs1} <103> (in Figure 1 said unit comprises the heat
10 exchanger <104>), water desorption unit W_{des1} (in Figure 1 said unit comprises the heat exchanger <108>), circuit U_1 (composed in Figure 1 of the conduits <106>, <111>, <113>, or <106>, <111>, <112>, <105>, and in each case optionally also conduit <114>) at least partially comprises a surface made of an aluminium material of construction O_{Al} and that disposed in the apparatus is at least one contact surface at which at least one of the liquid absorption media A_{VE} , A_{VE1} , A_{VE2}
15 contacts the surface made of an aluminium material of construction O_{Al} .

Figure 2 (abbreviated as "Fig. 2") shows in schematic fashion an absorption chiller into which an apparatus V_2 is integrated. The constituents <101> to <114> are shown as for the apparatus V_2 described in Figure 1. Additionally, the absorption chiller in Figure 2 also comprises a condenser <211> which is connected to the water desorption unit W_{des2} <109> via the conduit <110> and is
20 set up for condensing water at least partially removed from the liquid absorption medium A_{VO} in the water desorption unit W_{des2} . Condenser <211> preferably also comprises a heat exchanger <212> with which cooling water may be supplied.

The absorption chiller shown in Figure 2 also comprises an evaporator <214> connected to the condenser <211> via a conduit <216> (which may optionally comprise a throttling means <213>) and connected via the conduit <101> with the water absorption unit W_{abs2} . The evaporator <214> is
25 set up to evaporate condensed water from the condenser. Additionally, the evaporator <214> can further preferably also comprise a heat exchanger <215> which supplies a medium, heat being drawn off from the medium to thus evaporate the condensed water (for example a coolant conduit with, in particular, water as coolant, this coolant being passed into the evaporator <214>).

- 30 In an embodiment of the process according to the invention (described hereinbelow with reference to apparatus V_1 using Figure 2) moist gas mixture G originating from evaporator <214> is passed via the conduit <101> to the water absorption unit W_{abs1} <103>. The water removed in water desorption unit W_{des1} is supplied via the conduit <110> to the condenser <211> in which said water is recondensed. A cooling water circuit as heat exchanger <212> installed in the condenser is
35 optionally likewise used therefor. The condensed water is then supplied via a conduit <216> to the evaporator <214> in which the evaporation of water is effected in particular at low pressures thus bringing about a cooling effect. This may optionally also be effected using a throttling means <213>. This achieves a cooling action in the evaporator <214> and, for example, coolant may be cooled via the heat exchanger <215>. The water vapour generated is then returned to the water
40 absorption unit W_{abs1} <103> via conduit <101>.

The examples which follow are intended to elucidate the present invention without limiting said invention in any way.

Examples

Inventive examples **I1** to **I6** and the comparative examples **C1** and **C2** were carried out. In tests **C1**,
5 **I1-I3** anhydrous solutions were employed. In tests **C2**, **I4-I6** aqueous solutions were employed.

1. Chemicals employed

EMIM DEP (= ethylmethylimidazolium diethylphosphate) was obtained from Iolitec.
10 TEP (= triethyl phosphate) was obtained from Sigma Aldrich.

2. Test procedure

3 drops of the respective solution were dropped onto an aluminium plate (highest purity aluminium,
15 purity > 99.0%) having dimensions of 3 cm x 7 cm and a maximum thickness of 3 mm. The contact angle determination was carried out according to SOP 1827. The results are shown in the table which follows.

C1 is the comparative test with pure EMIM DEP while in the tests **I1**, **I2** and **I3** mixtures of EMIM DEP and 10 wt%, 1 wt% and 0.1 wt% of TEP respectively (the wt% values are based on the total
20 weight of the mixture) were analyzed.

C2 is the comparative test with a mixture of EMIM DEP and 10 wt% of water while in the tests **I4**, **I5** and **I6** mixtures of EMIM DEP and 10 wt% of water and 10 wt%, 1 wt% and 0.1 wt% of TEP respectively (the wt% values are based on the total weight of the mixture) were analyzed.

25 3. Results

Experi- ment	Solution employed	Contact angle (°)
C1	EMIM DEP	36.0
I1	EMIM DEP + 10 wt% of TEP	20.8
I2	EMIM DEP + 1 wt% of TEP	31.7
I3	EMIM DEP + 0.1 wt% of TEP	25.9
C2	EMIM DEP + 10 wt% of water	49.8
I4	EMIM DEP + 10 wt% of water + 10 wt% of TEP	19.4


I5	EMIM DEP + 10 wt% of water + 1 wt% of TEP	41.6
I6	EMIM DEP + 10 wt% of water + 0.1 wt% of TEP	43.1

- The results show that the absorption media according to the invention (**I1-I3**, **I4-I6**) exhibit a small contact angle to the aluminium-containing surface compared to those of the prior art (**C1**, **C2**) and thus ensure good heat conduction in the process according to the invention/for the apparatus
- 5 according to the invention. The use of imidazolium salts in combination with trialkyl phosphate (in this case triethylphosphate) accordingly surprisingly achieves better wetting of the aluminium-containing surface and thus greater and more efficient heat exchange.

Claims

1. Process for dehumidifying a moist gas mixture **G**, in particular moist air, in an apparatus **V**₁, comprising the steps of:

- 5 (a) contacting the moist gas mixture **G** with a liquid absorption medium **A**_{VE} comprising a mixture of at least one trialkyl phosphate of the structure (I) with



(I)

and at least one salt **S** selected from the group consisting of Q^+A^- , $\text{Q}^+(\text{R}^1\text{O})_2\text{PO}_2^-$, $(\text{Q}^+)_2\text{R}^2\text{OPO}_3^{2-}$, $\text{Q}^+\text{M}^+\text{R}^3\text{OPO}_3^{2-}$,

- 10 wherein the liquid absorption medium **A**_{VE} at least partially absorbs water from the moist gas mixture **G**,

to obtain a liquid absorption medium **A**_{VE1} having an elevated water content compared to the liquid absorption medium **A**_{VE} and a gas mixture **G**₁ having a relatively low water content compared to the moist gas mixture **G**,

- 15 (b) at least partially removing water from the liquid absorption medium **A**_{VE1} to obtain a liquid absorption medium **A**_{VE2} having a relatively low water content compared to the liquid absorption medium **A**_{VE1},

- wherein the apparatus **V**₁ at least partially comprises a surface made of an aluminium material of construction **O**_{Al} and in the apparatus **V**₁ at least one of the liquid absorption media selected from the group consisting of **A**_{VE}, **A**_{VE1}, **A**_{VE2} contacts the surface made of an aluminium material of construction **O**_{Al} via at least one contact surface,

characterized in that

Q^+ is a dialkylimidazolium cation,

wherein A^- is an anion selected from the group consisting of R^*COO^- , $\text{R}'\text{SO}_3^-$, HSO_4^- , $\text{R}''\text{SO}_4^-$,

- 25 wherein R^* , R' , R'' , R^{A} , R^{B} , R^{C} are each independently of one another an alkyl group,

wherein R^1 , R^2 , R^3 are each independently of one another an alkyl group,

and wherein M^+ is an alkali metal ion.

2. Process according to Claim 1, wherein Q^+ is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 10 carbon atoms, and wherein R^* , R' , R'' , R^{A} , R^{B} , R^{C} , R^1 , R^2 , R^3 are each independently of one another an alkyl group having 1 to 10 carbon atoms and wherein $\text{M}^+ = \text{Li}^+$, K^+ or Na^+ .

3. Process according to Claim 1 or 2, wherein the salt **S** is selected from the group Q^+A^- , $Q^+(R^1O)_2PO_2^-$, and Q^+ is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 6 carbon atoms, and A^- is an anion selected from the group consisting of R^*COO^- , $R'SO_3^-$, $R''SO_4^{2-}$, wherein R^* , R^1 , R' , R'' , R^A , R^B , R^C are each independently of one another an alkyl group having 1 to 6 carbon atoms.

4. Process according to any of Claims 1 to 3, wherein R^A , R^B , R^C are independently of one another selected from methyl, ethyl.

10

5. Process according to any of Claims 1 to 4, wherein the liquid absorption medium **A_{VE}** is an aqueous solution.

6. Process according to Claim 5, wherein in the liquid absorption medium **A_{VE}** the total weight of all trialkyl phosphates of structure **(I)** and all salts **S** is in the range from 65 wt% to 95 wt% based on the total weight of the aqueous solution.


15

7. Process according to any of Claims 1 to 6, wherein in the liquid absorption medium **A_{VE}** the ratio of the total weight of all trialkyl phosphates of structure **(I)** to the total weight of all salts **S** is in the range 1 : 9999 to 1:9.

20

8. Apparatus **V₂** for dehumidifying a moist gas mixture, comprising the components

(i) a liquid absorption medium **A_{VO}** comprising a mixture of at least one trialkyl phosphate of the structure **(I)** with



25

9. **(I)**

and at least one salt **S** selected from the group consisting of Q^+A^- , $Q^+(R^1O)_2PO_2^-$, $(Q^+)_2R^2OPO_3^{2-}$, $Q^+M^+R^3OPO_3^{2-}$,

(ii) at least one water absorption unit **W_{abs2}** set up for contacting the moist gas mixture with the liquid absorption medium **A_{VO}**,

(iii) at least one water desorption unit **W_{des2}** which comprises a heat exchanger **W_{x2}** and is set up for at least partially removing water from a liquid absorption medium **A_{VO}**,

30

(iv) and a circuit U_2 which connects the water absorption unit W_{abs2} with the water desorption unit W_{des2} and by means of which the liquid absorption medium A_{vo} may be circulated,

wherein at least one of the components water absorption unit W_{abs2} , water desorption unit W_{des2} , circuit U_2 at least partially comprises a surface made of an aluminium material of construction O_{Al} , and

wherein disposed in the apparatus V_2 is at least one contact surface at which the liquid absorption medium A_{vo} contacts the surface made of an aluminium material of construction O_{Al} ,

characterized in that

10 Q^+ is a dialkylimidazolium cation,

wherein A^- is an anion selected from the group consisting of R^*COO^- , $R'SO_3^-$, HSO_4^- , $R''SO_4^-$, wherein R^* , R' , R'' , R^A , R^B , R^C , are each independently of one another an alkyl group,

wherein R^1 , R^2 , R^3 are each independently of one another an alkyl group, and wherein M^+ is an alkali metal ion.

15

9. Apparatus V_2 according to Claim 8, wherein Q^+ is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 10 carbon atoms and wherein R^* , R' , R'' , R^A , R^B , R^C , R^1 , R^2 , R^3 are each independently of one another an alkyl group having 1 to 10 carbon atoms and wherein $M^+ = Li^+$, K^+ or Na^+ .

20

10. Apparatus V_2 according to Claim 8 or 9, wherein the salt S is selected from the group Q^+A^- , $Q^+(R^1O)_2PO_2^-$, and Q^+ is a dialkylimidazolium cation in which the alkyl groups each independently of one another have 1 to 6 carbon atoms, and A^- is an anion selected from the group consisting of R^*COO^- , $R'SO_3^-$, $R''SO_4^-$, wherein R^* , R^1 , R' , R'' , R^A , R^B , R^C are each independently of one another an alkyl group having 1 to 6 carbon atoms.

25

11. Apparatus V_2 according to any of Claims 8 to 10, wherein R^A , R^B , R^C are independently of one another selected from methyl, ethyl.

30 12. Apparatus V_2 according to any of Claims 8 to 11, wherein the liquid absorption medium A_{vo} is an aqueous solution.

13. Apparatus V_2 according to Claim 12, wherein in the liquid absorption medium A_{vo} the total weight of all trialkyl phosphates of structure (I) and all salts S is in the range from 65 wt% to 95 wt% based on the total weight of the aqueous solution.

35

14. Apparatus **V**₂ according to any of Claims 8 to 13, wherein in the liquid absorption medium **A**_{vo} the ratio of the total weight of all trialkyl phosphates of structure **(I)** to the total weight of all salts **S** is in the range 1 : 9999 to 1:9.

5

15. Absorption heat pump, comprising an apparatus **V**₂ according to any of Claims 8 to 14 and, as further components, a condenser, an evaporator and a coolant, wherein the coolant is water.