

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 October 2002 (03.10.2002)

PCT

(10) International Publication Number
WO 02/077137 A1

(51) International Patent Classification⁷: **C10M 169/06**,
115/08

(21) International Application Number: PCT/US02/00723

(22) International Filing Date: 11 January 2002 (11.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/817,415 26 March 2001 (26.03.2001) US

(71) Applicant: **EXXONMOBIL RESEARCH AND ENGINEERING COMPANY** [US/US]; P.O. Box 900, 1545 Route 22 East, Annandale, NJ 08801-0900 (US).

(72) Inventors: **LESLIE, Walter, Logan**; 1105 SW Trail Ridge Lane, Lee's Summit, MO 64081 (US). **ROOT, Jon, Carl**; 9000 Lee Blvd., Leawood, KS 66206 (US).

(74) Agents: **ALLOCCA, Joseph, J.** et al.; ExxonMobil Research and Engineering Company, P.O. Box 900, 1545 Route 22 East, Annandale, NJ 08801-0900 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOW FRICTION GREASE FOR CONSTANT VELOCITY UNIVERSAL JOINTS

(57) Abstract: A silicon elastomer compatible constant velocity joint grease comprises a urea grease composed of a lubricating oil and a urea thickener and an effective amount of a friction reducing additive package comprising vermiculite, molybdenum oxysulfide dithiocarbamate, polyphenylene sulfide and potassium triborate. The additive package solids have particle sizes below about 40 microns.



WO 02/077137 A1