

**TONGUE-AND-GROOVE COUPLING BETWEEN PANELS OF
SELF-SUPPORTING AIR-CONDITIONING DUCTS**

DESCRIPTION

5

OBJET OF THE INVENTION

The invention relates to a tongue-and-groove coupling between panels of self-supporting air-conditioning ducts and the like, of the type that is provided in order to establish an optimum fit of the canted edge corresponding to the panels that are coupled in a tongue-and-groove manner, intended to form self-supporting air-conditioning ducts or for other applications.

The aim of the invention is to obtain, besides an optimum coupling, to avoid the air coming into contact with the core of the duct therein, with the subsequent risk that particles of the insulating material, which form part of the panels, detach themselves towards the inside of the duct, during the mechanical cleaning operations or the duct arrangement.

BACKGROUND OF THE INVENTION

In the scope of practical application of the invention, i.e., that of the panels used for forming self-supporting air-conditioning ducts, the ducts preferably embodied in mineral wool, are well known, wherein the panels forming the duct are coupled in a tongue-and-groove manner establishing a canted edge in said coupling.

Theoretically, the coupling in a tongue-and-groove manner is carried out by means of perpendicular cuts between the two panels to be joined, which perpendicular cuts have been made relative to the longitudinal line of the panels' intersection.

Nevertheless, in reality, there are problems with the tongue-and-groove adjustment, caused by the curvatures resulting from the molding process, which make the surface to have cavities and irregularities at the joints of the different modules of the final duct.

With the aim of solving this problem, the applicant himself is the holder of the utility model U201100838, in which a coupling in a tongue-and-groove manner between this type of panels is described, wherein the coupling and juxtaposing canted edged or edge of both panels, has an oblique cut relative to the horizontality or the longitudinal intermediate line in the joint between the two

panels.

While this structure achieves a much effective inter-modules coupling, this solution poses a problem, i.e., given the coupling arrangement, it is possible that particles from the mineral wool core of the panel get detached in the event of mechanical cleaning or maintenance operations, falling towards the inside of the duct and being swept by the air flow.

DESCRIPTION OF THE INVENTION

The recommended coupling based on the aforementioned structure, offers a completely satisfactory solution to the problem set out above, preventing the entry of particles from the insulating core inside the duct formed by the panels themselves.

To this end, in a more specific manner, the panels of the invention are made up from a core of insulating material, which is supplemented on both external faces thereof with one aluminum layer or coating each, forming a “sandwich” type structure, having in their coupling edges a cut oblique to said edge, forming a sort of staggered coupling in a tongue-and-groove manner, with the special particularity that the aluminum layer or coating, which determines the inner face of the duct, extends beyond the edge of the panel, being fixed to the oblique surface that defines the coupling.

In this way, this aluminum layer or another coating is superimposed upon the tongue-and-groove coupling with the coating layer of the adjacent panel, perfectly insulated inside the duct against eventual detachments of the particles from the insulating core caused by mechanical cleaning or maintenance operations and in addition providing the edge with a higher mechanical resistance, since as the border adopts an acute angle shape it becomes considerably more fragile.

Given the oblique character of the tongue-and-groove profile, the same does not make necessary for the extensions of the coating layers of the inner faces of the panel to reach the end of said profile, although it is possible to adopt this solution without affecting the essence of the invention.

Optionally, one of the aluminum layers making up the outer layer of the panels may extend slightly in the longitudinal direction, such that the same overlaps the edge of the outer face of the adjacent panel, thus guaranteeing the sealing.

DESCRIPTION OF THE DRAWINGS

In order to complement the description being made below and with the aim of facilitating a better understanding of the invention characteristics, according to a preferred and practical exemplary embodiment thereof, a single plane is attached as an integral part thereof, in which by way of non-limiting example the following has been represented:

Figure 1.- Shows a sectional leveled view of the coupling in a tongue-and-groove manner between panels of air-ducts, realized according to the object of the present invention.

PREFERRED EMBODIMENT OF THE INVENTION

As can be observed in the referred figures, the coupling in a tongue-and-groove manner between two panels (1, 1') intended to form a self-supporting air-conditioning duct or similar, has a similar arrangement to that of the aforementioned utility model U201100838, in which the canted edge or edge corresponding to these panels (1, 1'), has an oblique cut (2, 2'), respectively, that defines a sort of oblique staggering with a straight and longitudinal length (3) of both panels (1, 1'), such that this oblique cut (2, 2') achieves the establishment of an optimal adjustment in the tongue-and-groove coupling, thus solving the problem caused by the curvatures (4, 4') of the panels (1, 1') when the corresponding molding process is carried out, both panels (1-1') being assisted by an outer coating layer (5-5') and an inner coating layer (6-6') conveniently adhered to the main core of the insulating material, and forming a sandwich-type structure, being it possible nevertheless, to embody this layers in Kraft-Aluminum, reinforced woven fiberglass fabric, veil made of acrylic glass or similar, without this affecting the essence of the invention.

Well then, now according to the invention, it has been foreseen that the aluminum inner layer or coating (6-6') extends through end sectors (7-7') beyond the panel edge, being fixed to the oblique surface that defines the coupling.

Although in figure 1 this end sectors (7-7') only extend up to the intermediate area of said coupling, this solution corresponds to the optimum solution, insofar, it enables avoiding the detachment of particles from the insulating material towards the inside of the duct in the event of cleaning or maintenance operations, although, the end sectors (7-7') could extend along the entire edge that defines the coupling, without this affecting the essence of the invention.

In order to achieve a better sealing in the coupling between panels, the upper aluminum sheet (5') of the panel (1') may extend along a short length (8), that remains free, intended to overlap the upper aluminum layer (5), as shown in figure 1.

CLAIMS

1. A tongue-and-groove coupling between panels of self-supporting air-conditioning ducts, of the type made up from a core of insulating material,
5 preferably mineral wool, supplemented with both an outer layer and an inner layer based on aluminum or some other coating such as Kraft-Aluminum, reinforced woven fiberglass fabric, veil made of acrylic glass or similar, the juxtaposing canted edge or edge between the panels having an oblique cut relative to the horizontality or longitudinal intermediate line in the joint between
10 the two panels, characterized in that the aluminum layer or coating, which determines the inner face of the duct, extends beyond the edge of the panel, being fixed to the oblique surface that defines the coupling profile.