

METHOD AND APPARATUS FOR PACKAGE REDUCTION IN STACKED CHIP AND BOARD ASSEMBLIES

5 TECHNICAL FIELD

Field of the Invention: The present invention relates to method and apparatus for increasing integrated circuit density. In particular, the present invention relates to a method and apparatus for semiconductor package volume and height reduction with enhanced reliability and simplification of the fabrication process for stacked semiconductor dice,

State of the Art: Chip-On-Board (“COB”) or Board-On-Chip (“BOC”) technology is used to attach a semiconductor die to a carrier substrate such as a printed circuit board (“PCB”) and may be effected using flip-chip attachment, wire bonding, and tape automated bonding (“TAB”).

15 Flip-chip attachment generally consists of electrically and mechanically
attaching a semiconductor die by its active surface to a carrier substrate using a pattern
of discrete conductive elements therebetween. The conductive elements are generally
disposed on the active surface of the die during fabrication, but may instead be disposed
on the carrier substrate. The discrete conductive elements may comprise minute
20 conductive bumps, balls or columns of various configurations. Each conductive
element is placed corresponding to superimposed, mutually aligned locations of bond
pads (or other I/O locations) on the semiconductor die and terminals on the carrier
substrate. The semiconductor die is thus electrically and mechanically connected to the
carrier substrate by, for example, reflowing conductive bumps of solder or curing
25 conductive or conductor-filled epoxy bumps. A dielectric underfill may then be
disposed between the die and the carrier substrate for environmental protection and to
enhance the mechanical attachment of the die to the carrier substrate.

Wire bonding and TAB attachment techniques generally begin with attaching a semiconductor die by its back side to the surface of a carrier substrate with an appropriate adhesive, such as an epoxy or silver solder. A plurality of fine wires are discretely attached to bond pads on the semiconductor die and then extended and bonded to corresponding terminals pad on a carrier substrate. The bond wires are generally attached through one of three conventional wire bonding techniques:

ultrasonic bonding - using a combination of pressure and ultrasonic vibration bursts to form a metallurgical cold weld; thermocompression bonding - using a combination of pressure and elevated temperature to form a weld; and thermosonic bonding - using a combination of pressure, elevated temperature, and ultrasonic vibration bursts. A
5 dielectric encapsulant such as a silicone or epoxy may then be applied to protect the fine wires and bond sites. In TAB, ends of metal leads carried on an insulating tape such as a polyimide to are attached to the bond pads on the semiconductor die and corresponding terminal pads on the carrier substrate.

Higher performance, lower cost, increased miniaturization of components,
10 and greater packaging density of integrated circuits are ongoing goals of the computer industry. As new generations of integrated circuit products are released, the number of components used to fabricate them tends to decrease due to advances in technology even though the functionality of the products increase. For example, on the average, there is approximately a 10 percent decrease in components for every product
15 generation over the previous generation having equivalent functionality.

In integrated circuit packaging, in addition to component reduction, surface mount technology has demonstrated an increase in semiconductor chip density on a single substrate or board, resulting from more compact designs and form factors and a significant increase in integrated circuit density. However, greater integrated density is
20 becoming significantly limited by the space or "real estate" available for the mounting of semiconductor dice on a carrier substrate.

One method of increasing integrated circuit density is to stack die vertically. U.S. Patent 5,012,323 ("the '323 patent") issued April 30, 1991 to Farnworth teaches combining a pair of die mounted on opposing sides of a lead frame. An upper, smaller
25 die is back-bonded to the upper surfaces of the leads of the lead frame via a first adhesively coated, insulated film layer. A lower, larger die is face-bonded to the lower surface of the lead frame at a die-bonding region via a second, adhesively coated, insulative, film layer. The wire-bonding pads on both upper die and lower die are interconnected with the ends of their associated lead extensions with gold or aluminum
30 bond wires. The lower die must be slightly larger than the upper die in order for the die pads to be accessible from above through a bonding window in the lead frame such that wire connections can be made to the lead extensions. This arrangement has a major

disadvantage from a production standpoint, due to the requirement for different-sized dice, a somewhat complex lead frame configuration and a somewhat difficult to execute wire bonding protocol.

U.S. Patent 5,291,061 issued March 1, 1994 to Ball teaches a multiple stacked
5 die device containing up to four stacked die supported on a die-attach paddle of a lead frame, the assembly purportedly not exceeding the height of then-current single die packages, and wherein the bond pads of each die are wire bonded to lead fingers. The relatively low profile of the device is achieved by close-tolerance stacking which is made possible by a low-loop-profile wire bonding operation and disposition of adhesive
10 layers between the stacked die. However, Ball requires relatively long bond wires to electrically connect the stacked dice to the lead frame. These long bond wires increase resistance and may facilitate shorting due to bond wire sweep during encapsulation. Also, Ball requires the use of spacers between the dice.

U.S. Patent 5,323,060 issued June 21, 1994 to Fogal et al. teaches a multi-chip
15 module that contains stacked die devices, the terminals or bond pads of which are wire bonded to a substrate or to adjacent die devices. However, as discussed with Ball, Fogal requires long bond wires to electrically connect the stacked die bond pads to the substrate. Fogal also requires the use of spacers between the dice.

U.S. Patent 5,422,435 and 5,495,398 to Takiar et al. ("Takiar") teach stacked
20 dice having bond wires extending to each other and to the leads of a carrier member such as a lead frame. However, Takiar also has the problem of long bond wires, as well as requiring specific sized or custom designed dice to achieve a properly stacked combination.

U.S. Patent 5,973,403 issued Oct. 26, 1999 to Wark teaches stacked dice on a
25 PCB. A first die is flip-chip mounted on the PCB and a second die is backside bonded on the first die having bond wires extending from the second die to the PCB. However, Wark also has the problem of long bond wires and the excessive and somewhat complex processing steps of both underfilling the first flip-chip mounted die and encapsulating the second die connected with bond wires.

30 U.S. Patent 6,051,878 issued April 18, 2000 to Akram et al. ("Akram") teaches multiple stacked substrates having dice mounted to the substrates using both wire

bonding and flip-chip techniques, where some dice are mounted on opposing substrate surfaces.

Therefore, it would be advantageous to develop a fairly straightforward technique and resulting semiconductor device assembly for increasing integrated circuit density of vertically stacked semiconductor dice by reducing the number process steps for fabricating the assembly in combination while reducing assembly height and employing commercially-available, widely-practiced semiconductor device fabrication techniques.

10

DISCLOSURE OF INVENTION

The present invention relates to a method and apparatus for increasing integrated circuit density by reducing package height and reducing the number of process steps for fabricating a semiconductor die assembly. The present invention includes a method and apparatus for reducing the height of a plurality of vertically stacked interposer substrates, each interposer substrate having at least one semiconductor die mounted thereon. The present invention includes stacking interposer substrates having dice mounted thereto, each die being electrically connected to conductive traces of its associated interposer substrate by wire bonding.

The present invention includes at least two oppositely-facing interposer substrates, each of the interposer substrates having secured thereto by its active surface at least one semiconductor die with a portion of its active surface and bond pads thereof exposed through an opening in the interposer substrate and wire bonds extending from the bond pads and looped through the opening to conductive terminals of a first set adjacent the opening and on the opposite side of the interposer substrate from the semiconductor die. The opposing interposer substrates are mutually electrically connected on their terminal sides by a plurality of conductive elements which extend transversely therebetween and electrically connect terminals of a second set on each interposer substrate and laterally offset from the first terminal set, conductive traces extending between associated terminals of the two sets on the same interposer substrate. A third terminal set on a die side of one of the interposer substrates carries a like second plurality of conductive elements extending transversely from that interposer substrate

for electrically connecting the stacked interposer substrates to a carrier substrate. An assembly including a carrier substrate is also encompassed by the invention.

According to one embodiment of the present invention, an exposed portion of the active surface of at least one semiconductor die attached to an interposer substrate substantially directly faces and is substantially laterally aligned with an exposed portion of the active surface of at least another semiconductor die attached to another, superimposed interposer substrate, the height of the gap between the two interposer substrates being least twice the height of the wire bond loops. In another embodiment of the present invention, an exposed portion of the active surface of at least one semiconductor die attached to an interposer substrate substantially directly faces but is at least partially laterally offset from an exposed portion of the active surface of at least another, opposingly oriented semiconductor die attached to another interposer substrate, the height of the gap between the interposer substrates in this instance being at least one wire bond loop height but less than two. In still another embodiment of the present invention, an exposed portion of the active surface of at least one semiconductor die attached to an interposer substrate substantially directly faces an exposed portion of the active surface of another semiconductor die attached to another interposer substrate but is completely laterally offset therefrom, the height of the gap between the interposer substrates being at least the wire bond loop height. Thus, wire bond height may be minimized, depending upon the opening alignment technique selected. In all of the embodiments, a flowable dielectric material may be disposed within the gap to substantially encapsulate both the wire bonds electrically connecting the opposing die and substrates and the discrete conductive elements connecting the terminals of the second sets on the two interposer substrates. Further, a flowable dielectric material may be introduced between the lowermost interposer substrate of an assembly and a carrier substrate to substantially encapsulate the second plurality of conductive elements.

BRIEF DESCRIPTION OF DRAWINGS

The method and apparatus of the present invention will be more fully understood from the detailed description of the invention taken in conjunction with the drawings, wherein:

FIGs. 1(a) - 1(d) are simplified cross-sectional views of a first embodiment, illustrating a method of vertically stacking, electrically connecting and filling the gaps between electrically connected interposer substrates each having a semiconductor die attached thereto, in accordance with the present invention;

5 FIG. 2 is a simplified cross-sectional view of a variation of the first embodiment, illustrating vertically stacked interposer substrates having multiple die attached to each interposer substrate, in accordance with the present invention;

FIG. 3 is a simplified cross-sectional view of a second embodiment, illustrating vertically stacked interposer substrates having at least partially laterally offset dice
10 attached thereto, in accordance with the present invention; and

FIG. 4 is a simplified cross-sectional view of a variation of the second embodiment, illustrating vertically stacked interposer substrates having substantially superimposed dice attached thereto, in accordance with the present invention.

15 BEST MODE FOR CARRYING OUT THE INVENTION

Embodiments of the present invention will be hereinafter described with reference to the accompanying drawings. It should be understood that the illustrations are not meant to be actual views of any particular apparatus and/or method, but are merely idealized representations which are employed to more clearly and fully depict
20 the present invention than would otherwise be possible. Additionally, elements and features common between the figures retain the same reference numeral designation.

A method and apparatus of a first embodiment of the present invention is shown in FIGs. 1(a) - 1(d). FIG. 1(a) illustrates a simplified cross-sectional view of a first interposer substrate 120 having a first semiconductor device or die ("first die") 130
25 attached thereto by its active surface 132 to provide a first assembly 110. The first interposer substrate 120 is a substrate that may comprise a flexible material, such as a polymer tape or resin, or a rigid material, such as silicon, ceramic, glass, semiconductor material or a glass fiber laminate such as an FR-4 laminate. The first interposer substrate 120 includes a first surface 122 and a second, opposing surface 124 having an
30 opening 126 in the form of a slot therethrough.

A dielectric adhesive or a double-sided adhesive tape may be provided to a portion of the second surface 124 surrounding a periphery of the opening 126 of the

first interposer 120, or alternatively, the adhesive may be provided to substantially cover the second surface 124 of the first interposer substrate 120. First die 130 is directly attached to the adhesive on the second surface 124 of the first interposer substrate 120, so that an active surface 132 of the first die 130 is face up and accessible
5 from the first surface 122 of the first interposer substrate 120 through the opening 126 therein.

Electrical interconnection between bond pads of the first die 130 and terminals of the first interposer substrate 120 on first side 122 may be effected by wire bonding. Wire bonds 140 formed to extend between bond pads on the active surface 132 of the
10 first die 130 through opening 126 and corresponding terminals on the first surface 122 of the first interposer substrate 120.

FIG. 1(b) depicts a simplified cross-sectional view of a stacked in-process interposer assembly 105 including the first assembly 110 mounted to a second assembly 110'. The second assembly 110' in the first embodiment of the present invention is
15 preferably structured substantially the same as the first assembly 110. Similar to the first assembly 110, the second assembly includes a second interposer substrate 120' having a first surface 122' and second opposing surface 124', a second semiconductor device or die ("second die") 130' having an active surface 132' which is attached to the second surface 124' of the second interposer substrate 120'. The second assembly 110'
20 also includes wire bonds 140' electrically connecting terminals of the second interposer substrate 120' and bond pads of second die 130'.

Mounting the first and second assemblies 110 and 110' together is accomplished by flipping the second assembly 110' so that the first surface 122' of the second interposer substrate 120' directly opposes or faces the first surface 122 of the first
25 interposer substrate 120, the active surfaces 132 and 132' thus also facing each other. In this manner, the second assembly 110' may be mounted and bonded to the first assembly 110 by a plurality of discrete conductive elements 150 formed of a lead/tin solder or conductive or conductor-filled epoxy. If solder is employed, reflowing discrete conductive elements 150 at a suitable temperature determined by the material
30 of the bumps 150 will connect terminals of a second set on first surfaces 122 and 122'. If conductive or conductor-filled epoxy is employed, the discrete conductive elements 150 may be heat-cured. The conductive elements 150 may be structured as balls,

bumps, pillars or columns, depending upon the material or materials employed to form same. Other materials for the conductive elements 150 may also include, but are not limited to, copper, silver or gold as well as alloys thereof. The conductive elements 150 may include a conductive or nonconductive core having one or more conductive layers thereon. Alternatively, a so-called "Z-axis" anisotropically conductive adhesive or adhesive layer may be employed in lieu of discrete conductive elements.

The stacked interposer assembly 105 with a plurality of discrete conductive elements 150 between the first surfaces 122 and 122' of the first and second assembly 120 and 120' provides a gap 160 therebetween having a height H_1 which is defined by the height of the discrete conductive elements 150. As previously set forth, the wire bonds 140 and 140' extend from bond pads of first and second dice 130 and 130' respectively to the first surfaces 122 and 122' of the first and second interposer substrates 120 and 120', the wire bonds 140 and 140' exhibiting a wire bond loop height H_2 . The wire bond loop height H_2 is the distance, for example, that the wire bonds 140 or 140' extend above the first surface 120 or 122' their associated interposer substrate 120 or 120', as shown in FIG. 1(b). According to the first embodiment of the present invention, the gap height H_1 must be greater than the wire bond loop height H_2 . However, it is preferred that the gap height H_1 be at least twice the wire bond loop height H_2 to prevent opposing, substantially superimposed wire bonds 140 and 140' from making contact and causing electrical shorts. As a precautionary measure against such shorting, the wire bonds 140 and 140' may have previously applied thereto a low viscosity-type dielectric resin film thereon before stacked interposer assembly 105 is assembled. This film will mutually insulate the wire bonds 140 and 140' and substantially eliminate electrical shorts that may otherwise have the potential to occur between the opposing wire bonds 140 and 140' of the first and second assembly 110 and 110', particularly if gap 160 is of marginal height with respect to the height of the wire bond loops.

As shown in FIG. 1(c), once the first assembly 110 and the second assembly 110' are electrically connected together as previously described, a dielectric filler material 170 may be disposed into gap 160 between the first assembly 110 and second assembly 110'. The dielectric filler material 170, commonly referred to as an "underfill" compound due to widespread use in flip-chip assemblies, serves to

distribute loads placed on the first and second assembly 110 and 110' due to thermal expansion and contraction during operation. If dielectric filler material 170 is thermally conductive, it may also facilitate transfer of heat generated from the first and second die 130 and 130'. The dielectric filler material 170 also reduces the potential for
5 environmental contamination between the first and second assembly 110 and 110' and provides an additional mechanical bond between the first and second assembly 110 and 110'. The filler material 170 may comprise a flowable polymeric material, such as an epoxy or an acrylic resin and may contain inert filler material therein to reduce cost.

To promote filling the gap 160 efficiently and effectively, it is necessary to fill
10 the gap 160 in a minimal of time without voids or air pockets forming in the filler material 170. Such efficiency may be optimized by a person of ordinary skill in the art manipulating the viscosity and surface tension of the filler material to accommodate the height of the gap 160. Another consideration to promote filling efficiency is in the method used to fill the gap 160. Such methods for filling the gap 160 may include, but
15 are not limited to, injecting, alone or in combination with pressurize and vacuum assist methods. For example, filling the gap 160 may be accomplished by applying the filler material 170 from a dispenser nozzle 175, which may comprise a needle. The dispenser nozzle 175 may fill the gap 160 by dispensing dielectric filler material 170 at either one side edge 112 or two adjacent side edges (such as side edge 112 in combination with an
20 edge facing the reader) of the stacked interposer assembly 105. The dielectric filler material 170 may then be allowed to freely flow and fill the gap 160 as a result of capillary forces between the first and second assembly 110 and 110'. The stacked interposer assembly 105 may be tilted downward away from dispenser nozzle 175 to employ a gravity assist to flow. Further, in utilizing the one-sided or two-sided dispense
25 method, the dielectric filler material 170, when of an appropriate viscosity, pushes and removes the air from the gap 160 as the filler material 170 fills the space therein. The dispenser nozzle 175 may be affixed to the reservoir of a syringe or any other dispensing apparatus known in the art. After application of the dielectric filler material 170, it may be cured by heat, ultraviolet light, other radiation, or other suitable means
30 (depending on the dielectric filler material selected) to at least a semisolid mass.

Additionally, as shown in FIG. 1(c), a dielectric encapsulation material 177 may be provided to edges 134 and 134' of the respective active surfaces 132 and 132' of the

first and second die 130 and 130'. The dielectric encapsulation material 177 provides an additional sealant between each die and its associated interposer substrate from the environment. Further, it provides an additional mechanical bond between each die and its associated interposer substrate to help distribute loading and thermal stress.

5 As shown in FIG. 1(d), a stacked multi-die assembly 100 comprises the stacked interposer assembly 105 attached to a carrier substrate 180 such as a PCB with a plurality of discrete conductive elements 182 therebetween. The conductive elements 182 may contact terminals of a third set on either of the second surfaces 124 and 124' of the first and second assembly 110 and 110' for mechanically and electrically connecting
10 stacked interposer assembly 105 to conductive traces of the carrier substrate 150. Discrete conductive elements 182 may comprise any of the materials or combinations thereof previously mentioned with respect to discrete conductive elements 150 and be of any suitable configuration.

 Further, as shown in FIG. 1(d), once the stacked interposer assembly 105 is
15 bonded to the carrier substrate 180 via the conductive interconnects 182, as previously set forth, next, a dielectric underfill material 186 may optionally be applied to fill a gap 184 therebetween. As previously discussed with respect to filling the gap 160 between the first assembly 110 and second assembly 110', the gap 184 may be similarly filled, employing any method known to one of ordinary skill in the art. Further, gap 184 must
20 be at least a height H_3 equal to or greater than the thickness of the first die 130 or second die 130' (depending upon which die is disposed between the lowermost interposer substrate and carrier substrate 180).

 Therefore, it is apparent that the above described stacked multi-die assembly 100, having gap 160 at a minimum height H_1 due to the absence of a die between the
25 adjacent interposer substrates 120 and 120', results in a substantial decrease in the height of the assembly. Further, it should be appreciated that the present invention provides encapsulation of both the wire bonds 140 and 140' for the first and second assembly 110 and 110', and additionally, encapsulation of the conductive bumps 150 between the first and second assembly 110 and 110', all of which is provided in one
30 process step of filling the gap 160 with the dielectric filler material 170. In sum, the present invention provides a method and apparatus that provides increased circuit density while also reducing the number of fabrication steps.

A variation 200 of the first embodiment of the present invention is illustrated in FIG. 2, depicting a simplified cross-sectional view of stacked interposer assembly 205 having multiple first and second dice 230 and 230' respectively attached to each of first and second interposer substrates 220 and 220'. This variation is similar to the stacked multi-die assembly 100 in every respect except the first and second assembly 210 and 210' includes, but is not limited to, multiple first and second die 230 and 230' directly attached over associated openings 226 and 226' in the first and second interposer substrates 220 and 220'.

A second embodiment 300 of the present invention is illustrated in FIG. 3, depicting a partial simplified cross-sectional view of stacked interposer assembly 305 having multiple first and second dice 330 and 330' respectively attached to each of first and second interposer substrates 320 and 320'. The second embodiment is similar to the first embodiment except the openings 326 and 326' in the first and second assemblies 310 and 310' include a staggered, or laterally offset, opening arrangement 390 so that the openings 326 and 326' in the opposing first and second interposer substrates 320 and 320' are not directly aligned and facing each other in mutual superimposition. As a result, the wire bonds 340, for example, in the first assembly 310 do not directly face and cannot contact the wire bonds 340' in the second assembly 310'. Significantly, the staggered or laterally offset opening configuration 390 reduces the necessary height H_1 of the gap 360 to be the same or only slightly larger than the wire bond loop height H_2 since opposing but laterally offset wire bonds 340 and 340' cannot contact each other. As shown in FIG. 3, the first and second interposer substrates 320 and 320' may each include multiple openings 326 and 326' in the staggered opening configuration 390 for attaching multiple first and second die 330 and 330' to the first and second interposer 320 and 320'. Alternatively, the first and second interposer substrates 320 and 320' may each include only one opening in the staggered opening configuration 390. It is notable that the second embodiment of the present invention includes the same advantages as that discussed in the first embodiment and, additionally, the second embodiment includes a minimized required gap height between the interposer substrates to promote a reduced package height for a high circuit density.

A variation 400 of the second embodiment is illustrated in FIG. 4, which depicts a partial simplified cross-sectional view of stacked interposer assembly 405 having

multiple first and second die 430 and 430' respectively attached to first and second interposer substrates 420 and 420'. This variation is similar to the second embodiment except that the staggered opening configuration 490 include opposing openings 426 and 426' partially aligned to directly face each other. In particular, the opposing openings
5 426 and 426' are preferably staggered so that, for example, one opening is directly aligned and facing at least a portion of an opposing opening. With this particular staggered opening configuration 490, the height H_1 of the gap 460 may be between the wire bond loop height H_2 and twice the wire bond loop height H_2 ($H_2 < H_1 < 2H_2$). As in
10 the previous embodiments and alternatives thereof, it is well appreciated that this structure offers the same advantages of increased integrated circuit density with a reduced package height as well as reducing the number of process steps.

The present invention also contemplates that an entire die secured to an interposer substrate may be over-molded for complete encapsulation of the sides and back side thereof, or may not be encapsulated whatsoever. Further, use of a dielectric
15 underfill material between adjacent interposer substrates may be omitted if desired, although use thereof is currently preferred. Additional openings may be formed in the interposer substrates to facilitate introduction of the dielectric underfill material or avoidance of bubbles or voids. Further, one or more additional dice or other electrical components may be secured to the interposer assembly on the top side thereof (as to be
20 mounted to a carrier substrate, and electrically connected to the interposer assembly as known in the art).

While the present invention has been disclosed in terms of certain illustrated embodiments, those of ordinary skill in the art will recognize and appreciate that the invention is not so limited. Additions, deletions and modifications to the disclosed
25 embodiments may be effected without departing from the scope of the invention as claimed herein. Similarly, features from one embodiment may be combined with those of another while remaining within the scope of the invention.



CLAIMS

What is claimed is:

1. A semiconductor device assembly comprising:
a carrier substrate having a surface;
5 a first interposer substrate having a first surface and a second surface and at least one opening extending therebetween, said second surface of said first interposer substrate substantially facing said surface of said carrier substrate, and said first substrate and said carrier substrate being electrically connected by a set of conductive elements extending transversely therebetween; and
10 a second interposer substrate having a first surface and a second surface and at least one opening extending therebetween, said first surface of said second interposer substrate substantially facing said first surface of said first substrate, said first and second substrates being electrically connected by another set of conductive elements extending transversely therebetween;
15 at least one first die and at least one second die each having an active surface, said active surface of said at least one first die attached to said second surface of said first interposer substrate over said at least one opening thereof and electrically connected to said first surface thereof through said at least one opening, said active surface of said at least one second die attached to said second surface of
20 said second substrate over said at least one opening thereof and electrically connected to said first surface thereof.
2. The assembly according to claim 2, wherein said active surface of said at least one first die is electrically connected to said second surface of said first interposer
25 substrate with wire bonds and said active surface of said at least one second die is electrically connected to said second surface of said second interposer substrate with wire bonds.
3. The assembly according to claim 2, further including a dielectric
30 material disposed between said first and second interposer substrates and substantially encapsulating said wire bonds and said set of conductive elements.



-14-

4. The assembly according to claim 2, wherein a transverse distance between said first and second interposer substrates is at least greater than a wire bond loop height.
5. The assembly according to claim 2, wherein a transverse distance between said first and second interposer substrates is between one wire bond loop height and two wire bond loop heights.
6. The assembly according to claim 2, wherein a transverse distance between said first and second interposer substrates is at least twice that of a wire bond loop height.
7. The assembly according to claim 1, further including a dielectric material disposed between said first and second interposer substrates and substantially encapsulating said set of conductive elements.
8. The assembly of claim 1, wherein said at least one opening of said first interposer substrate and said at least one opening of said second interposer substrate are at least partially mutually laterally offset.
9. The assembly of claim 1, wherein said at least one opening of said first interposer substrate and said at least one opening of said second interposer substrate are fully mutually laterally offset.
10. The assembly of claim 9, wherein said at least one first die and said at least one second die are respectively electrically connected to first surfaces of said first and second interposer substrates with wire bonds.



11. An interposer assembly configured for electrical connection to a carrier substrate, the assembly comprising:
- a first interposer substrate having a first surface, a second opposing surface and at least one opening therethrough;
- 5 a second interposer substrate having a first surface, a second opposing surface and at least one opening therethrough, said first surface of said first interposer substrate substantially facing said first surface of said second interposer substrate, said first and second interposer substrates being electrically connected by a plurality of conductive elements extending transversely there therebetween;
- 10 and
- at least one first die and at least one second die each having an active surface, said active surface of said at least one first die attached to said second surface of said first interposer substrate over said at least one opening thereof and electrically connected to said first surface thereof through said at least one opening, said
- 15 active surface of said at least one second die attached to said second surface of said second substrate over said at least one opening thereof and electrically connected to said first surface thereof;
- wherein a first surface of one of said first and said second interposer substrates carries another plurality of conductive elements projecting transversely therefrom and
- 20 arranged for effecting an electrical connection between said first surface of said one of said first and said second interposer substrates to a carrier substrate.
12. The assembly according to claim 11, wherein said active surface of said at least one first die is electrically connected to said second surface of said first
- 25 interposer substrate with wire bonds and said active surface of said at least one second die is electrically connected to said second surface of said second interposer substrate with wire bonds.
13. The assembly according to claim 12, further including a dielectric
- 30 material disposed between said first and second interposer substrates and substantially encapsulating said wire bonds and said plurality of conductive elements.



14. The assembly according to claim 12, wherein a transverse distance between said first and second interposer substrates is at least greater than a wire bond loop height.

5 15. The assembly according to claim 12, wherein a transverse distance between said first and second interposer substrates is between one wire bond loop height and two wire bond loop heights.

10 16. The assembly according to claim 12, wherein a transverse distance between said first and second interposer substrates is at least twice that of a wire bond loop height.

15 17. The assembly according to claim 11, further including a dielectric material disposed between said first and second interposer substrates and substantially encapsulating said plurality of conductive elements.

20 18. The assembly of claim 11, wherein said at least one opening of said first interposer substrate and said at least one opening of said second interposer substrate are at least partially mutually laterally offset.

19. The assembly of claim 11, wherein said at least one opening of said first interposer substrate and said at least one opening of said second interposer substrate are fully mutually laterally offset.

25 20. The assembly of claim 19, wherein said at least one first die and said at least one second die are respectively electrically connected to first surfaces of said first and second interposer substrates with wire bonds.



21. A semiconductor device assembly, comprising:
a first interposer substrate having at least one semiconductor die secured thereto on one
side thereof;
a second interposer substrate having at least one semiconductor die secured thereto on
5 one side thereof;
the first and second interposer substrates being disposed in mutually parallel
relationship and electrically connected through a first plurality of conductive
elements extending transversely therebetween; and
a second plurality of conductive elements extending transversely from a side of one of
10 the first and second interposer substrates for connecting the assembly to a
carrier substrate.

22. The assembly of claim 21, wherein the first and second interposer
substrates are oriented with no semiconductor dice located therebetween.

15

23. The assembly of claim 22, wherein each of the at least one
semiconductor die secured to each of the first and second interposer substrates is
located with an active surface facing its associated interposer substrate and extending
over an opening therethrough, and further including elongated conductive elements
20 extending from an active surface of each semiconductor die through an opening in the
associated interposer substrate and to an opposing side of the associated interposer
substrate.

24. The assembly of claim 23, wherein the elongated conductive elements
25 comprise wire bonds.

25. The assembly of claim 24, further including a dielectric material
disposed between the first and second interposer substrates and substantially
encapsulating the wire bonds and the first plurality of conductive elements.

30



26. The assembly of claim 23, wherein the elongated conductive elements comprise wire bonds, and at least one opening through one of the first and second interposer substrates is at least partially laterally offset from at least one opening through another of the first and second interposer substrates.

5

27. The assembly of claim 26, wherein each interposer substrate includes a like number of openings therethrough and each opening through one of the first and second interposer substrates is at least partially laterally offset from any opening in the other of the first and second interposer substrates.

10

28. The assembly of claim 26, wherein each interposer substrate includes a like number of openings therethrough and each opening through one of the first and second interposer substrates is fully laterally offset from any opening in the other of the first and second interposer substrates.

15

29. The assembly of claim 21, further comprising a carrier substrate electrically connected to the side of the one of the first and second interposer substrates through the second plurality of conductive elements.

20

30. The assembly of claim 29, further including a dielectric material disposed between the side of the one of the first and second interposer substrates and the carrier substrate and substantially encapsulating the second plurality of conductive elements.

25

31. A method of fabricating a stacked multi-die assembly, the method comprising:

securing at least one semiconductor die to one side of a first interposer substrate;

securing at least one semiconductor die to one side of a second interposer substrate; and

electrically connecting the first and second interposer substrates with a first plurality of

30

conductive elements extending transversely therebetween and with no

semiconductor dice disposed between the first and second interposer substrates.



-19-

32. The method of claim 31, further comprising:
introducing a flowable dielectric material between the first and second interposer
substrates and substantially encapsulating the first plurality of conductive
elements.

5

33. The method of claim 31, further comprising:
securing the semiconductor dice to the interposer substrates by active surfaces of the
semiconductor dice and with a portion of each active surface exposed through
an opening in the interposer substrate; and

10 electrically connecting each semiconductor die to the interposer substrate to which such
semiconductor die is secured by at least one wire bond extending from an
exposed portion of the active surface thereof to an opposite side of the
interposer substrate to which that semiconductor die is secured.

15 34. The method of claim 33, further comprising:
introducing a flowable dielectric material between the first and second interposer
substrates and substantially encapsulating the first plurality of conductive
elements and the wire bonds.

20 35. The method of claim 31, further comprising:
electrically connecting one of the first and second interposer substrates to a carrier
substrate with a second plurality of conductive elements extending transversely
therebetween.

25 36. The method of claim 35, further comprising:
introducing a flowable dielectric material between the one of the first and second
interposer substrates and the carrier substrate and substantially encapsulating the
second plurality of conductive elements.



-20-

37. The method of claim 28, further comprising:
forming at least one opening in each of the first and second interposer substrates in
locations whereby the at least one opening in each of the first and second
interposer substrates is at least partially laterally offset from at least one opening
5 in the other of the first and second interposer substrates when the first and
second interposer substrates are electrically connected.

38. The method of claim 28, further comprising:
forming at least one opening in each of the first and second interposer substrates in
10 locations whereby the at least one opening in each of the first and second
interposer substrates is fully laterally offset from at least one opening in the
other of the first and second interposer substrates when the first and second
interposer substrates are electrically connected.

15

20