

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 May 2003 (01.05.2003)

PCT

(10) International Publication Number
WO 03/035803 A1

(51) International Patent Classification⁷: **C10G 31/11**,
B01D 61/02, 65/08

(21) International Application Number: PCT/EP02/11712

(22) International Filing Date: 18 October 2002 (18.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01402702.3 18 October 2001 (18.10.2001) EP

(71) Applicant (for all designated States except US): **SHELL
INTERNATIONALE RESEARCH MAATSCHAPPIJ
B.V.** [NL/NL]; Carel Van Bylandtlaan 30, NL-2596 HR
The Hague (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CEDERLØF,
Gro** [NO/NL]; Badhuisweg 3, NL-1031 CM Amsterdam
(NL). **GEUS, Eduard, Rudolf** [NL/NL]; Badhuisweg 3,
NL-1031 CM Amsterdam (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTINUOUS PROCESS TO SEPARATE COLOUR BODIES AND/OR ASPHALTHENIC CONTAMINANTS FROM A HYDROCARBON MIXTURE

(57) Abstract: Continuous process to separate colour bodies and/or asphalthenic contaminants from a hydrocarbon mixture by passing part of the hydrocarbon mixture through a membrane over which membrane a pressure difference is maintained thereby obtaining a hydrocarbon permeate having a reduced content of colour bodies and/or contaminants, wherein at regular time intervals the pressure difference over the membrane is substantially lowered.



WO 03/035803 A1