

MODULAR SYSTEM AND METHOD FOR PROVIDING BICYCLES

RELATED APPLICATION

The present application claims priority of United States provisional patent
5 application No. 61/059,464 filed on June 6, 2008, the specification of which is
incorporated herein by reference.

FIELD OF THE INVENTION

The invention relates to systems and methods for providing bicycles. More
precisely, this invention pertains to a modular system for providing bicycles and
10 associated methods.

BACKGROUND OF THE INVENTION

Bicycles are very useful for humans and good for the environment. Moreover,
they help humans stay fit.

Having a bicycle in a large city however may not be as convenient as it seems for
15 various reasons. For instance, it might be complicated to store temporarily the
bicycle, such as for instance when a user reaches an intended destination, or
permanently, such as for instance when the user brings back his bicycle home.
This may discourage potential users from having and using a bicycle.

Some manufacturers have provided systems for renting bicycles that may be
20 installed at various locations in a given city. For instance, Squire et al. have
disclosed in US Patent N° 5,917,407 a system for renting bicycles.

Unfortunately, while the use of such system may be very attractive for an end-
user, the operator managing such system may be faced with various serious
challenges.

25 For instance, an end user may rent a bicycle at a first location and desire to drop
the bicycle at another location. Some locations may therefore become overfilled
with bicycles while some other locations may become depleted in bicycles. The
system may therefore become de-balanced and the operator may be faced with
the issue of having to transfer bicycles from one location to another to rebalance

the system which is a drawback since it adds operation costs and therefore reduces profits.

Moreover, such systems for renting bicycles may become cumbersome to operate and manage in cities where weather conditions are harsh such as for instance in Montreal.

Moreover, in case of a failure of some of the components, such system may require a technician *on site* to check and repair the defective component which may also be problematic since it may interrupt the normal operation of the whole system.

It will also be appreciated that the system may be complicated to use in the case of special, temporary outdoor events.

There is therefore a need for a method and apparatus that will overcome at least one of the above-identified drawbacks.

BRIEF SUMMARY

There is provided a modular system for providing bicycles at a given location according to a desired configuration, the modular system comprising at least one bicycle rack for storing a bicycle, each of the at least one bicycle rack comprising an electronic lock secured thereto for removably securing a corresponding bicycle, each of the at least one bicycle rack further comprising a corresponding attaching means having an electrical connector operatively coupled to the electronic lock, an energy providing means for providing energy to each electronic lock of the at least one bicycle rack, the energy providing means comprising a corresponding attaching means having an electrical connector operatively coupled thereto and a structure to be installed at the given location, the structure comprising an elongated base, a plurality of spaced-apart receiving means located on the base, each of the plurality of spaced-apart receiving means being adapted for receiving a selected attaching means from the at least one bicycle rack and the energy providing means according to the desired configuration and an electric network interconnecting each of the plurality of spaced-apart receiving means to thereby providing a modular system for

providing bicycles.

Thanks to its modularity, the system may be tailored according to specific needs, which is of great advantage.

Moreover, the modularity of the system may help to reduce down time of the whole system since a defective modular component may be easily replaced and repaired at a later time and/or at another location without disrupting the operating of the whole system, which is of great advantage.

In one embodiment, the elongated base comprises a sheet of rigid material having a first outer planar surface, a second outer planar surface and a third central planar surface extending therebetween, each of the receiving means extending on the central planar surface in an aligned configuration.

In another embodiment, the elongated base comprises at least one end suitable for connecting a neighboring elongated base thereto.

In another embodiment, the elongated base comprises a first end and a second end, each being suitable for connecting a corresponding neighboring elongated base thereto, the first end comprising a first connecting device and the second end comprising a second connecting device, the first connecting device being adapted for connecting with the corresponding second connecting device of the neighboring elongated base.

In a further embodiment, a corresponding one of the first and second connecting devices of the elongated base comprises a securing device cooperating with the corresponding connecting device of the corresponding end of the neighboring elongated base for securing the elongated base and the neighboring elongated base together.

In still a further embodiment, the first connecting device comprises at least one male connector projecting horizontally and comprising a hole extending upwardly, and the second connecting device comprises at least one corresponding female connector projecting horizontally and comprising a corresponding hole extending upwardly, each hole of two corresponding connecting devices extending in an

aligned configuration when connected together for providing a screw passage. The securing element comprises a corresponding bore extending through the elongated base and a screw adapted for insertion in the screw passage through the bore of the elongated base.

5 In another further embodiment, the first connecting device comprises an additional male connector and the second connecting device comprises an additional female connector, the securing element further comprising an additional corresponding bore extending through the elongated base and an additional screw.

10 In one embodiment, each of the first connecting device and the second connecting device comprises a corresponding complementary cooperating connecting member.

In another embodiment, the structure comprises a wire housing mounted under the elongated base and extending therealong for receiving at least a portion of
15 the electric network.

In one embodiment, each of the receiving means of the structure comprises an attaching device adapted for cooperating with a corresponding one of the attaching means of the at least one bicycle rack and the energy providing means.

In a further embodiment, the attaching device of each of the receiving means
20 comprises a plurality of holes, each of the attaching means of the at least one bicycle rack and the energy providing means comprising a plurality of corresponding holes and a plurality of corresponding screws for screwing the attaching means to a corresponding attaching device of the receiving means.

In one embodiment, the energy providing means comprise a solar energy
25 providing means. This is of great advantage since the system may operate in a stand alone configuration without requiring external energy.

In a further embodiment, the energy providing means comprise a base provided with the attaching means, an elongated member mounted on the base and a solar panel assembly mounted on the elongated member.

In still a further embodiment, the energy providing means further comprise a plurality of batteries mounted with the base and operatively connected to the solar panel assembly.

5 In one embodiment, the modular system further comprises a bicycle providing means interconnected to the electric network for managing a providing of a corresponding bicycle to a user.

In a further embodiment, the bicycle providing means comprises a user interface for establishing communication between the system and a user, the bicycle providing means further comprising a control unit for controlling the electronic
10 lock of the at least one bicycle rack according to a user request.

In another embodiment, the bicycle providing means is integrated with the energy providing means.

In one embodiment, the modular system further comprises a servicing module having a corresponding attaching means for attaching the servicing module in a
15 corresponding one of the receiving means, the servicing module being selected from a group comprising an advertising module, a vending machine, a ticket distribution booth and a payment module for renting at least a corresponding one of the bicycles.

In another embodiment, the servicing module comprises a payment module
20 comprising means for communicating with a distant server.

In one embodiment, the electric network comprises a plurality of network connectors, each being provided proximate to a corresponding receiving means of the elongated base for connecting with a corresponding connector of the at least one bicycle rack and the energy providing means. The electric network
25 further comprises at least one additional end connector mounted at an end thereof for coupling a neighboring electric network.

In one embodiment, the electric network interconnecting each of the plurality of spaced-apart receiving means comprises a configuration selected from a group consisting of a parallel configuration and a serial configuration.

In one embodiment, the structure further comprises a set of leveling screws mounted under the elongated base for enabling a leveling of the structure.

In another embodiment, the structure further comprises at least one ending element securable to a respective end of the elongated base, the ending element
5 being selected from a group consisting of an end covering for covering the corresponding connecting device and an upright panel.

According to another aspect, there is also provided a method for installing a modular system for providing bicycles at a given location according to a desired configuration, the method comprising providing an elongated base comprising a
10 plurality of spaced-apart receiving means; laying down the elongated base at the given location; providing at least one bicycle rack for storing a bicycle, each of the at least one bicycle rack comprising an electronic lock secured thereto for removably securing a corresponding bicycle; providing an energy providing means for providing energy; attaching each of the at least one bicycle rack and
15 the energy providing means in a corresponding one of the spaced-apart receiving means of the elongated base; and electrically interconnecting each of the at least one bicycle rack and the energy providing means together.

In one embodiment, the method further comprises providing at least one additional elongated base comprising a plurality of spaced-apart receiving
20 means; laying down the at least one additional elongated base at the given location proximate the elongated base; and operatively connecting the at least one additional elongated base at an end of the elongated base.

In one embodiment, the given location is selected from a group comprising a sidewalk, a portion of a street, a parking lot, a park, a beach and a substantially
25 horizontal surface.

In a further embodiment, the desired configuration comprises an initial predetermined configuration defined according to an intended use, the method further comprising monitoring use of the bicycles for providing current usage information based on the initial predetermined configuration; defining an optimal
30 configuration for the modular system based on the current usage information, the optimal configuration comprising an optimal number of the bicycles and the

associated bicycle racks and a corresponding number of elongated bases; and configuring the modular system according to the optimal configuration, the configuring comprising providing the corresponding number of elongated bases; laying down the corresponding number of elongated bases at the given location; 5 operatively connecting each of the corresponding number of elongated bases together; providing the optimal number of the bicycles and the associated bicycle racks; attaching each of the optimal number of bicycle racks in a corresponding one of the spaced-apart receiving means of a corresponding one of the elongated bases; and electrically interconnecting each of the optimal number of bicycle 10 racks and the energy providing means together.

In still a further embodiment, the current usage information comprises a bicycle occupation rate associated with each of the bicycles.

According to another aspect, there is also provided a method for providing bicycles at a given location according to a desired configuration, the method 15 comprising providing a modular system as previously described; installing the modular system at the given location according to the desired configuration; establishing communication between the system and a user for defining a user request; providing a corresponding bicycle to the user according to the user request; and after use, collecting the corresponding bicycle from the user.

20 In one embodiment, the collecting is performed at another location provided with another modular system.

In another embodiment, the providing a corresponding bicycle is done for a fee.

According to another aspect, there is also provided a method of doing business in providing bicycles at a given location according to a desired configuration with the 25 modular system as previously described, wherein the providing a corresponding bicycle is done for a fee.

In one embodiment, the providing a corresponding bicycle is done by a third party.

According to another aspect, there is also provided a method of doing business in

providing bicycles at a given location according to a desired configuration, the method comprising providing by a provider a modular system as previously described to a third party; operating the modular system wherein the operating is done by a third party for a fee; and reconveying by the third party a portion of the
5 fee to the provider.

In one embodiment, the fee is determined according to an occupation rate associated to each of the corresponding bicycles.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and advantages of the invention will become apparent
10 upon reading the detailed description and upon referring to the drawings in which:

Figure 1 is a front perspective view of an elongated base of a structure.

Figure 1A is an enlarged view of a portion of the elongated base disclosed in Fig. 1.

Figure 2 is a bottom perspective view of the elongated base disclosed in Fig. 1.

15 Figure 2A is an enlarged view of a portion of the elongated base disclosed in Fig. 2.

Figure 3 is a top plan view of the elongated base disclosed in Fig. 1.

Figure 4 is a bottom plan view of the elongated base disclosed in Fig. 1.

Figure 5 is a front elevation view of the elongated base disclosed in Fig. 1.

20 Figure 6 is a rear elevation view of the elongated base disclosed in Fig. 1.

Figure 7 is a left side view of the elongated base disclosed in Fig. 1.

Figure 8 is a right side view of the elongated base disclosed in Fig. 1.

Figure 9 is a front perspective view of a structure comprising two elongated bases.

25 Figure 10 is a bottom perspective view of the structure comprising two elongated

bases of Fig. 9.

Figure 11 is a front perspective view of the structure comprising two elongated bases disclosed in Fig. 9 wherein the two elongated bases have been connected together.

- 5 Figure 12 is a bottom perspective view of the structure disclosed in Fig. 9 wherein the two elongated bases have been connected one to another.

Figure 13 is a rear perspective view of the elongated base disclosed in Fig. 1, wherein a first embodiment of an energy providing means has been connected thereto.

- 10 Figure 13A is a rear perspective view of the elongated base disclosed in Fig. 1 wherein another embodiment of an energy providing means has been connected thereto.

- Figure 14 is a rear perspective view of an assembly of two elongated bases wherein a bicycle rack and an energy providing means have been secured
15 thereto.

Figure 15 is a front perspective view of a structure comprising two elongated bases wherein an energy providing means has been connected thereto and wherein a bicycle rack is shown in exploded view.

- Figure 16 is a front perspective view of a structure comprising two elongated
20 bases that have been connected one to another and further a plurality of bicycle racks together as well as an integrated solar energy and bicycle providing means have been installed on the structure.

- Figure 17 is a front perspective view, cross-sectioned longitudinally of the elongated base shown in Fig. 1 wherein an electric network has been inserted
25 therein.

Figure 18 is a front perspective view of an interconnecting element used for interconnecting two elongated bases together.

Figure 19 is a front perspective view of another interconnecting element used for

interconnecting two elongated bases together.

Figures 20A to 20E are top plan views of different structures comprising at least two elongated bases interconnected together with at least one interconnected element.

- 5 Figure 21 is a flow chart of a method of installing a modular system for providing bicycles at a given location according to a desired configuration.

Figure 22 is a flow chart of a method for providing bicycles at a given location according to a desired configuration.

- 10 Figure 23 is a flow chart of a method of doing business with the providing of bicycles at a given location according to a desired configuration.

Further details of the invention and its advantages will be apparent from the detailed description included below.

DETAILED DESCRIPTION

- 15 In the following description of the embodiments, references to the accompanying drawings are by way of illustration of an example by which the invention may be practiced. It will be understood that other embodiments may be made without departing from the scope of the invention disclosed.

- 20 The invention discloses a modular system for providing bicycles and associated methods. As previously mentioned, providing a user with a bicycle for a temporary use may present several advantages, particularly in large cities. The system disclosed may be easily installed, which is a great advantage. Moreover, the system is modular and may then be advantageously installed in temporary locations for special events, and may also be configured in a dynamic fashion according to specific needs, as it will be more clearly detailed thereafter.

- 25 The modular system disclosed, thanks to its modularity, may be easier to manage and repair, and may also help reducing down time of the whole system due to a defective component, as it will be more apparent upon reading of the description.

Moreover, as it will become more apparent upon the reading of the description, the modular system disclosed provides an efficient economical solution in the managing of a fleet of bicycles since it enables an optimization of the available resources, which is of great advantage.

- 5 Now referring to Fig. 1, there is shown an embodiment of a structure to be installed at a given location. It will be appreciated that the given location may be selected from a group consisting of sidewalks, portions of a street, parking lots, parks, beaches or any other planar surface. Moreover it will be appreciated that in one embodiment the given location is characterized by a substantially
10 horizontal surface.

Still referring to Fig. 1, the structure comprises an elongated base **100**. In one embodiment, the elongated base **100** has a substantially rectangular shape. Alternatively, the elongated base **100** may have any other shape suitable for a given configuration.

- 15 The elongated base **100** comprises in this embodiment a first planar surface **104**, a second planar surface **106** and a third planar surface **108**. It will be appreciated that each of the first planar surface **104**, the second planar surface **106** and the third planar surface **108** has a substantially rectangular shape. It will be appreciated that the second planar surface **106** is substantially horizontal. In this
20 embodiment the elongated base **100** comprises a sheet of rigid material that has been slightly bent to define the planar surfaces **104**, **106**, **108** but the skilled addressee will appreciate that other arrangements may be considered.

- A plurality of spaced-apart receiving means **102** is located on the elongated base **100**. In one embodiment, the plurality of spaced-apart receiving means **102** is
25 located on the second planar surface **106**. In the embodiment disclosed in Fig. 1, the plurality of spaced-apart receiving means **102** comprises a first receiving means **102a**, a second receiving means **102b**, a third receiving means **102c** and a fourth receiving means **102d**. The skilled addressee will further appreciate that while in Fig. 1, the first receiving means **102a**, the second receiving means **102b**,
30 the third receiving means **102c** and the fourth receiving means **102d** are aligned, various other configurations may be possible alternatively.

Still referring to Fig. 1, the elongated base **100** has a first connecting end **150** and a second connecting end **152**. Each of the first connecting end **150** and the second connecting end **152** is used to connect the elongated base **100** to another neighboring elongated base (not shown) to thereby create a structure comprising more than one elongated base. The skilled addressee will appreciate that an elongated base provided with a single connecting end may be envisaged.

In the embodiment disclosed in Fig. 1, the first connecting end **150** comprises a first connecting device **152** comprising a first male connector **112** and a second male connector **114**, each having a cylindrical elongated shape.

In the illustrated embodiment, the first male connector **112** and the second male connector **114** extend horizontally and define a corresponding horizontal surface. Moreover, as better shown in Fig. 1A, each of the first male connector **112** and the second male connector **114** comprises a vertically oriented tap hole **130** used for securing the elongated base **100** to a neighboring elongated base. It will be appreciated that two corresponding holes **132** are provided in the vicinity of the opposed connecting end **152**, as illustrated in Fig. 2A. The two corresponding holes **132** are used for receiving corresponding screws **160**, **162** acting as a securing means and used for securing the elongated base **100** to a neighboring elongated base located at the second connecting end **152**. In such case, the securing means comprises two corresponding bores **164**, **166** extending through the elongated base **100**. The screws **160**, **162** will be inserted in the two corresponding holes **130** of the first and second male connectors **112**, **114** through the bores **164**, **166** and will go further inside the two vertically oriented tap holes located on the corresponding connecting device of the neighboring elongated base to thereby secure the elongated base **100** to the neighboring elongated base, as it will be more apparent later with reference to Figure 2.

Still referring to Fig. 1, the structure comprises a wire housing **110**. In one embodiment, the wire housing **110** is mounted under the second planar surface **106**. More precisely, the wire housing **110** is mounted under each of the plurality of spaced-apart receiving means **102** and extends between the first connecting end **150** and the second connecting end **152**. In one embodiment, the wire housing **110** may be made of treated steel or stainless steel.

It will be appreciated that the elongated base **100** may be made of a rigid material such as steel to give appropriate stability and weight and may be further covered with an anti-slip safety coating to provide protection from water as well as other outside conditions. The skilled addressee will appreciate that other material
5 giving sufficient weight and stability may be considered.

Now referring to Fig. 2, there is shown a bottom view of the structure comprising the elongated base **100**.

It will be appreciated that the second connecting end **152** comprises a second connecting device **154** comprising a first female connector **202** and a second
10 female connector **200**, each having a cylindrical shape.

In the illustrated embodiment, the first female connector **202** and the second female connector **200** extend horizontally and define a horizontal surface. Each of the first female connector **202** and the second female connector **200** is adapted to receive a corresponding male connector from a neighboring elongated
15 base. Moreover, each of the first female connector **202** and the second female connector **200** is adapted to receive a corresponding screw **160**, **162** used to secure a corresponding male connector thereto. In other words, and as better shown in Fig. 2A, each of the first and second female connectors **202**, **200** comprises a hole **132** extending upwardly, each hole **132** extending in an aligned
20 configuration with a corresponding hole **130** of a corresponding male connector when two corresponding elongated bases are connected together for providing a corresponding passage screw.

The connecting devices used to connect two neighboring elongated bases together have been described as female and cooperating male connectors but
25 the skilled addressee will appreciate that various complementary cooperating members engageable together may be envisaged.

In one embodiment, the screws used to secure two neighboring elongated bases together comprise a securing element for preventing an unauthorized removal thereof. The skilled addressee will appreciate that various arrangements may be
30 used.

In the embodiment disclosed in Fig. 2, a second connecting end cover **204** has been secured to the second connecting end **152** of the elongated base **100** and is covering the first female connector **202** and the second female connector **200**. The skilled addressee will appreciate that the second connecting end cover **204** is used in instances where no elongated base is connected to the elongated base **100** using the female connectors **200**, **202**. The skilled addressee will also appreciate that a suitable first connecting end cover (not shown) may be used for covering the first and second male connectors **112**, **114**.

Now referring to Fig. 3, there is shown an embodiment of the structure comprising the elongated base **100**.

In this illustrated embodiment, the first receiving means **102a** comprises a first plurality of holes **300** and a second plurality of holes **302**. The first plurality of holes **300** is used for receiving corresponding attaching means from a module to be connected to the first receiving means **102a**. In one embodiment, the first plurality of holes **300** comprises four (4) holes located at each end of a rectangle. The second plurality of holes **302** is used for enabling the inserting of an electrical connector between the elongated base **100** and the module to be connected to the first receiving means **102a** as further explained below. In one embodiment, the second plurality of holes **302** comprises two (2) holes, each of the two holes being located respectively in the middle of each of the two smaller ends of the rectangle created by the first plurality of holes **300**, and each being adapted for enabling insertion of an electrical connector therein.

Similarly, the second receiving means **102b** comprises a first plurality of holes **304** and a second plurality of holes **306**. The first plurality of holes **304** is used for receiving corresponding attaching means from a module to be connected to the second receiving means **102b**. In one embodiment, the first plurality of holes **304** comprises four (4) holes located at each end of a rectangle. The second plurality of holes **306** is used for enabling the inserting of an electrical connector between the elongated base **100** and the module to be connected to the second receiving means **102b** as further explained below. In one embodiment, the second plurality of holes **306** comprises two (2) holes, each of the two holes being located respectively in the middle of each of the two smaller ends of the rectangle

created by the first plurality of holes **304**.

Similarly, the third receiving means **102c** comprises a first plurality of holes **308** and a second plurality of holes **310**. The first plurality of holes **308** is used for receiving corresponding attaching means from a module to be connected to the
5 third receiving means **102c**. In one embodiment, the first plurality of holes **308** comprises four (4) holes located at each end of a rectangle. The second plurality of holes **310** is used for enabling the inserting of an electrical connector between the elongated base **100** and the module to be connected to the third receiving means **102c** as further explained below. In one embodiment, the second plurality
10 of holes **310** comprises two (2) holes, each of the two holes being located respectively in the middle of each of the two smaller ends of the rectangle created by the first plurality of holes **308**.

Similarly, the fourth receiving means **102d** comprises a first plurality of holes **312** and a second plurality of holes **314**. The first plurality of holes **312** is used for
15 receiving corresponding attaching means from a module to be connected to the fourth receiving means **102d**. In one embodiment, the first plurality of holes **312** comprises four (4) holes located at each end of a rectangle. The second plurality of holes **314** is used for enabling the inserting of an electrical connector between the elongated base **100** and the module to be connected to the fourth receiving
20 means **102d** as further explained below. In one embodiment, the second plurality of holes **314** comprises two (2) holes, each of the two holes being located respectively in the middle of each of the two smaller ends of the rectangle created by the first plurality of holes **312**.

The skilled addressee will appreciate that various geometric configurations may
25 be envisaged for the holes used for receiving the attaching means from a module to be connected thereto. The skilled addressee will also appreciate that a symmetric configuration of each set of holes may be particularly advantageous since it would enable the mounting of each module in two opposed directions, as it will be more clearly detailed hereinafter.

30 Now referring to Fig. 4, there is shown an embodiment of the structure comprising the elongated base **100** which shows that the second connecting end

cover **204** is abutting the first female connector **202** and the second female connector **200** of the second connecting end **152** of the elongated base **100**.

Figs. 5 to 8 show various views of the structure comprising the elongated base **100**.

5 Now referring to Fig. 9, there is shown another embodiment of a structure. In this embodiment, the structure comprises the elongated base **100** as well as another elongated base **906**. It will be appreciated that this other embodiment of a structure is of great advantage in the case where the use of the elongated base **100** alone is not enough.

10 The elongated base **100** comprises the first receiving means **102a**, the second receiving means **102b**, the third receiving means **102c** and the fourth receiving means **102d**.

A plurality of spaced-apart receiving means **900** is located on the elongated base **906**. It will be appreciated that the other elongated base **906** is similar to the elongated base **100**. In the embodiment disclosed in Fig. 9, the plurality of spaced-apart receiving means **900** comprises a first receiving means **900a**, a second receiving means **900b**, a third receiving means **900c** and a fourth receiving means **900d**. The skilled addressee will further appreciate that while in Fig. 9, the first receiving means **900a**, the second receiving means **900b**, the third receiving means **900c** and the fourth receiving means **900d** are aligned, various other configurations are possible. Each of the first receiving means **900a**, the second receiving means **900b**, the third receiving means **900c** and the fourth receiving means **900d** is used to connect a module to the elongated base **906**. It will be appreciated that each of the plurality of receiving means **900** is similar to each of the plurality of receiving means **102**.

Still referring to Fig. 9, the elongated base **900** has a first connecting end and a second connecting end. Each of the first connecting end and the second connecting end may be used to connect the elongated base **900** to another neighboring elongated base to thereby create a structure comprising more than one elongated base.

The first connecting end comprises a first connecting device comprising a first male connector **902** and a second male connector **904**, each having a cylindrical shape.

5 In the illustrated embodiment, the first male connector **902** and the second male connector **904** are extending horizontally and are defining a horizontal surface. In a preferred embodiment, the first male connector **902** and the second male connector **904** are similar to the first male connector **112** and the second male connector **114**, and are also each provided with a suitable hole for receiving a screw used for securing the two neighboring bases together.

10 Still referring to Fig. 9, a wire housing **908** is mounted under the elongated base **906**. More precisely, the wire housing **908** is mounted under each of the plurality of spaced-apart receiving means **900** and extends between the first connecting end and the second connecting end of the elongated base **906**.

15 It will be appreciated that in one embodiment end caps **920**, **922** are used for sealingly close the wire housing **110** and the wire housing **908**. In one embodiment, the wire housing **908** is made of steel or any other material. It may be used like support to fix a waterproof hosing for each connector and to provide a water resistant connection for the input and output for the cable.

20 Fig. 10 shows a bottom view of the structure comprising the elongated base **100** and the elongated base **906**.

The skilled addressee will appreciate that in the embodiment disclosed, the second connecting end of the elongated base **906** comprises a second connecting device having a first female connector **1000** and a second female connector **1002**, each having a cylindrical shape.

25 In the illustrated embodiment, the first female connector **1000** and the second female connector **1002** are extending horizontally and are defining a horizontal surface. Each of the first connecting means **1000** and the second connecting means **1002** is adapted to receive a corresponding male connector from a neighboring elongated base, which in this case is the elongated base **100**.

Moreover, it will be appreciated by the skilled addressee that the first female connector **1000** and the second female connector **1002** are positioned facing respectively the first male connector **112** and the second male connector **114** of the elongated base **100**.

- 5 Now referring to Fig. 11, there is shown an embodiment where the elongated base **100** and the elongated base **906** have been secured one to another.

The structure resulting from the securing of the elongated base **100** with the elongated base **906** provides a plurality of receiving means comprising the plurality of receiving means **900** and the plurality of receiving means **102**. As
10 mentioned previously, the skilled addressee will appreciate that in using this resulting structure, it is possible to easily expand the receiving capability for modules.

Now referring to Fig. 12, there is shown a bottom view of the structure resulting from the elongated base **100** being secured to the elongated base **906**.

- 15 The skilled addressee will appreciate that in this embodiment the first male connector **112** of the elongated base **100** is inserted in the first female connector **1000** of the elongated base **906** while the second male connector **114** of the elongated base **100** is inserted in the second female connector **1002** of the elongated base **906**.

- 20 The skilled addressee will further appreciate that the wire housing **110** and the wire housing **908** are operatively connected, which is of great advantage.

Now referring to Fig. 13, there is shown an embodiment where the elongated base **100** is advantageously used.

- In this embodiment, an integrated solar energy and bicycle providing means **1300**
25 has been installed on the elongated base **100**. It will be appreciated that the integrated solar energy and bicycle providing means **1300** has been installed on the first receiving means **102a** of the elongated base **100**. The skilled addressee will appreciate that the integrated solar energy and bicycle providing means **1300** is of great interest for providing electrical energy as well as for obtaining a bicycle

as further explained below.

The integrated solar energy and bicycle providing means **1300** comprises a base **1306**, an elongated member **1304** and a solar panel assembly **1302** mounted at the top end of the elongated member **1304**. More precisely, it will be appreciated
5 that the integrated solar energy and bicycle providing means **1300** comprises a plurality of batteries **1308**, two batteries shown, located within the base **1306**. In one embodiment, the base **1306** is made using Munzprufer emp860. The skilled addressee will appreciate that various other embodiments are possible. The solar panel assembly **1302** is mounted on a distal end of the elongated member **1304**
10 while the proximal end of the elongated member **1304** is mounted on the base **1306** of the integrated solar energy and bicycle providing means **1300**. The solar panel assembly **1302** is operatively connected to the plurality of batteries **1308** and is used for generating electrical energy using photovoltaic technology.

In one embodiment, the solar panel assembly **1302** is manufactured using
15 SunWize technology (model sc18W – 12v). The skilled addressee will appreciate that various other embodiments may be possible. Still in one embodiment, the plurality of batteries **1308** is manufactured using Enerwatt technology (model WP88-12). The skilled addressee will appreciate that various other embodiments may be possible. In one embodiment, the elongated member **1304** and the base
20 **1306** are made of a rigid material known to the one skilled in the art. It will be appreciated that the integrated solar energy and bicycle providing means **1300** is mounted on the first receiving means **102a** using attaching means (not shown) comprising an electrical connector (not shown) operatively connected thereto. Moreover, it will be appreciated that the bicycle providing means of the integrated
25 solar energy and bicycle providing means **1300** is not shown. The skilled addressee will appreciate that various other embodiments may be possible.

Now referring to Fig. 13A, there is shown another embodiment of a structure comprising the elongated base **100** wherein an energy providing means **1380** has been installed on the elongated base **100**.

30 In this embodiment, the energy providing means **1380** comprises an electrical energy storing unit, an example of which is a plurality of batteries **1384**, two being

shown.

In one embodiment, the plurality of batteries **1384** is manufactured using Enerwatt technology (model WP88-12). The skilled addressee will appreciate that various other embodiments may be possible.

- 5 Still in this embodiment, a cover **1382** is used for selectively accessing the plurality of batteries **1384** of the energy providing means **1380** when required.

In one embodiment, the energy providing means **1380** has a casing made of a rigid material but various other embodiments are possible.

- Now referring to Fig. 14, there is shown an embodiment of a modular system for providing bicycles at a given location, according to a desired configuration.

- More precisely, the modular system comprises a bicycle rack **1402** for storing a bicycle. The bicycle rack **1402** comprises an electronic lock secured thereto for removably securing a corresponding bicycle (not shown). The bicycle rack **1402** further comprises a corresponding attaching means (not shown) having an electrical connector operatively coupled to the electronic lock. The skilled addressee will appreciate that the bicycle rack **1402** has been secured on the second receiving means **102b** of the elongated base **100**. The bicycle rack **1402** and its electronic lock has been disclosed in co-pending US Provisional Patent Application entitled "Method and apparatus for securing a movable item to a structure", having serial number 61/047,162 that was filed on April 23, 2008, the specification of which is hereby incorporated by reference.

- The modular system for providing bicycles at a given location shown in Fig. 14 further comprises the integrated solar energy and bicycle providing means **1300** for providing electrical energy to the electronic lock (not shown) of the bicycle rack **1402**. The integrated solar energy and bicycle providing means **1300** comprises a corresponding attaching means having an electrical connector (not shown) operatively coupled thereto. The integrated solar energy and bicycle providing means **1300** has been secured on the first receiving means **102a** of the elongated base **100** using its attaching means. It will be appreciated that the integrated solar energy and bicycle providing means **1300** further comprises a

user interface **1400** used for controlling the use of the bicycle rack **1402**.

It will be further appreciated that the modular system shown in Fig. 14 further comprises an electric network (not shown) interconnecting each of the plurality of spaced-apart receiving means **102a**, **102b**, **102c**, **102d**, **900a**, **900b**, **900c** and
5 **900d** of the two elongated connected bases. The skilled addressee will therefore appreciate that the integrated solar energy and bicycle providing means **1300** and the bicycle rack **1402** are operatively coupled using the electric network. The electric network is used to distribute electricity to each element coupled to the electric network. The electric network may further be used to share
10 communication data between elements connected to the elongated base. The skilled addressee will appreciate that this is of great advantage since in this embodiment, the modular system does not require any additional source of energy aside the integrated solar energy and bicycle providing means **1300**. In other words, the use of solar energy is of great advantage since it enables a
15 stand-alone use of the system.

Now referring to Fig. 15, there is shown another view of the modular system disclosed in Fig. 14. In this embodiment, there is shown that the bicycle rack **1402** comprises a casing **1501** comprising attaching means **1502**. The bicycle rack **1402** further comprises the electronic lock **1500**, a first molded assembly
20 **1504** and a second molded assembly **1506**.

As shown in Fig. 15, a first connector **1526** (not shown) is used for operatively coupling the integrated solar energy and bicycle providing means **1300** to an electric network; a second connector **1524** is used for operatively coupling the bicycle rack **1402** to the electric network; a third connector **1508** is used for
25 operatively coupling a module secured to the third receiving means **102c** to the electric network. A fourth connector **1510** is used for operatively coupling a module secured to the fourth receiving means **102d** to the electric network; a fifth connector **1512** is used for operatively coupling a module secured to the receiving means **900a**; a sixth connector **1514** is used for operatively coupling a
30 module secured to the receiving means **900b**; a seventh connector **1516** is used for operatively coupling a module secured to the receiving means **900c** and a eighth connector **1518** is used for operatively coupling a module secured to the

receiving means **900d**.

It will be further appreciated that an optional connector **1522** is provided for coupling a neighboring electric network of a neighboring elongated base to the electric network.

- 5 Now referring to Fig. 16, there is shown another embodiment of a modular system for providing bicycles.

In this embodiment, the modular system for providing bicycles comprises the integrated solar energy and bicycle providing means **1300**. The modular system for providing bicycles further comprises six (6) bicycle racks, respectively **1600a**,
10 **1600b**, **1600c**, **1600d**, **1600e**, **1600f**, and an advertisement module **1602**, each being secured to a corresponding receiving means of a plurality of receiving means located on two elongated bases secured together. Each of the plurality of bicycle racks **1600a** to **1600f** is similar to the bicycle rack **1402**.

The skilled addressee will further appreciate that each of the plurality of bicycle
15 racks **1600a** to **1600f** as well as the advertisement module **1602** is operatively connected to the integrated solar energy and bicycle providing means **1300** via the electric network.

Moreover, the skilled addressee will also appreciate that a receiving means cover (not shown) may be used to cover a location where no module is installed.

- 20 As previously mentioned with reference to Fig. 2, first and second end covers **1604** and **1606** are used for sealingly covering each extremity of the assembly.

Now referring to Fig. 17, there is shown how the electric network interconnecting each element mounted on a corresponding one of the plurality of spaced-apart receiving means is installed according to one embodiment.

- 25 More precisely, the electric network **1702** comprises a first optional connector **1700** for connecting the electric network **1702** to the electric network of a neighboring elongated base if required. It will be appreciated by the skilled addressee that the first optional connector **1700** is installed in the wire housing **110** of the elongated base **100**.

The electric network **1702** further comprises a second optional connector **1704** for connecting the electric network **1702** to another electric network of another neighboring elongated base if required. Similarly, it will be appreciated by the skilled addressee that the second optional connector **1704** is located in the wire housing **110** of the elongated base **100**.

The first connector **1526** is used for operatively coupling a module secured to the first receiving means **102a**, while the second connector **1524** is used for operatively coupling a module secured to the second receiving means **102b** and the third connector **1508** is used for operatively coupling a module secured to the third receiving means **102c** and the fourth connector **1510** is used for operatively coupling a module secured to the fourth receiving means **102d**.

It will be appreciated by the skilled addressee that while in the embodiment disclosed in Fig. 17, the first connector **1526**, the second connector **1524**, the third connector **1508**, the fourth connector **1510**, the first optional connector **1700** and the second optional connector **1704** are connected together using a daisy chain configuration, various other embodiments may be provided. In one embodiment, the connectors **1526**, **1524**, **1508**, **1510**, **1700** and **1704** may be connected in a serial configuration while, in another embodiment, they may be connected in a parallel configuration. Moreover, and in a preferred embodiment, the electric network is adapted for providing electricity as well as communication data using the plurality of receiving means.

In one embodiment, each of the second optional connector **1704**, the first connector **1526**, the second connector **1524**, the third connector **1508** and the fourth connector **1510** is installed in a box such as a closed-bottom 2 cable glands provided by Revos. Each box is secured to a corresponding wire housing. Moreover, and in one embodiment, each of the first connector **1526**, the second connector **1524**, the third connector **1508** and the fourth connector **1510** is a female connector provided in one embodiment by Revos (6/6 pole + ground). Still in one embodiment, the first optional connector **1700** comprises a male connector provided in one embodiment by Revos (6/6 pole + ground) while the second optional connector **1704** is a female connector provided in one embodiment by Revos (6/6 pole + ground). The skilled addressee will appreciate that various

other arrangements may be considered.

It will be further appreciated that in one embodiment each connector to be connected to a corresponding connector of the first connector **1526**, the second connector **1524**, the third connector **1508** and the fourth connector **1510**, as well
5 as the first optional connector **1700**, comprises a corresponding male connector provided in this embodiment by Revos (6/6 pole + ground). It will be appreciated that in this embodiment, the connector is embedded in a data cable feed-through with one or two brushings such as the ones provided by Revos. The skilled addressee will appreciate that various other embodiments may be possible.

10 It will be appreciated that the system may receive other types of modules.

For instance, the system may receive a servicing module for using the system, an example of which is a payment module used for renting a bicycle of the system. This module may be used for instance by a user that has not been registered to the system yet. Using this module, the user may perform a payment on the
15 payment module and receive an authorization code that may then be entered at one of the plurality of bicycle racks. In such embodiment, the payment module comprises means for communicating with the at least one bicycle rack. It will be appreciated that the means for communicating with the at least one bicycle rack comprises one of wired means and wireless means. In a preferred embodiment,
20 the means for communicating with the at least one bicycle rack comprises a data network interface operating according to the RS485 or I2C protocol. Still in this embodiment, the system comprises a data network integrated in the electric network interconnecting each of the plurality of spaced-apart receiving means. The data network interface is operatively connected to the data network using an
25 electrical connector. It will also be appreciated that the payment module may comprise means for communicating with a distant server in the case where a credit card or a debit card is used to perform the payment. In a preferred embodiment, the means for communicating to the distant server comprises a wireless communication interface.

30 Another type of module that may be connected to the system is a module for providing a good to a user, an example of which is a vending machine. It will be

appreciated that various types of vending machines may be used such as vending machines for providing snacks, candies, beverages as well as other products to consumers. Subject to local legislations, the module may be used to provide products such as cigarettes and alcohol. In such embodiment, the
5 module for providing a good to a user comprises attaching means having an electrical connector operatively coupled to the module. The module for providing a good to a user is secured to the system by connecting the attaching means to one of the plurality of receiving means located on the elongated base.

A further type of module may be a module for providing information to a user, an
10 example of which is an advertisement module comprising a display device. It will be appreciated that the display device may be of various types such as for instance a plasma display panel or a liquid crystal display (LCD). Alternatively, the display device may comprise a static advertisement panel. The skilled addressee will appreciate that the module for providing information to a user may
15 be of various shapes and configurations depending on an intended use. In such embodiment the module for providing information to a user comprises attaching means having a connector operatively coupled to the module. The module for providing information to a user is secured to the system by connecting the attaching means to one of the plurality of receiving means located on the base
20 according to a desired configuration.

It will be appreciated by the skilled addressee that the modular system disclosed herein is of great advantage since it enables an operator to provide a system for providing bicycles, as well as other services or goods using the above described modules, according to a desired configuration. The desired configuration for a
25 given system may be selected by the operator according to various criteria such as for instance, a number of existing or forecast users for the system, a surrounding environment of the system, an availability of resources such as electricity, environmental considerations such as temperature or the like. Moreover, end-user needs other than the ones related to bicycle *stricto sensu*,
30 may be taken in consideration for determining the desired configuration.

Moreover, the skilled addressee will appreciate that such system is of great advantage since defective components may be easily replaced by operating ones

thanks to its modularity. In such case, the defective components may be fixed later off site. The skilled addressee will appreciate that this is of great advantage for both the operator and the users since it reduces the duration of unplanned downtime operations. The skilled addressee will appreciate that this can translate
5 into a decrease of losses dues to the unplanned downtime operations.

Furthermore, the skilled addressee will appreciate that such system may be of great advantage in the case of non permanent events such as outdoor festivals or outdoor events in general. In such embodiment, such system may be installed at selected places on the site of the event. The location where the system may be
10 installed may be selected depending on various criteria. Moreover, the configuration *per se* of the system may be fully adapted according to various considerations such as ornamental considerations, economic consideration or the like. In particular, it will be appreciated that new modules adapted to a given situation may be added to the system. For instance and as explained above, a
15 vending machine may be operatively connected to the elongated base of the system using one of the receiving means. Alternatively, a ticket distribution booth may be operatively connected to the elongated base of the system using one of the receiving means.

In a further embodiment, the free connecting ends of a structure comprising at
20 least one elongated base may also be used for attaching other types of modules thereto. For example, an upright panel having a bottom part similar to the end covers **1604**, **1606** may be considered for providing additional information space or advertising space.

The skilled addressee will appreciate that in one embodiment an adaptor may be
25 provided for securing future modules to the securing means. The adaptor may be secured to the bottom end of the module to install. The adaptor may comprise an attaching means which is adapted to be secured to the attaching means of a corresponding receiving means of the elongated base as well as connectors if required.

30 Now referring to Figs. 18 and 19, there is shown two different embodiments of an interconnecting element **1800** and **1900** for interconnecting at least two elongated

bases together. Each of these interconnecting elements **1800**, **1900** comprises at least one end suitable for connecting an elongated base thereto. In one embodiment, the end suitable for connecting an elongated base thereto comprises a connecting device **1802** or **1902** adapted for connecting with the connecting device of an elongated base. The connecting device of the
5 interconnecting element **1800** or **1900** may comprise a pair of female connectors or a pair of male connectors as described above.

Now referring to Figs. 20A to 20E, there are shown five different configurations of a modular system for providing bicycles which use at least one of the
10 interconnecting elements shown in Figs. 18 and 19. In Fig. 20A, the configuration comprises two elongated bases **100**, **906** and two interconnecting elements **1800a** and **1800b** shown in Fig. 18 mounted in a U-shaped configuration. In Fig. 20B, the configuration comprises three elongated bases **100**, **906**, **2000** interconnected together with a first interconnecting element **1800** shown in Fig. 18 and a second interconnecting element **1900** shown in Fig. 19. In Fig. 20C, the
15 configuration comprises two elongated bases **100**, **906** connected to each other through an interconnecting element **1900**. In Fig. 20D, the configuration comprises two pairs of elongated bases **100a**, **100b**, **100c**, **100d** mounted face to face, a first interconnecting element **1900a** mounted between the two pairs of elongated bases and a second interconnecting element **1900b** mounted at an end of a pair of elongated bases. In Fig. 20E, the configuration comprises two elongated bases **100**, **906** and an interconnecting element **1900** mounted therebetween. The skilled addressee will appreciate that the interconnecting elements **1800** and **1900** shown in Figs. 18 and 19 may be of great advantage for
20 providing a particular configuration according to specific needs. The skilled addressee will also appreciate that various other configurations may be envisaged for the interconnecting elements. For example, an interconnecting element provided with four sides, each being provided with a corresponding connecting device may be considered for mounting a plurality of bases in a star
25 configuration.
30

Still referring to Figs. 20A to 20E and also to Figs. 18 and 19, the interconnecting elements **1800** and **1900** may be used for attaching additional modules, which is

of great advantage. In one embodiment, the interconnecting element **1800** may be provided with receiving means **1804** adapted for receiving a selected attaching means of a bicycle rack or an energy providing means or any other type of module. In the embodiment illustrated in Fig. 19, two receiving means **1904** are provided for receiving two additional modules (not shown) in a face to face configuration. In the embodiment illustrated in Fig. 18, two receiving means **1804** are provided for mounting a single module in a first orientation or in another orientation perpendicular to the first configuration. The skilled addressee will note that the embodiments of the receiving means illustrated in Figs. 18 and 19 are different from the embodiment of the receiving means illustrated in Fig. 1, even if they may be similar.

As previously mentioned, in a preferred embodiment, the receiving means are adapted for mounting a module thereon in either a first direction or either a second direction opposed to the first direction. This provides additional flexibility to the modular system.

Referring again to Fig. 16, the skilled addressee will appreciate that the structure is substantially flat, which is of great advantage since it enables a user to pass through the structure without requiring getting round the whole system. This is of great advantage in the case a large structure is needed.

The skilled addressee will appreciate that, in a further embodiment, the structure may comprise a set of adjustable leveling screws mounted under the elongated base for enabling a leveling of the structure. This feature is of great advantage in the case the structure is installed on an inclined surface.

Now referring to Fig. 21, there is shown a flow chart of a method for installing a modular system for providing bicycles at a given location according to a desired configuration.

According to step **2100**, an elongated base comprising a plurality of spaced-apart receiving means is provided.

According to step **2102**, the elongated base is laid down at the given location.

According to step **2104**, at least one bicycle rack for storing a bicycle is provided. Each of the bicycle rack comprises an electronic lock secured thereto for removably securing a corresponding bicycle.

5 According to step **2106**, an energy providing means is provided for providing energy.

According to step **2108**, each of the at least one bicycle rack and the energy providing means is attached in a corresponding one of the spaced-apart receiving means of the elongated base.

10 According to step **2110**, each of the at least one bicycle rack and the energy providing means are electrically interconnected together.

In a further embodiment of the method for installing a modular system as previously described, at least one additional elongated base comprising a plurality of spaced-apart receiving means is provided. Each of the additional elongated bases is laid down at the given location proximate the elongated base.

15 The first additional elongated base is operatively connected to an end of the elongated base and the remaining additional elongated bases are connected to a free end of one of the elongated bases. The skilled addressee will appreciate that the interconnecting elements shown in Figs. 18 and 19 may be used for installing the modular system according to a specific configuration.

20 As previously mentioned, in one embodiment, the given location is selected from a group consisting of a sidewalk, a portion of a street, a parking lot, a park, a beach and a substantially horizontal surface. The skilled addressee will appreciate that various other locations may be considered.

In a further embodiment of the method, the desired configuration comprises an initial predetermined configuration defined according to an intended use. The method comprises the step of monitoring use of the bicycles for providing current usage information based on the initial predetermined configuration. An optimal configuration for the modular system is then defined based on the current usage information, the optimal configuration comprising an optimal number of the

25 bicycles and the associated bicycle racks and a corresponding number of

30

elongated bases. According to this embodiment, the modular system is then configured according to the optimal configuration.

The above mentioned step of configuring according to the optimal configuration comprises providing the corresponding number of elongated bases; laying down
5 the corresponding number of elongated bases at the given location; operatively connecting each of the corresponding number of elongated bases together; providing the optimal number of the bicycles and the associated bicycle racks; attaching each of the optimal number of bicycle racks in a corresponding one of
10 the spaced-apart receiving means of a corresponding one of the elongated bases; and electrically interconnecting each of the optimal number of bicycle racks and the energy providing means together.

In one embodiment, the current usage information comprises a bicycle occupation rate associated with each of the bicycles. The skilled addressee will appreciate that various other parameters may be taken into consideration for
15 defining the optimal configuration.

Now referring to Fig. 22, there is shown a flow chart of a method for providing bicycles at a given location according to a desired configuration.

According to step **2200**, a modular system, as previously described, is provided.

According to step **2202**, the modular system is installed at the given location
20 according to the desired configuration.

According to step **2204**, communication between the system and a user is established for defining a user request.

According to step **2206**, a corresponding bicycle is provided to the user according to the user request.

25 According to step **2208**, the corresponding bicycle is collected from the user after use.

In one embodiment, the collecting is performed at another location provided with another modular system, which is of great advantage for a user.

In another embodiment, the providing of a corresponding bicycle is done for a fee, as it will be more detailed thereafter.

Now referring to Fig. 23, there is shown a flow chart of a method of doing business in providing bicycles at a given location according to a desired configuration.

According to step 2300, a third party is provided by a provider with a modular system as previously described.

According to step 2302, the modular system is operated by a third party for a fee.

According to step 2304, the third party reconveys a portion of the fee to the provider.

In one embodiment, the fee is determined according to an occupation rate associated to each of the corresponding bicycles:

It will be appreciated that the system described herein may be operated by the owner of the system. Alternatively, the system may be operated by a third party for a fee. In one embodiment, the fee may be a share of the revenues while in an alternative embodiment, the fee may comprise a fixed fees. It will be appreciated by the skilled addressee that such system may be used in two separate geographic locations depending on weather conditions. For instance, the system may be installed at a first location during a first part of the year while it is then installed to a second location during a second part of the year. The skilled addressee will appreciate that this is of great advantage since it helps maximizing the revenues originating from the system.

Moreover, it will be further appreciated that the system may be easily upgraded since it is modular. For instance, the design of the bicycle rack may be upgraded easily and this does not require changing the whole system, which is of great advantage. In particular, the design of the bicycle rack may be different depending on a location where the system is provided.

Moreover, the modular system may be installed at any particular location without requiring complex installation steps such as providing anchoring holes in the

ground. Indeed, as explained above, in a preferred embodiment, the structure and the bicycle racks are made of a rigid and heavy material such as steel for providing to the system an appropriate weight that provides sufficient stability to the system. In others words, the system remains in place under the gravity effect
5 without any ground anchoring.

Although the above description relates to a specific preferred embodiment as presently contemplated by the inventor, it will be understood that the invention in its broad aspect includes mechanical and functional equivalents of the elements described herein.

WHAT IS CLAIMED IS:

1. A modular system for providing bicycles at a given location according to a desired configuration, the modular system comprising:

at least one bicycle rack for storing a bicycle, each of said at least one bicycle rack comprising an electronic lock secured thereto for removably securing a corresponding bicycle, each of the at least one bicycle rack further comprising a corresponding attaching means having an electrical connector operatively coupled to the electronic lock;

an energy providing means for providing energy to each electronic lock of the at least one bicycle rack, the energy providing means comprising a corresponding attaching means having an electrical connector operatively coupled thereto; and

a structure to be installed at said given location, the structure comprising:

an elongated base;

a plurality of spaced-apart receiving means located on said elongated base, each of the plurality of spaced-apart receiving means being adapted for receiving any one of the attaching means of the at least one bicycle rack and the attaching means of the energy providing means according to the desired configuration; and

an electric network interconnecting each of the plurality of spaced-apart receiving means to thereby providing a modular system for providing bicycles.

2. The modular system as claimed in claim 1, wherein said elongated base comprises a sheet of rigid material having a first outer planar surface, a second outer planar surface and a third central planar surface extending therebetween, each of said receiving means extending on the central planar surface in an aligned configuration.

3. The modular system as claimed in any one of claims 1 to 2, wherein said elongated base comprises at least one end suitable for connecting a neighboring elongated base thereto.

4. The modular system as claimed in any one of claims 1 to 2, wherein said elongated base comprises a first end and a second end, each being suitable for connecting a corresponding neighboring elongated base thereto, said first end comprising a first connecting device and said second end comprising a second connecting device, said first connecting device being adapted for connecting with the corresponding second connecting device of said neighboring elongated base.

5. The modular system as claimed in claim 4, wherein a corresponding one of said first and second connecting devices of said elongated base comprises a securing device cooperating with the corresponding connecting device of the corresponding end of said neighboring elongated base for securing said elongated base and said neighboring elongated base together.

6. The modular system as claimed in claim 5, wherein said first connecting device comprises at least one male connector projecting horizontally and comprising a hole extending upwardly, and wherein said second connecting device comprises at least one corresponding female connector projecting horizontally and comprising a corresponding hole extending upwardly, each hole of two corresponding connecting devices extending in an aligned configuration when connected together for providing a screw passage, said securing element comprising a corresponding bore extending through the elongated base and a screw adapted for insertion in said screw passage through the bore of the elongated base.

7. The modular system as claimed in claim 6, wherein said first connecting device comprises an additional male connector and said second connecting device comprises an additional female connector, said securing element further comprising an additional corresponding bore extending through the elongated base and an additional screw.

8. The modular system as claimed in claim 4, wherein each of said first connecting device and said second connecting device comprises a corresponding complementary cooperating connecting member.

9. The modular system as claimed in any one of claims 1 to 8, wherein said structure comprises a wire housing mounted under said elongated base and extending therealong for receiving at least a portion of said electric network.

10. The modular system as claimed in any one of claims 1 to 9, wherein each of said receiving means of said structure comprises an attaching device adapted for cooperating with a corresponding one of the attaching means of the at least one bicycle rack and the energy providing means.

11. The modular system as claimed in claim 10, wherein said attaching device of each of said receiving means comprises a plurality of holes, each of said attaching means of said at least one bicycle rack and said energy providing means comprising a plurality of corresponding holes and a plurality of corresponding screws for screwing said attaching means to a corresponding attaching device of said receiving means.

12. The modular system as claimed in claim 11, wherein the plurality of holes of each of said attaching means of said at least one bicycle rack and said energy providing means and the plurality of holes of said attaching device of each of said receiving means are arranged in a symmetrical configuration adapted for enabling an attaching of said at least one bicycle rack and said energy providing means in a first direction and in an second opposed direction.

13. The modular system as claimed in any one of claims 1 to 12, wherein said energy providing means comprise a solar energy providing means.

14. The modular system as claimed in claim 13, wherein said energy providing means comprise a base provided with said attaching means, an elongated member mounted on said base and a solar panel assembly mounted on said elongated member.

15. The modular system as claimed in claim 14, wherein said energy providing means further comprise a plurality of batteries mounted with said base and operatively connected to said solar panel assembly.

16. The modular system as claimed in any one of claims 1 to 15, further comprising a bicycle providing means interconnected to the electric network for managing a providing of a corresponding bicycle to a user.

17. The modular system as claimed in claim 16, wherein said bicycle providing means comprises a user interface for establishing communication between said system and a user, said bicycle providing means further comprising a control unit for controlling the electronic lock of said at least one bicycle rack according to a user request.

18. The modular system as claimed in any one of claims 16 to 17, wherein said bicycle providing means is integrated with said energy providing means.

19. The modular system as claimed in any one of claims 1 to 18, further comprising a servicing module having a corresponding attaching means for attaching said servicing module in a corresponding one of said receiving means, said servicing module being selected from a group comprising an advertising module, a vending machine, a ticket distribution booth and a payment module for renting at least a corresponding one of said bicycles.

20. The modular system as claimed in claim 19, wherein said servicing module comprises a payment module comprising means for communicating with a distant server.

21. The modular system as claimed in any one of claims 1 to 20, wherein said electric network comprises a plurality of network connectors, each being provided proximate to a corresponding receiving means of said elongated base for connecting with a corresponding connector of the at least one bicycle rack and the energy providing means, said electric network further comprising at least one additional end connector mounted at an end thereof for coupling a neighboring electric network.

22. The modular system as claimed in any one of claims 1 to 21, wherein the electric network interconnecting each of the plurality of spaced-apart receiving means comprises a configuration selected from a group consisting of a parallel configuration and a serial configuration.

23. The modular system as claimed in any one of claims 1 to 22, wherein said structure further comprises a set of leveling screws mounted under the elongated base for enabling a leveling of the structure.

24. The modular system as claimed in claim 4, wherein said structure further comprises at least one ending element securable to a respective end of said elongated base, said ending element being selected from a group consisting of an end covering for covering the corresponding connecting device and an upright panel.

25. A method for installing a modular system for providing bicycles at a given location according to a desired configuration, said method comprising:

providing an elongated base comprising a plurality of spaced-apart receiving means;

laying down said elongated base at said given location;

providing at least one bicycle rack for storing a bicycle, each of said at least one bicycle rack comprising an electronic lock secured thereto for removably securing a corresponding bicycle;

providing an energy providing means for providing energy;

attaching each of said at least one bicycle rack and said energy providing means in any one of said spaced-apart receiving means of said elongated base such that said at least one bicycle rack and said energy providing means are electrically interconnected together.

26. The method as claimed in claim 25, further comprising:

providing at least one additional elongated base comprising a plurality of spaced-apart receiving means;

laying down said at least one additional elongated base at said given location proximate said elongated base; and

operatively connecting said at least one additional elongated base at an end of said elongated base.

27. The method as claimed in any one of claims 25 to 26, wherein said given location is selected from a group consisting of a sidewalk, a portion of a street, a parking lot, a park, a beach and a substantially horizontal surface.

28. The method as claimed in any one of claims 25 to 27, wherein said desired configuration comprises an initial predetermined configuration defined according to an intended use, said method further comprising:

monitoring use of said bicycles for providing current usage information based on said initial predetermined configuration;

defining an optimal configuration for said modular system based on said current usage information, said optimal configuration comprising an optimal number of said bicycles and said associated bicycle racks and a corresponding number of elongated bases; and

configuring the modular system according to said optimal configuration, said configuring comprising:

providing said corresponding number of elongated bases;

laying down said corresponding number of elongated bases at said given location;

operatively connecting each of said corresponding number of elongated bases together;

providing said optimal number of said bicycles and said associated bicycle racks;

attaching each of said optimal number of bicycle racks in a corresponding one of said spaced-apart receiving means of a corresponding one of said elongated base such that said optimal number of bicycle racks and said energy providing means are electrically interconnected together.

29. The method as claimed in claim 28, wherein said current usage information comprises a bicycle occupation rate associated with each of said bicycles.