

(51) International Patent Classification:
H01L 21/66 (2006.01)

(21) International Application Number:

PCT/US2011/042850

(22) International Filing Date:

1 July 2011 (01.07.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/361,800	6 July 2010 (06.07.2010)	US
13/172,001	29 June 2011 (29.06.2011)	US

(71) Applicant (for all designated States except US): **FORM-FACTOR, INC.** [US/US]; FormFactor, Inc., 7005 SouthFront Road, Livermore, CA 94551 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ELDRIDGE, Benjamin, N.** [US/US]; 7005 SouthFront Road, Livermore, CA 94551 (US).(74) Agent: **BURRSTON, N., Kenneth**; Kirton & McConkie, 60 East South Temple, Suite 1800, Salt Lake City, UT 84111 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) Title: TESTING TECHNIQUES FOR THROUGH-DEVICE VIAS

Figure 1



(57) Abstract: Techniques for testing an electronic device with through-device vias can include using a probe card assembly with probes for contacting connection structures of the electronic device including ends of through-device vias of the electronic device. A pair of the probes can be electrically connected in the probe card assembly and can thus contact and form a direct return loop from one through-device via to another through-device via of a pair of the through-device vias with which the pair of probes is in contact. The electronic device can include test circuitry for driving a test signal onto the one of the through-device vias and a receiver for detecting the test signal on the other of the through-device vias.



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:
26 April 2012