

- 1 -

APPARATUSES AND METHODS FOR USE IN CREATING AN AUDIO SCENE

FIELD OF THE INVENTION

5 The present invention relates generally to
apparatuses and methods for use in creating an audio scene,
and has particular - but by no means exclusive -
application for use in creating an audio scene for a
virtual environment.

10

BACKGROUND OF THE INVENTION

 There have been significant advances in creating
visually immersive virtual environments in recent years.
15 These advances have resulted in the widespread uptake of
massively multi-player role-playing games, in which
participants can enter a common virtual environment (such
as a battlefield) and are represented in the virtual
environment by an avatar, which is typically in the form of
20 an animated character. In the case of a virtual
environment in the form of a battle field that avatar could
be of a soldier.

 The widespread uptake of visually immersive
25 virtual environments is due in part to significant advances
in image processing technology that enables highly detailed
and realistic graphics virtual environment to be generated.
The proliferation of three-dimensional sound cards provides
the ability to supply participants in a virtual environment
30 with high quality sound. However, despite the prolific use
of three-dimensional sound cards today's visually immersive
virtual environments are generally unable to provide
realistic mechanisms for participants to communicate with
each other. Many environments use non-immersive
35 communication mechanisms such as text based chat or walkie-
talkie style voice.

- 2 -

DEFINITIONS

5 The following provides definitions for various terms used throughout this specification:

- Weighted audio stream - audio information that comprises one or more pieces of audio information, each of which
10 has an amplitude that is modified (increased or decreased) based on a distance between a source and recipient of the audio information.
- Unweighted audio stream - audio information that
15 comprises one or more pieces of audio information, but unlike a weighted audio stream the amplitude of each piece of audio information in an unweighted audio stream is un-modified from the original amplitude.
- Audio Scene - audio information comprising combined
20 sounds (for example, voices belonging to other avatars and other sources of sound within the virtual environment) that are spatially placed and perhaps attenuated according to a distance between a source and
25 recipient of the sound. An audio scene may also comprise sound effects that represent the acoustic characteristics of the environment.

SUMMARY OF THE INVENTION

30

According to a first aspect of the present invention there is provided an apparatus for creating an audio scene for an avatar in a virtual environment, the apparatus comprising:

35

an audio processor operable to create a weighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and

- 3 -

associating means operable to associate the weighted audio stream with a datum that represents a location of the portion of the hearing range in the virtual environment, wherein the weighted audio stream and the
5 datum represent the audio scene.

The apparatus according to the first aspect of the present invention has several advantages. One advantage is that by dividing the hearing range in to one
10 or more portions, the fidelity of the audio scene can be adjusted to a required level. The greater the number of portions in the hearing range, the higher the fidelity of the audio scene. It is envisaged that the apparatus is not restricted to a single weighted audio stream for one
15 portion. In fact, the apparatus is capable of multiple weighted audio streams each comprising audio from an object located in other portions of the hearing range. Another advantage of the apparatus is that the weighted audio stream can replicate characteristics such as attenuation of
20 the audio as a result of having to travel a distance between the object and the recipient. Yet another advantage of the present invention is that the audio stream can be reproduced as if it emanated from the location. Thus, if the datum indicated that the location of the object was to
25 the right hand side of the recipient, the audio could be reproduced using the right channel of a stereo sound system.

Preferably, the audio processor is further
30 operable to create the weighted audio stream such that it comprises an unweighted audio stream that comprises audio from another object located in the portion of the hearing range of the avatar.

35 An advantage of including the unweighted audio stream in the weighted audio stream is that it provides a means for representing audio from one or more other objects

- 4 -

that are located at the periphery of the portion of the hearing range of the avatar. An advantage of the unweighted audio stream is that it can be reused for creating audio scenes of many avatars, which can reduce the overall
5 processing requirements for creating the audio scene.

Preferably, the audio processor is operable to create the weighted audio stream in accordance with a predetermined mixing operation, the predetermined mixing
10 operation comprising identification information that identifies the object and/or the other objects, and weighting information that can be used by the audio processor to set an amplitude of the audio and unweighted audio stream in the weighted audio stream.

15 Preferably, the apparatus further comprises a communication means operable to receive the audio, the unweighted audio stream and the mixing operation via a communication network, the communication means further
20 being operable to send the weighted audio stream and the datum via the communication network.

Using the communication means is advantageous because it enables the apparatus to be used in a
25 distributed environment.

According to a second aspect of the present invention, there is provided an apparatus operable to create audio information for use in an audio scene for an
30 avatar in a virtual environment, the apparatus comprising:
an audio processor operable to create an unweighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and
associating means operable to associate the
35 unweighted audio stream with a datum that represents an approximate location of the object in the virtual environment, wherein the unweighted audio stream and the

- 5 -

datum represent the audio information.

5 The apparatus according to the second aspect of the present invention has several advantages, two of which are similar to the aforementioned first and second advantages of the first aspect of the present invention.

10 Preferably, the audio processor is operable to create the unweighted audio stream in accordance with a predetermined mixing operation, the predetermined mixing operation comprising identification information that identifies the object.

15 Preferably, the apparatus further comprises a communication means operable to receive the audio and the predetermined mixing operation via a communication network, the communication means also being operable to send the unweighted audio stream and the datum via the communication network.

20

 Using the communication means is advantageous because it enables the apparatus to be used in a distributed environment.

25 According to a third aspect of the present invention there is provided an apparatus for obtaining information that can be used to create an audio scene for an avatar in a virtual environment, the apparatus comprising:

30 identifying means operable to determine an identifier of an object located in a portion of a hearing range of the avatar;

 weighting means operable to determine a weighting to be applied to audio from the object; and

35 locating means operable to determine a location of the portion in the virtual environment, wherein the identifier, weighting and the location represent the

- 6 -

information that can be used to create the audio scene.

The ability of the third aspect of the present invention to obtain the weighting and the location is
5 advantageous for several reasons. First, the weighting can be used to create a weighted audio stream that comprises the audio from the object. In this regard, the weighting can be used to set an amplitude of the audio when inserted into the weighted audio stream. Second, the location can be
10 used to reproduce the audio as if it were coming from the location. For example, if the location indicated that the location of the object was to the right hand side of the recipient, the audio could be reproduced using the right channel of a stereo sound system.

15 Preferably, the apparatus further comprises a communication means operable to send, via a communication network, the identifier, the weighting and the location to one of a plurality of systems for processing.

20 Using the communication means is advantageous because it enables the apparatus to be used in a distributed environment. Furthermore, it enables the apparatus to send the identifier, the weighting and the
25 location to a system that has the necessary resources (processing ability) to perform the required processing.

Preferably, the communication means is further operable to create routeing information for the
30 communication network, wherein the routeing information is such that it can be used by the communication network to route the audio to the one of the plurality of system for processing.

35 Being able to provide the routeing information is advantageous because it allows the apparatus to effectively select the links in the communications network that will be

- 7 -

used to transfer the audio.

Preferably, the identifying means, the weighting means and the locating means are operable to respectively
5 determine the identifier, the weighting and the location by processing a representation of the virtue environment.

Preferably, the identifying means is operable to determine the portion of the hearing range by:

- 10 selecting a first of a plurality of avatars in the virtual environment;
- identifying a second of the plurality of avatars that is proximate the first of the avatars;
- determining whether the second of the avatars can
15 be included in an existing cluster;
- including the second of the avatars in the existing cluster upon determining that it can be included therein;
- creating a new cluster that includes the second
20 of the avatars upon determining that the second of the avatars cannot be included in the existing cluster to thereby create a plurality of clusters;
- determining an angular gap between two of the clusters;
- 25 creating a further cluster that is substantially located in the angular gap; and
- including at least one of the avatars in the further cluster.

30 Alternatively, the identifying means is operable to determined the portion of the hearing range by:

- selecting one of a plurality of avatars in the virtual environment;
- determining a radial ray that extends from the
35 avatar to the one of the plurality of avatars;
- calculating the absolute angular distance that each of the plurality of avatars is from the radial ray;

- 8 -

arranging the absolute angular distance of each of the avatars into an ascending ordered list;

calculating a differential angular separation between successive ones of the absolute angular distance in
5 the ascending ordered list;

selecting at least one of the differential angular separation that has a higher value than another differential angular separation; and

determining another radial ray that emanates from
10 the avatar and which bisects two of the avatars that are associated with the at least one of the differential angular separation.

According to a fourth aspect of the present
15 invention there is provided an apparatus for creating information that can be used to create an audio scene for an avatar in a virtual environment, the apparatus comprising:

identifying means operable to determine an
20 identifier of an object located in a portion of a hearing range of the avatar; and

locating means operable to determine an approximate location of the object in the virtual environment, wherein the identifier and the approximate
25 location represent the information that can be used to create the audio scene.

Determining the approximate location of the object is advantageous because it can be used to reproduce
30 audio from the object as if it were emanating from the location.

Preferably, the apparatus further comprises a communication means operable to send, via a communication
35 network, the identifier and the location to one of a plurality of systems for processing.

- 9 -

Using the communication means is advantageous because it enables the apparatus to be used in a distributed environment. Furthermore, it enables the apparatus to send the identifier, the weighting and the location to a system that has the necessary resources (processing ability) to perform the required processing.

Preferably, the communication means is further operable to create routeing information for the communication network, wherein the routeing information is such that it can be used by the communication network to route the audio to the one of the plurality of systems for processing.

Being able to provide the routeing information is advantageous because it allows the apparatus to effectively select the links in the communication network that will be used to transfer the audio.

Preferably, the identifying means and the locating means are operable to respectively determine the identifier and the location by processing a representation of the virtual environment.

Preferably, the identifying means is operable to determine the approximate location of the object by:
dividing the virtual environment into a plurality of cells; and
determining a location in one of the cells about which the object is located.

According to a fifth aspect of the present invention there is provided an apparatus for rendering an audio scene for an avatar in a virtual environment, the apparatus comprising:

obtaining means operable to obtain a weighted audio stream that comprises audio from an object located in

- 10 -

a portion of a hearing range of the avatar, and a datum that is associated with the weighted audio stream and which represents a location of the portion of the hearing range in the virtual environment; and

5 a spatial audio rendering engine that is operable to process the weighted audio stream and the datum in order to render the audio scene.

10 According to a sixth aspect of the present invention there is provided a method of creating an audio scene for an avatar in a virtual environment, the method comprising the steps of:

15 creating a weighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and

20 associating the weighted audio stream with a datum that represents a location of the portion of the hearing range in the virtual environment, wherein the weighted audio stream and the datum represent the audio scene.

25 Preferably, the step of creating the weighted audio stream is such that the weighted audio stream comprises an unweighted audio stream that comprises audio from another object located in the portion of the hearing range of the avatar.

30 Preferably, the step of creating the weighted audio stream is carried out in accordance with a predetermined mixing operation, the predetermined mixing operation comprising identification information that identifies the object and/or the other objects, and weighting information that can be used by the audio processor to set an amplitude of the audio and unweighted
35 audio stream in the weighted audio stream.

Preferably, the method further comprises the

- 11 -

steps of:

receiving the audio, the unweighted audio stream
and the mixing operation via a communication network; and
sending the weighted audio stream and the datum
5 via the communication network.

According to a seventh aspect of the present
invention, there is provided a method of creating audio
information for use in an audio scene for an avatar in a
10 virtual environment, the method comprising the steps of:
creating an unweighted audio stream that
comprises audio from an object located in a portion of a
hearing range of the avatar; and
associating the unweighted audio stream with a
15 datum that represents an approximate location of the object
in the virtual environment, wherein the unweighted audio
stream and the datum represent the audio information.

Preferably, the step of creating the unweighted
20 audio stream is carried out in accordance with a
predetermined mixing operation, wherein the predetermined
mixing operation comprises identification information that
identifies the object.

Preferably, the method further comprises the
25 steps of:
receiving the audio and the predetermined mixing
operation via a communication network; and
sending the unweighted audio stream and the datum
30 via the communication network.

According to a eighth aspect of the present
invention there is provided a method of obtaining
information that can be used to create an audio scene for
35 an avatar in a virtual environment, the method comprising
the steps of:
determining an identifier of an object located in

- 12 -

a portion of a hearing range of the avatar;

determining a weighting to be applied to audio from the object; and

5 determining a location of the portion in the virtual environment, wherein the identifier, weighting and the location represent the information that can be used to create an audio scene.

10 Preferably, the method further comprises the step of sending, via a communication network, the identifier, the weighting and the location to one of a plurality of systems for processing.

15 Preferably, the method further comprises the step of creating routeing information for the communication network, wherein the routeing information is such that it can be used by the communication network to route the audio to the one of the plurality of system for processing.

20 Preferably, the steps of determining the identifier, the weighting and the location respectively comprise determining the identifier, the weighting and the location by processing a representation of the virtual environment.

25

Preferably, the method further comprises the following steps to determine the portion of the hearing range:

30 selecting a first of a plurality of avatars in the virtual environment;

identifying a second of the plurality of avatars that is proximate the first of the avatars;

determining whether the second of the avatars can be included in an existing cluster;

35 including the second of the avatars in the existing cluster upon determining that it can be included therein;

- 13 -

creating a new cluster that includes the second of the avatars upon determining that the second of the avatars cannot be included in the existing cluster to thereby create a plurality of clusters;

5 determining an angular gap between two of the clusters;

 creating a further cluster that is located in the angular gap; and

10 including at least one of the avatars in the further cluster.

Alternatively, the method comprises the following steps to determine the position of the hearing range:

15 selecting one of a plurality of avatars in the virtual environment;

 determining a radial ray that extends from the avatar to the one of the plurality of avatars;

 calculating the absolute angular distance that each of the plurality of avatars is from the radial ray;

20 arranging the absolute angular distance of each of the avatars into an ascending ordered list;

 calculating a differential angular separation between successive ones of the absolute angular distance in the ascending ordered list; and

25 selecting at least one of the differential angular separation that has a higher value than another differential angular separation; and

30 determining another radial ray that emanates from the avatar and which bisects two of the avatars that are associated with the differential angular separation.

According to a ninth aspect of the present invention there is provided a method of creating information that can be used to create an audio scene for
35 an avatar in a virtual environment, the method comprising the steps of:

 determining an identifier of an object located in

- 14 -

a portion of a hearing range of the avatar; and
determining an approximate location of the object
in the virtual environment, wherein the identifier and the
approximate location represent the information that can be
5 used to create the audio scene.

Preferably, the method further comprises the step
of sending, via a communication network, the identifier and
the location to one of a plurality of systems for
10 processing.

Preferably, the method further comprises the step
of creating routeing information for the communication
network, wherein the routeing information is such that it
15 can be used by the communication network to route the audio
to the one of the plurality of systems for processing.

Preferably, the steps of determining the
identifier and the approximate location respectively
20 comprise the step of determining the identifier and the
location by processing a representation of the virtual
environment.

Preferably, the method further comprises the
25 following steps to determine the approximate location of
the object:

dividing the virtual environment into a plurality
of cells; and

determining a location in one of the cells about
30 which the object is located.

According to a tenth aspect of the present
invention there is provided a method of rendering an audio
scene for an avatar in a virtual environment, the method
35 comprising the steps of:

obtaining a weighted audio stream that comprises
audio from an object located in a portion of a hearing

- 15 -

range of the avatar, and a datum that is associated with the weighted audio stream and which represents a location of the portion of the hearing range in the virtual environment; and

5 processing the weighted audio stream and the datum in order to render the audio scene.

 According to an eleventh aspect of the present invention there is provided a computer program comprising
10 at least one instruction for causing a computing device to carry out the method according to the sixth, seventh, eighth, ninth or tenth aspect of the present invention.

 According to a twelfth aspect of the present invention there is provided a computer readable medium
15 comprising the computer program according to the eleventh aspect of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

20

 Notwithstanding any other embodiments that may fall within the scope of the present invention, an embodiment of the present invention will now be described, by way of example only, with reference to the accompanying
25 figures, in which:

 figure 1 provides a block diagram of a system in accordance with the embodiment of the present invention;

30 figure 2 provides a flow chart of various steps performed by the system shown in figure 1;

 figure 3 provides a flow chart of the steps involved in a grid summarisation algorithm used in the
35 system shown in figure 1;

 figure 4 illustrates a map used by the system

- 16 -

shown in figure 1;

figure 5 illustrates a control table used by the system shown in figure 1;

5

figure 6 provides a flow chart of the steps involved in a cluster summarisation algorithm used in the system shown in figure 1;

10

figure 7 is an illustration of the clusters formed using the algorithm of figure 6;

figure 8 is a flow chart of the various steps involved in an alternative clustering algorithm;

15

figure 9 provides a visual depiction of the result of running the alternative clustering algorithm of figure 8 on the map shown in figure 4;

20

figure 10 illustrates another control table used by the system shown in figure 1;

figure 11 provides a flow chart of the steps involved in a process performed by the system shown in figure 1;

25

figure 12 provides a flow chart of the steps involved in a process performed by the system shown in figure 1.

30

AN EMBODIMENT OF THE INVENTION

With reference to figure 1, which illustrates a system 101 embodying the present invention, the system 101 comprises: an audio scene creation system 103; a virtual environment state maintenance system 105; and a client computing device 107. The system 101 also comprises a

35

- 17 -

communication network 109. The audio scene creation system 103, the virtual environment state maintenance system 105 and the client computing device 107 are connected to the communication network 109 and arranged to use the network
5 109 in order to operate in a distributed manner; that is, exchange information with each other via the communication network 109. The communication network 109 is in the form of a public access packet switched network such as the Internet, and is therefore made up of numerous interconnect
10 routers (not shown in the figures).

Generally speaking, the virtual environment state maintenance system 105 is arranged to maintain dynamic state information pertaining to a virtual environment (such
15 as a battlefield). The dynamic state information maintained by the system 105 includes, for example, the location of various avatars in the virtual environment and, where the virtual environment relates to a game, individual players' scores. The audio scene creation system 103 is basically
20 arranged to create and manage the real-time audio related aspects of participants in the virtual environment (such as the participants voice); that is, create and manage audio scenes. The client computing device 107 is essentially
25 arranged to interact with the virtual environment state maintenance system 105 and the audio scene creation system 103 to allow a person using the client computing device 107 to participate in the virtual environment.

More specifically, the graphical environment
30 state maintenance system 105 is in the form of a computer server (or in an alternative embodiment, a plurality of distributed computer servers interconnected to each other) that comprises traditional computer hardware such as a motherboard, hard disk storage, and random access memory.
35 In addition to the hardware the computer server also comprises an operating system (such as Linux or Microsoft Windows) that performs various system level operations (for

- 18 -

example, memory management). The operating system also provides an environment for executing application software. In this regard, the computer server comprises an application package that is loaded on the hard disk storage and which is capable of maintaining the dynamic state information pertaining to the virtual environment. In this regard, if the virtual environment was, for example, a battlefield then the dynamic state information may indicate that a particular avatar (which, for example, represents a soldier) is situated in a tank. The virtual environment state maintenance system 105 essentially comprises two modules 111 and 113 in the form of software. The first of the modules 111 is essentially responsible for sending and receiving the dynamic state information (pertaining to the virtual environment) to/from the client computing device 107. The second of modules 113 is arranged to send the dynamic state information to the audio scene creation system 103.

As mentioned previously, the audio scene creation system 103 is basically arranged to create and manage audio scenes. Each audio scene basically represents a realistic reproduction of the sounds that would be heard by an avatar in the virtual environment. In order to create the audio scenes, the audio scene creation system 103 comprises a control server 115, a summarisation server 117 (alternative embodiments of the present invention may include a plurality of distributed summarisation servers), and a plurality of distributed scene creation servers 119. The control server 115, the summarisation server 117 and the plurality of distributed scene creation servers 119 are connected to the communication network 109 and use the communication network 109 to cooperate with each other in a distributed fashion.

The control server 115 is in the form of a computer server that comprises traditional computer

- 19 -

hardware such as a motherboard, hard disk storage, and random access memory. In addition to the hardware the computer server also comprises an operating system (such as Linux or Microsoft Windows) that performs various system level operations. The operating system also provides an environment for executing application software. In this regard, the computer server comprises application software that is loaded on the hard disk storage and which is arranged to carry out the various steps of the flow chart 201 shown in figure 2. The first step 203 that the application software performs is to interact with the virtual environment state maintenance system 105 to obtain the dynamic state information pertaining to the virtual environment. The application software obtains and processes the dynamic state information in order to identify the various avatars present in the virtual environment and the location of the avatars in the virtual environment. The virtual environment state maintenance system 105 can also process the dynamic state information to obtain details of the status of the avatars (for example, active or inactive) and details of any sound barriers. To obtain the dynamic state information the application software of the control server 115 interacts with the second of the modules 113 in the virtual environment state maintenance system 105 via the communication network 109.

Once the application software of the control server 115 has obtained the dynamic state information from the virtual environment state maintenance system 105, it proceeds to process the dynamic state information in order to create a number of mixing operation that are processed by the summarisation server 117 and scene creation servers 119 in order to create audio scenes for each avatar in the virtual environment. Following on from the initial step 203 the control server 115 performs the step 205 of running a grid summarisation algorithm. With reference to figure 3,

- 20 -

which shows a flow chart 301 of the grid summarisation algorithm, the first step 303 of the grid summarisation algorithm is to use the dynamic state information obtained during the initial step 203 to form a map 401, which can be
5 seen in figure 4, of the virtual environment. The map 401 is divided into a plurality of cells and depicts the location of the avatars in the virtual environment. The map 401 depicts the avatars as the small black dots. Whilst the present embodiment includes only a single map 401, it
10 is envisaged that multiple maps 401 could be employed in alternative embodiments of the present invention.

It is noted that each avatar in the virtual environment is considered to have a hearing range that is
15 divided into an interactive zone and a background zone. The interactive zone is generally considered the section of the hearing range immediately surrounding the avatar, whilst the background zone is the section of the hearing range that is located around the periphery (outer limits) of the
20 hearing range. As an example, the interactive zone of a hearing range of an avatar is shown in figure 4 as a circle surrounding the avatar.

In forming the map 401, the application software
25 of the control server 115 ensures that the size of each cell is greater than or equal to the interactive zone of the avatars.

The next step 305 performed when carrying out the
30 grid summarisation algorithm is to determine a 'centre of mass' of each of the cells in the map 401. The centre of mass is basically determined by identifying the point in each cell around which the avatars therein are centred. The centre of mass can be considered an approximate location of
35 the avatars in the virtual environment. The final step 307 in the grid summarisation algorithm is to update a control table 501 (which is shown in figure 5) used by the

- 21 -

summarisation server 117 based on the map 401. The control table 501 comprises a plurality of rows, each of which represents one of the cells in the map 401. Each row also contains an identifier of each avatar in the respective
5 cell and the centre of mass thereof. Each row in the control table 501 can effectively be considered a unweighted mixing operation. In order to update the control table 501 the application software of the control server 115, interacts with the summarisation server 117 via the
10 communication network 109.

Once the application software of the control server 115 has completed the step 205 of running the grid summarisation algorithm, the next step 207 it performs is
15 to run a cluster summarisation algorithm. Figure 6 provides a flow chart 601 of the various steps involved in the cluster summarisation algorithm. The first step 603 of the cluster summarisation algorithm is to select a first of the avatars in the virtual environment. Following on from the
20 first step 603 the cluster summarisation algorithm involves the step 605 of selecting a second of the avatars that is closest to the first of the avatars, which was selected during the first step 603. Once the second of the avatars has been selected, the cluster summarisation algorithm
25 involves the step 607 of determining whether the second of the avatars fits in to a previously defined cluster. Following on from the previous step 607 the cluster summarisation algorithm involves the step 609 of placing the second of the avatars in to the previously defined
30 cluster if it fits therein. On the other hand if it is determined that the second of the avatars does not fit in to a previously defined cluster then the cluster summarisation algorithm involves carrying out the step 611 of establishing a new cluster that is centred around the
35 second of the clusters. It is noted that the preceding steps 603 to 611 are performed until a predetermined number of clusters M are established.

- 22 -

Once the M clusters have been established, the cluster summarisation algorithm involves performing the step 613 of finding the largest angular gap between the M clusters. Once the largest angular gap has been determined
5 the cluster summarisation algorithm involves the step 615 of establishing a new cluster in the largest angular gap. The previous steps 613 and 615 are repeated until a total of K clusters have been established. It is noted that the
10 number of M clusters is $\leq$ the number of K clusters.

The final step 617 of the cluster summarisation algorithm involves placing all remaining avatars within the best of the K clusters, which are those clusters that
15 result in the least angular error; that is, the angular difference between where a sound source is rendered from the perspective of the first of the avatars and the actual location of the sound source if the sound from the source was not summarised.

20

Once the steps 603 to 617 of the cluster summarisation algorithm have been performed the application software running on the control server 115 proceeds to carry out the last step 209, which is discussed in detail
25 in subsequent paragraphs of this specification. An illustration of the clusters established using the cluster summarisation algorithm is shown in figure 7.

Persons skilled in the art will readily
30 appreciate that the present invention is not limited to being used with the aforementioned clustering algorithm. By way of example, the following describes an alternative clustering algorithm that can be employed in another embodiment of the present invention. The flow chart 807 in
35 figure 8 shows the steps involved in the alternative clustering algorithm.

- 23 -

The first step 803 of the alternative cluster summarisation algorithm is to select one of the avatars in the virtual environment. The next step 805 is to then determine the total number of avatars and grid summaries that are located in the hearing range of the avatar. The grid summaries are essentially unweighted audio streams produced by the summarisation server 117. A detailed description of this aspect of the summarisation server 117 is set out in subsequent paragraphs of this specification.

10

Following on from the previous step 805, the next step 807 is to assess whether the total number of avatars and grid summaries in the hearing range is less than or equal to K , which is a number selected based on the amount of bandwidth available for transmitting an audio scene. If it is determined that the total number of avatars and grid summaries is less than or equal to K , then the application software running on the control server 115 proceeds to the final step 209 of the algorithm (which is discussed in subsequent paragraphs of this specification).

15

20

In the event that the total number of avatars and/or grid summaries in the hearing range is greater than K , the control server 115 continues to carry out the alternative cluster summarisation algorithm. In this situation the next step 809 in the alternative cluster summarisation algorithm is to effectively plot on the map 401 a radial ray that emanates from the avatar (selected during the previous step 803) and goes through any of the other avatars in the hearing range of the avatar.

25

30

Subsequent to step 809, the next step 811 is to calculate the absolute angular distance of every avatar and grid summary in the hearing range of the avatar. Following on from step 811 the alternative clustering algorithm involves the step 813 of arranging the absolute angular distances in an ascending ordered list. The next step 815 is to calculate the differential angular separation of each two

35

- 24 -

successive absolute angular distances in the ascending ordered list. Once the previous step 815 has been carried out, the next step 817 is to identify the K largest differential angular distances. The next step 819 is to
5 divide the hearing range of the avatar into K portions by effectively forming radial rays between each of the avatars that are associated with the K highest differential angular distances. The area between the radial rays is referred to as a portion of the hearing range. Figure 9 depicts the
10 effect of running the alternative cluster summarisation algorithm on the map 401.

As an example of the previous steps of the alternative cluster summarisation algorithm, consider a
15 virtual environment comprising a total of 10 avatars/grid summaries, and a K that equals 4. Assume that the initial steps 811 and 813 of the alternative cluster summarisation algorithm result in the following list of absolute angular distances in ascending ordered:

20 0, 10, 16, 48, 67, 120, 143, 170, 222 and 253, which correspond respectively to avatars/grid summaries A_0 to A_9 .

The subsequent step 815 of the alternative
25 cluster summarisation algorithm which involves calculating the differential angular separation of each two successive absolute angular distances in the above list will result in the following:

30 10, 6, 32, 19, 53, 23, 27, 52, 31 and 107

The step 817 of the alternative cluster summarisation algorithm which involves identifying the K (4) largest differential angular distances will result in
35 the following being selected:

107, 53, 52 and 32

- 25 -

The step 819 of the alternative cluster summarisation algorithm which involves dividing the hearing ranging into portions will result in the following K (4) clusters of avatars being defined:

- 1: A_0 , A_1 and A_3
- 2: A_3 and A_4
- 3: A_5 , A_6 and A_7
- 4: A_8 and A_9

Following on from the previous steps, the alternative cluster summarisation algorithm involves the step 821 of determining the locations of the avatars in the virtual environment. The application software running on the control server 115 does this by interacting with the second of the modules 113 in the virtual environment state maintenance system 105. Once the location of the avatars has be determined, the alternative cluster summarisation algorithm involves the step 823 of using the locations of the avatars to determine a distances between the avatars and the avatar for which the alternative cluster summarisation algorithm is being run. Subsequent to the step 823 the alternative cluster summarisation algorithm involves the step 825 of using the distances to determine a weighting to be applied to audio emanating from the avatars in the hearing range of the avatar. The step 825 also involves the step of using the centre of mass (determined from the grid summarisation algorithm) to determine a weighting for each of the grid summaries in the hearing range of the avatar.

At this stage, the alternative cluster summarisation algorithm involves the step 827 of determining a centre of mass for each of the portions of the hearing range identified during the previous step 819 of dividing up the hearing range. As with the grid

- 26 -

summarisation algorithm, the alternative cluster summarisation algorithm determines the centre of mass by selecting a location in each of the portions around which the avatars are centred.

5

The final step 829 of the alternative cluster summarisation algorithm involves updating a control table 1001 (which is shown in figure 10) in the scene creation servers 119. This involves updating the control tables 1001 to include the identifier of each of the avatars in the portions of the hearing range, the weightings to be applied to the avatars in the portions, and the centre of mass of each of the portions. It is noted that the control server 115 updates the control table 1001 in the scene creation server 119 via the communication network 109.

As can be seen in figure 10, the control table 1001 in the scene creation servers 119 comprises a plurality of rows. Each of the rows corresponds to a portion of the hearing range of an avatar and contains the identifiers of the avatars/grid summaries (S_h and Z_i , respectively) in each portion of the hearing range. Each row of the control table 1001 also comprises the weighting to be applied to audio from the avatars/grid summaries (W), and the centre of mass of the portions, (which is contained in the "Location Coord" column of the control table 801). The centre of mass is in the form of x, y coordinates.

Upon completing the final step 829 of the alternative cluster summarisation algorithm, the application software running on the control server 115 proceeds to carry out its last step 209. The last step 209 involves interacting with the communication network 109 to establish specific communication links. The communication links are such that that they enable audio to be transferred from the client computing device 107 to the summarisation server 117 and/or the scene creation servers

- 27 -

119, and grid summaries (unweighted audio streams) to be transferred from the summarisation server 117 to the scene creation servers 119.

5 Once the control server 115 has completed the previous steps 203 to 209, the summarisation server 117 is in a position to create unweighted audio streams (grid summaries). The summarisation server 117 is in the form of a computer server that comprises traditional computer
10 hardware such as a motherboard, hard disk storage means, and random access memory. In addition to the hardware the computer server also comprises an operating system (such as Linux or Microsoft Window) that performs various system level operations. The operating system also provides an
15 environment for executing application software. In this regard, the computer server comprises application software that is arranged to carry out a mixing process, the steps of which are shown in the flow chart 1101 illustrated in figure 11, in order to create unweighted audio streams.

20 The first step 1103 of the flow chart 1101 is to obtain the audio streams S_n associated with each of the avatars identified in the "Streams to be mixed" column of the control table 501 in the summarisation server 117. The
25 control table 501 being illustrated in figure 5. It is noted that the summarisation server 117 obtains the audio streams S_n via the communication network 109. In this regard, the previous step 209 of the control server 115 interacting with the communication network 109 established
30 the necessary links in the communication network 109 to enable the summarisation server 117 to receive the audio streams S_n . Then for each row in the control table 501, the next step 1105 is to mix together the identified audio streams S_n , to thereby produce M mixed audio streams. Each
35 of the M mixed audio streams comprises the audio streams S_n identified in the "Streams to be mixed" column of each of the M rows in the control table 501. When mixing the audio

- 28 -

streams S_n during the mixing step 1105 each audio stream S_n is such that they have their original unaltered amplitude. The M mixed audio streams are therefore considered unweighted audio streams. As indicated previously, the
5 unweighted audio streams contain audio from the avatars located in the cells of the map 401, which is shown in figure 4.

The next step 1107 in the flow chart 1101 is to
10 tag the unweighted audio streams with the corresponding centre of mass of the respective cell in the map 401. This step 1107 effectively involves inserting the x , y coordinates from the "centre of mass of the cell" columns of the control table 501. The final step 1109 in the
15 process 1101 is to forward the unweighted audio streams from the summarisation server 117 to the appropriate scene creation server 119, which is achieved by using the communication network 109 to transfer the unweighted audio streams from the summarisation server 117 to the scene
20 creation server 119. The previous step 209 of the control server 115 interacting with the communication network 109 established the necessary links in the communication network 109 to enable the unweighted audio streams to be transferred from the summarisation server 117 to the scene
25 creation server 119.

Once the unweighted audio streams have been transferred to the scene creation server 119 it is in a position to carry out a mixing process to create weighted
30 audio streams. The steps involved in the mixing process are shown in the flow chart 1201 of figure 12. Each scene creation server 119 is in the form of a computer server that comprises traditional computer hardware such as a motherboard, hard disk storage means, and random access
35 memory. In addition to the hardware the computer server also comprises an operating system (such as Linux or Microsoft Window) that performs various system level

- 29 -

operations. The operating system also provides an environment for executing application software. In this regard, the computer server comprises application software that is arranged to carry out the various steps of the flow
5 chart 1201.

The steps of the flow chart 1201 are essentially the same as the steps of the flow chart 1101 carried out by the summarisation server 117, except that instead of
10 producing an unweighted audio stream the steps of the latter flow chart 1201 result in weighted audio streams being created. As can be seen in figure 12 the first step 1203 involves obtaining the audio streams Z_i and S_n identified in the control table 1001 of the scene creation
15 server 119, where Z_i is an unweighted audio stream from the summarisation server 117 and S_n is an audio stream associated with a particular avatar. Then, for each row in the control table 1001, the flow chart 1201 involves the step 1205 of mixing the audio streams Z_i and S_n identified
20 in the "Cluster summary streams" of the control table 1001, to thereby produce weighted audio streams. Each of the weighted audio streams comprises the audio streams Z_i and S_n identified in the corresponding row of the control table 1001. Unlike the unweighted audio streams created by the
25 summarisation server 117, the amplitude of the audio streams Z_i and S_n in the weighted audio streams have different amplitudes. The amplitudes are determined during the mixing step 1205 by effectively multiplying the audio streams Z_i and S_n by their associated weightings W_n , which
30 are also contained in the "Cluster summary streams" column of the control table 1001.

The next step 1207 in the flow chart 1201 is to tag the weighted audio streams with the center of mass
35 contained in the corresponding "Location Coord" column of the control table 1001. This effectively involves inserting the x, y coordinates contained in the "Location Coord"

- 30 -

column. The final step 1209 of the flow chart 1201 is to forward, via the communication network 109, the weighted audio streams to the client computing device 107 for processing.

5

The client computing device 107 is in the form of a personal computer comprising typical computer hardware such as a motherboard, hard disk and memory. In addition to the hardware, the client computing device 107 is loaded with an operating system (such as Microsoft Windows) that manages various system level operations and provides an environment in which application software can be executed. The client computing device 107 also comprises: an audio client 121; a virtual environment client 123; and a spatial audio rendering engine 125. The audio client 121 is in the form of application software that is arranged to receive and process the weighted audio streams from the scene creation servers 119. The spatial audio rendering engine 125 is in the form of audio rendering software and soundcard. On receiving the weighted audio streams from the scene creation server 119, the audio client 121 interacts with the spatial audio rendering engine 125 to render (reproduce) the weighted audio streams and thereby create an audio scene to the person using the client computing device 107. In this regard, the spatial audio rendering engine 125 is connected to a set of speakers that are used to convey the audio scene to the person. It is noted that the audio client 121 extracts the location information inserted into the weighted audio stream by a scene creation server 119 during the previous step 1207 of tagging the weighted audio streams. The extracted location information is conveyed to the spatial audio rendering engine 125 (along with the weighted audio streams), which in turn uses the location information to reproduce the information as if it was emanating from the location; that is, for example from the right hand side.

- 31 -

The virtual environment client 123 is in the form of software (and perhaps some dedicated image processing hardware in alternative embodiments) and is basically arranged to interact with the first of the modules 111 of the virtual environment state maintenance system 105 in order to obtain the dynamic state information pertaining to the virtual environment. On receiving the dynamic state information the graphics client 123 process the dynamic state information to reproduce (render) the the virtual environment. To enable the virtual environment to be displayed to the person using the client computing device 107, the client computing device 107 also comprises a monitor (not shown). The graphics client 123 is also arranged to provide the virtual environment state maintenance system 105 with dynamic information pertaining to the person's presence in the virtual environment.

Those skilled in the art will appreciate that the invention described herein is susceptible to variations and modifications other than those specifically described. It should be understood that the invention includes all such variations and modifications which fall within the spirit and scope of the invention.

- 32 -

WE CLAIM:

1. An apparatus for creating an audio scene for an avatar in a virtual environment, the apparatus
5 comprising:

an audio processor operable to create a weighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and

10 associating means operable to associate the weighted audio stream with a datum that represents a location of the portion of the hearing range in the virtual environment, wherein the weighted audio stream and the datum represent the audio scene.

15 2. The apparatus as claimed in claim 1, wherein the audio processor is further operable to create the weighted audio stream such that it comprises an unweighted audio stream that comprises audio from another object located in the portion of the hearing range of the avatar.

20 3. The apparatus as claimed in claim 1 or 2, wherein the audio processor is operable to create the weighted audio stream in accordance with a predetermined mixing operation, the predetermined mixing operation
25 comprising identification information that identifies the object and/or the other objects, and weighting information that can be used by the audio processor to set an amplitude of the audio and unweighted audio stream in the weighted audio stream.

30 4. The apparatus as claimed in claim 3, wherein the apparatus further comprises a communication means operable to receive the audio, the unweighted audio stream and the mixing operation via a communication network, the
35 communication network also being operable to send the weighted audio stream and the datum via the communication network.

- 33 -

5. An apparatus operable to create audio information for use in an audio scene for an avatar in a virtual environment, the apparatus comprising:

an audio processor operable to create an
5 unweighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and
associating means operable to associate the
unweighted audio stream with a datum that represents an
approximate location of the object in the virtual
10 environment, wherein the unweighted audio stream and the datum represent the audio information.

6. The apparatus as claimed in claim 5, wherein the audio processor is operable to create the unweighted
15 audio stream in accordance with a predetermined mixing operation, the predetermined mixing operation comprising identification information that identifies the object.

7. The apparatus as claimed in claim 6, further
20 comprising a communication means operable to receive the audio and the predetermined mixing operation via a communication network, the communication network also being operable to send the unweighted audio stream and the datum via the communication network.

25

8. An apparatus for obtaining information that can be used to create an audio scene for an avatar in a virtual environment, the apparatus comprising:

identifying means operable to determine an
30 identifier of an object located in a portion of a hearing range of the avatar;

weighting means operable to determine a weighting to be applied to audio from the object; and

locating means operable to determine a location
35 of the portion in the virtual environment, wherein the identifier, weighting and the location represent the information that can be used to create the audio scene.

- 34 -

9. The apparatus as claimed in claim 8, further comprising a communication means operable to send, via a communication network, the identifier, the weighting and the location to one of a plurality of systems for
5 processing.

10. The apparatus as claimed in claim 9, wherein the communication means is further operable to create routing information for the communication network, wherein
10 the routing information is such that it can be used by the communication network to route the audio to the one of the plurality of system for processing.

11. The apparatus as claim in any one of claims
15 8 to 10, wherein the identifying means, the weighting means and the locating means are operable to respectively determine the identifier, the weighting and the location by processing a representation of the virtue environment.

12. The apparatus as claimed in any one of
20 claims 8 to 11, wherein the identifying means is operable to determine the portion of the hearing range by:

selecting a first of a plurality of avatars in the virtual environment;

25 identifying a second of the plurality of avatars that is proximate the first of the avatars;

determining whether the second of the avatars can be included in an existing cluster;

including the second of the avatars in the
30 existing cluster upon determining that it can be included therein;

creating a new cluster that includes the second of the avatars upon determining that the second of the avatars cannot be included in the existing cluster to
35 thereby create a plurality of clusters;

determining an angular gap between two of the clusters;

- 35 -

creating a further cluster that is located in the angular gap; and

including at least one of the avatars in the further cluster.

5

13. The apparatus as claimed in any one of claims 8 to 11, wherein the identifying means is operable to determine the portion of the hearing range by:

10 selecting one of a plurality of avatars in the virtual environment;

determining a radial ray that extends from the avatar to the one of the plurality of avatars;

calculating the absolute angular distance that each of the plurality of avatars is from the radial ray;

15 arranging the absolute angular distance of each of the avatars into an ascending ordered list;

calculating a differential angular separation between successive ones of the absolute angular distance in the ascending ordered list; and

20 selecting at least one of the differential angular separation that has a higher value than another differential angular separation; and

25 determining another radial ray that emanates from the avatar and which bisects two of the avatars that are associated with the differential angular separation.

14. An apparatus for creating information that can be used to create an audio scene for an avatar in a virtual environment, the apparatus comprising:

30 identifying means operable to determine an identifier of an object located in a portion of a hearing range of the avatar; and

35 locating means operable to determine an approximate location of the object in the virtual environment, wherein the identifier and the approximate location represent the information that can be used to create the audio scene.

- 36 -

15. The apparatus as claimed in claim 14,
further comprising a communication means operable to send,
via a communication network, the identifier and the
5 location to one of a plurality of systems for processing.

16. The apparatus as claimed in claim 15,
wherein the communication means is further operable to
create routing information for the communication network,
10 wherein the routing information is such that it can be used
by the communication network to route the audio to the one
of the plurality of systems for processing.

17. The apparatus as claimed in any one of
15 claims 14 to 16, wherein the identifying means and the
locating means are operable to respectively determine the
identifier and the location by processing a representation
of the virtual environment.

19. The apparatus as claimed in any one of
20 claims 14 to 17, wherein the identifying means is operable
to determine the approximate location of the object by:

dividing the virtual environment into a plurality
25 of cells; and

determining a location in the one of the cells
about which the object is located.

19. An apparatus for rendering an audio scene
30 for an avatar in a virtual environment, the apparatus
comprising:

obtaining means operable to obtain a weighted
audio stream that comprises audio from an object located in
a portion of a hearing range of the avatar, and a datum
35 that is associated with the weighted audio stream and which
represents a location of the portion of the hearing range
in the virtual environment; and

- 37 -

a spatial audio rendering engine that is operable to process the weighted audio stream and the datum in order to render the audio scene.

5 20. A method of creating an audio scene for an avatar in a virtual environment, the method comprising the steps of:

 creating a weighted audio stream that comprises audio from an object located in a portion of a hearing
10 range of the avatar; and

 associating the weighted audio stream with a datum that represents a location of the portion of the hearing range in the virtual environment, wherein the weighted audio stream and the datum represent the audio
15 scene.

 21. The method as claimed in claim 20, wherein the step of creating the weighted audio stream is such that the weighted audio stream comprises an unweighted audio
20 stream that comprises audio from another object located in the portion of the hearing range of the avatar.

 22. The method as claimed in claim 20 or 21, wherein the step of creating the weighted audio stream is
25 carried out in accordance with a predetermined mixing operation, the predetermined mixing operation comprising identification information that identifies the object and/or the other objects, and weighting information that can be used by the audio processor to set an amplitude of
30 the audio and unweighted audio stream in the weighted audio stream.

 23. The method as claimed in claim 22, further comprises the steps of:

35 receiving the audio, the unweighted audio stream and the mixing operation via a communication network; and
 sending the weighted audio stream and the datum

- 38 -

via the communication network.

24. A method of creating audio information for use in an audio scene for an avatar in a virtual environment, the method comprising the steps of:

creating an unweighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar; and

associating the unweighted audio stream with a datum that represents an approximate location of the object in the virtual environment, wherein the unweighted audio stream and the datum represent the audio information.

25. The method as claimed in claim 24, wherein the step of creating the unweighted audio stream is carried out in accordance with a predetermined mixing operation, wherein the predetermined mixing operation comprising identification information that identifies the object.

26. The method as claimed in claim 25, further comprising the steps of:

receiving the audio and the predetermined mixing operation via a communication network; and

sending the unweighted audio stream and the datum via the communication network.

27. A method of obtaining information that can be used to create an audio scene for an avatar in a virtual environment, the method comprising the steps of:

determining an identifier of an object located in a portion of a hearing range of the avatar;

determining a weighting to be applied to audio from the object; and

determining a location of the portion in the virtual environment, wherein the identifier, weighting and the location represent the information that can be used to create an audio scene.

- 39 -

28. The method as claimed in claim 27, further comprising the step of sending, via a communication network, the identifier, the weighting and the location to one of a plurality of systems for processing.

29. The method as claimed in claim 28, further comprising the step of creating routing information for the communication network, wherein the routing information is such that it can be used by the communication network to route the audio to the one of the plurality of system for processing.

30. The method as claimed in any one of claims 27 to 29, wherein the steps of determining the identifier, the weighting and the location respectively comprise determining the identifier, the weighting and the location by processing a representation of the virtue environment.

31. The method as claimed in any one of claims 27 to 30, further comprising the following steps to determine the portion of the hearing range:

selecting a first of a plurality of avatars in the virtual environment;

identifying a second of the plurality of avatars that is proximate the first of the avatars;

determining whether the second of the avatars can be included in an existing cluster;

including the second of the avatars in the existing cluster upon determining that it can be included therein;

creating a new cluster that includes the second of the avatars upon determining that the second of the avatars cannot be included in the existing cluster to thereby create a plurality of clusters;

determining an angular gap between two of the clusters;

- 40 -

creating a further cluster that is located in the angular gap; and

including at least one of the avatars in the further cluster.

5

32. The method as claimed in any one of claims 27 to 30, further comprising the following steps to determine the portion of the hearing range:

10 selecting one of a plurality of avatars in the virtual environment;

determining a radial ray that extends from the avatar to the one of the plurality of avatars;

calculating the absolute angular distance that each of the plurality of avatars is from the radial ray;

15 arranging the absolute distance of each of the avatars into an ascending ordered list;

calculating a differential angular separation between successive ones of the plurality of avatars based on the absolute angular distance;

20 selecting at least one of the differential angular separation that has a higher value than another differential angular separation; and

25 determining another radial ray that emanates from the avatar and which bisects two of the avatars which are associated with the differential angular separation.

33. A method of creating information that can be used to create an audio scene for an avatar in a virtual environment, the method comprising the steps of:

30 determining an identifier of an object located in a portion of a hearing range of the avatar; and

determining an approximate location of the object in the virtual environment, wherein the identifier and the approximate location represent the information that can be
35 used to create the audio scene.

34. The method as claimed in claim 33, further

- 41 -

comprising the step of sending, via a communication network, the identifier and the location to one of a plurality of systems for processing.

5 35. The method as claimed in claim 34, further comprising the step of creating routing information for the communication network, wherein the routing information is such that it can be used by the communication network to route the audio to the one of the plurality of systems for
10 processing.

 36. The method as claimed in any one of claims 33 to 35, wherein the steps of determining the identifier and the approximate location respectively comprises the
15 step of determine the identifier and the location by processing a representation of the virtue environment.

 37. The method as claimed in any one of claims 33 to 36, further comprising the following steps to
20 determine the approximate location of the object:

 selecting at least once of the differential angular separation that has a higher value than another differential angular separation; and

 determining another radial ray that emanates from
25 the avatar and which bisects two of the avatars that are associated with the differential angular separation.

 38. A method of rendering an audio scene for an avatar in a virtual environment, the method comprising the
30 steps of:

 obtaining a weighted audio stream that comprises audio from an object located in a portion of a hearing range of the avatar, and a datum that is associated with the weighted audio stream and which represents a location
35 of the portion of the hearing range in the virtual environment; and

 processing the weighted audio stream and the

- 42 -

datum in order to render the audio scene.

39. A computer program comprising at least one
instruction for causing a computing device to carry out the
5 method defined in any one of claims 20 to 38.

40. A computer readable medium comprising the
computer program defined in claim 39.