

UPDATE OF LOOK UP TABLE: FIFO, CONSTRAINED FIFO**CROSS REFERENCE TO RELATED APPLICATIONS**

[0001] Under the applicable patent law and/or rules pursuant to the Paris Convention, this application is made to timely claim the priority to and benefits of International Patent Application No. PCT/CN2018/093663, filed on June 29, 2018, International Patent Application No. PCT/CN2018/094929, filed on July 7, 2018, International Patent Application No. PCT/CN2018/101220, filed on August 18, 2018, International Patent Application No. PCT/CN2018/117627, filed on November 27, 2018, and International Patent Application No. PCT/CN2019/071214, filed on January 10, 2019. For all purposes under the U.S. law, the entire disclosures of International Patent Application No. PCT/CN2018/093663, International Patent Application No. PCT/CN2018/094929, International Patent Application No. PCT/CN2018/101220, International Patent Application No. PCT/CN2018/117627, and International Patent Application No. PCT/CN2019/071214 are incorporated by reference as part of the disclosure of this application

TECHNICAL FIELD

[0002] This patent document relates to video coding and decoding techniques, devices and systems.

BACKGROUND

[0003] In spite of the advances in video compression, digital video still accounts for the largest bandwidth use on the internet and other digital communication networks. As the number of connected user devices capable of receiving and displaying video increases, it is expected that the bandwidth demand for digital video usage will continue to grow.

SUMMARY

[0004] This document discloses methods, systems, and devices for encoding and decoding digital video.

[0005] In one example aspect, a video processing method is provided to include maintaining

one or more tables, wherein each table includes one or more motion candidates and each motion candidate is associated with corresponding motion information; performing a conversion between a current block and a bitstream representation of a video including the current block by using motion information in a table; and updating, after performing of the conversion, one or more tables based on M sets of additional motion information associated with the current block, M being an integer.

[0006] In another example aspect, another video processing method is provided to performing a conversion between a current block and a bitstream representation of a video including the current block by using one or more tables, wherein each table includes a one or more motion candidates and each motion candidate is associated with corresponding motion information; and updating, based on the conversion, one or more tables, based on M sets of additional motion information associated with the current block, M being an integer.

[0007] In yet another example aspect, a video encoder device that implements a video encoding method described herein is disclosed.

[0008] In yet another representative aspect, the various techniques described herein may be embodied as a computer program product stored on a non-transitory computer readable media. The computer program product includes program code for carrying out the methods described herein.

[0009] In yet another representative aspect, a video decoder apparatus may implement a method as described herein.

[0010] The details of one or more implementations are set forth in the accompanying attachments, the drawings, and the description below. Other features will be apparent from the description and drawings, and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 is a block diagram showing an example of a video encoder implementation

[0012] FIG. 2 illustrates macroblock partitioning in the H.264 video coding standard.

[0013] FIG. 3 illustrates an example of splitting coding blocks (CB) into prediction blocks (PU).

[0014] FIG. 4 illustrates an example implementation for subdivision of a CTB into CBs and transform block (TBs). Solid lines indicate CB boundaries and dotted lines indicate TB

boundaries, including an example CTB with its partitioning, and a corresponding quadtree.

[0015] FIG. 5 shows an example of a Quad Tree Binary Tree (QTBT) structure for partitioning video data.

[0016] FIG. 6 shows an example of video block partitioning.

[0017] FIG. 7 shows an example of quad-tree partitioning.

[0018] FIG. 8 shows an example of tree-type signaling.

[0019] FIG. 9 shows an example of a derivation process for merge candidate list construction.

[0020] FIG. 10 shows example positions of spatial merge candidates.

[0021] FIG. 11 shows examples of candidate pairs considered for redundancy check of spatial merge candidates.

[0022] FIG. 12 shows examples of positions for the second PU of $N \times 2N$ and $2N \times N$ partitions.

[0023] FIG. 13 illustrates motion vector scaling for temporal merge candidates.

[0024] FIG. 14 shows candidate positions for temporal merge candidates, and their co-located picture.

[0025] FIG. 15 shows an example of a combined bi-predictive merge candidate.

[0026] FIG. 16 shows an example of a derivation process for motion vector prediction candidates.

[0027] FIG. 17 shows an example of motion vector scaling for spatial motion vector candidates.

[0028] FIG. 18 shows an example Alternative Temporal Motion Vector Prediction (ATMVP) for motion prediction of a CU.

[0029] FIG. 19 pictorially depicts an example of identification of a source block and a source picture.

[0030] FIG. 20 shows an example of one CU with four sub-blocks and neighboring blocks.

[0031] FIG. 21 illustrates an example of bilateral matching.

[0032] FIG. 22 illustrates an example of template matching.

[0033] FIG. 23 depicts an example of unilateral Motion Estimation (ME) in Frame Rate Up Conversion (FRUC).

[0034] FIG. 24 shows an example of DMVR based on bilateral template matching.

- [0035] FIG. 25 shows an example of spatially neighboring blocks used to derive spatial merge candidates.
- [0036] FIG. 26 depicts an example how selection of a representative position for look-up table updates.
- [0037] FIG. 27A and 27B illustrate examples of updating look up table with new set of motion information.
- [0038] FIG. 28 is a block diagram of an example of a hardware platform for implementing a visual media decoding or a visual media encoding technique described in the present document.
- [0039] FIG. 29 is a flowchart for an example method of video bitstream processing.
- [0040] FIG. 30 is a flowchart for another example method of video bitstream processing.
- [0041] FIG. 31 shows an example of a decoding flow chart with the proposed HMVP method.
- [0042] FIG. 32 shows examples of updating tables using the proposed HMVP method.
- [0043] FIGS. 33A and 33B show examples of a redundancy-removal based LUT updating method (with one redundancy motion candidate removed).
- [0044] FIGS. 34A and 34B show examples of a redundancy-removal based LUT updating method (with multiple redundancy motion candidates removed).

DETAILED DESCRIPTION

[0045] To improve compression ratio of video, researchers are continually looking for new techniques by which to encode video.

[0046] 1. Introduction

[0047] The present document is related to video coding technologies. Specifically, it is related to motion information coding (such as merge mode, AMVP mode) in video coding. It may be applied to the existing video coding standard like HEVC, or the standard (Versatile Video Coding) to be finalized. It may be also applicable to future video coding standards or video codec.

[0048] Brief discussion

[0049] Video coding standards have evolved primarily through the development of the well-known ITU-T and ISO/IEC standards. The ITU-T produced H.261 and H.263, ISO/IEC produced MPEG-1 and MPEG-4 Visual, and the two organizations jointly produced the

H.262/MPEG-2 Video and H.264/MPEG-4 Advanced Video Coding (AVC) and H.265/HEVC standards. Since H.262, the video coding standards are based on the hybrid video coding structure wherein temporal prediction plus transform coding are utilized. An example of a typical HEVC encoder framework is depicted in FIG. 1.

2.1 Partition Structure

2.1.1 Partition tree structure in H.264/AVC

[0050] The core of the coding layer in previous standards was the macroblock, containing a 16×16 block of luma samples and, in the usual case of 4:2:0 color sampling, two corresponding 8×8 blocks of chroma samples.

[0051] An intra-coded block uses spatial prediction to exploit spatial correlation among pixels. Two partitions are defined: 16×16 and 4×4 .

[0052] An inter-coded block uses temporal prediction, instead of spatial prediction, by estimating motion among pictures. Motion can be estimated independently for either 16×16 macroblock or any of its sub-macroblock partitions: 16×8 , 8×16 , 8×8 , 8×4 , 4×8 , 4×4 (see FIG. 2). Only one motion vector (MV) per sub-macroblock partition is allowed.

[0053] 2.1.2 Partition tree structure in HEVC

[0054] In HEVC, a CTU is split into CUs by using a quadtree structure denoted as coding tree to adapt to various local characteristics. The decision whether to code a picture area using inter-picture (temporal) or intra-picture (spatial) prediction is made at the CU level. Each CU can be further split into one, two or four PUs according to the PU splitting type. Inside one PU, the same prediction process is applied and the relevant information is transmitted to the decoder on a PU basis. After obtaining the residual block by applying the prediction process based on the PU splitting type, a CU can be partitioned into transform units (TUs) according to another quadtree structure similar to the coding tree for the CU. One of key feature of the HEVC structure is that it has the multiple partition conceptions including CU, PU, and TU.

[0055] In the following, the various features involved in hybrid video coding using HEVC are highlighted as follows.

[0056] 1) Coding tree units and coding tree block (CTB) structure: The analogous structure in HEVC is the coding tree unit (CTU), which has a size selected by the encoder and can be larger than a traditional macroblock. The CTU consists of a luma CTB and the corresponding

chroma CTBs and syntax elements. The size $L \times L$ of a luma CTB can be chosen as $L = 16, 32$, or 64 samples, with the larger sizes typically enabling better compression. HEVC then supports a partitioning of the CTBs into smaller blocks using a tree structure and quadtree-like signaling.

[0057] 2) Coding units (CUs) and coding blocks (CBs): The quadtree syntax of the CTU specifies the size and positions of its luma and chroma CBs. The root of the quadtree is associated with the CTU. Hence, the size of the luma CTB is the largest supported size for a luma CB. The splitting of a CTU into luma and chroma CBs is signaled jointly. One luma CB and ordinarily two chroma CBs, together with associated syntax, form a coding unit (CU). A CTB may contain only one CU or may be split to form multiple CUs, and each CU has an associated partitioning into prediction units (PUs) and a tree of transform units (TUs).

[0058] 3) Prediction units and prediction blocks (PBs): The decision whether to code a picture area using inter picture or intra picture prediction is made at the CU level. A PU partitioning structure has its root at the CU level. Depending on the basic prediction-type decision, the luma and chroma CBs can then be further split in size and predicted from luma and chroma prediction blocks (PBs). HEVC supports variable PB sizes from 64×64 down to 4×4 samples. FIG. 3 shows examples of allowed PBs for a $M \times M$ CU.

[0059] 4) TUs and transform blocks: The prediction residual is coded using block transforms. A TU tree structure has its root at the CU level. The luma CB residual may be identical to the luma transform block (TB) or may be further split into smaller luma TBs. The same applies to the chroma TBs. Integer basis functions similar to those of a discrete cosine transform (DCT) are defined for the square TB sizes 4×4 , 8×8 , 16×16 , and 32×32 . For the 4×4 transform of luma intra picture prediction residuals, an integer transform derived from a form of discrete sine transform (DST) is alternatively specified.

[0060] FIG. 4 shows an example of a subdivision of a CTB into CBs [and transform block (TBs)]. Solid lines indicate CB borders and dotted lines indicate TB borders. (a) CTB with its partitioning. (b) corresponding quadtree.

[0061] 2.1.2.1 Tree-Structured Partitioning into Transform Blocks and Units

[0062] For residual coding, a CB can be recursively partitioned into transform blocks (TBs). The partitioning is signaled by a residual quadtree. Only square CB and TB partitioning is specified, where a block can be recursively split into quadrants, as illustrated in FIG. 4. For a given luma CB of size $M \times M$, a flag signals whether it is split into four blocks of size $M/2 \times M/2$.

If further splitting is possible, as signaled by a maximum depth of the residual quadtree indicated in the SPS, each quadrant is assigned a flag that indicates whether it is split into four quadrants. The leaf node blocks resulting from the residual quadtree are the transform blocks that are further processed by transform coding. The encoder indicates the maximum and minimum luma TB sizes that it will use. Splitting is implicit when the CB size is larger than the maximum TB size. Not splitting is implicit when splitting would result in a luma TB size smaller than the indicated minimum. The chroma TB size is half the luma TB size in each dimension, except when the luma TB size is 4×4 , in which case a single 4×4 chroma TB is used for the region covered by four 4×4 luma TBs. In the case of intra-picture-predicted CUs, the decoded samples of the nearest-neighboring TBs (within or outside the CB) are used as reference data for intra picture prediction.

[0063] In contrast to previous standards, the HEVC design allows a TB to span across multiple PBs for inter-picture predicted CUs to maximize the potential coding efficiency benefits of the quadtree-structured TB partitioning.

[0064] **2.1.2.2 Parent and child nodes**

[0065] A CTB is divided according to a quad-tree structure, the nodes of which are coding units. The plurality of nodes in a quad-tree structure includes leaf nodes and non-leaf nodes. The leaf nodes have no child nodes in the tree structure (i.e., the leaf nodes are not further split). The non-leaf nodes include a root node of the tree structure. The root node corresponds to an initial video block of the video data (e.g., a CTB). For each respective non-root node of the plurality of nodes, the respective non-root node corresponds to a video block that is a sub-block of a video block corresponding to a parent node in the tree structure of the respective non-root node. Each respective non-leaf node of the plurality of non-leaf nodes has one or more child nodes in the tree structure.

[0066] **2.1.3 Quadtree plus binary tree block structure with larger CTUs in JEM**

[0067] To explore the future video coding technologies beyond HEVC, Joint Video Exploration Team (JVET) was founded by VCEG and MPEG jointly in 2015. Since then, many new methods have been adopted by JVET and put into the reference software named Joint Exploration Model (JEM).

[0068] **2.1.3.1 QTBT block partitioning structure**

[0069] Different from HEVC, the QTBT structure removes the concepts of multiple partition

types, i.e. it removes the separation of the CU, PU and TU concepts, and supports more flexibility for CU partition shapes. In the QTBT block structure, a CU can have either a square or rectangular shape. As shown in FIG. 5, a coding tree unit (CTU) is first partitioned by a quadtree structure. The quadtree leaf nodes are further partitioned by a binary tree structure. There are two splitting types, symmetric horizontal splitting and symmetric vertical splitting, in the binary tree splitting. The binary tree leaf nodes are called coding units (CUs), and that segmentation is used for prediction and transform processing without any further partitioning. This means that the CU, PU and TU have the same block size in the QTBT coding block structure. In the JEM, a CU sometimes consists of coding blocks (CBs) of different colour components, e.g. one CU contains one luma CB and two chroma CBs in the case of P and B slices of the 4:2:0 chroma format and sometimes consists of a CB of a single component, e.g., one CU contains only one luma CB or just two chroma CBs in the case of I slices.

[0070] The following parameters are defined for the QTBT partitioning scheme.

- CTU size: the root node size of a quadtree, the same concept as in HEVC
- *MinQTSIZE*: the minimally allowed quadtree leaf node size
- *MaxBTSIZE*: the maximally allowed binary tree root node size
- *MaxBTDepth*: the maximally allowed binary tree depth
- *MinBTSIZE*: the minimally allowed binary tree leaf node size

[0071] In one example of the QTBT partitioning structure, the CTU size is set as 128×128 luma samples with two corresponding 64×64 blocks of chroma samples, the *MinQTSIZE* is set as 16×16 , the *MaxBTSIZE* is set as 64×64 , the *MinBTSIZE* (for both width and height) is set as 4×4 , and the *MaxBTDepth* is set as 4. The quadtree partitioning is applied to the CTU first to generate quadtree leaf nodes. The quadtree leaf nodes may have a size from 16×16 (i.e., the *MinQTSIZE*) to 128×128 (i.e., the CTU size). If the leaf quadtree node is 128×128 , it will not be further split by the binary tree since the size exceeds the *MaxBTSIZE* (i.e., 64×64). Otherwise, the leaf quadtree node could be further partitioned by the binary tree. Therefore, the quadtree leaf node is also the root node for the binary tree and it has the binary tree depth as 0. When the binary tree depth reaches *MaxBTDepth* (i.e., 4), no further splitting is considered. When the binary tree node has width equal to *MinBTSIZE* (i.e., 4), no further horizontal splitting is considered. Similarly, when the binary tree node has height equal to *MinBTSIZE*, no further vertical splitting is

considered. The leaf nodes of the binary tree are further processed by prediction and transform processing without any further partitioning. In the JEM, the maximum CTU size is 256×256 luma samples.

[0072] FIG. 5 (left) illustrates an example of block partitioning by using QTBT, and FIG. 5 (right) illustrates the corresponding tree representation. The solid lines indicate quadtree splitting and dotted lines indicate binary tree splitting. In each splitting (i.e., non-leaf) node of the binary tree, one flag is signalled to indicate which splitting type (i.e., horizontal or vertical) is used, where 0 indicates horizontal splitting and 1 indicates vertical splitting. For the quadtree splitting, there is no need to indicate the splitting type since quadtree splitting always splits a block both horizontally and vertically to produce 4 sub-blocks with an equal size.

[0073] In addition, the QTBT scheme supports the ability for the luma and chroma to have a separate QTBT structure. Currently, for P and B slices, the luma and chroma CTBs in one CTU share the same QTBT structure. However, for I slices, the luma CTB is partitioned into CUs by a QTBT structure, and the chroma CTBs are partitioned into chroma CUs by another QTBT structure. This means that a CU in an I slice consists of a coding block of the luma component or coding blocks of two chroma components, and a CU in a P or B slice consists of coding blocks of all three colour components.

[0074] In HEVC, inter prediction for small blocks is restricted to reduce the memory access of motion compensation, such that bi-prediction is not supported for 4×8 and 8×4 blocks, and inter prediction is not supported for 4×4 blocks. In the QTBT of the JEM, these restrictions are removed.

[0075] 2.1.4 Ternary-tree for VVC

[0076] As proposed in [6], tree types other than quad-tree and binary-tree are supported. In the implementation, two more ternary tree (TT) partitions, i.e., horizontal and vertical center-side ternary-trees are introduced, as shown in FIG. 6 (d) and (e).

[0077] FIG. 6 shows: (a) quad-tree partitioning (b) vertical binary-tree partitioning (c) horizontal binary-tree partitioning (d) vertical center-side ternary-tree partitioning (e) horizontal center-side ternary-tree partitioning.

[0078] In [6], there are two levels of trees, region tree (quad-tree) and prediction tree (binary-tree or ternary-tree). A CTU is firstly partitioned by region tree (RT). A RT leaf may be further split with prediction tree (PT). A PT leaf may also be further split with PT until max PT depth is

reached. A PT leaf is the basic coding unit. It is still called CU for convenience. A CU cannot be further split. Prediction and transform are both applied on CU in the same way as JEM. The whole partition structure is named 'multiple-type-tree'.

[0079] 2.1.5 An example of Partitioning structure

[0080] The tree structure used in this response, called Multi-Tree Type (MTT), is a generalization of the QTBT. In QTBT, as shown in FIG. 5, a Coding Tree Unit (CTU) is firstly partitioned by a quad-tree structure. The quad-tree leaf nodes are further partitioned by a binary-tree structure.

[0081] The fundamental structure of MTT constitutes of two types of tree nodes: Region Tree (RT) and Prediction Tree (PT), supporting nine types of partitions, as shown in FIG. 7.

[0082] FIG. 7 shows: (a) quad-tree partitioning (b) vertical binary-tree partitioning (c) horizontal binary-tree partitioning (d) vertical ternary-tree partitioning (e) horizontal ternary-tree partitioning (f) horizontal-up asymmetric binary-tree partitioning (g) horizontal-down asymmetric binary-tree partitioning (h) vertical-left asymmetric binary-tree partitioning (i) vertical-right asymmetric binary-tree partitioning.

[0083] A region tree can recursively split a CTU into square blocks down to a 4x4 size region tree leaf node. At each node in a region tree, a prediction tree can be formed from one of three tree types: Binary Tree (BT), Ternary Tree (TT), and Asymmetric Binary Tree (ABT). In a PT split, it is prohibited to have a quadtree partition in branches of the prediction tree. As in JEM, the luma tree and the chroma tree are separated in I slices. The signaling methods for RT and PT are illustrated in FIG. 8.

[0084] 2.2 Inter prediction in HEVC/H.265

[0085] Each inter-predicted PU has motion parameters for one or two reference picture lists. Motion parameters include a motion vector and a reference picture index. Usage of one of the two reference picture lists may also be signalled using *inter_pred_idc*. Motion vectors may be explicitly coded as deltas relative to predictors, such a coding mode is called AMVP mode.

[0086] When a CU is coded with skip mode, one PU is associated with the CU, and there are no significant residual coefficients, no coded motion vector delta or reference picture index. A merge mode is specified whereby the motion parameters for the current PU are obtained from neighbouring PUs, including spatial and temporal candidates. The merge mode can be applied to any inter-predicted PU, not only for skip mode. The alternative to merge mode is the explicit

transmission of motion parameters, where motion vector, corresponding reference picture index for each reference picture list and reference picture list usage are signalled explicitly per each PU.

[0087] When signalling indicates that one of the two reference picture lists is to be used, the PU is produced from one block of samples. This is referred to as ‘uni-prediction’. Uni-prediction is available both for P-slices and B-slices.

[0088] When signalling indicates that both of the reference picture lists are to be used, the PU is produced from two blocks of samples. This is referred to as ‘bi-prediction’. Bi-prediction is available for B-slices only.

[0089] The following text provides the details on the inter prediction modes specified in HEVC [2]. The description will start with the merge mode.

[0090] **2.2.1 Merge mode**

[0091] **2.2.1.1 Derivation of candidates for merge mode**

[0092] When a PU is predicted using merge mode, an index pointing to an entry in the *merge candidates list* is parsed from the bitstream and used to retrieve the motion information. The construction of this list is specified in the HEVC standard and can be summarized according to the following sequence of steps:

- Step 1: Initial candidates derivation
 - Step 1.1: Spatial candidates derivation
 - Step 1.2: Redundancy check for spatial candidates
 - Step 1.3: Temporal candidates derivation
- Step 2: Additional candidates insertion
 - Step 2.1: Creation of bi-predictive candidates
 - Step 2.2: Insertion of zero motion candidates

[0093] These steps are also schematically depicted in FIG. 9. For spatial merge candidate derivation, a maximum of four merge candidates are selected among candidates that are located in five different positions. For temporal merge candidate derivation, a maximum of one merge candidate is selected among two candidates. Since constant number of candidates for each PU is assumed at decoder, additional candidates are generated when the number of candidates does not reach to maximum number of merge candidate (MaxNumMergeCand) which is signalled in slice header. Since the number of candidates is constant, index of best merge candidate is encoded

using truncated unary binarization (TU). If the size of CU is equal to 8, all the PUs of the current CU share a single merge candidate list, which is identical to the merge candidate list of the $2N \times 2N$ prediction unit.

[0094] In the following, the operations associated with the aforementioned steps are detailed.

[0095] **2.2.1.2 Spatial candidates derivation**

[0096] In the derivation of spatial merge candidates, a maximum of four merge candidates are selected among candidates located in the positions depicted in FIG. 10. The order of derivation is A_1 , B_1 , B_0 , A_0 and B_2 . Position B_2 is considered only when any PU of position A_1 , B_1 , B_0 , A_0 is not available (e.g. because it belongs to another slice or tile) or is intra coded. After candidate at position A_1 is added, the addition of the remaining candidates is subject to a redundancy check which ensures that candidates with same motion information are excluded from the list so that coding efficiency is improved. To reduce computational complexity, not all possible candidate pairs are considered in the mentioned redundancy check. Instead only the pairs linked with an arrow in FIG. 11 are considered and a candidate is only added to the list if the corresponding candidate used for redundancy check has not the same motion information. Another source of duplicate motion information is the “*second PU*” associated with partitions different from $2N \times 2N$. As an example, FIG. 12 depicts the second PU for the case of $N \times 2N$ and $2N \times N$, respectively. When the current PU is partitioned as $N \times 2N$, candidate at position A_1 is not considered for list construction. In fact, by adding this candidate will lead to two prediction units having the same motion information, which is redundant to just have one PU in a coding unit. Similarly, position B_1 is not considered when the current PU is partitioned as $2N \times N$.

[0097] **2.2.1.3 Temporal candidate derivation**

[0098] In this step, only one candidate is added to the list. Particularly, in the derivation of this temporal merge candidate, a scaled motion vector is derived based on co-located PU belonging to the picture which has the smallest POC difference with current picture within the given reference picture list. The reference picture list to be used for derivation of the co-located PU is explicitly signalled in the slice header. The scaled motion vector for temporal merge candidate is obtained as illustrated by the dashed line in FIG. 13, which is scaled from the motion vector of the co-located PU using the POC distances, t_b and t_d , where t_b is defined to be the POC difference between the reference picture of the current picture and the current picture and t_d is defined to be the POC difference between the reference picture of the co-located picture

and the co-located picture. The reference picture index of temporal merge candidate is set equal to zero. A practical realization of the scaling process is described in the HEVC specification [1]. For a B-slice, two motion vectors, one is for reference picture list 0 and the other is for reference picture list 1, are obtained and combined to make the bi-predictive merge candidate. Illustration of motion vector scaling for temporal merge candidate.

[0099] In the co-located PU (Y) belonging to the reference frame, the position for the temporal candidate is selected between candidates C_0 and C_1 , as depicted in FIG. 14. If PU at position C_0 is not available, is intra coded, or is outside of the current CTU, position C_1 is used. Otherwise, position C_0 is used in the derivation of the temporal merge candidate.

[00100] 2.2.1.4 Additional candidates insertion

[00101] Besides spatio-temporal merge candidates, there are two additional types of merge candidates: combined bi-predictive merge candidate and zero merge candidate. Combined bi-predictive merge candidates are generated by utilizing spatio-temporal merge candidates. Combined bi-predictive merge candidate is used for B-Slice only. The combined bi-predictive candidates are generated by combining the first reference picture list motion parameters of an initial candidate with the second reference picture list motion parameters of another. If these two tuples provide different motion hypotheses, they will form a new bi-predictive candidate. As an example, FIG. 15 depicts the case when two candidates in the original list (on the left), which have $mvL0$ and $refIdxL0$ or $mvL1$ and $refIdxL1$, are used to create a combined bi-predictive merge candidate added to the final list (on the right). There are numerous rules regarding the combinations which are considered to generate these additional merge candidates.

[00102] Zero motion candidates are inserted to fill the remaining entries in the merge candidates list and therefore hit the $MaxNumMergeCand$ capacity. These candidates have zero spatial displacement and a reference picture index which starts from zero and increases every time a new zero motion candidate is added to the list. The number of reference frames used by these candidates is one and two for uni and bi-directional prediction, respectively. Finally, no redundancy check is performed on these candidates.

[00103] 2.2.1.5 Motion estimation regions for parallel processing

[00104] To speed up the encoding process, motion estimation can be performed in parallel whereby the motion vectors for all prediction units inside a given region are derived simultaneously. The derivation of merge candidates from spatial neighbourhood may interfere

with parallel processing as one prediction unit cannot derive the motion parameters from an adjacent PU until its associated motion estimation is completed. To mitigate the trade-off between coding efficiency and processing latency, HEVC defines the motion estimation region (MER) whose size is signalled in the picture parameter set using the “log2_parallel_merge_level_minus2” syntax element. When a MER is defined, merge candidates falling in the same region are marked as unavailable and therefore not considered in the list construction.

7.3.2.3 Picture parameter set RBSP syntax

7.3.2.3.1 General picture parameter set RBSP syntax

pic_parameter_set_rbsp() {	Descript or
pps_pic_parameter_set_id	ue(v)
pps_seq_parameter_set_id	ue(v)
dependent_slice_segments_enabled_flag	u(1)
...	
pps_scaling_list_data_present_flag	u(1)
if(pps_scaling_list_data_present_flag)	
scaling_list_data()	
lists_modification_present_flag	u(1)
log2_parallel_merge_level_minus2	ue(v)
slice_segment_header_extension_present_flag	u(1)
pps_extension_present_flag	u(1)
...	
rbsp_trailing_bits()	
}	

log2_parallel_merge_level_minus2 plus 2 specifies the value of the variable Log2ParMrgLevel, which is used in the derivation process for luma motion vectors for merge mode as specified in clause 8.5.3.2.2 and the derivation process for spatial merging candidates as specified in clause 8.5.3.2.3. The value of log2_parallel_merge_level_minus2 shall be in the range of 0 to CtbLog2SizeY – 2, inclusive.

The variable Log2ParMrgLevel is derived as follows:

$$\text{Log2ParMrgLevel} = \text{log2_parallel_merge_level_minus2} + 2 \quad (7-37)$$

NOTE 3 – The value of Log2ParMrgLevel indicates the built-in capability of parallel derivation of the merging candidate lists. For example, when Log2ParMrgLevel is equal to 6, the merging

candidate lists for all the prediction units (PUs) and coding units (CUs) contained in a 64x64 block can be derived in parallel.

[00105] 2.2.2 Motion vector prediction in AMVP mode

[00106] Motion vector prediction exploits spatio-temporal correlation of motion vector with neighbouring PUs, which is used for explicit transmission of motion parameters. It constructs a motion vector candidate list by firstly checking availability of left, above temporally neighbouring PU positions, removing redundant candidates and adding zero vector to make the candidate list to be constant length. Then, the encoder can select the best predictor from the candidate list and transmit the corresponding index indicating the chosen candidate. Similarly with merge index signalling, the index of the best motion vector candidate is encoded using truncated unary. The maximum value to be encoded in this case is 2 (e.g., FIGs. 2 to 8). In the following sections, details about derivation process of motion vector prediction candidate are provided.

[00107] 2.2.2.1 Derivation of motion vector prediction candidates

[00108] FIG. 16 summarizes derivation process for motion vector prediction candidate.

[00109] In motion vector prediction, two types of motion vector candidates are considered: spatial motion vector candidate and temporal motion vector candidate. For spatial motion vector candidate derivation, two motion vector candidates are eventually derived based on motion vectors of each PU located in five different positions as depicted in FIG. 11.

[00110] For temporal motion vector candidate derivation, one motion vector candidate is selected from two candidates, which are derived based on two different co-located positions. After the first list of spatio-temporal candidates is made, duplicated motion vector candidates in the list are removed. If the number of potential candidates is larger than two, motion vector candidates whose reference picture index within the associated reference picture list is larger than 1 are removed from the list. If the number of spatio-temporal motion vector candidates is smaller than two, additional zero motion vector candidates is added to the list.

[00111] 2.2.2.2 Spatial motion vector candidates

[00112] In the derivation of spatial motion vector candidates, a maximum of two candidates are considered among five potential candidates, which are derived from PUs located in positions as depicted in FIG. 11, those positions being the same as those of motion merge. The order of derivation for the left side of the current PU is defined as A_0 , A_1 , and scaled A_0 , scaled A_1 . The

order of derivation for the above side of the current PU is defined as B₀, B₁, B₂, scaled B₀, scaled B₁, scaled B₂. For each side there are therefore four cases that can be used as motion vector candidate, with two cases not required to use spatial scaling, and two cases where spatial scaling is used. The four different cases are summarized as follows.

- No spatial scaling
 - (1) Same reference picture list, and same reference picture index (same POC)
 - (2) Different reference picture list, but same reference picture (same POC)
- Spatial scaling
 - (3) Same reference picture list, but different reference picture (different POC)
 - (4) Different reference picture list, and different reference picture (different POC)

[00113] The no-spatial-scaling cases are checked first followed by the spatial scaling. Spatial scaling is considered when the POC is different between the reference picture of the neighbouring PU and that of the current PU regardless of reference picture list. If all PUs of left candidates are not available or are intra coded, scaling for the above motion vector is allowed to help parallel derivation of left and above MV candidates. Otherwise, spatial scaling is not allowed for the above motion vector.

[00114] In a spatial scaling process, the motion vector of the neighbouring PU is scaled in a similar manner as for temporal scaling, as depicted as FIG. 17. The main difference is that the reference picture list and index of current PU is given as input; the actual scaling process is the same as that of temporal scaling.

[00115] 2.2.2.3 Temporal motion vector candidates

[00116] Apart for the reference picture index derivation, all processes for the derivation of temporal merge candidates are the same as for the derivation of spatial motion vector candidates (see, e.g., FIG. 6). The reference picture index is signalled to the decoder.

[00117] 2.2.2.4 Signaling of AMVP information

[00118] For the AMVP mode, four parts may be signalled in the bitstream, i.e., prediction direction, reference index, MVD and mv predictor candidate index.

Syntax tables:

prediction_unit(x0, y0, nPbW, nPbH) {	Descript or
if(cu_skip_flag[x0][y0]) {	
if(MaxNumMergeCand > 1)	
merge_idx [x0][y0]	ae(v)
} else { /* MODE_INTER */	
merge_flag [x0][y0]	ae(v)
if(merge_flag[x0][y0]) {	
if(MaxNumMergeCand > 1)	
merge_idx [x0][y0]	ae(v)
} else {	
if(slice_type == B)	
inter_pred_idc [x0][y0]	ae(v)
if(inter_pred_idc[x0][y0] != PRED_L1) {	
if(num_ref_idx_l0_active_minus1 > 0)	
ref_idx_l0 [x0][y0]	ae(v)
mvd_coding(x0, y0, 0)	
mvp_l0_flag [x0][y0]	ae(v)
}	
if(inter_pred_idc[x0][y0] != PRED_L0) {	
if(num_ref_idx_l1_active_minus1 > 0)	
ref_idx_l1 [x0][y0]	ae(v)
if(mvd_l1_zero_flag && inter_pred_idc[x0][y0] == PRED_BI)	
{	
MvdL1[x0][y0][0] = 0	
MvdL1[x0][y0][1] = 0	
} else	
mvd_coding(x0, y0, 1)	
mvp_l1_flag [x0][y0]	ae(v)
}	
}	
}	
}	

7.3.8.9 Motion vector difference syntax

mvd_coding(x0, y0, refList) {	Descript or
abs_mvd_greater0_flag[0]	ae(v)
abs_mvd_greater0_flag[1]	ae(v)
if(abs_mvd_greater0_flag[0])	
abs_mvd_greater1_flag[0]	ae(v)
if(abs_mvd_greater0_flag[1])	
abs_mvd_greater1_flag[1]	ae(v)
if(abs_mvd_greater0_flag[0]) {	
if(abs_mvd_greater1_flag[0])	
abs_mvd_minus2[0]	ae(v)
mvd_sign_flag[0]	ae(v)
}	
if(abs_mvd_greater0_flag[1]) {	
if(abs_mvd_greater1_flag[1])	
abs_mvd_minus2[1]	ae(v)
mvd_sign_flag[1]	ae(v)
}	
}	

[00119] 2.3 New inter prediction methods in JEM (Joint Exploration Model)

[00120] 2.3.1 Sub-CU based motion vector prediction

[00121] In the JEM with QTBT, each CU can have at most one set of motion parameters for each prediction direction. Two sub-CU level motion vector prediction methods are considered in the encoder by splitting a large CU into sub-CUs and deriving motion information for all the sub-CUs of the large CU. Alternative temporal motion vector prediction (ATMVP) method allows each CU to fetch multiple sets of motion information from multiple blocks smaller than the current CU in the collocated reference picture. In spatial-temporal motion vector prediction (STMVP) method motion vectors of the sub-CUs are derived recursively by using the temporal motion vector predictor and spatial neighbouring motion vector.

[00122] To preserve more accurate motion field for sub-CU motion prediction, the motion compression for the reference frames is currently disabled.

[00123] 2.3.1.1 Alternative temporal motion vector prediction

[00124] In the alternative temporal motion vector prediction (ATMVP) method, the motion

vectors temporal motion vector prediction (TMVP) is modified by fetching multiple sets of motion information (including motion vectors and reference indices) from blocks smaller than the current CU. As shown in FIG. 18, the sub-CUs are square $N \times N$ blocks (N is set to 4 by default).

[00125] ATMVP predicts the motion vectors of the sub-CUs within a CU in two steps. The first step is to identify the corresponding block in a reference picture with a so-called temporal vector. The reference picture is called the motion source picture. The second step is to split the current CU into sub-CUs and obtain the motion vectors as well as the reference indices of each sub-CU from the block corresponding to each sub-CU, as shown in FIG. 18.

[00126] In the first step, a reference picture and the corresponding block is determined by the motion information of the spatial neighbouring blocks of the current CU. To avoid the repetitive scanning process of neighbouring blocks, the first merge candidate in the merge candidate list of the current CU is used. The first available motion vector as well as its associated reference index are set to be the *temporal vector* and the index to the motion source picture. This way, in ATMVP, the corresponding block may be more accurately identified, compared with TMVP, wherein the corresponding block (sometimes called collocated block) is always in a bottom-right or center position relative to the current CU. In one example, if the first merge candidate is from the left neighboring block (i.e., A_1 in FIG. 19), the associated MV and reference picture are utilized to identify the source block and source picture.

[00127] FIG. 19 shows an example of the identification of source block and source picture

[00128] In the second step, a corresponding block of the sub-CU is identified by the temporal vector in the motion source picture, by adding to the coordinate of the current CU the temporal vector. For each sub-CU, the motion information of its corresponding block (the smallest motion grid that covers the center sample) is used to derive the motion information for the sub-CU. After the motion information of a corresponding $N \times N$ block is identified, it is converted to the motion vectors and reference indices of the current sub-CU, in the same way as TMVP of HEVC, wherein motion scaling and other procedures apply. For example, the decoder checks whether the low-delay condition (i.e. the POCs of all reference pictures of the current picture are smaller than the POC of the current picture) is fulfilled and possibly uses motion vector MV_x (the motion vector corresponding to reference picture list X) to predict motion vector MV_y (with X being equal to 0 or 1 and Y being equal to $1-X$) for each sub-CU.

[00129] 2.3.1.2 Spatial-temporal motion vector prediction

[00130] In this method, the motion vectors of the sub-CUs are derived recursively, following raster scan order. FIG. 20 illustrates this concept. Let us consider an 8×8 CU which contains four 4×4 sub-CUs A, B, C, and D. The neighbouring 4×4 blocks in the current frame are labelled as a, b, c, and d.

[00131] The motion derivation for sub-CU A starts by identifying its two spatial neighbours. The first neighbour is the $N \times N$ block above sub-CU A (block c). If this block c is not available or is intra coded the other $N \times N$ blocks above sub-CU A are checked (from left to right, starting at block c). The second neighbour is a block to the left of the sub-CU A (block b). If block b is not available or is intra coded other blocks to the left of sub-CU A are checked (from top to bottom, starting at block b). The motion information obtained from the neighbouring blocks for each list is scaled to the first reference frame for a given list. Next, temporal motion vector predictor (TMVP) of sub-block A is derived by following the same procedure of TMVP derivation as specified in HEVC. The motion information of the collocated block at location D is fetched and scaled accordingly. Finally, after retrieving and scaling the motion information, all available motion vectors (up to 3) are averaged separately for each reference list. The averaged motion vector is assigned as the motion vector of the current sub-CU.

[00132] FIG. 20 shows an example of one CU with four sub-blocks (A-D) and its neighbouring blocks (a-d).

[00133] 2.3.1.3 Sub-CU motion prediction mode signalling

[00134] The sub-CU modes are enabled as additional merge candidates and there is no additional syntax element required to signal the modes. Two additional merge candidates are added to merge candidates list of each CU to represent the ATMVP mode and STMVP mode. Up to seven merge candidates are used, if the sequence parameter set indicates that ATMVP and STMVP are enabled. The encoding logic of the additional merge candidates is the same as for the merge candidates in the HM, which means, for each CU in P or B slice, two more RD checks is needed for the two additional merge candidates.

[00135] In the JEM, all bins of merge index is context coded by CABAC. While in HEVC, only the first bin is context coded and the remaining bins are context by-pass coded.

[00136] 2.3.2 Adaptive motion vector difference resolution

[00137] In HEVC, motion vector differences (MVDs) (between the motion vector and

predicted motion vector of a PU) are signalled in units of quarter luma samples when use_integer_mv_flag is equal to 0 in the slice header. In the JEM, a locally adaptive motion vector resolution (LAMVR) is introduced. In the JEM, MVD can be coded in units of quarter luma samples, integer luma samples or four luma samples. The MVD resolution is controlled at the coding unit (CU) level, and MVD resolution flags are conditionally signalled for each CU that has at least one non-zero MVD components.

[00138] For a CU that has at least one non-zero MVD components, a first flag is signalled to indicate whether quarter luma sample MV precision is used in the CU. When the first flag (equal to 1) indicates that quarter luma sample MV precision is not used, another flag is signalled to indicate whether integer luma sample MV precision or four luma sample MV precision is used.

[00139] When the first MVD resolution flag of a CU is zero, or not coded for a CU (meaning all MVDs in the CU are zero), the quarter luma sample MV resolution is used for the CU. When a CU uses integer-luma sample MV precision or four-luma-sample MV precision, the MVPs in the AMVP candidate list for the CU are rounded to the corresponding precision.

[00140] In the encoder, CU-level RD checks are used to determine which MVD resolution is to be used for a CU. That is, the CU-level RD check is performed three times for each MVD resolution. To accelerate encoder speed, the following encoding schemes are applied in the JEM.

[00141] During RD check of a CU with normal quarter luma sample MVD resolution, the motion information of the current CU (integer luma sample accuracy) is stored. The stored motion information (after rounding) is used as the starting point for further small range motion vector refinement during the RD check for the same CU with integer luma sample and 4 luma sample MVD resolution so that the time-consuming motion estimation process is not duplicated three times.

[00142] RD check of a CU with 4 luma sample MVD resolution is conditionally invoked. For a CU, when RD cost integer luma sample MVD resolution is much larger than that of quarter luma sample MVD resolution, the RD check of 4 luma sample MVD resolution for the CU is skipped.

[00143] **2.3.3 Pattern matched motion vector derivation**

[00144] Pattern matched motion vector derivation (PMMVD) mode is a special merge mode based on Frame-Rate Up Conversion (FRUC) techniques. With this mode, motion information of a block is not signalled but derived at decoder side.

[00145] A FRUC flag is signalled for a CU when its merge flag is true. When the FRUC flag is false, a merge index is signalled and the regular merge mode is used. When the FRUC flag is true, an additional FRUC mode flag is signalled to indicate which method (bilateral matching or template matching) is to be used to derive motion information for the block.

[00146] At encoder side, the decision on whether using FRUC merge mode for a CU is based on RD cost selection as done for normal merge candidate. That is the two matching modes (bilateral matching and template matching) are both checked for a CU by using RD cost selection. The one leading to the minimal cost is further compared to other CU modes. If a FRUC matching mode is the most efficient one, FRUC flag is set to true for the CU and the related matching mode is used.

[00147] Motion derivation process in FRUC merge mode has two steps. A CU-level motion search is first performed, then followed by a Sub-CU level motion refinement. At CU level, an initial motion vector is derived for the whole CU based on bilateral matching or template matching. First, a list of MV candidates is generated and the candidate which leads to the minimum matching cost is selected as the starting point for further CU level refinement. Then a local search based on bilateral matching or template matching around the starting point is performed and the MV results in the minimum matching cost is taken as the MV for the whole CU. Subsequently, the motion information is further refined at sub-CU level with the derived CU motion vectors as the starting points.

[00148] For example, the following derivation process is performed for a $W \times H$ CU motion information derivation. At the first stage, MV for the whole $W \times H$ CU is derived. At the second stage, the CU is further split into $M \times M$ sub-CUs. The value of M is calculated as in (16), D is a predefined splitting depth which is set to 3 by default in the JEM. Then the MV for each sub-CU is derived.

$$M = \max\{4, \min\{\frac{M}{2^D}, \frac{N}{2^D}\}\} \quad (1)$$

[00149] As shown in the FIG. 21, the bilateral matching is used to derive motion information of the current CU by finding the closest match between two blocks along the motion trajectory of the current CU in two different reference pictures. Under the assumption of continuous motion trajectory, the motion vectors MV0 and MV1 pointing to the two reference blocks shall be proportional to the temporal distances, i.e., TD0 and TD1, between the current picture and the

two reference pictures. As a special case, when the current picture is temporally between the two reference pictures and the temporal distance from the current picture to the two reference pictures is the same, the bilateral matching becomes mirror based bi-directional MV.

[00150] As shown in FIG. 22, template matching is used to derive motion information of the current CU by finding the closest match between a template (top and/or left neighbouring blocks of the current CU) in the current picture and a block (same size to the template) in a reference picture. Except the aforementioned FRUC merge mode, the template matching is also applied to AMVP mode. In the JEM, as done in HEVC, AMVP has two candidates. With template matching method, a new candidate is derived. If the newly derived candidate by template matching is different to the first existing AMVP candidate, it is inserted at the very beginning of the AMVP candidate list and then the list size is set to two (meaning remove the second existing AMVP candidate). When applied to AMVP mode, only CU level search is applied.

[00151] 2.3.3.1 CU level MV candidate set

[00152] The MV candidate set at CU level consists of:

- (i) Original AMVP candidates if the current CU is in AMVP mode
- (ii) all merge candidates,
- (iii) several MVs in the interpolated MV field.
- (iv) top and left neighbouring motion vectors

[00153] When using bilateral matching, each valid MV of a merge candidate is used as an input to generate a MV pair with the assumption of bilateral matching. For example, one valid MV of a merge candidate is (MV_a, ref_a) at reference list A. Then the reference picture ref_b of its paired bilateral MV is found in the other reference list B so that ref_a and ref_b are temporally at different sides of the current picture. If such a ref_b is not available in reference list B, ref_b is determined as a reference which is different from ref_a and its temporal distance to the current picture is the minimal one in list B. After ref_b is determined, MV_b is derived by scaling MV_a based on the temporal distance between the current picture and ref_a, ref_b.

[00154] Four MVs from the interpolated MV field are also added to the CU level candidate list. More specifically, the interpolated MVs at the position (0, 0), (W/2, 0), (0, H/2) and (W/2, H/2) of the current CU are added.

[00155] When FRUC is applied in AMVP mode, the original AMVP candidates are also added to CU level MV candidate set.

[00156] At the CU level, up to 15 MVs for AMVP CUs and up to 13 MVs for merge CUs are added to the candidate list.

[00157] **2.3.3.2 Sub-CU level MV candidate set**

[00158] The MV candidate set at sub-CU level consists of:

- (i) an MV determined from a CU-level search,
- (ii) top, left, top-left and top-right neighbouring MVs,
- (iii) scaled versions of collocated MVs from reference pictures,
- (iv) up to 4 ATMVP candidates,
- (v) up to 4 STMVP candidates

[00159] The scaled MVs from reference pictures are derived as follows. All the reference pictures in both lists are traversed. The MVs at a collocated position of the sub-CU in a reference picture are scaled to the reference of the starting CU-level MV.

[00160] ATMVP and STMVP candidates are limited to the four first ones.

[00161] At the sub-CU level, up to 17 MVs are added to the candidate list.

[00162] **2.3.3.3 Generation of interpolated MV field**

[00163] Before coding a frame, interpolated motion field is generated for the whole picture based on unilateral ME. Then the motion field may be used later as CU level or sub-CU level MV candidates.

[00164] First, the motion field of each reference pictures in both reference lists is traversed at 4×4 block level. For each 4×4 block, if the motion associated to the block passing through a 4×4 block in the current picture (as shown in FIG. 23) and the block has not been assigned any interpolated motion, the motion of the reference block is scaled to the current picture according to the temporal distance TD0 and TD1 (the same way as that of MV scaling of TMVP in HEVC) and the scaled motion is assigned to the block in the current frame. If no scaled MV is assigned to a 4×4 block, the block's motion is marked as unavailable in the interpolated motion field.

[00165] **2.3.3.4 Interpolation and matching cost**

[00166] When a motion vector points to a fractional sample position, motion compensated interpolation is needed. To reduce complexity, bi-linear interpolation instead of regular 8-tap HEVC interpolation is used for both bilateral matching and template matching.

[00167] The calculation of matching cost is a bit different at different steps. When selecting the candidate from the candidate set at the CU level, the matching cost is the absolute sum

difference (SAD) of bilateral matching or template matching. After the starting MV is determined, the matching cost C of bilateral matching at sub-CU level search is calculated as follows:

$$C = SAD + w \cdot (|MV_x - MV_x^s| + |MV_y - MV_y^s|) \quad (2)$$

[00168] where w is a weighting factor which is empirically set to 4, MV and MV^s indicate the current MV and the starting MV, respectively. SAD is still used as the matching cost of template matching at sub-CU level search.

[00169] In FRUC mode, MV is derived by using luma samples only. The derived motion will be used for both luma and chroma for MC inter prediction. After MV is decided, final MC is performed using 8-taps interpolation filter for luma and 4-taps interpolation filter for chroma.

[00170] 2.3.3.5 MV refinement

[00171] MV refinement is a pattern based MV search with the criterion of bilateral matching cost or template matching cost. In the JEM, two search patterns are supported – an unrestricted center-biased diamond search (UCBDS) and an adaptive cross search for MV refinement at the CU level and sub-CU level, respectively. For both CU and sub-CU level MV refinement, the MV is directly searched at quarter luma sample MV accuracy, and this is followed by one-eighth luma sample MV refinement. The search range of MV refinement for the CU and sub-CU step are set equal to 8 luma samples.

[00172] 2.3.3.6 Selection of prediction direction in template matching FRUC merge mode

[00173] In the bilateral matching merge mode, bi-prediction is always applied since the motion information of a CU is derived based on the closest match between two blocks along the motion trajectory of the current CU in two different reference pictures. There is no such limitation for the template matching merge mode. In the template matching merge mode, the encoder can choose among uni-prediction from list0, uni-prediction from list1 or bi-prediction for a CU. The selection is based on a template matching cost as follows:

If $cost_{Bi} \leq factor * \min(cost0, cost1)$

bi-prediction is used;

Otherwise, if $cost0 \leq cost1$

uni-prediction from list0 is used;

Otherwise,

uni-prediction from list1 is used;

[00174] where cost0 is the SAD of list0 template matching, cost1 is the SAD of list1 template matching and costBi is the SAD of bi-prediction template matching. The value of *factor* is equal to 1.25, which means that the selection process is biased toward bi-prediction.

The inter prediction direction selection is only applied to the CU-level template matching process.

[00175] 2.3.4 Decoder-side motion vector refinement

[00176] In bi-prediction operation, for the prediction of one block region, two prediction blocks, formed using a motion vector (MV) of list0 and a MV of list1, respectively, are combined to form a single prediction signal. In the decoder-side motion vector refinement (DMVR) method, the two motion vectors of the bi-prediction are further refined by a bilateral template matching process. The bilateral template matching applied in the decoder to perform a distortion-based search between a bilateral template and the reconstruction samples in the reference pictures in order to obtain a refined MV without transmission of additional motion information.

[00177] In DMVR, a bilateral template is generated as the weighted combination (i.e. average) of the two prediction blocks, from the initial MV0 of list0 and MV1 of list1, respectively, as shown in FIG. 23. The template matching operation consists of calculating cost measures between the generated template and the sample region (around the initial prediction block) in the reference picture. For each of the two reference pictures, the MV that yields the minimum template cost is considered as the updated MV of that list to replace the original one. In the JEM, nine MV candidates are searched for each list. The nine MV candidates include the original MV and 8 surrounding MVs with one luma sample offset to the original MV in either the horizontal or vertical direction, or both. Finally, the two new MVs, i.e., MV0' and MV1' as shown in FIG. 24, are used for generating the final bi-prediction results. A sum of absolute differences (SAD) is used as the cost measure.

[00178] DMVR is applied for the merge mode of bi-prediction with one MV from a reference picture in the past and another from a reference picture in the future, without the transmission of additional syntax elements. In the JEM, when LIC, affine motion, FRUC, or sub-CU merge candidate is enabled for a CU, DMVR is not applied.

[00179] 2.3.5 Merge/Skip mode with Bilateral Matching refinement

[00180] A merge candidate list is first constructed by inserting the motion vectors and reference indices of the spatial neighboring and temporal neighboring blocks into the candidate list with redundancy checking until the number of the available candidates reaches the maximum candidate size of 19. The merge candidate list for the merge/skip mode is constructed by inserting spatial candidates (FIG. 11), temporal candidates, affine candidates, advanced temporal MVP (ATMVP) candidate, spatial temporal MVP (STMVP) candidate and the additional candidates as used in HEVC (Combined candidates and Zero candidates) according to a pre-defined insertion order:

[00181] - Spatial candidates for blocks 1-4.

[00182] - Extrapolated affine candidates for blocks 1-4.

[00183] - ATMVP.

[00184] - STMVP.

[00185] - Virtual affine candidate.

[00186] - Spatial candidate (block 5) (used only when the number of the available candidates is smaller than 6).

[00187] - Extrapolated affine candidate (block 5).

[00188] - Temporal candidate (derived as in HEVC).

[00189] - Non-adjacent spatial candidates followed by extrapolated affine candidate (blocks 6 to 49, as depicted in FIG. 25).

[00190] - Combined candidates.

[00191] - Zero candidates

[00192] It is noted that IC flags are also inherited from merge candidates except for STMVP and affine. Moreover, for the first four spatial candidates, the bi-prediction ones are inserted before the ones with uni-prediction.

[00193] In [8], blocks which are not connected with the current block may be accessed. If a non-adjacent block is coded with non-intra mode, the associated motion information may be added as an additional merge candidate.

[00194] **3. Examples of Problems Addressed by Embodiments disclosed herein**

[00195] The current HEVC design could take the correlation of current block its neighbouring blocks (next to the current block) to better code the motion information. However, it is possible that that the neighbouring blocks correspond to different objects with different motion

trajectories. In this case, prediction from its neighbouring blocks is not efficient.

[00196] Prediction from motion information of non-adjacent blocks could bring additional coding gain with the cost of storing all the motion information (typically on 4x4 level) into cache which significantly increase the complexity for hardware implementation.

[00197] **4. Some Examples**

[00198] Embodiments of the presently disclosed technology overcome the drawbacks of existing implementations, thereby providing video coding with higher coding efficiencies.

[00199] To overcome the drawbacks of existing implementations, LUT-based motion vector prediction techniques using one or more tables (e.g., look up tables) with at least one motion candidate stored to predict motion information of a block can be implemented in various embodiments to provide video coding with higher coding efficiencies. A look up table is an example of a table which can be used to include motion candidates to predict motion information of a block and other implementations are also possible. Each LUT can include one or more motion candidates, each associated with corresponding motion information. Motion information of a motion candidate can include partial or all of the prediction direction, reference indices/pictures, motion vectors, LIC flags, affine flags, Motion Vector Derivation (MVD) precisions, and/or MVD values. Motion information may further include the block position information to indicate from which the motion information is coming.

[00200] The LUT-based motion vector prediction based on the disclosed technology, which may enhance both existing and future video coding standards, is elucidated in the following examples described for various implementations. Because the LUTs allow the encoding/decoding process to be performed based on historical data (e.g., the blocks that have been processed), the LUT-based motion vector prediction can also be referred to as History-based Motion Vector Prediction (HMVP) method. In the LUT-based motion vector prediction method, one or multiple tables with motion information from previously coded blocks are maintained during the encoding/decoding process. These motion candidates stored in the LUTs are named HMVP candidates. During the encoding/decoding of one block, the associated motion information in LUTs may be added to the motion candidate lists (e.g., merge/AMVP candidate lists), and after encoding/decoding one block, LUTs may be updated. The updated LUTs are then used to code the subsequent blocks. That is, the updating of motion candidates in the LUTs are based on the encoding/decoding order of blocks. The examples below should be considered as

examples to explain general concepts. These examples should not be interpreted in a narrow way. Furthermore, these examples can be combined in any manner.

[00201] The examples below should be considered as examples to explain general concepts. These examples should not be interpreted in a narrow way. Furthermore, these examples can be combined in any manner.

[00202] Some embodiments may use one or more look up tables with at least one motion candidate stored to predict motion information of a block. Embodiments may use motion candidate to indicate a set of motion information stored in a look up table. For conventional AMVP or merge modes, embodiments may use AMVP or merge candidates for storing the motion information.

[00203] The examples below explain general concepts.

[00204] Examples of tables

[00205] Example A1: Each look up table may contain one or more motion candidates wherein each candidate is associated with its motion information.

- a. Motion information of a motion candidate here may include partial or all of the prediction direction, reference indices/pictures, motion vectors, LIC flag, affine flag, MVD precision, MVD values.
- b. Motion information may further include the block position information and/or block shape to indicate wherein the motion information is coming from.
- c. A counter may be further assigned for each look up table.
- d. The table size (number of allowed motion candidates) and/or number of tables may be the fixed or adaptive. The table size may be same for all tables, or different for different tables.

[00206] Selection of LUTs

[00207] Example B1: For coding a block, partial or all of motion candidates from one look up table may be checked in order. When one motion candidate is checked during coding a block, it may be added to the motion candidate list (e.g., AMVP, merge candidate lists).

[00208] Usage of look up tables

[00209] Example C1: The total number of motion candidates in a look up table to be checked may be pre-defined.

[00210] Example C2: The motion candidate(s) included in a look up table may be directly inherited by a block.

- a. They may be used for the merge mode coding, i.e., motion candidates may be checked in the merge candidate list derivation process.

[00211] Example C3: The motion candidate(s) included in a look up table may be used as a predictor for coding motion information of a block.

- a. They may be used for the AMVP mode coding, i.e., motion candidates may be checked in the AMVP candidate list derivation process.

[00212] Example C4: The checking order of motion candidates in a look up table is defined as follows (suppose K ($K \geq 1$) motion candidates are allowed to be checked):

- a. The last K motion candidates in the look up table, e.g., in descending order of entry indices to the LUT.

[00213] Example C5: Enabling/disabling the usage look up tables for motion information coding of a block may be signalled in SPS, PPS, Slice header, tile header, CTU, CTB, CU or PU, region covering multiple CTU/CTB/CU/PUs.

[00214] Example C6: Whether to apply prediction from look up tables may further depend on the coded information. When it is inferred not to apply for a block, additional signaling of indications of the prediction is skipped. Alternatively, when it is inferred not to apply for a block, there is no need to access motion candidates of look up tables, and the checking of related motion candidates is omitted.

[00215] Example C7: Motion candidates of a look up table in previously coded frames/slices/tiles may be used to predict motion information of a block in a different frame/slice/tile.

[00216] Update of look up tables

[00217] Example D1: After coding a block with motion information (i.e., IntraBC mode, inter coded mode), one or multiple look up tables may be updated.

- a. In one example, whether to update a look up table may reuse the rules for selecting look up tables, e.g., when a look up table could be selected for coding

the current block, after coding/decoding the block, the selected look up table may further be updated.

- b. Look up tables to be updated may be selected based on coded information, and/or positions of the block/LCU.
- c. If the block is coded with motion information directly signaled (such as AMVP mode, MMVD mode for normal/affine inter mode, AMVR mode for normal/affine inter mode), the motion information for the block may be added to a look up table.
 - i. Alternatively, if the block is coded with motion information directly inherited from a spatial neighboring block without any refinement (e.g., spatial merge candidate without refinement), the motion information for the block shouldn't be added to a look up table.
 - ii. Alternatively, if the block is coded with motion information directly inherited from a spatial neighboring block with refinement (such as DMVR, FRUC), the motion information for the block shouldn't be added to any look up table.
 - iii. Alternatively, if the block is coded with motion information directly inherited from a motion candidate stored in a look up table, the motion information for the block shouldn't be added to any look up table.
 - iv. In one example, such motion information may be directly added to the look up table, such as to the last entry of the table or to the entry which is used for storing the next available motion candidate.
 - v. Alternatively, such motion information may be directly added to the look up table without pruning, e.g., without any pruning.
 - vi. Alternatively, such motion information may be used to reorder the look up table.
 - vii. Alternatively, such motion information may be used to update the look up table with limited pruning. In various implementations, the pruning may include a) comparing the motion information with existing entries for uniqueness, b) if unique, then adding the motion information to the

- list, c) if not unique, then either c1) not adding or c2) adding the motion information and deleting existing entry that matched.
- d. $M (M \geq 1)$ representative position within the block is chosen and the motion information associated with the representative position is used to update look up tables.
- i. In one example, the representative position is defined as one of the four corner positions (e.g., C0-C3 in FIG. 26) within the block.
 - ii. In one example, the representative position is defined as the center position (e.g., Ca – Cd in FIG. 26) within the block.
 - iii. When sub-block prediction is disallowed for block, M is set to 1.
 - iv. When sub-block prediction is allowed for block, M could be set to 1 or total number of sub-blocks or any other value between [1, number of sub-blocks] exclusively.
 - v. Alternatively, when sub-block prediction is allowed for block, M could be set to 1 and the selection of a representative sub-block is based on
 1. the frequency of utilized motion information,
 2. whether it is a bi-prediction block
 3. based on the reference picture index/reference picture
 4. motion vector differences compared to other motion vectors (e.g., selecting the maximum MV differences)
 5. other coded information.
- e. When $M (M \geq 1)$ sets of representative positions are selected to update look up tables, further conditions may be checked before adding them as additional motion candidates to look up tables.
- i. Pruning may be applied to the new sets of motion information to the existing motion candidates in the look up table.
 - ii. In one example, a new set of motion information shouldn't be identical to any or partial of existing motion candidates in the look up table.
 - iii. Alternatively, for same reference pictures from a new set of motion information and one existing motion candidate, the MV difference should be no smaller than one/multiple thresholds. For example,

horizontal and/or vertical component of the MV difference should be larger than 1-pixel distance.

- iv. Alternatively, the new sets of motion information are only pruned with the last K candidates or the first $K\%L$ existing motion candidates when $K > L$ to allow reactivating the old motion candidates.
 - v. Alternatively, no pruning is applied.
- f. If M sets of motion information are used to update a look up table, the corresponding counter should be increased by M.
- g. Suppose a counter of a look up table to be updated is denoted by K before coding the current block, after coding the block, for one selected set of motion information (with methods mentioned above, it is added as an additional motion candidate with index equal to $K\%L$ (wherein L is the look up table size)). Examples are shown in FIG. 27A and 27B.
- i. Alternatively, it is added as an additional motion candidate with index equal to $\min(K+1, L-1)$. Alternatively, furthermore, if $K \geq L$, the first motion candidate (index equal to 0) is removed from the look-up table, and the following K candidates indices are reduced by 1.
 - ii. For above both methods (either adding the new motion candidate to entry index equal to $K\%L$ or adding it with index equal to $\min(K+1, L-1)$), they are trying to keep the latest few sets of motion information from previously coded blocks regardless whether there are identical/similar motion candidates.
 - iii. Alternatively, when adding a new set of motion information as a motion candidate to a LUT, redundancy checking is firstly applied. In this case, the LUT will keep the latest several sets of motion information from previously coded blocks, however, redundant ones may be removed from LUTs. Such a method is called redundancy-removal based LUT updating method.
 - 1. If there are redundant motion candidates in the LUT, the counter associated with the LUT may be not increased or decreased.

2. The redundant checking may be defined as the pruning process in merge candidate list construction process, e.g., checking whether the reference pictures/reference picture indices are the same, and motion vector differences are within a range or identical.
3. If there is a redundant motion candidate found in a LUT, the redundant motion candidate is moved from its current position to the last one of the LUT.
 - a. Similarly, if there is a redundant motion candidate found in a LUT, this redundant motion candidate is removed from the LUT. In addition, all the motion candidates inserted to LUT after the redundant motion candidate move forward to refill the removed entry of the redundant motion candidate. After the shifting, the new motion candidate is added to the LUT.
 - b. In this case, the counter is kept unchanged.
 - c. Once a redundant motion candidate is identified in a LUT, the redundant checking process is terminated.
4. Multiple redundant motion candidates may be identified. In this case, all of them are removed from the LUT. In addition, all of the remaining motion candidates may move forward in order.
 - a. In this case, the counter is decreased by (number of redundant motion candidates minus 1).
 - b. The redundant checking process is terminated after identifying $maxR$ redundant motion candidates ($maxR$ is a positive integer variable).
5. The redundancy checking process may start from the first to the last motion candidate (i.e., in the order of added to LUTs, in the order of decoding process of blocks where motion information is from).

6. Alternatively, when there are redundant motion candidates in LUT, instead of removing one or multiple of redundant ones from LUTs, virtual motion candidates may be derived from redundant ones and the virtual motion candidates may be used to replace the redundant ones.
 - a. Virtual motion candidates may be derived from a redundant motion candidate by adding offset(s) to horizontal and/or vertical component of one or multiple motion vectors; or average of two motion vectors if pointing to the same reference pictures. Alternatively, the virtual motion candidate may be derived from any function with motion vectors in the look up table as the input. Exemplary functions are: Adding two or more motion vectors together; Averaging two or more motion vectors. The motion vectors may be scaled before being input into the function.
 - b. Virtual motion candidates may be added to the same position as the redundant motion candidates.
 - c. Virtual motion candidates may be added before all the other motion candidates (e.g., starting from smallest entry indices, like zero).
 - d. In one example, it is applied only under certain conditions, such as when the current LUT is not full.
7. The redundancy-removal based LUT updating method may be invoked under certain conditions, such as
 - a. the current block is coded with merge mode,
 - b. the current block is coded with AMVP mode but with at least one component of MV difference is non-zero;
 - c. the current block is or is not coded with sub-block based motion prediction/motion compensation methods (e.g., not coded with affine mode)

- d. the current block is coded with merge mode and the motion information is associated with a certain type (e.g., from the spatial neighboring blocks, from the left neighboring block, from the temporal block)
- h. After encoding/decoding one block, one or more look-up tables may be updated by just inserting the M sets of motion information to the end of the table, i.e., after all existing candidates.
 - i. Alternatively, furthermore, some existing motion candidates in the table may be removed.
 - 1. In one example, if the table is full after inserting the M sets of motion information, the first several entries of motion candidates may be removed from the table.
 - 2. In one example, if the table is full before inserting the M sets of motion information, the first several entries of motion candidates may be removed from the table.
 - ii. Alternatively, furthermore, if the block is coded with a motion candidate from a table, the motion candidates in the table may be reordered so that the selected motion candidate is put to the last entry of the table.
 - 1. In one example, before encoding/decoding a block, a look-up table may include motion candidates denoted by $HMVP_0$, $HMVP_1$, $HMVP_2$, ..., $HMVP_{K-1}$, $HMVP_K$, $HMVP_{K+1}$, ..., $HMVP_{L-1}$ wherein $HMVP_i$ denotes the i-th entry in the look-up table. If the block is predicted from $HMVP_K$ (K is within the range $[0, L-1]$, inclusively), after encoding/decoding this block, the look-up table is re-ordered to: $HMVP_0$, $HMVP_1$, $HMVP_2$, ..., $HMVP_{K-1}$, $HMVP_K$, $HMVP_{K+1}$, ..., $HMVP_{L-1}$, $HMVP_K$.
- i. The look-up table may be emptied after coding one intra-constrained block.
- j. If an entry of motion information is added into the lookup table, more entries of motion information may also be added into the table by derivation from the motion information. In this case, the counter associated with the look up table may be increased more than 1.

- i. In one example, the MV of an entry of motion information is scaled and put into the table;
- ii. In one example, the MV of an entry of motion information is added by (dx, dy) and put into the table;
- iii. In one example, the average of MVs of two or more entries of motion information is calculated and put into the table.

[00218] Example D2: If one block is located at a picture/slice/tile border, updating of look up tables may be always disallowed.

[00219] Example D3: Motion information of above LCU rows may be disabled to code the current LCU row.

- a. In this case, at the beginning of a new slice/tile/LCU row, the number of available motion candidates may be reset to 0.

[00220] Example D4: At the beginning of coding a slice/tile with a new temporal layer index, the number of available motion candidates may be reset to 0.

[00221] Example D5: The look up table may be continuously updated with one slice/tile/LCU row/slices with same temporal layer index.

- a. Alternatively, the look up table may be updated only after coding/decoding each S ($S \geq 1$) CTUs/CTBs/CUs/CBs or after coding/decoding a certain region (e.g., size equal to 8×8 or 16×16).
- b. Alternatively, the look up table may be updated only after coding/decoding each S ($S \geq 1$) blocks (e.g., CUs/CBs) with certain modes (e.g., S inter-coded blocks). Alternatively, the look up table may be updated only after coding/decoding each S ($S \geq 1$) inter-coded blocks (e.g., CUs/CBs) which are not coded with sub-block based motion prediction/motion compensation method (e.g., not coded with affine and/or ATMVP mode).
- c. Alternatively, the look up table may be updated only when the left-top coordinate of the coded/decoded block satisfies some conditions. For example, the look up table is updated only when $(x \& M == 0) \& (y \& M == 0)$, where (x, y) is left-top coordinate of the coded/decoded block. M is an integer such as 2, 4, 8, 16, 32, or 64.

- d. Alternatively, one look up table may stop updating once it reaches a maximumly allowed counter.
- e. In one example, the counter may be predefined. Alternatively, it be signalled in Video Parameter Set (VPS), Sequence Parameter Set (SPS), Picture Parameter Set (PPS), Slice header, tile header, Coding Tree Unit (CTU), Coding Tree Block (CTB), Coding Unit (CU) or Prediction Unit (PU), region covering multiple CTU/CTB/CU/PUs.

[00222] Example D6: Look up table updating process may be invoked within different procedures.

- a. In one example, for a block coded with merge mode, the look up table updating process may be invoked after decoding the merge candidate or after constructing the merge list or after decoding the motion information with and/or without refinement.
- b. In one example, for a block coded with AMVP mode, the look up table updating process may be invoked after decoding the motion information with and/or without refinement.
- c. When and/or how to update the look up table may depend on the coded mode, block dimension, video processing data unit, low delay check, etc.
 - i. In one example, when one block is coded with AMVP mode, look up table may be directly updated without pruning.
 - ii. Alternatively, when one block is coded with merge mode, look up table may be updated with pruning.
 - iii. Alternatively, when one block is coded with merge mode and its motion information is derived from spatial and/or temporal blocks, look up table may be updated with pruning.
 - iv. Alternatively, when one block is coded with merge mode and its motion information is derived from motion candidates in a look up table, look up table may be reordered without pruning.
 - v. Alternatively, when one block is coded with merge mode and its motion information is derived from virtual candidates (e.g., combined bi,

pairwise, zero motion vector candidates) in a look up table, look up table may not be updated.

- vi. Alternatively, when one block is coded with sub-block merge mode and/or triangular merge mode, look up table may not be updated.
- vii. Alternatively, when one block is coded with the merge with motion vector differences (MMVD) mode and its motion information is derived from spatial and/or temporal blocks, look up table may be directly updated.
- viii. In one example, when one block is coded with illumination compensation (IC) mode and/or Overlapped Block Motion Compensation (OBMC) mode and/or Decode-side Motion Vector Derivation (DMVD) mode, look up table may not be updated. Alternatively, when one block is coded with such a mode, look up table may be updated.

[00223] Additional Example Embodiments

[00224] A history-based MVP (HMVP) method is proposed wherein a HMVP candidate is defined as the motion information of a previously coded block. A table with multiple HMVP candidates is maintained during the encoding/decoding process. The table is emptied when a new slice is encountered. Whenever there is an inter-coded block, the associated motion information is added to the last entry of the table as a new HMVP candidate. The overall coding flow is depicted in FIG. 31.

[00225] In one example, the table size is set to be L (e.g., L = 16 or 6, or 44), which indicates up to L HMVP candidates may be added to the table.

[00226] In one embodiment (corresponding to example D1.g.i), if there are more than L HMVP candidates from the previously coded blocks, a First-In-First-Out (FIFO) rule is applied so that the table always contains the latest previously coded L motion candidates. FIG. 32 depicts an example wherein the FIFO rule is applied to remove a HMVP candidate and add a new one to the table used in the proposed method.

[00227] In another embodiment (corresponding to example D1.g.iii), whenever adding a new motion candidate (such as the current block is inter-coded and non-affine mode), a redundancy checking process is applied firstly to identify whether there are identical or similar motion

candidates in LUTs.

[00228] Some examples are depicted as follows:

[00229] FIG. 33A shows an example when the LUT is full before adding a new motion candidate.

[00230] FIG. 33B shows an example when the LUT is not full before adding a new motion candidate.

[00231] FIG. 33A and 33B together show an example of redundancy-removal based LUT updating method (with one redundancy motion candidate removed).

[00232] FIG. 34A and 34B show example implementation for two cases of the redundancy-removal based LUT updating method (with multiple redundancy motion candidates removed, 2 candidates in the figures)

[00233] FIG. 34A shows an example case of when the LUT is full before adding a new motion candidate.

[00234] FIG. 34B shows an example case of When the LUT is not full before adding a new motion candidate

[00235] HMVP candidates could be used in the merge candidate list construction process. All HMVP candidates from the last entry to the first entry (or the last $K0$ HMVP, e.g., $K0$ equal to 16 or 6) in the table are inserted after the TMVP candidate. Pruning is applied on the HMVP candidates. Once the total number of available merge candidates reaches the signaled maximally allowed merge candidates, the merge candidate list construction process is terminated.

Alternatively, once the total number of added motion candidates reaches a given value, the fetching of motion candidates from LUTs is terminated.

[00236] Similarly, HMVP candidates could also be used in the AMVP candidate list construction process. The motion vectors of the last $K1$ HMVP candidates in the table are inserted after the TMVP candidate. Only HMVP candidates with the same reference picture as the AMVP target reference picture are used to construct the AMVP candidate list. Pruning is applied on the HMVP candidates. In one example, $K1$ is set to 4.

[00237] FIG. 28 is a block diagram of a video processing apparatus 2800. The apparatus 2800 may be used to implement one or more of the methods described herein. The apparatus 2800 may be embodied in a smartphone, tablet, computer, Internet of Things (IoT) receiver, and so on. The apparatus 2800 may include one or more processors 2802, one or more memories 2804 and

video processing hardware 2806. The processor(s) 2802 may be configured to implement one or more methods described in the present document. The memory (memories) 2804 may be used for storing data and code used for implementing the methods and techniques described herein. The video processing hardware 2806 may be used to implement, in hardware circuitry, some techniques described in the present document.

[00238] FIG. 29 is a flowchart for an example of a video decoding method 2900. The method 2900 includes, at step 2902, maintaining one or more tables, wherein each table includes one or more motion candidates and each motion candidate is associated with corresponding motion information. The method 2900 further includes, at step 2904, performing a conversion between a current block and a bitstream representation of a video including the current block by using motion information in a table. The method 2900 further includes, at step 2906, updating, after performing of the conversion, one or more tables based on M sets of additional motion information associated with the current block, M being an integer.

[00239] FIG. 30 is a flowchart for an example of video decoding method 3000. The method 3000 includes, at step 3002, performing a conversion between a current block and a bitstream representation of a video including the current block by using one or more tables, wherein each table includes a one or more motion candidates and each motion candidate is associated with corresponding motion information. The method 3000 further includes, at step 3004, updating, based on the conversion, one or more tables, based on M sets of additional motion information associated with the current block, M being an integer.

[00240] With respect to methods 2900 and 3000, in some embodiments, the motion information includes at least one of: a prediction direction, a reference picture index, motion vector values, intensity compensation flag, affine flag, motion vector difference precision, and motion vector difference value. Further, the motion information may further include block position information indicating source of the motion information. In some embodiments, the video block may be a CU or a PU and the portion of video may correspond to one or more video slices or one or more video pictures.

[00241] In some embodiments, each LUT includes an associated counter, wherein the counter is initialized to a zero value at beginning of the portion of video and increased for each encoded video region in the portion of the video. The video region comprises one of a coding tree unit, a coding tree block, a coding unit, a coding block or a prediction unit. In some embodiments, the

counter indicates, for a corresponding LUT, a number of motion candidates that were removed from the corresponding LUT. In some embodiments, the set of motion candidates may have a same size for all LUTs. In some embodiments, the portion of video corresponds to a slice of video, and wherein the number of LUTs is equal to $N \times P$, wherein N is an integer representing LUTs per decoding thread, and P is an integer representing a number of Largest Coding Unit rows or a number of tiles in the slice of video. Additional details of the methods 2900 and 3000 are described in the examples provided in Section 4 and the examples listed below.

[00242] Additional features and embodiments of the above-described methods/techniques are described below using a clause-based description format.

[00243] 1. A video processing method, comprising: maintaining one or more tables, wherein each table includes one or more motion candidates and each motion candidate is associated with corresponding motion information; performing a conversion between a current block and a bitstream representation of a video including the current block by using motion information in a table; and updating, after performing of the conversion, one or more tables based on M sets of additional motion information associated with the current block, M being an integer.

[00244] 2. A video processing method, comprising: performing a conversion between a current block and a bitstream representation of a video including the current block by using one or more tables, wherein each table includes a one or more motion candidates and each motion candidate is associated with corresponding motion information; and updating, based on the conversion, one or more tables, based on M sets of additional motion information associated with the current block, M being an integer.

[00245] 3. The method of clause 1 or 2, wherein M is equal to 1.

[00246] 4. The method of clause 1 or 2, further including adding the M sets of motion information as M additional motion candidates to a table.

[00247] 5. The method of clause 4, wherein the updating of a table further includes applying a comparing operation to a set in the M sets of motion information before the set of motion information is added as an additional motion candidate to a table.

[00248] 6. The method of clause 5, wherein the set of motion information is pruned with last K candidates or the first $K \% L$ existing motion candidates, wherein K is an integer representing a counter of motion candidates corresponding to a table and L indicates a size of the table.

[00249] 7. The method of clause 4, wherein a set in the M sets of motion information is added

as an additional motion candidate to a table, and any comparing operation is not applied.

[00250] 8. The method of clause 4, further comprising, when adding a set in the M sets of motion information to a table, the set of motion information includes motion information different from any or partial of current motion candidates in the table.

[00251] 9. The method of clause 4, further comprising, when adding a set in the M sets of motion information, a motion vector (MV) difference between a MV of a current motion candidate in a table and the MV of a same reference picture from the set of motion information is not smaller than one or multiple thresholds.

[00252] 10. The method of clause 1 or 2, wherein each table has a corresponding counter and the corresponding counter is increased by M.

[00253] 11. The method of clause 4, wherein an additional motion candidate is added with an index equal to $K\%L$ in the table, K representing a counter of motion candidates corresponding to a table to be updated and L representing a size of the table.

[00254] 12. The method of clause 4, wherein an additional motion candidate is added with an index equal to $\min(K+1, L-1)$ in the table, K representing a counter of motion candidates corresponding to a table to be updated and L representing a size of the table.

[00255] 13. The method of clause 4, wherein in a case that K is not smaller than L, a first motion candidate having an index of 0 is removed from the table.

[00256] 14. The method of clause 11 or 12, wherein latest sets of motion information from previously coded blocks are maintained regardless of whether there are identical or similar motion candidates.

[00257] 15. The method of clause 4, wherein the updating of the one or more tables includes checking a redundancy of current motion candidates in the table with an additional motion candidate.

[00258] 16. The method of clause 15, wherein the updating of the one or more tables includes performing a redundancy-removal based table updating in which one or more redundant current motion candidates are removed from a table and latest sets of motion information from previous coded blocks are maintained.

[00259] 17. The method of clause 16, wherein the latest sets of motion information include unduplicated motion information.

[00260] 18. The method of clause 16, wherein when at least one of current motion candidates

in the table is redundant to the additional motion candidate, the counter associated with the table is not increased.

[00261] 19. The method of clause 16, wherein the redundancy-removal based table updating process includes performing a comparing operation on an additional motion candidate to be added to a table to the current motion candidates in a table.

[00262] 20. The method of clause 19, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, the identified redundant current motion candidate is moved from a current position to a last position after the remaining current motion candidates in the table.

[00263] 21. The method of clause 19, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, the identified redundant current motion candidate is removed from the table to provide an empty entry in the table and non-redundant current motion candidates after the identified redundant current motion candidate in the table are moved forward to fill the empty entry.

[00264] 22. The method of clause 21, wherein the adding of the additional motion candidate is performed after the moving of the non-redundant current motion candidates in the table.

[00265] 23. The method of clause 16, wherein the performing of the redundancy-removal based table updating includes checking a redundancy of current motion candidates in the table to identify multiple redundant motion candidates and removing all of the identified multiple redundant motion candidates.

[00266] 24. The method of clause 23, wherein a counter corresponding to the table is decreased by a value obtained by subtracting 1 from the number of the identified multiple redundant motion candidates.

[00267] 25. The method of clause 23, wherein the checking of the redundancy is terminated after the number of the identified multiple redundant motion candidates reaches a maximum value, maxR, where maxR being a positive integer variable.

[00268] 26. The method of clause 16, wherein the checking of the redundancy is terminated when a redundant current motion candidate is identified.

[00269] 27. The method of clause 16, wherein the checking of the redundancy is performed in an order from a first current motion candidate to a last current motion candidate in a table.

[00270] 28. The method of clause 16, wherein the checking of the redundancy is performed in

an order that the current motion candidates have been added to the table or in an order of a decoding process of blocks from where the current motion candidates have been obtained.

[00271] 29. The method of clause 16, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, a virtual motion candidate is derived from the identified redundant candidate and the identified multiple redundant candidate is removed from the table.

[00272] 30. The method of clause 29, wherein the virtual motion candidates are derived by i) adding offset(s) to a horizontal or vertical component of one or more motion vectors or ii) averaging two motion vectors pointing to same reference pictures.

[00273] 31. The method of clause 29, wherein the virtual motion candidates are derived from a function of motion vectors associated with current motion candidates in the table.

[00274] 32. The method of clause 29, wherein the virtual motion candidates are added to positions of the identified redundant motion candidates in the table.

[00275] 33. The method of clause 16, wherein the virtual motion candidates are added before current motion candidates in the table, the current motion candidates corresponding to motion candidates in the table except the identified redundant motion candidate.

[00276] 34. The method of clause 16, wherein the redundancy-removal based table updating process is invoked under the determination of certain conditions are satisfied.

[00277] 35. The method of clause 34, wherein the condition comprises when the current block is coded with merge mode.

[00278] 36. The method of clause 35, wherein the condition comprises when the current block is not coded neither with a sub-block based motion prediction nor a sub-block based motion compensation method.

[00279] 37. The method of clause 1 or 2, where the updating of the one or more tables is performed only after performing of the conversion of S blocks, S being ≥ 1 .

[00280] 38. The method of clause 37, wherein the S blocks are inter-coded blocks.

[00281] 39. The method of clause 37, wherein the S blocks are not coded with neither a sub-block based motion prediction nor sub-block based motion compensation method.

[00282] 40. The method of clause 39, wherein the condition comprises when the current block is coded with a merge mode and a source of motion information of a corresponding motion candidate has a certain type.

- [00283] 41. The method of clause 40, wherein the source of motion information of a corresponding motion candidate is from spatial neighboring block, including a left neighboring block, or a temporal block.
- [00284] 42. The method of clause 4, wherein the M additional motion candidates are added after the current motion candidates that have been added to the table prior to the M additional motion candidates.
- [00285] 43. The method of clause 42, further comprising some of the current motion candidates are removed from the table.
- [00286] 44. The method of clause 43, wherein first one or multiple entries in the set of motion candidates are removed from the table when the table is full before or after inserting the M set of motion information.
- [00287] 45. The method of clause 1 or 2, wherein when the current block is coded with motion information directly signaled, the motion information is added to a table.
- [00288] 46. The method of clause 41, wherein the current block is coded in an AMVP mode, a merge with motion vector differences (MMVD) mode for normal/affine inter mode, or an advanced motion vector prediction (AMVR) mode for normal/affine inter mode.
- [00289] 47. The method of clause 45, wherein the motion information is added to a last entry of the table or to an entry used for storing a next available motion candidate.
- [00290] 48. The method of clause 1, 2 or 16, further comprising adding additional motion candidates to the table by a motion information derivation process based on the M sets of motion information.
- [00291] 49. The method of clause 44, wherein a counter corresponding to the table is increased by a value more than 1.
- [00292] 50. The method of clause 44, wherein the motion information derivation process comprises scaling a motion vector of a set in the M sets of motion information.
- [00293] 51. The method of clause 48, wherein the motion information derivation process comprises adding a motion vector offset (dx, dy) to a motion vector of a set of the M sets of motion information.
- [00294] 52. The method of clause 48, wherein the motion information derivation process comprises using an average value of motion vectors of two or more sets in the M sets of motion information.

[00295] 53. The method of any one of clauses 1-52, wherein the updating includes modifying the M sets of motion information before being added to the tables.

[00296] 54. The method of clause 1 or 2, wherein the performing of the conversion includes generating the bitstream representation from the current block.

[00297] 55. The method of clause 1 or 2, wherein the performing of the conversion includes generating the current block from the bitstream representation.

[00298] 56. The method of any one of clauses 1 to 55, wherein a motion candidate is associated with motion information including at least one of: a prediction direction, a reference picture index, motion vector values, an intensity compensation flag, an affine flag, a motion vector difference precision, or motion vector difference value.

[00299] 57. The method of any one of clauses 1-55, wherein the motion candidates correspond to motion candidates for intra prediction modes for intra mode coding.

[00300] 58. The method of any one of clauses 1-55, wherein the motion candidates correspond to motion candidates that include illumination compensation parameters for IC parameter coding.

[00301] 59. The method of any one of clauses 1 to 58, further comprising: performing a conversion between a subsequent video block of the video and the bitstream representation of the video based on the updated tables.

[00302] 60. An apparatus comprising a processor and a non-transitory memory with instructions thereon, wherein the instructions upon execution by the processor, cause the processor to implement the method in any one of clauses 1 to 59.

[00303] 61. A computer program product stored on a non-transitory computer readable media, the computer program product including program code for carrying out the method in any one of clauses 1 to 59.

[00304] From the foregoing, it will be appreciated that specific embodiments of the presently disclosed technology have been described herein for purposes of illustration, but that various modifications may be made without deviating from the scope of the invention. Accordingly, the presently disclosed technology is not limited except as by the appended claims.

[00305] The disclosed and other embodiments, modules and the functional operations described in this document can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this document and their structural equivalents, or in combinations of one or more of them. The disclosed and other

embodiments can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer readable medium for execution by, or to control the operation of, data processing apparatus. The computer readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more them. The term “data processing apparatus” encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal, that is generated to encode information for transmission to suitable receiver apparatus.

[00306] A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

[00307] The processes and logic flows described in this document can be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

[00308] Processors suitable for the execution of a computer program include, by way of

example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read only memory or a random-access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However, a computer need not have such devices. Computer readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

[00309] While this patent document contains many specifics, these should not be construed as limitations on the scope of any invention or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular inventions. Certain features that are described in this patent document in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

[00310] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Moreover, the separation of various system components in the embodiments described in this patent document should not be understood as requiring such separation in all embodiments.

[00311] Only a few implementations and examples are described and other implementations, enhancements and variations can be made based on what is described and illustrated in this patent document.

CLAIMS

What is claimed is:

1. A video processing method, comprising:
maintaining one or more tables, wherein each table includes one or more motion candidates and each motion candidate is associated with corresponding motion information;
performing a conversion between a current block and a bitstream representation of a video including the current block by using motion information in a table; and
updating, after performing of the conversion, one or more tables based on M sets of additional motion information associated with the current block, M being an integer.
2. A video processing method, comprising:
performing a conversion between a current block and a bitstream representation of a video including the current block by using one or more tables, wherein each table includes a one or more motion candidates and each motion candidate is associated with corresponding motion information; and
updating, based on the conversion, one or more tables, based on M sets of additional motion information associated with the current block, M being an integer.
3. The method of claim 1 or 2, wherein M is equal to 1.
4. The method of claim 1 or 2, further including adding the M sets of motion information as M additional motion candidates to a table.
5. The method of claim 4, wherein the updating of a table further includes applying a comparing operation to a set in the M sets of motion information before the set of motion information is added as an additional motion candidate to a table.
6. The method of claim 5, wherein the set of motion information is pruned with last K candidates or the first $K\%L$ existing motion candidates, wherein K is an integer representing a counter of motion candidates corresponding to a table and L indicates a size of the table.

7. The method of claim 4, wherein a set in the M sets of motion information is added as an additional motion candidate to a table, and any comparing operation is not applied.
8. The method of claim 4, further comprising, when adding a set in the M sets of motion information to a table, the set of motion information includes motion information different from any or partial of current motion candidates in the table.
9. The method of claim 4, further comprising, when adding a set in the M sets of motion information, a motion vector (MV) difference between a MV of a current motion candidate in a table and the MV of a same reference picture from the set of motion information is not smaller than one or multiple thresholds.
10. The method of claim 1 or 2, wherein each table has a corresponding counter and the corresponding counter is increased by M.
11. The method of claim 4, wherein an additional motion candidate is added with an index equal to $K\%L$ in the table, K representing a counter of motion candidates corresponding to a table to be updated and L representing a size of the table.
12. The method of claim 4, wherein an additional motion candidate is added with an index equal to $\min(K+1, L-1)$ in the table, K representing a counter of motion candidates corresponding to a table to be updated and L representing a size of the table.
13. The method of claim 4, wherein in a case that K is not smaller than L, a first motion candidate having an index of 0 is removed from the table.
14. The method of claim 11 or 12, wherein latest sets of motion information from previously coded blocks are maintained regardless of whether there are identical or similar motion candidates.

15. The method of claim 4, wherein the updating of the one or more tables includes checking a redundancy of current motion candidates in the table with an additional motion candidate.
16. The method of claim 15, wherein the updating of the one or more tables includes performing a redundancy-removal based table updating in which one or more redundant current motion candidates are removed from a table and latest sets of motion information from previous coded blocks are maintained.
17. The method of claim 16, wherein the latest sets of motion information include unduplicated motion information.
18. The method of claim 16, wherein when at least one of current motion candidates in the table is redundant to the additional motion candidate, the counter associated with the table is not increased.
19. The method of claim 16, wherein the redundancy-removal based table updating process includes performing a comparing operation on an additional motion candidate to be added to a table to the current motion candidates in a table.
20. The method of claim 19, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, the identified redundant current motion candidate is moved from a current position to a last position after the remaining current motion candidates in the table.
21. The method of claim 19, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, the identified redundant current motion candidate is removed from the table to provide an empty entry in the table and non-redundant current motion candidates after the identified redundant current motion candidate in the table are moved forward to fill the empty entry.

22. The method of claim 21, wherein the adding of the additional motion candidate is performed after the moving of the non-redundant current motion candidates in the table.
23. The method of claim 16, wherein the performing of the redundancy-removal based table updating includes checking a redundancy of current motion candidates in the table to identify multiple redundant motion candidates and removing all of the identified multiple redundant motion candidates.
24. The method of claim 23, wherein a counter corresponding to the table is decreased by a value obtained by subtracting 1 from the number of the identified multiple redundant motion candidates.
25. The method of claim 23, wherein the checking of the redundancy is terminated after the number of the identified multiple redundant motion candidates reaches a maximum value, $\max R$, where $\max R$ being a positive integer variable.
26. The method of claim 16, wherein the checking of the redundancy is terminated when a redundant current motion candidate is identified.
27. The method of claim 16, wherein the checking of the redundancy is performed in an order from a first current motion candidate to a last current motion candidate in a table.
28. The method of claim 16, wherein the checking of the redundancy is performed in an order that the current motion candidates have been added to the table or in an order of a decoding process of blocks from where the current motion candidates have been obtained.
29. The method of claim 16, wherein the checking of the redundancy identifies a redundant current motion candidate in the table, a virtual motion candidate is derived from the identified redundant candidate and the identified multiple redundant candidate is removed from the table.

30. The method of claim 29, wherein the virtual motion candidates are derived by i) adding offset(s) to a horizontal or vertical component of one or more motion vectors or ii) averaging two motion vectors pointing to same reference pictures.
31. The method of claim 29, wherein the virtual motion candidates are derived from a function of motion vectors associated with current motion candidates in the table.
32. The method of claim 29, wherein the virtual motion candidates are added to positions of the identified redundant motion candidates in the table.
33. The method of claim 16, wherein the virtual motion candidates are added before current motion candidates in the table, the current motion candidates corresponding to motion candidates in the table except the identified redundant motion candidate.
34. The method of claim 16, wherein the redundancy-removal based table updating process is invoked under the determination of certain conditions are satisfied.
35. The method of claim 34, wherein the condition comprises when the current block is coded with merge mode.
36. The method of claim 34, wherein the condition comprises when the current block is not coded neither with a sub-block based motion prediction nor a sub-block based motion compensation method.
37. The method of claim 1 or 2, wherein the updating of the one or more tables is performed only after performing of the conversion of S blocks, S being an integer not smaller than 1.
38. The method of claim 37, wherein the S blocks are inter-coded blocks.
39. The method of claim 37, wherein the S blocks are not coded with neither a sub-block based motion prediction nor sub-block based motion compensation method.

40. The method of claim 39, wherein the condition comprises when the current block is coded with a merge mode and a source of motion information of a corresponding motion candidate has a certain type.
41. The method of claim 40, wherein the source of motion information of a corresponding motion candidate is from spatial neighboring block, including a left neighboring block, or a temporal block.
42. The method of claim 4, wherein the M additional motion candidates are added after the current motion candidates that have been added to the table prior to the M additional motion candidates.
43. The method of claim 42, further comprising some of the current motion candidates are removed from the table.
44. The method of claim 43, wherein first one or multiple entries in the set of motion candidates are removed from the table when the table is full before or after inserting the M set of motion information.
45. The method of claim 1 or 2, wherein when the current block is coded with motion information directly signaled, the motion information is added to a table.
46. The method of claim 45, wherein the current block is coded in an AMVP mode, a merge with motion vector differences (MMVD) mode for normal/affine inter mode, or an advanced motion vector prediction (AMVR) mode for normal/affine inter mode.
47. The method of claim 45, wherein the motion information is added to a last entry of the table or to an entry used for storing a next available motion candidate.

48. The method of claim 1, 2 or 16, further comprising adding additional motion candidates to the table by a motion information derivation process based on the M sets of motion information.
49. The method of claim 48, wherein a counter corresponding to the table is increased by a value more than 1.
50. The method of claim 48, wherein the motion information derivation process comprises scaling a motion vector of a set in the M sets of motion information.
51. The method of claim 48, wherein the motion information derivation process comprises adding a motion vector offset (dx, dy) to a motion vector of a set of the M sets of motion information.
52. The method of claim 48, wherein the motion information derivation process comprises using an average value of motion vectors of two or more sets in the M sets of motion information.
53. The method of any one of claims 1-52, wherein the updating includes modifying the M sets of motion information before being added to the tables.
54. The method of claim 1 or 2, wherein the performing of the conversion includes generating the bitstream representation from the current block.
55. The method of claim 1 or 2, wherein the performing of the conversion includes generating the current block from the bitstream representation.
56. The method of any one of claims 1 to 55, wherein a motion candidate is associated with motion information including at least one of: a prediction direction, a reference picture index, motion vector values, an intensity compensation flag, an affine flag, a motion vector difference precision, or motion vector difference value.

57. The method of any one of claims 1-55, wherein the motion candidates correspond to motion candidates for intra prediction modes for intra mode coding.
58. The method of any one of claims 1-55, wherein the motion candidates correspond to motion candidates that include illumination compensation parameters for IC parameter coding.
59. The method of any one of claims 1 to 58, further comprising:
performing a conversion between a subsequent video block of the video and the bitstream representation of the video based on the updated tables.
60. An apparatus comprising a processor and a non-transitory memory with instructions thereon, wherein the instructions upon execution by the processor, cause the processor to implement the method recited in one or more of claims 1 to 59.
61. A computer program product stored on a non-transitory computer readable media, the computer program product including program code for carrying out the method recited in one or more of claims 1 to 59.