

Description

TECHNICAL FIELD

The present invention relates to a buckle for watch bands.

U.S. Patent 4,675,955 discloses a buckle having a lock mechanism which reliably locks the buckle and can be easily operated by a user. Figs. 1 to 3 show a buckle disclosed in the U.S. Patent. An engaging projection 4 provided on a clasping member 1 is engaged with an edge 3a of an opening 3 formed in a lock member 2, so that the opposite watch bands are connected to each other through the buckle. To disengage the buckle, a projected end of the lock member 2 and a projected end of a pressing up member 5 are simultaneously and inwardly pushed, whereby the engaging projection 4 is released from the edge 3a and pushed by the slant of the pressing up member 5. Thus, the clasping member 1 is released from the lock member 2 and pushed up.

However, the buckle has disadvantages as follows. The lock member 2 and the pressing up member 5 are formed by bending metal plates so as to be slidable on guide pins 7. Further, both the members 2 and 5 are vertically disposed as shown in Fig. 3. Consequently, the buckle becomes large in thickness. Further, as shown in Fig. 3, a pair of holes 8 from which the ends of both members are projected are not equal in height. Therefore, the appearance of the buckle is asymmetrical.

The U.S. Patent discloses a further embodiment solving the problem of thickness. However, in the embodiment, the length of the buckle in the longitudinal direction of watch bands is increased. As a result, the buckle becomes large in size, which causes the range of design to reduce.

GB-A-2,169,950 discloses a buckle for a watch with opposite bands, the buckle having a first engaging member and a second engaging member. The first engaging member comprises a frame member having at least one base frame and a pair of side frames, each of the side frames having a hole which corresponds to the hole of the other side frame with both the holes being located at the same height. A lock lever is also provided having a locking portion, and a pressing-up lever having a body, and a pressing-up slant. Each of the levers is laterally slidably mounted in the frame member and has an operating lug projected from the hole of one of the side frames. The second engaging member comprises a lock member engageable with the lock lever and a slant member to be raised by the pressing-up lever, with a spring being provided between the lock lever and the pressing-up lever so as to urge outwardly both the levers.

The object of the present invention is to provide a buckle which may be made in a small size with a good appearance.

DISCLOSURE OF THE INVENTION

The invention provides a buckle which is characterized in that:

the pressing-up lever is located lower than the lock lever, and

the locking portion of the lock lever and the body of the pressing-up lever are disposed so as to overlap with each other, and the surface of the operating lug of the lever is located higher than the body by a height substantially equal to the thickness of locking portion so that the operating lug is inserted into the corresponding hole.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a conventional buckle;

Fig. 2 is an enlarged perspective view of a lock member of the buckle;

Fig. 3 is a sectional view showing the engaging state of the buckle;

Fig. 4 is an exploded perspective view of a buckle for a watch band according to the present invention;

Fig. 5 is an exploded perspective view showing a first engaging member of the buckle shown in Fig. 4;

Fig. 6 is a plan view of the first engaging member; Fig. 7 is a sectional view of the first engaging member;

Fig. 8 is a side view of the first engaging member; Fig. 9 is an exploded perspective view showing a buckle of a second embodiment of the present invention;

Fig. 10 is an enlarged perspective view showing a lock lever and a pressing-up lever of the buckle of Fig. 9;

Fig. 11 is a plan view showing the buckle of Fig. 9;

Fig. 12 is a sectional view of the buckle;

Fig. 13 is a side view showing a buckle of a third embodiment;

Fig. 14 is a perspective view showing a first engaging member of the buckle of Fig. 13;

Fig. 15 is an exploded perspective view of the first engaging member; and

Fig. 16 is a perspective view showing a frame member of the buckle.

BEST MODE FOR EMBODYING THE INVENTION

Referring to Figs. 4 to 8, a buckle according to the present invention comprises a first engaging member 10 and a second engaging member 11. The first engaging member 10 comprises a frame member 20, a lock mechanism 40 mounted in the frame member 20 and a cover 25. The second engaging member 11

comprises a clasp 30 and a hook 32. The frame member 20 comprises a base frame 23 and a pair of side frames 21 and 22 integral with the base frame 23, and has an engaging pin 24 laterally provided between the side frames 21 and 22. The clasp 30 has a cover plate 31, a snap 33 and a composite member 34 having a lock member and a slant member. The snap 33 and the composite member 34 are secured to the cover plate 31 by brazing. The clasp 30 and the hook 32 are pivotally connected on a pin 36 provided on an end of a band 35. The base frame 23 is connected to another band 37 by screws.

The lock mechanism 40 comprises a lock lever 41, a pressing-up lever 42, and a spring 43. The lock lever 41 comprises a body 41a, an operating lug 41b to be projected from a hole 21a formed in the side frame 21, and an L-shaped projecting portion 41c. As shown in Fig. 7, a locking portion 41e having a guide slant 41d is formed on the inside of the projecting portion 41c. The pressing-up lever 42 has a body 42d, and an operating lug 42a. The operating lug 42a is formed by a pair of parallel slits extending from an outer end of the body 42d and upwardly bent by the height which is approximately the same as the thickness of the lock lever 41. An inner projection 42b projected from the body 42d has an upward slant 42c as a pressing-up slant to be abutted on a downward slant 34a of the composite member 34.

The cover 25 has side and lower projections 25d to be engaged with the frame member 20, and a pair of lateral side plates 25b and 25c for guiding the levers 41 and 42. The projections 25d are engaged with the base frame 23 and the side frames 21 and 22 for mounting the cover 25 on the frame member 20.

As shown in Fig. 7, the body 42d of the lever 42 is slidably mounted on the base frame 23 and the lock lever 41 is slidably mounted on the body 42d. Since the position of the operating lug 42a of the pressing-up lever 42 is higher than the body 42d by the thickness of the lock lever 41, the operating lug 42a is approximately the same level as the operating lug 41b. Both the levers 41 and 42 can be slid between the base frame 23 and the cover 25 secured to the frame member 20.

The operating lugs 41b and 42a of the lock lever 41 and the pressing-up lever 42 are projected from holes 21a and 22a formed in the side frames 21 and 22 at the same level with each other. Thus, the operating lugs 41b and 42a are symmetrical, thereby giving good design. Each of the operating lugs 41b and 42a has a comparatively long width, so that the lugs do not pain fingers of the user when operating although the plate has a small thickness as 1 mm.

The V-shaped spring 43 has a circle 43a at a base portion thereof. The base circle 43a engages with a boss 42e formed on the body 42d of the lever 42. Both ends of the spring 43 are abutted on the projecting portion 41c of the lock lever 41 and an upward bent

portion 42f of the pressing-up lever 42 (Fig. 7), respectively, to urge both levers outwardly in the opposite directions to project the operating lugs 41b and 42a from holes 21a and 22a. As shown in Fig. 7, the lock lever 41 is held by the pressing-up lever 42 to form a space under the lock lever 41. The composite member 34 secured to the cover plate 31 is located in the space.

Method of coupling the buckle is as follows. The hook 32 of the clasp 30 is engaged with the pin 24 and the cover plate 31 is rotated so that the snap 33 resiliently engages with an edge of an opening 25a of the cover 25. At the same time, the composite member 34 is inserted into the opening 25a. The downward slant 34a of the composite member 34 slides on the guide slant 41d of the lock lever 41 so that the lock lever 41 is inwardly moved. When the slant 34a passes the slant 41d, the lock lever 41 is returned to the home position by the elastic force of the spring 43. As shown in Fig. 7, the locking portion 41e engages with the composite member 34. Thus, the clasp 30 is locked by the lock mechanism 40.

In operation for disengaging the buckle, the operating lugs 41b and 42a of levers 41 and 42 are pushed by a thumb and a first finger of the user to release the locking portion 41e from the composite member 34, while the upward slant 42c of the pressing-up lever 42 pushes the downward slant 34a upward. The cover plate 31 is pushed up against engaging force of the snap 33 by the slant 42c and released from the cover 25. Then, the hook 32 is disengaged from the pin 24.

In the present invention, the thickness of the buckle is the total thicknesses of base frame 23, both the levers 41 and 42, cover 25 and cover plate 31. Consequently, a comparatively thinner buckle is provided. The lock lever 41 is mounted on the pressing-up lever 42, so that the lateral length of the buckle is reduced.

In accordance with the invention, a thinner and compact buckle is provided, with balanced design and simple structure and may be manufactured by quantity-production work.

Figs. 9 to 12 show a buckle of the second embodiment of the invention. The buckle of the second embodiment has basically the same construction as the first embodiment. In the second embodiment, a lock lever 54 of the buckle has an L-shaped retainer portion 54a and a pressing-up lever 56 has an inverted L-shaped retainer portions 56a, each extending from the body. A coil spring 38 is disposed in a space defined by the retainer portions 54a and 56a, cover 25 and base frame 23. The levers 54 and 56 are further provided with a pair of regulating ends 54b and 56b, respectively. Both projecting ends 54c and 56c formed on the L-shaped retainer portions 54a and 56a also serve as regulating ends. The regulating ends 54b, 56b, 54c and 56c abut on the side plates

25b and 25c of the cover 25 so as to guide the levers 54 and 56 in the lateral direction of the band. Therefore, the levers 54 and 56 can be smoothly operated.

Referring to Figs. 11 and 12, the coil spring 38 is disposed in the space defined by the L-shaped retainer portion 56a of the pressing-up lever 56, the L-shaped retainer portions 54a of the lock lever 54 mounted on the lever 56, the cover 25, the side plate 25b and the base frame 23.

If widths ℓ_1 and ℓ_2 of the projecting ends 54c and 56c are minimized within an allowable range of press working, the space for the coil spring 38 (length of the coil spring) becomes maximum, so that the spring 38 having a sufficient resilient force can be employed.

The L-shaped retainer portion 56a of the pressing-up lever 56 extends over a pressing up slant 56d to form one side of the space for the spring 38. Thus, such an accident that a part of the coil spring 38 enters the space under the lock lever 54, which disables the levers 54 and 56 from returning to the home positions, does not occur.

Since the side portion of each L-shaped retainer portion 54a (56a) engages with the periphery of the spring 38 so that the lateral displacement of the lever 54 (56) is restricted by the spring when operating.

Since the levers 54 and 56 are partially overlapped with each other and guided by the side plates 25b and 25c of the cover 25, the levers are smoothly moved during operation. Thus, even if a spring having a small elastic force is used, the spring reliably urges both the levers to the corresponding side frames. Consequently, the levers can be operated by a small pressing force.

In order to reduce the thickness of the buckle, if the thicknesses of both the levers 54 and 56 are reduced, the height of the cover plate 31 heaved by the upward slant 56d reduces. In order to keep the necessary height for the cover plate 31, it is necessary to increase the height of the composite member 34 and the length of the slant 34a of the composite member 34. However, it is impossible to increase the height of the composite member 34 without increasing the thickness of the buckle. Such an increase can be achieved by forming a hole in the base frame 23 and inserting the lower end of the composite member 34 into the hole.

Figs. 13 to 16 show a buckle of the third embodiment. In the first and second embodiments, the first engaging member 10 is secured to the end of the band 37. A first engaging member of the buckle of the third embodiment has a clamping spring member 60 for attaching the first engaging member to a band 72 at a preferable position. Namely, the effective length of the band 72 can be adjusted by changing the position of the first engaging member. The clamping spring member 60 comprises a body 61 having a U-shaped section. The body 61 is rotatably mounted on a pin 62 laterally provided between side frames 66 and 67 of

the frame member of the buckle. A clamping portion 63 is formed on a lower portion of the body 61 to be inserted into the underside of the pin 62 for clamping the first engaging member to the band 72.

The frame member comprises a pair of lateral base frames 64 and 65, supporting plates 68 and 69 inwardly projected from the side frames 66 and 67 for supporting a lock mechanism. The lock mechanism comprises a lock lever 70 and a pressing up lever 71. The levers 70 and 71 are similar to the lock lever 54 and the pressing-up lever 56 of the second embodiment. Each of the levers 70 and 71 has a more simplified construction than the second embodiment but has the same functions as the second embodiment. Other parts are the same as the second embodiment in construction and the same parts thereof are identified with the same reference numerals of Figs. 9 to 12.

The band 72 is inserted between the base frames 64 and 65 and the supporting plates 68 and 69. As shown in Fig. 13, the clamping portion 63 of the clamping spring member 60 is pressed against the band 72 so that the first engaging member is secured to the band 72. At that time, the outside contour of the clamping spring member 60 coincides with contours of the side frames 66 and 67. An end of a cover plate 73 connected to the other band is engaged with a shoulder 74 formed on the clamping spring member 60 when the cover plate 73 is coupled to the first engaging member. In the coupled state, the end of the cover plate 73 flushes with the upper surface of the clamping spring member 60 and the contour thereof coincides with the peripheries of the side frames 66 and 67.

In order to change the position of the first engaging member on the band 72, the clamping spring member 60 is rotated by a tool to disengage the clamping portion 63 from the band 72.

PROBABILITY OF INDUSTRIAL EXPLOITATION

In accordance with the present invention, a buckle which is compact in size and balanced in design can be provided. Since the number of parts of the buckle is small, the buckle can be easily manufactured at a low manufacturing cost.

Claims

1. A buckle for a watch with opposite bands, the buckle having a first engaging member (10) and a second engaging member (11), the first engaging member (10) comprising a frame member (20) having at least one base frame (23) and a pair of side frames (21,22), each of the side frames (21,22) having a hole (21a,22a) which corresponds to the hole of the other side frame with both the holes (21a,22a) being



25b and 25c of the cover 25 so as to guide the levers 54 and 56 in the lateral direction of the band. Therefore, the levers 54 and 56 can be smoothly operated.

Referring to Figs. 11 and 12, the coil spring 38 is disposed in the space defined by the L-shaped retainer portion 56a of the pressing-up lever 56, the L-shaped retainer portions 54a of the lock lever 54 mounted on the lever 56, the cover 25, the side plate 25b and the base frame 23.

If widths ℓ_1 and ℓ_2 of the projecting ends 54c and 56c are minimized within an allowable range of press working, the space for the coil spring 38 (length of the coil spring) becomes maximum, so that the spring 38 having a sufficient resilient force can be employed.

The L-shaped retainer portion 56a of the pressing-up lever 56 extends over a pressing up slant 56d to form one side of the space for the spring 38. Thus, such an accident that a part of the coil spring 38 enters the space under the lock lever 54, which disables the levers 54 and 56 from returning to the home positions, does not occur.

Since the side portion of each L-shaped retainer portion 54a (56a) engages with the periphery of the spring 38 so that the lateral displacement of the lever 54 (56) is restricted by the spring when operating.

Since the levers 54 and 56 are partially overlapped with each other and guided by the side plates 25b and 25c of the cover 25, the levers are smoothly moved during operation. Thus, even if a spring having a small elastic force is used, the spring reliably urges both the levers to the corresponding side frames. Consequently, the levers can be operated by a small pressing force.

In order to reduce the thickness of the buckle, if the thicknesses of both the levers 54 and 56 are reduced, the height of the cover plate 31 heaved by the upward slant 56d reduces. In order to keep the necessary height for the cover plate 31, it is necessary to increase the height of the composite member 34 and the length of the slant 34a of the composite member 34. However, it is impossible to increase the height of the composite member 34 without increasing the thickness of the buckle. Such an increase can be achieved by forming a hole in the base frame 23 and inserting the lower end of the composite member 34 into the hole.

Figs. 13 to 16 show a buckle of the third embodiment. In the first and second embodiments, the first engaging member 10 is secured to the end of the band 37. A first engaging member of the buckle of the third embodiment has a clamping spring member 60 for attaching the first engaging member to a band 72 at a preferable position. Namely, the effective length of the band 72 can be adjusted by changing the position of the first engaging member. The clamping spring member 60 comprises a body 61 having a U-shaped section. The body 61 is rotatably mounted on a pin 62 laterally provided between side frames 66 and 67 of

the frame member of the buckle. A clamping portion 63 is formed on a lower portion of the body 61 to be inserted into the underside of the pin 62 for clamping the first engaging member to the band 72.

The frame member comprises a pair of lateral base frames 64 and 65, supporting plates 68 and 69 inwardly projected from the side frames 66 and 67 for supporting a lock mechanism. The lock mechanism comprises a lock lever 70 and a pressing up lever 71. The levers 70 and 71 are similar to the lock lever 54 and the pressing-up lever 56 of the second embodiment. Each of the levers 70 and 71 has a more simplified construction than the second embodiment but has the same functions as the second embodiment. Other parts are the same as the second embodiment in construction and the same parts thereof are identified with the same reference numerals of Figs. 9 to 12.

The band 72 is inserted between the base frames 64 and 65 and the supporting plates 68 and 69. As shown in Fig. 13, the clamping portion 63 of the clamping spring member 60 is pressed against the band 72 so that the first engaging member is secured to the band 72. At that time, the outside contour of the clamping spring member 60 coincides with contours of the side frames 66 and 67. An end of a cover plate 73 connected to the other band is engaged with a shoulder 74 formed on the clamping spring member 60 when the cover plate 73 is coupled to the first engaging member. In the coupled state, the end of the cover plate 73 flushes with the upper surface of the clamping spring member 60 and the contour thereof coincides with the peripheries of the side frames 66 and 67.

In order to change the position of the first engaging member on the band 72, the clamping spring member 60 is rotated by a tool to disengage the clamping portion 63 from the band 72.

PROBABILITY OF INDUSTRIAL EXPLOITATION

In accordance with the present invention, a buckle which is compact in size and balanced in design can be provided. Since the number of parts of the buckle is small, the buckle can be easily manufactured at a low manufacturing cost.

Claims

1. A buckle for a watch with opposite bands, the buckle having a first engaging member (10) and a second engaging member (11), the first engaging member (10) comprising a frame member (20) having at least one base frame (23) and a pair of side frames (21,22), each of the side frames (21,22) having a hole (21a,22a) which corresponds to the hole of the other side frame with both the holes (21a,22a) being



located at the same height, a lock lever (41) having a locking portion (41e), and a pressing-up lever (42) having a body (42d), a pressing-up slant (42c), each of the levers (41,42) being laterally slidably mounted in the frame member and having an operating lug (41a,42a) projected from the hole (21a,22a) of one of the side frames (21,22), and the second engaging member (11) comprising a lock member (34) engageable with the lock lever (41) and a slant member (34a) to be raised by the pressing-up lever (42), with a spring (43) being provided between the lock lever (41) and the pressing-up lever (42) so as to urge outwardly both the levers, characterized in that

the pressing-up lever (42) is located lower than the lock lever (41), and

the locking portion (41e) of the lock lever (41) and the body (42d) of the pressing-up lever (42) are disposed so as to overlap with each other, and the surface of the operating lug (42a) of the lever (42) is located higher than the body by a height substantially equal to the thickness of locking portion (41e) so that the operating lug is inserted into the corresponding hole (22a).

2. A buckle according to Claim 1 wherein the spring (43) is disposed between an inner end of one of the levers (41) and the bent portion (42a) of the other lever (42).

3. A buckle according to Claim 1 or Claim 2 wherein the lock lever (41) is flat and the pressing-up slant (42c) of the pressing-up lever (42) is different from the operating lug (42a) thereof in height.

4. A buckle according to any one of Claims 1 - 3 wherein the first engaging member (10) has a cover (25) having a pair of lateral side plates (25b,25c) at both ends in the longitudinal direction of the band, the cover is secured to the frame member (23), sides of the lock lever (41) and the pressing-up lever (42) engage with the side plates so as to be moved along the side plates.

5. A buckle according to any one of Claims 1 - 4 wherein the first engaging member (10) is secured to the band (37) by a clamping spring member, the second engaging member (11) comprises a cover plate (31) having a lock member and a slant member, the cover plate engages with the clamping spring member at an end thereof, and the surface of the cover plate flushes with the upper surface of the clamping spring member in the coupling state.

6. A buckle according to Claim 2 wherein the spring is made of a spring plate and disposed between an end of the lock lever and a bend portion of the pressing-up lever so as to urge both the levers to the side frames.

7. A buckle according to Claim 4 wherein each lever has regulating ends at end portions thereof, which engage with the lateral side plates of the cover so as to be moved along the lateral side plates.

8. A buckle according to Claim 4 wherein each

lever has an L-shaped retainer portion, the spring is disposed in a space defined by the L-shaped retainer portions, the cover, a base frame of the frame member and one of the lateral side plates.

Patentansprüche

1. Verschluß für eine Uhr mit gegenüberliegenden Bändern, wobei der Verschluß ein erstes Einrastelement (10) und ein zweites Einrastelement (11) aufweist, wobei das erste Einrastelement ein Rahmenelement (20) mit wenigstens einem Basisrahmen (23) und einem Paar von Seitenrahmen (21, 22), wobei jeder der Seitenrahmen (21, 22) ein Loch (21a, 22a) besitzt, das dem Loch des anderen Seitenrahmens entspricht, wobei beide Löcher (21a, 22a) auf derselben Höhe angeordnet sind, einen Verriegelungshebel (41) mit einem Verriegelungsbereich (41e), und einen Hochdruckhebel (42) mit einem Körper (42d) und einer Hochdruckschräge (42c) umfaßt, wobei jeder der Hebel (41, 42) seitlich gleitend in das Rahmenelement montiert ist und eine Betätigungsnahe (41a, 42a) besitzt, die von dem Loch (21a, 22a) eines der Seitenrahmen (21, 22) vorsteht, und wobei das zweite Einrastelement (11) ein Verriegelungselement (34) umfaßt, das mit dem Verriegelungshebel und der Schräge (34a) in Verbindung treten kann, um von dem Hochdruckhebel (42) nach oben gedrückt zu werden, wobei eine Feder (43) zwischen dem Verriegelungshebel (41) und dem Hochdruckhebel (42) vorgesehen ist, um die beiden Hebel nach außen zu drücken, dadurch gekennzeichnet, daß

der Hochdruckhebel (42) tiefer als der Verriegelungshebel (41) angeordnet ist, und daß

der Verriegelungsbereich (41e) des Verriegelungshebels (41) und der Körper (42d) des Hochdruckhebels (42) so angeordnet sind, daß sie einander überlappen, und daß die Oberfläche der Betätigungsnahe (42a) des Hebels (42) um eine Höhe, die im wesentlichen gleich der Dicke des Verriegelungsbereichs (41e) ist, höher als Körper angeordnet ist, so daß die Betätigungsnahe in das entsprechende Loch (22a) eingesetzt wird.

2. Verschluß nach Anspruch 1, wobei die Feder (43) zwischen einem inneren Ende eines der Hebel (41) und dem gebogenen Bereich (42a) des anderen Hebels angeordnet ist.

3. Verschluß nach Anspruch 1 oder 2, wobei der Verriegelungshebel (41) flach ist und die Hochdruckschräge (42c) des Hochdruckhebels (42) in der Höhe von der Betätigungsnahe (42a) desselben verschieden ist.

4. Verschluß nach einem der Ansprüche 1 - 3, wobei das erste Einrastelement (10) eine Abdeckung (25) mit einem Paar lateraler Seitenplatten (25b, 25c) an beiden Enden in der longitudinalen Richtung des Bandes besitzt, wobei die Abdeckung an dem Rah-



mentelement (23) befestigt ist, wobei die Seiten des Verriegelungshebels (41) und des Hochdrückhebels (42) sich mit den Seitenplatten verbinden, um entlang der Seitenplatten bewegt zu werden.

5. Verschuß nach einem der Ansprüche 1 - 4, wobei das erste Einrastelement (10) durch ein Klemmfederelement (37) an dem Band befestigt ist, das zweite Einrastelement (1) eine Abdeckplatte (31) mit einem Verriegelungselement und einer Schrägen umfaßt, wobei die Abdeckplatte mit dem Klemmfederelement an dessen Ende in Verbindung tritt, und wobei die Oberfläche der Abdeckplatte mit der oberen Oberfläche des Klemmfederelements im Kopplungszustand fluchtet.

6. Verschuß nach Anspruch 2, wobei die Feder aus einer Federplatte besteht und zwischen einem Ende des Verriegelungshebels und einem gebogenen Bereich des Hochdrückhebels angeordnet ist, um beide Hebel zu den Seitenrahmen zu drücken.

7. Verschuß nach Anspruch 4, wobei jeder Hebel regulierende Enden und Endbereiche aufweist, die mit den lateralen Seitenplatten der Abdeckung in Verbindung treten, um entlang der lateralen Seitenplatten bewegt zu werden.

8. Verschuß nach Anspruch 4, wobei jeder Hebel einen L-förmigen Rückhaltebereich besitzt und die Feder in einem von den L-förmigen Rückhaltebereichen, der Abdeckung, einem Basisrahmen des Rahmenelements und einer der lateralen Seitenplatten gebildeten Raum angeordnet ist.

Revendications

1. Pièce de fermeture pour un bracelet montre à bandes opposées, comprenant une première pièce d'engagement (10) et une seconde pièce d'engagement (11), la première pièce d'engagement (10) comprenant un cadre (20) muni d'au moins un cadre de base (23) et d'une paire de cadres latéraux (21, 22), chacun des cadres latéraux (21, 22) possédant un trou (21a, 22a) correspondant avec celui de l'autre cadre latéral, chacun des trous (21a, 22a) étant situé à la même hauteur, un levier de verrouillage (41) possédant une partie de verrouillage (41e) et un levier de pressage vers le haut (42) possédant un corps (42d), une pente de pressage vers le haut (42c), chacun des leviers (41, 42) étant monté coulissant latéralement dans le cadre et possédant une patte d'actionnement (41a, 42a) se projetant à partir du trou (21a, 22a) de l'un des cadres latéraux (21, 22) et la seconde pièce d'engagement (11) comprenant une pièce de verrouillage (34) pouvant coopérer avec le levier de verrouillage (41) et une pièce à pente (34a) devant être soulevée par le levier de pressage vers le haut (42), un ressort (43) étant prévu entre le levier de verrouillage (41) et le levier de pressage vers le haut (42) de façon à pousser vers l'extérieur chacun des leviers,

pièce de fermeture caractérisée en ce que :

le levier de pressage vers le haut (42) est situé plus bas que le levier de verrouillage (41) et

la partie de blocage (41e) du levier de verrouillage (41) et le corps (42d) du levier de pressage vers le haut (42) sont placés de façon à se chevaucher et la surface de la patte d'actionnement (42a) du levier (42) est située plus haut que le corps d'une hauteur sensiblement égale à l'épaisseur de la partie de verrouillage (41e) de façon à ce que la patte d'actionnement s'insère dans le trou correspondant (22a).

2. Pièce de fermeture selon la revendication 1, dans laquelle le ressort (43) est placé entre une extrémité interne de l'un des leviers (41) et la partie courbée (42a) de l'autre levier (42).

3. Pièce de fermeture selon la revendication 1 ou 2, dans laquelle le levier de verrouillage (41) est plat et la pente de pressage vers le haut (42c) du levier de pressage vers le haut (42) est de hauteur différente de celle de la patte d'actionnement (42a).

4. Pièce de fermeture selon l'une quelconque des revendications 1 à 3, dans laquelle une première pièce d'engagement (10) possède un couvercle (25) muni d'une paire de plaques latérales (25b, 25c) à chaque extrémité selon la direction longitudinale du bracelet, le couvercle étant fixé au cadre (23) à côté du levier de verrouillage (41) et le levier de pressage vers le haut (42) coopérant avec les plaques latérales de façon à se déplacer le long de ces plaques latérales.

5. Pièce de fermeture selon l'une quelconque des revendications 1 à 4, dans laquelle la première pièce d'engagement (10) est fixée sur le bracelet (37) à l'aide d'une pièce d'accrochage élastique, la seconde pièce d'engagement (11) comprenant une plaque de couverture (31) munie d'une pièce de verrouillage et d'une pièce à pente, la plaque de couverture coopérant avec la pièce d'accrochage élastique à une extrémité et la surface de la plaque de couverture affleurant la surface supérieure de la pièce d'accrochage élastique à l'état couplé.

6. Pièce de fermeture selon la revendication 2, dans laquelle le ressort est constitué d'une plaque élastique placée entre une extrémité du levier de verrouillage et une partie courbée du levier de pressage vers le haut de façon à pousser chacun des leviers vers les cadres latéraux.

7. Pièce de fermeture selon la revendication 4, dans laquelle chaque levier possède des extrémités de régulation coopérant avec les plaques latérales du couvercle de façon à se déplacer le long des plaques latérales.

8. Pièce de fermeture selon la revendication 4, dans laquelle chaque levier possède une partie de retenue en forme de L, le ressort étant disposé dans un espace défini par les parties de retenue en forme de L, le couvercle, un cadre de base de la pièce d'encadrement et une des plaques latérales.