

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 April 2008 (17.04.2008)

PCT

(10) International Publication Number
WO 2008/045781 A1

(51) International Patent Classification:
H04L 27/26 (2006.01)

(21) International Application Number:
PCT/US2007/080560

(22) International Filing Date: 5 October 2007 (05.10.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/850,942 10 October 2006 (10.10.2006) US

(71) Applicant (for all designated States except US): **QUALCOMM INCORPORATED** [US/US]; International Ip Administration, 5775 Morehouse Drive, San Diego, CA 92121 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MALLADI, Durga Prasad** [US/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US). **MONTOJO, Juan** [ES/US]; 5775

Morehouse Drive, San Diego, CA 92121 (US). **ZHANG, Xiaoxia** [CN/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US).


(74) Agents: **BACHAND, Richard A.** et al.; 5775 Morehouse Drive, San Diego, CA 92121 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: UPLINK PILOT MULTIPLEXING IN SU-MIMO AND SDMA FOR SC-FDMA SYSTEMS



(57) Abstract: Systems and methodologies are described that facilitate adaptive uplink pilot multiplexing schemes. In various embodiments, frequency position and pilot channel bandwidth can be adaptively varied in a block over time based on the uplink channel data, such as the number of streams to be multiplexed. Thus, the provided adaptive uplink pilot multiplexing schemes provide flexible uplink pilot allocation schemes while maintaining single carrier waveform for improved transmit power efficiency and orthogonality of pilots within blocks for improve channel estimation and suppression of interference.



FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,
PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*