12 OCT 2004

PRIVATE RETRIEVAL OF DIGITAL OBJECTS

Technical Field

The present invention relates generally to secure and private communications enabling retrieval of digital objects from a computerized database.

Background Art

The World Wide Web (WWW) has evolved from a service focused on academic areas and offering scientific content into a medium for common users to access information of various origins. While surfing the Web, many users are not aware that a large number of organizations such as those in the marketing industry are gathering their private information. This information is supplemented when a user accesses a Web site, clicks a Web page, makes an electronic purchase, or downloads a file. From all the records and computerized analysis, the information collector can build a digital dossier about the users—what they do, where they go, what they read, what they buy, *etc.*

There has, therefore, been general recognition of the need for privacy protection on the Internet. One situation in which privacy is a large concern is when databases containing users' personal information are accessed. To illustrate, suppose there is a database that maintains groups of digital objects, and a user wishes to retrieve a subset of the digital objects. Two desirable constraints on database access are as follows:

1) the user can access the data the user wants, without disclosing to the database the specific digital objects actually desired; and
2) the user can not get any additional information from the database without the consent of the database.

The first constraint is referred to as *user privacy* and the second constraint is referred to as *database security.*

One example that illustrates these concepts is the task of providing electronic newspaper services over the Internet. A database maintains a collection of digital news articles. Assuming that a subscriber requests n articles, database security requires that the subscriber gets only n articles, while user privacy requires that the database cannot determine which n specific articles are retrieved by the subscriber.

The problem of private information retrieval was reviewed by B. Chor, O. Goldreich, E. Kushilevita, and M. Sudan, "Private Information Retrieval," *Proceedings of the 36h Annual Symposium on Foundations of Computer Science, pp, 41-50, 1995.* The authors were concerned with information-theoretical security and proposed a solution using multiple databases. However, the security of this solution relies on the assumption that the multiple databases do not communicate with each other, which is not guaranteed to be the case, and is additionally outside of the user's control and ability to independently verify.

Private information retrieval schemes using a single database were later proposed in B. Chor and N. Gilboa, "Computational Private Information Retrieval," *Proceedings of the 29th Annual ACM Symposium on Theory of Computing, pp. 304-313, 1997,* and E. Kushilevita and R. Ostrovsky, "Single-Database Computationally Private Information Retrieval," *Proceedings of the 38th Annual Symposium on Foundation of Computer Science, 1997.* These solutions are concerned with security based on computational assumption theory, and in particular the difficulty of factoring large prime numbers, as is done in the well-known RSA encryption scheme. However, the

12 OCT 2004

computational costs of these solutions are prohibitively large due to their bit-by-bit processing approach. For example, the scheme in the Kushilevita and Ostrovsky reference requires a computational cost on the order of *O(N)* multiplication modulo a 1024-bit number just to retrieve 1 bit of information, where *N* is the number of bits of data maintained by the database.

The requirement of database security in the context of private information retrieval was studied in Y. Gertner, Y. Ishai, E. Kushilevita and T. Malkin, "Protecting Data Privacy in Private Information Retrieval Schemes," *Proceedings of the 30th ACM Annual Symposium on Theory of Computing, 1998.*

All of the proposed solutions to the problem of private information retrieval described above employ the bit-by-bit processing approach. Therefore, they have only theoretical values, and are not feasible in practical applications, because of the time that would be required to solve each problem.

Therefore, what is needed is a way of allowing a user to achieve information retrieval from a database in an efficient manner while maintaining privacy.

DISCLOSURE OF INVENTION

In accordance with the present invention, there is provided a way to allow a user (102) to achieve private information retrieval from a database (104) in an efficient manner. The database (104) maintains one or more groups (106) of digital objects (202) available for users to access. A user (102) can retrieve a subset of digital objects (202) from a group (106) of digital objects (202) in the database (104) such that:

1) the user can access the data (202) the user (102) wants, without disclosing to the database (104) the specific digital objects (202) actually desired; and
2) the user (102) can not access additional information (202) from the database (104) without the consent of the database (104).

Objects (202) in the database (104) are stored in one or more different groups (106). The user (102) identifies some particular objects (202) of interest in the database (104), and additionally to which groups (106) those objects (202) belong. The user (102) then sends (302) a request to the database (104), specifying only the groups (106) containing the desired objects (202), but does not specifically identify the particular digital objects (202) desired. At this point, an electronic commerce transaction might take place, where the user (102) pays for access to a specified number of digital objects (202). The database (104) then encrypts (304) all digital objects (202) in each requested group (106) into ciphertext (206). In addition, a key (204) for each ciphertext (206) is encrypted (306). The database (104) then sends back (308) to the user (102) both the ciphertexts (206) and the associated encrypted keys (208).

At this point, the database (104) knows only that the user (102) desires one or more digital objects (202) from a particular group (106) of digital objects in the database (104), but is unable to determine which particular objects (202) are of interest.

The user identifies (310) the ciphertexts (206) of the desired digital objects (202), and their associated keys (208). Next, the user re-encrypts (312) the identified keys (208), and returns (314) the re-encrypted keys (506) to the database (104). The database decrypts (316) the keys (506) to the extent that it is able—i.e., the database (104) reverses the encryption it previously applied to those keys (506). However, the database (104) is unable to identify which digital objects (202) the keys (506) are associated with, because the keys (512) remain encrypted with the user's encryption scheme. The database (104) now sends (318) the keys (512) back to the user (102).

Once the user (102) receives the keys (512) back from the database (104), the next step is simply to decrypt (320) them using the user's own decryption scheme (604), thus revealing the unencrypted keys (204). Finally, the user (102) uses those keys (204) to decrypt (322) the appropriate digital object ciphertexts (206).

OCT 2004

Since the database (104) is unable to determine which keys (204) it has decrypted, user (102) privacy is maintained. And, since the user (102) cannot gain access to any key (204) unless the database (104) first decrypts it, the user (102) will not be able to access any more objects (202) than are authorized. Thus, both constraints discussed above have been satisfied.

The present invention does not require multiple databases. Processing is digital object (202) oriented instead of bit oriented. User (102) privacy is guaranteed without any computational constraint and without additional constraints on the "honesty" of the database (104). This means that the user's interest in specific digital objects (202) is not disclosed. The security of the database (104) is based on the assumption of the intractability of computing discrete logarithms, which forms the basis of many existing digital signature schemes and the Diffie-Hellman key exchange protocol. See W. Diffie and M. Hellman, "New directions in cryptography," *IEEE Transactions on Information Theory*, Vol. IT-22, No. 6, pp. 644-654, November 1976.

The present invention also provides a balance between user (102) privacy and communication cost. Communication cost can be reduced by decreasing the size of a digital object group (106), while a large digital object group (106) size gives better user (102) privacy protection.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other more detailed and specific objects and features of the present invention are more fully disclosed in the following specification, reference being had to the accompanying drawings, in which:

Fig. 1 is a block diagram of a data access system between a (102) user and a database (104).

Fig. 2 is a block diagram of digital objects (202) inside a group (106), and corresponding keys (204), ciphertexts (206), and key ciphertexts (208) associated with the digital objects (202).

Fig. 3 is a flowchart of the operation of the illustrative embodiment of the present invention.

Fig. 4 is a block diagram illustrating the encryption of digital objects (202) into ciphertext (206), and of keys (204) into key ciphertexts (208).

Figs. 5a and 5b are block diagrams illustrating, respectively, the re-encryption of a ciphertext key (208), and the partial decryption of such a key (208).

Figs. 6a and 6b are block diagrams illustrating, respectively, the decryption of a key (512), and the decryption of a digital object ciphertext (206) using a key (204).

Fig. 7 is a block diagram of an apparatus that is a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A cryptographic system, or cryptosystem, has an encryption key to convert plaintext into ciphertext and a decryption key to recover the plaintext from ciphertext. If the encryption key and the decryption key are identical, the cryptosystem is called a symmetric key cryptosystem. If the encryption key and the decryption key are different and it is computationally infeasible to determine the decryption key from the mathematically-related encryption key, the cryptosystem is called an asymmetric key cryptosystem, or a public key cryptosystem. For illustrative purposes, the preferred embodiments described here make reference to symmetric key cryptosystems for encryption and decryption. It will be apparent to those skilled in the art, however, that asymmetric key cryptosystems could also be used. See, for example, A. Menezes, P. Oorschot, and S. Vanstone, *Handbook of Applied Cryptography*, CRC Press, 1996, or C.

Kaufman, R. Perlman, and M. Speciner, *Network Security - Private Communication in A Public World*, PTR Prentice Hall, Englewoor Cliffs, NJ, 1995.

For purposes of clarity, we use e(k, m) to denote encryption of a digital object *m* with key *k* in a symmetric key cryptosystem; and d(k, c) to denote the decryption of a ciphertext *c* with key *k* in a symmetric key cryptosystem.

Fig. 1 is a model of a data access system between a user **102** and a database **104**. The system contains a user **102**, and a database **104**. The database **104** maintains groups **106** of digital objects *m* **202**. The user **102** wishes to access digital objects **202** in the database **104** by subscribing to the database's service, or by paying the database **104** with electronic cash, or by other means as required by the database **104**. A connection **108** between the user **102** and the database **104** could be any standard communication media, such as the Internet or other wide area network. Further, the database **104** maintains one or more groups **106** of digital objects *m* , and the user **102** is interested in retrieving digital objects **202** from the group of N digital objects {m, i = 1, 2, ..., N} **106** in the database **104**. In Fig. 1, the illustrated database **104** contains Groups A through G; however it will be appreciated that the present invention is applicable to a database **104** containing any number of groups **106**. It should also be noted that the particular manner in which the user **102** discovers the desired group **106** is not material to the present invention. All that is required is that the user **102**, either directly or through the use of client software operated by the user **102**, be aware of the digital object **202** the user wants, and the group **106** in which that object **202** is located.

Fig. 2 is a block diagram of a group **106** of digital objects **202** contained within the database **104**. A group **106** contains one or more digital objects **202**. The number of digital objects **202** in a group **106** is determined by the operator/maintainer of the database **104**, and may be determined by factors not within the scope of the present invention. For purposes of the present invention, however, it will be noted from the description that decreasing the size of a group **106** reduces communication cost, but also

decreases privacy protection for the user **102**. Initially, encryption is performed upon all objects **202** in the group **106**, as indicated below. Thus, each digital object **202** in the group **106** will have a ciphertext **206** and a key **204**, and each key **204** will additionally have an associated ciphertext **208**.

Fig. 3 shows a flowchart of the operation of a preferred embodiment of the present invention. The database **104** and user **102** have agreed on some prime number p, such that $p = vq + 1$, where q is a large prime number, for example 160 bits in length, and v is a large integer, for example 800 bits in length. The prime number q is chosen such that p will be prime as well. When the user **102** wants to retrieve digital objects **202** from the group **106**, the user **102** sends **302** a request and optionally the corresponding payment to the database **104**. Upon receipt of the request, the database **104** generates **303** a random number R, $0 < R < p - 1$, and N keys k_i, $i = 1, 2, \ldots, N$, for a symmetric key cryptosystem in a fashion well known in the art. One key k is associated with each digital object m. The database then encrypts **304** each digital object m_i **202** in the group **106** with k_i **204** using the symmetric key cryptosystem to obtain ciphertext $c_i = e(k_i, m_i)$, $i = 1, 2, \ldots, N$ **206**. Finally, the database **104** encrypts **306** the keys **204** themselves to obtain $s_i = k_i^R \bmod p$, $i = 1, 2, \ldots, N$ **208**.

The database **104** next transmits **308** the encrypted objects **206** and keys **208** (c_i, s_i), $i = 1, 2, \ldots, N$ to the user **102**. Assuming that the user **102** intends to retrieve n, $n < N$, digital objects $m_{i1}, m_{i2}, \ldots, m_{in}$ **202** from the group **106**, the user **102** identifies **310** the objects **206** and keys **208** desired, and generates **311** n random numbers w_j, $0 < w_j < p - 1$, and then obtains **312** n re-encrypted keys $W_j = s_{ij}^{wj} \bmod p$, $j = 1, 2, \ldots, n$. The user **102** sends **314** W_j, $j = 1, 2, \ldots, n$ and optionally the required payment to the database **104**. The database **104** computes **316** and sends **318** $U_j = W_j^{1/r \bmod (p-1)} \bmod p$, $j = 1, 2, \ldots, n$, back to the user **102**.

12 OCT 201

The user 102 computes 320 $k_{ij} = U_j^{1/wj \bmod (p-1)} \bmod p$, $j = 1, 2, \ldots, n$, and then decrypts c_{ij} with k_{ij} using the symmetric key cryptosystem to recover digital objects $m_{ij} = d(k_{ij}, c_{ij})$, $j = 1, 2, \ldots, n$ 202.

Fig. 4 is a block diagram that further illustrates the encryption performed on a digital object 202 by the database 104. The digital object 202 and its associated key 204 are provided to the cryptosystem 406, to produce the ciphertext 206, $e(k_i, m_i)$. Similarly, using a prime number p 404, the key 204 and random number R 402, the key 204 itself is encrypted into ciphertext 208 via the cryptosystem 406.

Fig. 5a is a block diagram illustrating the process carried out by the user 102 of re-encrypting 312 the key 204. In addition to the key ciphertext 208, a prime number p 404 and random number w 502 are processed through the encryption algorithm ($s_{ij}^{wj} \bmod p$, as described above) 504 to obtain the re-encrypted key 506.

Similarly, Fig. 5b illustrates the partial decryption 314 performed by the database 104 on the re-encrypted key 506. Using the previously-generated random number R 402 and prime number p 404, the re-encrypted key 506 is then decrypted 314 using the decryption algorithm ($W_j^{1/r \bmod (p-1)} \bmod p$) 508 to obtain the partially decrypted key U 510.

Fig. 6a illustrates the step of transforming the partially decrypted key U 510 into the unencrypted key K 204. The partially decrypted key U 510, the random number w 502, and prime number p 404 are input into the user decryption algorithm ($U_j^{1/wj \bmod (p-1)} \bmod p$) 602, thus revealing the unencryped key K 204.

Then, as shown in Fig. 6b, key k 204 and ciphertext c 206 are input into the cryptosystem decryption algorithm ($d(k_{ij}, c_{ij})$) 604 to obtain the digital object m 202.

Fig. 7 is a block diagram of an apparatus that is a preferred embodiment of the present invention. Note that the apparatus can be implemented either as hardware, firmware, or software. The user 102 has a user bus 726 through which each of the user

12 OCT 2004

modules communicate. Similarly, the database **104** has a database bus **728**. The user bus **726** and database bus **728** communicate via connection **108**. The user **102** requests a group from the database **104** using the requesting module **714**. The user generates random numbers using the random number generating module **718**. Transmissions from the database **104** to the user **102** are received by the receiving module **716**. Data is sent from the user **102** to the database **104** via the transmitting module **722**. User **102** encryption is performed by the encrypting module **720**, and user **102** decryption by the decryption module **724**.

Focusing on the database **104** modules illustrated in Fig. 7, the database **104** generates random numbers using the random number generating module **702**. Transmissions from the user **102** to the database **104** are received by the receiving module **710**. Transmissions from the database **104** to the user **102** are sent by the transmitting module **708**. The database **104** also has a key generating module **704** for generating keys **204**, an encrypting module **706**, and a decrypting module **712**.

Security Considerations:

First, it can be easily seen from this description that the user **102** can obtain the desired digital objects m_{ij} **202** by decrypting ciphertexts c_{ij} **206** with computes $k_{ij} = U_j^{1/wj \bmod (p-1)} \bmod p, j = 1, 2, ..., n$. That is, if both the database **104** and user **102** follow the protocol, the user **102** gets the desired information. However, under no circumstances is the database **104** able to pinpoint which digital objects **202** are being retrieved by the user **102**. In order for the database **104** to find out which digital object **202** the user **102** is interested in retrieving, the database **104** would need to figure out which s_{ij} **208** is being used to compute $W_j = s_{ij}^{wj} \bmod p$ **506** by the user **102**. However, the only information available to the database **104** is $W_j = s_{ij}^{wj} \bmod p, 1, 2, ..., n$ and $s_i, i = 1, 2, ..., N$. Since w_j's are randomly chosen and kept secret by the user **102**, it is equally likely that all s_{ij}'s **208** are being used in computing $W_j = s_{ij}^{wj} \bmod p, j = 1, 2, ..., n$. Therefore, the user's privacy is satisfied without having to rely on any computational assumptions.

Next, we consider database **104** security. Without loss of generality, assume that the user **102** has paid and retrieved m_1, m_2, ..., m_j **202**. The user **102** then tries to recover m_{j+1}, which the user **102** is not authorized to access, without the database's **104** help. This problem is equivalent to, given s_1 **208(1)**, k_1 **204(1)**, s_2 **208(2)**, k_2 **204(2)**, ..., s_j, k_j, and s_{j+1}, finding k_{j+1} such that $s_{j+1} = k_{j+1}^R \bmod p$. One approach to solving this problem is to find R **402** from, for example, $s_j = k_j^R \bmod p$ and then compute $k_{j+1} = s_{j+1}^{1/R(p-1)} \bmod p$. But this is equivalent to solving the discrete logarithm problem, and is therefore not feasible. The second approach is to express s_{j+1} in terms of multiplication or division of $s_1, s_2, ..., s_j$. Then k_{j+1} can be found from a corresponding expression in terms of $k_1, k_2, ..., k_j$. However, since $k_1, k_2, ..., k_j$ and k_{j+1} are all independently and randomly chosen, finding the relationship between the s_i's is also not computationally feasible.

Finally, digital objects **202** are encrypted with a symmetric key cryptosystem and the encryption keys **204** are protected using large exponentiations. To recover the digital objects **202** from the ciphertexts **206**, an eavesdropper must be able to break the symmetric key cryptosystem or solve the discrete logarithm problem. Both are computationally infeasible for well-designed ciphers and exponentiations with large prime modulus.

The above description is included to illustrate the operation of the preferred embodiments and is not meant to limit the scope of the invention. The scope of the invention is to be limited only by the following claims. From the above discussion, many variations will be apparent to one skilled in the art that would yet be encompassed by the spirit and scope of the present invention.

Claims

1. A method for retrieving digital objects from a group of digital objects maintained by a database, the group of digital objects being represented by the equation $G = \{m_i, i = 1, 2, ..., N\}$, wherein G represents the group of digital objects, N represents the number of digital objects maintained by the database, i represents an index having allowable values between 1 and N inclusive, and m_i represents an i^{th} digital object within the group of digital objects, the method comprising:

generating a random number R and keys k_i, i having allowable values between 1 and N inclusive, for a symmetric key cryptosystem;

determining a prime number p;

encrypting digital object m_i with key k_i using the symmetric key cryptosystem to obtain ciphertext c_i;

assigning a value of $k_i^R \bmod p$ to a key ciphertext s_i;

responsive to the database receiving a request signal from a user, sending c_i, and s_i to the user;

receiving from the user a number n of input signals W_j, such that n is less than N, and j is an index having allowable values between 1 and n inclusive;

computing changed ciphertext U_j, such that U_j is equal to $W_j^{1/R \bmod (p-1)} \bmod p$; and

sending U_j to the user.

2. The method of claim 1, where the modulo operations may be carried out in any group in which a discrete logarithm is infeasible to compute.

3. A method for a user to privately retrieve digital objects from a group of digital objects G = { m_i, i = 1, 2, ..., N) maintained by a database, the method comprising the steps of:

sending a request signal to the database;

receiving reply signals c_i, s_i, l = 1, 2, ..., N from the database;

generating random numbers w_j, computing and sending $W_j = s_{ij}^{wj} \bmod p$, j = 1, 2, ..., n to the database;

receiving signals U_j, j = 1, 2, ..., n from the database;

computing $k_{ij} = Uj^{1/wj \bmod (p-1)} \bmod p$, j = 1, 2, ..., n; and

decrypting c_{ij} with k_{ij} and a symmetric key cryptosystem to recover digital objects m_{ij}, j = 1, 2, ..., n.

4. The method of claim 3, wherein the modulo operations may be carried out in any group in which a discrete logarithm is infeasible to compute.

5. A method for selectively retrieving digital objects from a database of digital objects using a symmetric key cryptosystem, the method comprising:

for each digital object in the database:

generating a unique key for the symmetric key cryptosystem;

associating the key with the digital object;

encrypting the digital object using the associated key and the symmetric key cryptosystem to produce a ciphertext of the digital object;

encrypting the associated key to obtain a ciphertext of the key;

transmitting the ciphertext of the digital object and the ciphertext of the key associated with the digital object to a user;

receiving at least one changed ciphertext of the keys associated with the digital objects in the database;

decrypting each received changed ciphertext; and

transmitting the decrypted received changed ciphertexts.

6. A method for retrieving digital objects from a group of digital objects maintained by a database, the method comprising the steps of:

selectively requesting a plurality of digital objects from the database;

receiving encrypted ciphertext digital objects from the database;

receiving from the database encrypted ciphertext keys associated with the received ciphertext digital objects;

encrypting at least one of the encrypted ciphertext keys to obtain changed ciphertext keys;

sending the changed ciphertext keys to the database;

receiving partially decrypted changed ciphertext keys from the database;

decrypting the partially decrypted changed ciphertext keys; and

decrypting at least one of the received ciphertext digital objects using the decrypted keys.

7. An apparatus comprising:

a computerized database;

coupled to the database, a computer user;

coupled to the database, a transmitting module for transmitting data to the user;

coupled to the database, a receiving module for receiving data from the user;

coupled to the database, a random number generating module for generating random numbers;

coupled to the database, a computer user;

coupled to the database, a transmitting module for transmitting digital objects to the user;

coupled to the database, a receiving module for receiving digital objects from the user;

coupled to the database, a random number generating module for generating random numbers;

coupled to the database, a key generating module for generating cryptographic keys;

coupled to the database, an encrypting module for encrypting digital objects;

coupled to the database, a decrypting module for decrypting digital objects;

coupled to the user, a requesting module for requesting digital objects from the database;

coupled to the user, a transmitting module, for transmitting digital objects to the database;

coupled to the user, a receiving module, for receiving digital objects from the database;

coupled to the user, a random number generating module for generating random numbers;

coupled to the user, an encrypting module for encrypting digital objects; and

coupled to the user, a decrypting module for decrypting digital objects.

8. A computer program product stored on a computer readable medium for retrieving digital objects from a group of digital objects maintained by a database, the computer program product controlling a processor coupled to the medium to perform the operations of:

for each digital object in the database:

generating a unique key for a symmetric key cryptosystem;

associating the key with the digital object; encrypting the digital object using the associated key and the symmetric key cryptosystem to produce a ciphertext of the digital object;

encrypting the associated key to obtain a ciphertext of the key;

transmitting to a user the ciphertext of the digital object and the ciphertext of the key associated with the digital object to a user;

receiving at least one changed ciphertext of the keys associated with the digital objects in the database;

decrypting each received changed ciphertext; and

transmitting to the user the decrypted received changed ciphertexts.

Abstract of the Disclosure

PRIVATE RETRIEVAL OF DIGITAL OBJECTS

A database (104) maintains one or more groups (106) of digital objects (202). A user (102) wishes to retrieve one or more digital objects (202) from the database (104), without the database (104) being able to determine which particular digital objects (202) have been retrieved. In addition, the database (104) should not allow the user (102) to retrieve any digital objects (202) to which the user (102) has not been granted access. The user (102) requests the groups (106) containing the digital objects (202) the user (102) wishes to download, but does not identify the digital objects (202) within each group (106) that the user (102) is interested in. Using a symmetric key cryptosystem, the database (104) generates a key (204) for and encrypts each digital object (202) in the requested group (106) into ciphertext (206), and additionally encrypts each key (204). The database (104) transmits the ciphertexts (206) and encrypted keys (208) to the user (102). The user (102) identifies the keys (208) associated with the digital objects (202) of interest, and further encrypts the keys (208), returning the changed keys (506) to the database (104). The database (104) reverses its encryption of the keys (506), and transmits the partially decrypted keys (510) back to the user (102). The user (102) then applies the user's (102) own decryption algorithm to the keys (510), and then uses the decrypted keys (204) to decrypt the digital objects (202) of interest.

Figure 3.