

**METHOD AND ELECTRONIC DEVICE FOR CREATING AN ELECTRONIC
SIGNATURE**

CROSS-REFERENCE TO RELATED APPLICATION

5 This application claims priority of Taiwanese Patent
Application No. 107116100, filed on May 11, 2018.

FIELD

 The disclosure relates to a method and a system for
creating an electronic signature on an original
10 electronic document.

BACKGROUND

 U.S. Patent No. US 9,798,706 B2 discloses a
conventional method for generating an electronic
signature. In the conventional method for generating
15 an electronic signature, a web server provides a webpage
to be displayed on a touch screen of an electronic device,
and receives from the electronic device a representative
signal of a handwritten signature that is inputted by
a signer and a dynamic image that presents a motion of
20 the signer during signing the handwritten signature.
The dynamic image is captured by a dynamic image
capturing module of the electronic device
simultaneously with the inputting of the handwritten
signature. Afterward, the web server stores the dynamic
25 image as a streaming file, compiles a data file that
includes the representative signal and the streaming
file, and executes the data file in the webpage as an

electronic signature.

SUMMARY

One object of the disclosure is to provide a method for creating an electronic signature on an original
5 electronic document.

According to one embodiment of the disclosure, the method is implemented using an electronic device that includes a processor, an image capturing component and an input/output module including a display component.
10 The method includes steps of:

generating a document-related image based on content of the original electronic document;

displaying, by the display component, the original electronic document;

15 recording, by the image capturing component, a real-time video of a user as the user inputs a set of signature strokes that constitute a signature on the input/output module;

generating, by the processor, a superimposition
20 video based on the real-time video and the document-related image, wherein in the superimposition video, the document-related image and a part of the real-time video are superimposed; and

generating, by the processor, an electronic signed
25 document by embedding the superimposition video in the original electronic document.

Another object of the disclosure is to provide an

electronic device that is capable of executing the above-mentioned method.

According to one embodiment of the disclosure, the electronic device for creating an electronic signed document from an original electronic document, and includes a processor, an image capturing component connected to the processor, and an input/output module that is connected to the processor, and that includes a display component.

10 The processor is configured to:

 generate a document-related image based on content of the original electronic document,

 control the display component to display the original electronic document,

15 control the image capturing component to record a real-time video of a user as the user inputs a set of signature strokes that constitute a signature on the input/output module,

 generate a superimposition video based on the real-time video and the document-related image, wherein in the superimposition video, the document-related image and a part of the real-time video are superimposed, and

20 generate an electronic signed document by embedding the superimposition video in the original electronic document.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Other features and advantages of the disclosure will become apparent in the following detailed description of the embodiments with reference to the accompanying drawings, of which:

Figure 1 is a block diagram illustrating an electronic device according to one embodiment of the disclosure;

Figure 2 is a schematic diagram illustrating implementations of the electronic device;

Figure 3 illustrates an original electronic document displayed on the electronic device;

Figure 4 illustrates an exemplary superimposition video being played on the electronic device;

Figure 5 illustrates an electronic signed document that is generated according to one embodiment of this disclosure; and

Figure 6 is a flowchart illustrating steps of a method for creating an electronic signed document according to one embodiment of this disclosure.

DETAILED DESCRIPTION

Before the disclosure is described in greater detail, it should be noted that where considered appropriate, reference numerals or terminal portions of reference numerals have been repeated among the figures to indicate corresponding or analogous elements, which may optionally have similar characteristics.

Figure 1 is a block diagram illustrating an electronic

device 1 according to one embodiment of the disclosure.

As shown in Figure 2, the electronic device 1 may be embodied using a personal computer, a laptop, a tablet, a mobile device (e.g., a smartphone), a personal digital assistant (PDA), etc., and includes an input/output module, an image capturing component 12, a positioning component 13, a communication component 14, a data storage 15 and a processor 16 (see Figure 1).

The input/output module may include an output device such as a display component (e.g., a touchscreen), and an input device such as a writing pad, etc. In this embodiment, the input and output devices are integrated as a touchscreen 11. The image capturing component 12 may be embodied using a physical built-in camera that is built in the electronic device 1 or an external camera connected to the electronic device 1. The positioning component 13 may be embodied using a global positioning system (GPS) component for obtaining a set of location coordinates that indicates a geolocation of the electronic device 1.

The communication component 14 may include a short-range wireless communicating module supporting a short-range wireless communication network using a wireless technology of Bluetooth® and/or Wi-Fi, etc., and a mobile communicating module supporting telecommunication using Long-Term Evolution (LTE), the third generation (3G) and/or fourth generation (4G) of

wireless mobile telecommunications technology, and/or the like.

The data storage 15 may be embodied using a non-volatile storage medium such as a hard disk, flash
5 memory, etc. The data storage 15 stores an operating system (OS) of the electronic device 1 and a software application that can be executed by the processor 16, and at least one original electronic document.

The processor 16 may include, but not limited to,
10 a single core processor, a multi-core processor, a dual-core mobile processor, a microprocessor, a microcontroller, a digital signal processor (DSP), a field-programmable gate array (FPGA), an application specific integrated circuit (ASIC), a radio-frequency
15 integrated circuit (RFIC), etc.

Figure 6 is a flowchart illustrating steps of a method for generating an electronic signed document from an original electronic document. In this embodiment, as shown in Figure 3, the electronic device 1 is embodied
20 using a tablet, the input/output module is embodied using the touchscreen 11, and when it is desired for a user to "sign" the original electronic document, the user may operate the electronic device 1 to execute the software application in step 41. In response, the
25 processor 16 controls the touchscreen 11 to display the original electronic document 2 in step 42.

In one example as shown in Figure 3, the original

electronic document 2 displayed by the touchscreen 11 includes a signature field 211 and a video field 212. For example, the original electronic document 2 is a contract document having multiple pages (e.g., four), and the signature field 211 and the video field 212 are located on a first page of the original electronic document 2. In a case that the original electronic document 2 needs multiple signatures from different parties, additional signature fields and video fields may be present at various locations/pages in the original electronic document 2.

In step 43, the processor 16 generates at least one document-related image based on content of the original electronic document 2.

Referring to Figure 4, for example, the original electronic document 2 is a contract document having four pages. As such, four document-related images 331 (only one is depicted) are generated. Each of the four document-related images 331 may be a screen capture image of one page of the original electronic document 2, or a part of one page of the original electronic document 2. That is to say, the technique of capturing image used on known electronic devices may be employed.

Additional document-related image(s) may be generated to include other features related to the original electronic document 2. For example, one additional document-related image 332 may include

thumbnails 331' respectively of the document-related images 331.

It is noted that, in this embodiment, each of the document-related images 331, 332 may be adjusted to be translucent; that is to say, when one of the document-related images 331 is displayed by the touchscreen 11, the content covered by the one of the document-related images 331 (e.g., a background) can still be visible.

When the user is ready to sign the original electronic document 2, the user may operate the electronic device 1 to input an initiating command associated with the signature field 211 (e.g., by directly touching the touchscreen 11 at a position corresponding to the signature field 211).

The processor 16 determines, in step 44, whether the initiating signal is received. In response to the receipt of the initiating signal, in step 45, the processor 16 obtains the set of location coordinates from the positioning component 13. Otherwise, the processor 16 stands by until the initiating signal is received.

It is noted that in different embodiments, steps 43 and 44 may be carried out in an arbitrary order, or simultaneously.

At this stage, the user (i.e., a signer) is enabled to input the signature in the signature field 211.

In practice, the user inputs a set of signature

strokes 31, one stroke at a time, to compose a signature in the signature field 211 using a finger or a stylus pen. Further in step 45, for each stroke of the set of signature strokes 31, the processor 16 receives a
5 representative signal from the touchscreen 11. The representative signal is embedded with a markup language.

For the signature that includes a plurality of signature strokes, the processor 16 receives a plurality
10 of the representative signals respectively representing the plurality of signature strokes 31, and each of the representative signals is embedded with a respective markup language. In this embodiment, the markup language may be selected from Javascript, Java,
15 Swift, Objective C, etc.

Additionally in step 45, as the user inputs the set of signature strokes 31 that constitute a signature in the signature field 211, the processor 16 controls the image capturing component 12 to start capturing images
20 and recording the images thus captured as a real-time video 32. Specifically, in this embodiment, the image capturing component 12 captures at least the face of the signer during the course of the user/signer inputting the set of signature strokes 31.

25 In this embodiment, the real-time video 32 may be in the form of a streaming media in a format selected from the following: H.263, H.264, flash video (.f4v),

Realmedia (.rm), Windows Media Video (.wmv), .m4v, Quicktime File Format (.mov), etc. In this embodiment, as it is being recorded, the real-time video 32 is displayed in the video field 212.

5 After the user has finished inputting the set of signature strokes 31, he/she may operate the electronic device 1 to input a completion command (e.g., by directly touching the touchscreen 11 at a position corresponding to a complete button).

10 In response to receipt of the completion command, in step 46, the processor 16 generates a superimposition video 3 based on at least the real-time video 32 and the document-related image(s) 331, and, optionally, the additional document-related image 332. In embodiments,
15 the superimposition video 3 may be generated by superimposing the real-time video 32 with other elements such as the document-related image(s) 331 and/or the additional document-related image 332.

 Figure 4 illustrates an exemplary superimposition
20 video 3 that is generated by the processor 16 and is played on the touchscreen 11. In the superimposition video 3, the document-related images 331, 332 and a part of the real-time video 32 are superimposed.

 Specifically, for the example shown in Figure 4, in
25 the superimposition video 3, one of the document-related images 331 superimposes a part of the real-time video 32 while the real-time video 32 is still visible since

the document-related images 331, 332 are translucent, and the set of signature strokes 31 is also incorporated in the superimposition video 3. This may be done by the processor 16 generating a signature file that includes
5 the set of signature strokes 31, and incorporating the signature file in the superimposition video 3. In one implementation, the signature file may be converted into a number of visual elements that can be incorporated into the superimposition video 3, such that when the
10 superimposition video 3 is played, the set of signature strokes 31 are presented.

Additionally, since a large number of document-related images 331 may be present, in order to properly present the document-related images 331 in
15 the superimposition video 3, the superimposition video 3 may be generated to present the document-related images 331 in several ways. For example, each of the document-related images 331 may be configured to be displayed sequentially during playback of the
20 superimposition video 3, in the form of a slideshow. In one example, the superimposition video 3 may be generated such that the document-related image 331 associated with the first page of the original electronic document 2 first appears in the superimposition video
25 3, fades out after one second, and the document-related image 331 associated with the second page of the original electronic document 2 appears and then fades out, and

so forth. In other examples, the document-related images 331 and the additional document-related image 332 (which includes the thumbnails 331') may be arranged to "move" in the superimposition video 3, as if being scrolled by a user, during playback of the superimposition video 3. In the example of Figure 4, the scrolling movement may be horizontal (e.g., from right to left or from left to right), but may be in other manners, such as vertical (e.g., from top to bottom or from bottom to top), in various examples.

It is noted that the document-related images 331, 332 are configured to be displayed sequentially and cyclically during playback of the superimposition video 3. That is to say, after one of the document-related images 331, 332 that is arranged to be displayed last (e.g., the document-related image 331 associated with a last page of the original electronic document 2) has been displayed, one of the document-related images 331 that is arranged to be displayed first (e.g., the additional document-related image 332) may be configured to be displayed again to restart the loop.

In one embodiment, the processor 16 further determines a duration of the real-time video 32 (e.g., 5 to 10 seconds), and generates the superimposition video 3 in a manner that each of the plurality of document-related images 331, 332 is configured to be displayed sequentially, at least once, within a

predetermined time period (which may be shorter than or equal to the duration of the real-time video 32) which falls completely within duration of the real-time video 32 during playback of the superimposition video 3.

5 After the superimposition video 3 is generated, in step 47, the processor 16 generates an electronic signed document 2' (see Figure 5) by embedding the superimposition video 3 in the original electronic document 2 (see Figure 3).

10 Specifically, as shown in Figure 5, the electronic signed document 2' is generated by embedding the superimposition video 3 in the video field 212 of the original electronic document 2. Additionally, the processor 16 further embeds the set of signature strokes
15 31 in the signature field 211 of the original electronic document 2.

 In some embodiments, in step 47, the processor 16 further embeds the set of location coordinates in the original electronic document 2 so as to generate the
20 electronic signed document 2' to have data of the set of location coordinates. The set of location coordinates may be one associated with a current location of the electronic device 1 at which the signing (in step 45) took place, and is obtained using the positioning
25 component 13.

 In some embodiments, in step 47, the processor 16 further generates an encryption value, and further

embeds the encryption value in the original electronic document 2 so as to generate the electronic signed document 2' to have the encryption value.

For example, the encryption value may be in the form of a hash value that is generated based on one or more of the following parameters: a geolocation of the electronic device 1; a position of the signature field 211 and/or the video field 212 on the original electronic document 2; and one or more values extracted from the signature file.

In this way, a hash value thus generated is different from other hash values when one of the above parameters is altered. It is noted that in other embodiments, additional parameters (such as features of the face of the user, a time point at which the real-time video 32 is recorded) may be incorporated in generating the hash value.

In some embodiments, in step 47, the processor 16 further obtains a time stamp from a time stamp authority (TSA), and embeds the time stamp in the original electronic document 2 so as to generate the electronic signed document 2' to have the time stamp. This is done to serve as verification that the electronic signed document 2' is generated at a specific time as indicated by the time stamp.

To sum up, embodiments of the disclosure provide a method and an electronic device that is capable of

generating an electronic signed document 2' that introduces an association among the user, the contents of the original electronic document 2, and the set of signature strokes 31. In this manner, it may be
5 established that the set of signature strokes 31 included in the electronic signed document 2' is signed by the user himself/herself.

Additionally, since the superimposition video 3 includes the set of signature strokes 31, the real-time
10 video 32, and at least a part of the original electronic document 2 (the document-related image(s) 331, and, optionally, the additional document-related image 332), by embedding the superimposition video 3 in the original electronic document 2 as a single element, instead of
15 embedding the above elements in the original electronic document 2 separately, the generation of the electronic signed document 2' may be implemented relatively easily by the electronic device 1 since fewer elements need to be processed.

20 Moreover, one or more verification measures (e.g., the encryption value, the time stamp, etc.) may be selectively incorporated in the electronic signed document 2' in order to verify that the set of signature strokes 31 included the electronic signed document 2' is signed or inputted by the user himself/herself, in
25 order to enhance the authenticity.

In the description above, for the purposes of

explanation, numerous specific details have been set forth in order to provide a thorough understanding of the embodiments. It will be apparent, however, to one skilled in the art, that one or more other embodiments may be practiced without some of these specific details. 5 It should also be appreciated that reference throughout this specification to "one embodiment," "an embodiment," an embodiment with an indication of an ordinal number and so forth means that a particular feature, structure, or characteristic may be included 10 in the practice of the disclosure. It should be further appreciated that in the description, various features are sometimes grouped together in a single embodiment, figure, or description thereof for the purpose of streamlining the disclosure and aiding in the 15 understanding of various inventive aspects, and that one or more features or specific details from one embodiment may be practiced together with one or more features or specific details from another embodiment, where appropriate, in the practice of the disclosure. 20

While the disclosure has been described in connection with what are considered the exemplary embodiments, it is understood that this disclosure is not limited to the disclosed embodiments but is intended to cover 25 various arrangements included within the spirit and scope of the broadest interpretation so as to encompass all such modifications and equivalent arrangements.

CLAIMS:

1. A method for creating an electronic signed document from an original electronic document, the method to be implemented using an electronic device
5 that includes a processor, an image capturing component and an input/output module including a display component, the method comprising steps of:
generating a plurality of document-related images based on content of the original electronic
10 document;
displaying, by the display component, the original electronic document;
recording, by the image capturing component, a real-time video of a user as the user inputs a set
15 of signature strokes that constitute a signature on the input/output module;
generating, by the processor, a superimposition video based on the real-time video and the document-related image, wherein in the superimposition video,
20 the document-related image and a part of the real-time video are superimposed; and
generating, by the processor, an electronic signed document by embedding the superimposition video in the original electronic document;
25 wherein in the superimposition video, the document-related image superimposes a part of the real-time video;

wherein each of the plurality of document-related images is a screen capture image of the original electronic document;

5 wherein in the step of generating a superimposition video, the superimposition video is generated in a manner that each of the plurality of document-related images is configured to be displayed sequentially during playback of the
10 superimposition video.

2. The method of Claim 1, wherein one of the plurality of document-related images is a screen capture image of at least a part of a page of the original electronic document.

15 3. The method of Claim 1, wherein in the step of generating a superimposition video, the processor further generates a signature file that includes the set of signature stokes, and incorporates the signature file in the superimposition video.

20 4. The method of Claim 1, wherein in the step of generating a superimposition video, the superimposition video is generated in a manner that each of the plurality of document-related images is configured to be displayed sequentially and
25 cyclically during playback of the superimposition video.

5. The method of Claim 1, wherein in the step of

generating a superimposition video, the superimposition video is generated in a manner that each of the plurality of document-related images is configured to be displayed sequentially at least once within a predetermined time period during playback of the superimposition video.

6. The method of Claim 1, wherein one of the document-related images includes a thumbnail of the screen capture image of the original electronic document.

7. An electronic device for creating an electronic signed document from an original electronic document, comprising:

a processor;

an image capturing component connected to said processor; and

an input/output module that is connected to said processor, and that includes a display component,

wherein said processor is configured to

generate a plurality of document-related images based on content of the original electronic document,

control said display component to display the original electronic document,

control said image capturing component to record a real-time video of a user as the user inputs a set of signature strokes that constitute a

signature on said input/output module,

generate a superimposition video based on the
real-time video and the plurality of document-
related images, wherein in the superimposition video,
5 the plurality of document-related images and a part
of the real-time video are superimposed, and

generate an electronic signed document by
embedding the superimposition video in the original
electronic document;

10 wherein said processor is configured to generate
the superimposition video in a manner that each of
the plurality of document-related images
superimposes a part of the real-time video;

wherein each of the plurality of document-
15 related images is a screen capture image of the
original electronic document;

wherein said processor is configured to generate
the superimposition video in a manner that each of
the plurality of document-related images is
20 configured to be displayed sequentially during
playback of the superimposition video.

8. The electronic device of Claim 7, wherein one of
the plurality of document-related images is a screen
capture image of at least a part of a page of the
25 original electronic document.

9. The electronic device of Claim 7, wherein said
processor is further configured to generate a

signature file that includes the set of signature stokes, and to incorporate the signature file in the superimposition video.

5 10. The electronic device of Claim 7, wherein said processor is configured to generate the superimposition video in a manner that each of the plurality of document-related images is configured to be displayed sequentially and cyclically during playback of the superimposition video.

10 11. The electronic device of Claim 7, wherein said processor is configured to generate the superimposition video in a manner that each of the plurality of document-related images is configured to be displayed sequentially at least once within a
15 predetermined time period during playback of the superimposition video.

12. The electronic device of Claim 7, wherein one of the document-related images includes a thumbnail of the screen capture image of the original electronic
20 document.

13. The electronic device of Claim 7, wherein:

the original electronic document includes a plurality of pages;

25 each of the plurality of document-related images generated by said processor is a screen capture image of at least a part of a corresponding page of the

original electronic document; and

said processor is configured to generate the
superimposition video in a manner that each of the
plurality of document-related images is configured
5 to be displayed sequentially during playback of the
superimposition video.

14. The method of Claim 2, wherein:

the original electronic document includes a
10 plurality of pages; and

in the step of generating a plurality of
document-related images, the processor generates
each of the plurality of document-related images to
be a screen capture image of at least a part of a
15 corresponding page of the original electronic
document.