

PRIMING SYSTEM FOR DRUG DELIVERY DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority to United States Provisional Application Serial No. 62/612,842 entitled “Priming System for Drug Delivery Device” filed January 2, 2018, the entire disclosure of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present disclosure relates generally to a drug delivery device and, in particular, to a priming assembly for a drug delivery device.

Description of Related Art

[0003] Various types of automatic injection or drug delivery devices have been developed to allow drug solutions and other liquid therapeutic preparations to be administered by untrained personnel or to be self-injected. Generally, these devices include a reservoir that is pre-filled with the liquid therapeutic preparation, and some type of automatic needle-injection mechanism that can be triggered by the user. When the volume of fluid or drug to be administered is generally below a certain volume, such as 1 mL, an auto-injector is typically used, which typically has an injection time of about 10 to 15 seconds. When the volume of fluid or drug to be administered is above 1 mL, the injection time generally becomes longer resulting in difficulties for the patient to maintain contact between the device and the target area of the patient’s skin. Further, as the volume of drug to be administered becomes larger, increasing the time period for injection becomes desirable. The traditional method for a drug to be injected slowly into a patient is to initiate an IV and inject the drug into the patient’s body slowly. Such a procedure is typically performed in a hospital or outpatient setting.

[0004] Certain devices allow for self-injection in a home setting and are capable of gradually injecting a liquid therapeutic preparation into the skin of a patient. In some cases, these devices are small enough (both in height and in overall size) to allow them to be “worn” by a patient while the liquid therapeutic preparation is being infused into the patient. These devices typically include a pump or other type of discharge mechanism to force the liquid therapeutic preparation to flow out of a reservoir and into the injection needle. Such devices also typically include a valve or flow

control mechanism to cause the liquid therapeutic preparation to begin to flow at the proper time and a triggering mechanism to initiate the injection.

SUMMARY OF THE INVENTION

[0005] In one aspect, a priming assembly for a drug delivery device includes a hub, a base connected to the hub and moveable relative to the hub between a first position and a second position, with the base defining a passageway, a cap defining an interior chamber and a passageway in fluid communication with the interior chamber, and a needle connected to the hub and positioned within the interior chamber of the cap. The passageway of the base is in fluid communication with the passageway of the cap when the base is in the first position, and the passageway of the base is isolated from the passageway of the cap when the base is in the second position.

[0006] The cap and the base may form a sealed interface between the cap and the base. The cap may include a closed first end and an open second end, with the open second end secured to the hub. The cap may be manufactured from an elastomeric material. The cap is configured to deform from a first position where an end of the needle is positioned within the cap and a second position where the end of the needle is positioned outside of the cap. One of the hub and the base may define a slot and the other of the hub and the base may include a projection received within the slot, with the slot having a first end and a second end, and where, when the projection is at the first end of the slot, the base is in the first position, and, when the projection is at the second end of the slot, the base is in the second position. The assembly may further include a priming fluid tube in fluid communication with the passageway of the base. The assembly may further include a delivery tube connected to the hub and in fluid communication with the needle.

[0007] In a further aspect, a drug delivery device includes a housing, a cartridge received within the housing with the cartridge configured to receive a medicament, a drive assembly received with the housing and configured to engage the cartridge and dispense medicament from the cartridge, a needle actuator assembly received within the housing with the needle actuator assembly including a patient needle configured to pierce a user's skin, and a priming system. The priming system includes a cartridge priming assembly including a hub, a base connected to the hub and moveable relative to the hub between a first position and a second position, a cap defining an interior chamber

and a passageway in fluid communication with the interior chamber, and a needle connected to the hub and positioned within the interior chamber of the cap. The base defines a passageway. The priming system further includes a needle actuator priming assembly including a hub, a base connected to the hub and moveable relative to the hub between a first position and a second position, a cap defining an interior chamber and a passageway in fluid communication with the interior chamber, and a needle connected to the hub and positioned within the interior chamber of the cap, with the base defining a passageway. The priming system also includes a delivery tube in fluid communication with the hub of the cartridge priming assembly and the hub of the needle actuator priming assembly. The passageway of the base of the cartridge priming assembly is in fluid communication with the passageway of the cap of the cartridge priming assembly when the base is in the first position, and the passageway of the base of the cartridge priming assembly is isolated from the passageway of the cap when the base is in the second position.

[0008] The passageway of the base of the needle actuator priming assembly may be in fluid communication with the passageway of the cap of the needle actuator priming assembly when the base is in the first position, and the passageway of the base cartridge of the needle actuator priming assembly may be isolated from the passageway of the cap when the base is in the second position. The device may further include an inflow tube in fluid communication with the passageway of the base of the cartridge priming assembly. The device may further include an outflow tube in fluid communication with the passageway of the base of the needle actuator priming assembly. The cap and the base of the cartridge priming assembly and the needle actuator priming assembly may each form a sealed interface between the cap and the base. The caps of the cartridge priming assembly and the needle actuator priming assembly may each include a closed first end and an open second end, with the open second ends secured to the respective hubs. The caps of the cartridge priming assembly and the needle actuator priming assembly may each comprise an elastomeric material. The caps of the cartridge priming assembly and the needle actuator priming assembly may each be configured to deform from a first position where an end of the needle is positioned within the cap and a second position where the end of the needle is positioned outside of the cap. One of the hub and the base of the cartridge priming assembly may define a slot and the other of the hub and the base may include a projection received within the slot, with the slot having a first end and a second end, and where, when the projection is at the first end of the slot, the base is in the first position, and, when the projection is at the second end of the slot, the base is in the second position.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The above-mentioned and other features and advantages of this disclosure, and the manner of attaining them, will become more apparent and the disclosure itself will be better understood by reference to the following descriptions of embodiments of the disclosure taken in conjunction with the accompanying drawings, wherein:

[0010] FIG. 1 is a perspective view of a drug delivery system according to one aspect of the present invention.

[0011] FIG. 2 is a perspective, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention.

[0012] FIG. 3 is a front, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention.

[0013] FIG. 4 is a top view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing a top portion of the housing removed and the drug delivery system in a pre-use position.

[0014] FIG. 5 is a top, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a pre-use position.

[0015] FIG. 6 is a front, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a pre-use position.

[0016] FIG. 7 is a top view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing a top portion of the housing removed and the drug delivery system in an initial actuation position.

[0017] FIG. 8 is a top, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in an initial actuation position.

[0018] FIG. 9 is a front, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in an initial actuation position.

[0019] FIG. 10 is a top view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing a top portion of the housing removed and the drug delivery system in a use position.

[0020] FIG. 11 is a top, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a use position.

[0021] FIG. 12 is a front, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a use position.

[0022] FIG. 13 is a top view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing a top portion of the housing removed and the drug delivery system in a post-use position.

[0023] FIG. 14 is a top, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a post-use position.

[0024] FIG. 15 is a front, cross-sectional view of the drug delivery system of FIG. 1 according to one aspect of the present invention, showing the drug delivery system in a post-use position.

[0025] FIG. 16 is a perspective view of a priming assembly according to one aspect of the present invention, showing the assembly in an open position and with a cap shown as transparent for clarity.

[0026] FIG. 17 is a front view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in an open position.

[0027] FIG. 18 is a top view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in an open position.

[0028] FIG. 19 is a top view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in a closed position.

[0029] FIG. 20 is a perspective view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in a closed position.

[0030] FIG. 21 is a top view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in a use position.

[0031] FIG. 22 is a perspective view of the priming assembly of FIG. 16 according to one aspect of the present invention, showing the assembly in a use position.

[0032] FIG. 23 is a front view of a priming system according to one aspect of the present invention, showing an open position of the system.

[0033] FIG. 24A is a front view of the priming system of FIG. 23 according to one aspect of the present invention, showing an open position of the system while fluid fills the fluid path.

[0034] FIG. 24B is a front view of the priming system of FIG. 23 according to one aspect of the present invention, showing an open position of the system with the fluid path filled with fluid.

[0035] FIG. 25 is a front view of the priming system of FIG. 23 according to one aspect of the present invention, showing a closed position of the system.

[0036] FIG. 26 is a front view of the priming system of FIG. 23 according to one aspect of the present invention, showing drug delivery device interfaces.

[0037] FIG. 27 is a top view of a drug delivery device according to one aspect of the present invention, showing a pre-use position of the device.

[0038] FIG. 28 is a top view of the drug delivery device of FIG. 27 according to one aspect of the present invention, showing a use position of the device.

[0039] FIG. 29 is a top view of the drug delivery device of FIG. 27 according to one aspect of the present invention, showing a further use position of the device.

[0040] FIG. 30 is a top view of a drug delivery device according to one aspect of the present invention, showing a pre-use position of the device.

[0041] FIG. 31 is a top view of a drug delivery device according to one aspect of the present invention, showing a use position of the device.

[0042] FIG. 32 is a front view of a priming system according to one aspect of the present invention, showing an open position of the system.

[0043] FIG. 33 is a front view of the priming system of FIG. 32 according to one aspect of the present invention, showing an open position of the system while fluid fills the fluid path.

[0044] FIG. 34 is a front view of the priming system of FIG. 32 according to one aspect of the present invention, showing a closed position of the system with the fluid path filled with fluid.

DETAILED DESCRIPTION

[0045] The following description is provided to enable those skilled in the art to make and use the described embodiments contemplated for carrying out the invention. Various modifications, equivalents, variations, and alternatives, however, will remain readily apparent to those skilled in the art. Any and all such modifications, variations, equivalents, and alternatives are intended to fall within the spirit and scope of the present invention.

[0046] For purposes of the description hereinafter, the terms “upper”, “lower”, “right”, “left”, “vertical”, “horizontal”, “top”, “bottom”, “lateral”, “longitudinal”, and derivatives thereof shall relate to the invention as it is oriented in the drawing figures. However, it is to be understood that

the invention may assume various alternative variations, except where expressly specified to the contrary. It is also to be understood that the specific devices illustrated in the attached drawings, and described in the following specification, are simply exemplary embodiments of the invention. Hence, specific dimensions and other physical characteristics related to the embodiments disclosed herein are not to be considered as limiting.

[0047] Referring to FIGS. 1-15, a drug delivery device 10 according to one aspect of the present disclosure includes a drive assembly 12, a container 14, a valve assembly 16, and a needle actuator assembly 18. The drive assembly 12, the container 14, the valve assembly 16, and the needle actuator assembly 18 are at least partially positioned within a cavity defined by a housing 20. The housing 20 includes a top portion 22 and a bottom portion 24, although other suitable arrangements for the housing 20 may be utilized. In one aspect, the drug delivery device 10 is an injector device configured to be worn or secured to a user and to deliver a predetermined dose of a medicament provided within the container 14 via injection into the user. The device 10 may be utilized to deliver a “bolus injection” where a medicament is delivered within a set time period. The medicament may be delivered over a time period of up to 45 minutes, although other suitable injection amounts and durations may be utilized. A bolus administration or delivery can be carried out with rate controlling or have no specific rate controlling. The device 10 may deliver the medicament at a fixed pressure to the user with the rate being variable. The general operation of the device 10 is described below in reference to FIGS. 1-15.

[0048] Referring again to FIGS. 1-15, the device 10 is configured to operate through the engagement of an actuation button 26 by a user, which results in a needle 28 of the needle actuator assembly 18 piercing the skin of a user, the actuation of the drive assembly 12 to place the needle 28 in fluid communication with the container 14 and to expel fluid or medicament from the container 14, and the withdrawal of the needle 28 after injection of the medicament is complete. The general operation of a drug delivery system is shown and described in International Publication Nos. 2013/155153 and 2014/179774, which are hereby incorporated by reference in their entirety. The housing 20 of the device 10 includes an indicator window 30 for viewing an indicator arrangement 32 configured to provide an indication to a user on the status of the device 10 and a container window 31 for viewing the container 14. The indicator window 30 may be a magnifying lens for providing a clear view of the indicator arrangement 32. The indicator arrangement 32 moves along with the needle actuator assembly 18 during use of the device 10 to

indicate a pre-use status, use status, and post-use status of the device 10. The indicator arrangement 32 provides visual indicia regarding the status, although other suitable indicia, such as an auditory or tactile, may be provided as an alternative or additional indicia.

[0049] Referring to FIGS. 4-6, during a pre-use position of the device 10, the container 14 is spaced from the drive assembly 12 and the valve assembly 16 and the needle 28 is in a retracted position. During the initial actuation of the device 10, as shown in FIGS. 7-9, the drive assembly 12 engages the container 14 to move the container 14 toward the valve assembly 16, which is configured to pierce a closure 36 of the container 14 and place the medicament within the container 14 in fluid communication with the needle 28 via a tube (not shown) or other suitable arrangement. The drive assembly 12 is configured to engage a stopper 34 of the container 14, which will initially move the entire container 14 into engagement with the valve assembly 16 due to the incompressibility of the fluid or medicament within the container 14. The initial actuation of the device 10 is caused by engagement of the actuation button 26 by a user, which releases the needle actuator assembly 18 and the drive assembly 12 as discussed below in more detail. During the initial actuation, the needle 28 is still in the retracted position and about to move to the extended position to inject the user of the device 10.

[0050] During the use position of the device 10, as shown in FIGS. 10-12, the needle 28 is in the extended position at least partially outside of the housing 20 with the drive assembly 12 moving the stopper 34 within the container 14 to deliver the medicament from the container 14, through the needle 28, and to the user. In the use position, the valve assembly 16 has already pierced a closure 36 of the container 14 to place the container 14 in fluid communication with the needle 28, which also allows the drive assembly 12 to move the stopper 34 relative to the container 14 since fluid is able to be dispensed from the container 14. At the post-use position of the device 10, shown in FIGS. 13-15, the needle 28 is in the retracted position and engaged with a pad 38 to seal the needle 28 and prevent any residual flow of fluid or medicament from the container 14. The container 14 and valve assembly 16 may be the container 14 and valve assembly 16 shown and described in International Publication No. WO 2015/081337, which is hereby incorporated by reference in its entirety.

[0051] Referring to FIGS. 16-25, a priming system 50 for use in connection with the drug delivery device 10 is shown. Although the priming system 50 is shown in connection with the delivery device 10, the priming system 50 may also be incorporated into any other suitable device

or system for delivering medicament to patient. The priming system 50 includes a cartridge priming assembly 52, a needle actuator priming assembly 54, and a delivery tube 56 extending between the cartridge priming assembly 52 and the needle actuator priming assembly 54.

[0052] Referring to FIGS. 16-22, each of the priming assemblies 52, 54 includes a hub 60, 80, a base 62, 82 connected to the hub 60, 80 and defining a passageway 64, 84, a cap 66, 86 defining an interior chamber 68, 88 and a passageway 70, 90 in fluid communication with the interior chamber 68, 88, and a needle 72, 92 connected to the hub 60, 80 and positioned within the interior chamber 68, 88 of the cap 66, 86. The base 62, 82 is moveable relative to the hub 60, 80 between a first position and a second position. In particular, the base 62, 82 is rotatable relative to the cap 66, 86 and the hub 60, 80 between the first and second positions. The delivery tube 56 is in fluid communication with the hub 60 of the cartridge priming assembly 52 and the hub 80 of the needle actuator priming assembly 54. For each assembly 52, 54, the passageway 64, 84 of the base 62, 82 is in fluid communication with the passageway 70, 90 of the cap 66, 86 when the base 62, 82 is in the first position, and the passageway 64, 84 of the base 62, 82 is isolated from the passageway 70, 90 of the cap 66, 86 when the base 62, 82 is in the second position. The cap 66, 86 and the base 62, 82 of the priming assemblies 52, 54 each form a sealed interface between the cap 66, 86 and the base 62, 82. The sealed interface prevents any leakage from the passageway 70, 90 of the cap 66, 86 during movement of the base 62, 82 between the first and second positions. The sealed interface may be provided by the engagement between the cap 66, 86 and the base 62, 82. In particular, the cap 66, 86 may be manufactured from an elastomeric material that forms a seal with the base 62, 82 and the hub 60, 80. The cap 66, 86 includes a closed first end 74, 94 and an open second end 76, 96, with the open second end 76, 96 positioned over and secured to the hub 60, 80. The open second end 76, 96 is engaged with the base 62, 82.

[0053] Referring again to FIGS. 16-22, the needle 72, 92 includes a first end 102, 112 secured to and in fluid communication with the hub 60, 80 and a second end 104, 114 positioned within the interior chamber 68, 88 of the cap 66, 86. The second end 104, 114 of the needle 72, 92 may be sharpened and configured to pierce the cap 66, 86 and a closure 36 of the cartridge 14. For each of the priming assemblies 52, 54, the cap 66, 86 is configured to deform from a first, pre-use position where the second end 104, 114 of the needle 72, 92 is positioned within the cap 66, 86 and a second, use position where the second end 104, 114 of the needle 72, 92 is positioned outside of the cap 66, 86.

[0054] Referring again to FIGS. 16-25, the cartridge priming assembly 52 includes an inflow tube 120 in fluid communication with the passageway 64 of the base 62 of the cartridge priming assembly 52. The needle actuator priming assembly 54 includes an outflow tube 122 in fluid communication with the passageway 84 of the base 82 of the needle actuator priming assembly 54.

[0055] Referring to FIGS. 23-25, prior to use of the priming system 50, the priming assemblies 52, 54 and the delivery tube 56 are filled with air and are ready for filling. The priming system 50 is primed by delivering priming fluid through the inflow tube 120 of the cartridge priming assembly 52 with the base 62 in the first position such that fluid flows through the inflow tube 120, through the passageway 64 of the base 62, through the passageway 70 of the cap 66, and into the interior chamber 68 of the cap 66. From the interior chamber 68 of the cap 66, the fluid continues to flow through the needle 72, through the hub, and into the delivery tube 56. With the base 82 of the needle actuator priming assembly 54 in the first position, the fluid flows through the hub 80 of the needle actuator priming assembly 54, through the needle 92, into the interior chamber 88 of the cap 86 of the needle actuator priming assembly 54, and into the outflow tube 122 of the needle actuator priming assembly 54. Once the priming system 50 is fully primed and all air is removed from the system 50, the bases 62, 82 of the cartridge priming assembly 52 and the needle actuator priming assembly 54 are each rotated from the first position to the second position to seal the primed fluid with the priming system 50. When the bases 62, 82 are in the second position, the passageways 64, 84 of the bases 62, 82 are isolated from and are sealed from the passageways 70, 90 of the cap. The priming fluid may be buffered saline, heparin, or any other suitable priming fluid.

[0056] Referring to FIGS. 26-31, the priming system 50 is configured to be primed and assembled into the drug delivery device 10. In one aspect, the cartridge priming assembly 52 replaces the valve assembly 16 and the needle actuator priming assembly 54 replaces the needle 28 while functioning the same as the valve assembly 16 and needle 28. As shown in FIG. 26, the cartridge priming assembly 52 and the needle actuator priming assembly 54 include interfaces 124, 125 for cooperating with the device 10 in the same manner as the valve assembly 16 and needle 28. As shown in FIG. 27, in a pre-use state, the priming system 50 is primed and filled with priming fluid. As shown in FIG. 28, during an injection, the cartridge 14 engages the cap 66 of the cartridge priming assembly 52 and deforms the cap 66 to the second position with the needle

72 being placed in fluid communication with the medicament in the cartridge 14. The priming fluid is pushed out by the medicament from the cartridge 14, which flows from the cartridge 14 through the cartridge priming system 52, through the delivery tube 56, and through the needle actuator priming assembly 54 and into a patient. As shown in FIG. 29, during injection, all of the priming fluid has been injected and the medicament from the cartridge 14 is being injected.

[0057] Referring to FIGS. 32-34, in one aspect, the hub 60, 80 of the priming assemblies 52, 54 defines a slot 126, 136 and the base 62, 82 includes a projection 128, 138 received within the slot 126, 136. The slot 126, 136 has a first end 130, 140 and a second end 132, 142. When the projection 128, 138 is at the first end 130, 140 of the slot 126, 136, as shown in FIG. 32, the base 62, 82 is in the first position and, when the projection 128, 138 is at the second end of the slot 126, 136, as shown in FIG. 33, the base 62, 82 is in the second position. Accordingly, the base 62, 82 is rotatable between the first and second positions and movement of the base 62, 82 may be restricted to movement between the first and second positions. The slots 126, 136 may include bumps or other structures to retain the projections 128, 138 in the first and second ends 130, 132, 140, 142 of the slots 126, 136. Further, the slot 126, 136 and projection 128, 138 may provide a visual and/or tactile feedback regarding whether the base 62, 82 is in the first position or the second position. Although the slot 126, 136 is provided on the hub 60, 80 and the projection 128, 138 is provided on the base 62, 82, the position of the slot 126, 136 and the projection 128, 138 may be reversed with the base 62, 82 defining the slot 126, 136 and the hub 60, 80 including the projection 128, 138. As shown in FIG. 34, the inflow and outflow tubes 120, 122 may be removed after the priming system 50 is primed and sealed.

[0058] Elements of one disclosed aspect can be combined with elements of one or more other disclosed aspects to form different combinations, all of which are considered to be within the scope of the present invention.

[0059] While this disclosure has been described as having exemplary designs, the present disclosure can be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains and which fall within the limits of the appended claims.

WHAT IS CLAIMED IS:

1. A priming assembly for a drug delivery device comprising:
 - a hub;
 - a base connected to the hub and rotatable relative to the hub between a first position and a second position, the base defining a passageway;
 - a cap defining an interior chamber and a passageway in fluid communication with the interior chamber; and
 - a needle connected to the hub and positioned within the interior chamber of the cap, wherein the passageway of the base is in fluid communication with the passageway of the cap when the base is in the first position, and wherein the passageway of the base is isolated from the passageway of the cap when the base is in the second position,wherein one of the hub and the base defines a slot and the other of the hub and the base comprises a projection received within the slot, the slot having a first end and a second end, and wherein, when the projection is at the first end of the slot, the base is in the first position, and, when the projection is at the second end of the slot, the base is in the second position.
2. The assembly of claim 1, wherein the cap and the base form a sealed interface between the cap and the base.
3. The assembly of claim 1, wherein the cap includes a closed first end and an open second end, the open second end secured to the hub.
4. The assembly of claim 3, wherein the cap comprises an elastomeric material.
5. The assembly of claim 3, wherein the cap is configured to deform from a first position where an end of the needle is positioned within the cap to a second position where the end of the needle is positioned outside of the cap.

6. The assembly of claim 1, further comprising a priming fluid tube in fluid communication with the passageway of the base.

7. The assembly of claim 6, further comprising a delivery tube connected to the hub and in fluid communication with the needle.

8. A drug delivery device comprising:

a housing;

a cartridge received within the housing, the cartridge configured to receive a medicament;

a drive assembly received with the housing and configured to engage the cartridge and dispense medicament from the cartridge;

a needle actuator assembly received within the housing, the needle actuator assembly comprising a patient needle configured to pierce a user's skin; and

a priming system comprising:

a cartridge priming assembly comprising a first hub, a first base connected to the first hub and moveable relative to the first hub between a first position and a second position, a first cap defining a first cap interior chamber and a first cap passageway in fluid communication with the first cap interior chamber, and a first needle connected to the first hub and positioned within the first cap interior chamber of the first cap, the base defining a first base passageway;

a needle actuator priming assembly comprising a second hub, a second base connected to the second hub and moveable relative to the second hub between a first position and a second position, a second cap defining a second cap interior chamber and a second cap passageway in fluid communication with the second cap interior chamber, and a second needle connected to the second hub and positioned within the second cap interior chamber of the second cap, the second base defining a second base passageway; and

a delivery tube in fluid communication with the first hub of the cartridge priming assembly and the second hub of the needle actuator priming assembly,

wherein the first base passageway of the first base of the cartridge priming assembly is in fluid communication with the first cap passageway of the first cap of the cartridge priming assembly when the first base is in the first position, and wherein the

first base passageway of the first base of the cartridge priming assembly is isolated from the first cap passageway of the first cap when the first base is in the second position.

9. The device of claim 8, wherein the second base passageway of the second base of the needle actuator priming assembly is in fluid communication with the second cap passageway of the second cap of the needle actuator priming assembly when the second base is in the first position, and wherein the second base passageway of the second base of the needle actuator priming assembly is isolated from the second cap passageway of the second cap when the second base is in the second position.

10. The device of claim 8, further comprising an inflow tube in fluid communication with the first base passageway of the first base of the cartridge priming assembly.

11. The device of claim 10, further comprising an outflow tube in fluid communication with the second base passageway of the second base of the needle actuator priming assembly.

12. The device of claim 8, wherein the first cap and the first base of the cartridge priming assembly form a sealed interface between the first cap and the first base, and the second cap and the second base of the needle actuator priming assembly form a sealed interface between the second cap and the second base.

13. The device of claim 8, wherein the first cap of the cartridge priming assembly and the second cap of the needle actuator priming assembly each include a closed first end and an open second end, the open second ends secured to the respective first and second hubs.

14. The device of claim 13, wherein the first cap of the cartridge priming assembly and the second cap of the needle actuator priming assembly each comprise an elastomeric material.

15. The device of claim 13, wherein the first cap of the cartridge priming assembly is configured to deform from a first position where an end of the first needle is positioned within the first cap and a second position where the end of the first needle is positioned outside of the first cap, and the second cap of the needle actuator priming assembly is configured to deform from a first position where an end of the second needle is positioned within the second cap and a second position where the end of the second needle is positioned outside of the second cap.

16. The device of claim 8, wherein one of the first hub and the first base of the cartridge priming assembly defines a slot and the other of the first hub and the first base comprises a projection received within the slot, the slot having a first end and a second end, and wherein, when the projection is at the first end of the slot, the first base is in the first position, and, when the projection is at the second end of the slot, the first base is in the second position.

17. A priming assembly for a drug delivery device comprising:

a hub;

a base connected to the hub and rotatable relative to the hub between a first position and a second position, the base defining a passageway;

a cap defining an interior chamber and a passageway in fluid communication with the interior chamber, wherein the cap includes a closed first end and an open second end, the open second end secured to the hub; and

a needle connected to the hub and positioned within the interior chamber of the cap, wherein the passageway of the base is in fluid communication with the passageway of the cap when the base is in the first position, and wherein the passageway of the base is isolated from the passageway of the cap when the base is in the second position,

wherein the cap is configured to deform from a first position where an end of the needle is positioned within the cap to a second position where the end of the needle is positioned outside of the cap.