

WHAT IS CLAIMED IS:

1. A system for plant culture, comprising:
 - a chamber comprising one or more walls enclosing a spatial volume internal to the
 - 5 chamber, wherein the one or more walls comprise a surface for supporting a plant within the enclosed spatial volume;
 - a gas delivery apparatus, comprising at least one gas source;
 - a nutrient delivery apparatus comprising a reservoir;
 - a sampling apparatus connected to a port formed in the one or more walls; and
 - 10 a controller connected to the gas delivery apparatus and the nutrient delivery apparatus, and configured so that during operation of the system, with a plant entirely positioned within the enclosed spatial volume of the chamber, the controller:
 - activates the nutrient delivery apparatus to deliver an aqueous growth medium to the plant; and
 - 15 activates the gas delivery apparatus to deliver into the enclosed spatial volume a mixture of isotopically-substituted gases.
2. The system of claim 1, wherein a height of the enclosed spatial volume measured between the surface and a wall or wall portion opposite the surface is at least 0.5 meters.
- 20 3. The system of claim 2, wherein the height is at least 3.0 meters.
4. The system of claim 1, wherein the enclosed spatial volume is at least 500 L.
- 25 5. The system of claim 4, wherein the enclosed spatial volume is at least 1000 L.
6. The system of claim 1, wherein when the chamber is filled with a gas at a pressure of 1.5 atmospheres, a leakage rate of the gas from the chamber is less than 0.5 L/day.
- 30 7. The system of claim 1, wherein the leakage rate is less than 0.1 L/day.
8. The system of claim 1, wherein when the chamber is filled with a gas at a pressure p at a first time, the one or more walls of the chamber are sufficiently impermeable so that the

gas pressure within the chamber at a second time at least 7 days after the first time is $0.80p$ or more.

9. The system of claim 8, wherein the gas pressure within the chamber at the second
5 time is $0.90p$ or more.

10. The system of claim 1, wherein the gas delivery apparatus comprises a valve
connected to the controller, and wherein during operation of the system, the controller is
configured to activate the valve to regulate gas delivery from the gas delivery apparatus.
10

11. The system of claim 10, wherein during operation of the system, the at least one gas
source comprises a source of nitrogen gas for which an isotopic ratio of ^{15}N to ^{14}N is greater
than a ratio of ^{15}N to ^{14}N in atmospheric nitrogen gas.

12. The system of claim 10, wherein during operation of the system, the at least one gas
15 source comprises a source of nitrogen gas for which an isotopic ratio of ^{13}N to ^{14}N is greater
than a ratio of ^{13}N to ^{14}N in atmospheric nitrogen gas.

13. The system of claim 11, wherein during operation of the system, the controller is
20 configured to adjust the isotopic ratio of ^{15}N to ^{14}N in the chamber.

14. The system of claim 13, wherein during operation of the system, the nitrogen gas
mixture in the chamber comprises at least 0.1 atom% ^{15}N .

15. The system of claim 14, wherein the nitrogen gas mixture comprises at least 0.5
25 atom% ^{15}N .

16. The system of claim 12, wherein during operation of the system, the control is
configured to adjust the isotopic ratio of ^{13}N to ^{14}N in the chamber.
30

17. The system of claim 16, wherein during operation of the system, the nitrogen gas
mixture in the chamber comprises at least 0.1 atom% ^{13}N .

18. The system of claim 17, wherein the nitrogen gas mixture comprises at least 0.5 atom% ^{13}N .

19. The system of claim 12, further comprising a gas detector connected to the controller
5 and configured to generate a measurement signal in response to a presence of one or more gas species within the chamber.

20. The system of claim 19, wherein the gas detector is configured to generate a measurement signal representing the isotopic ratio of ^{15}N to ^{14}N in the chamber, and wherein
10 the controller is configured to regulate delivery of the nitrogen gas into the chamber based on the measurement signal.

21. The system of claim 1, further comprising a gas removal apparatus connected to a port formed in the one or more walls.
15

22. The system of claim 21, wherein the gas removal apparatus comprises an oxygen gas scrubber.

23. The system of claim 21, further comprising a gas detector connected to the controller
20 and configured to generate a measurement signal representing an amount of oxygen gas in the chamber.

24. The system of claim 23, wherein the controller is connected to the gas removal apparatus, and wherein during operation of the system, the controller is configured to activate
25 the gas removal apparatus based on the measurement signal to adjust an oxygen gas concentration in the chamber.

25. The system of claim 10, wherein during operation of the system, the gas delivery apparatus comprises a source of carbon dioxide gas.
30

26. The system of claim 25, further comprising a gas detector connected to the controller and configured to generate a measurement signal representing an amount of carbon dioxide gas in the chamber.

27. The system of claim 26, wherein during operation of the system, the controller is configured to regulate carbon dioxide delivery into the chamber based on the measurement signal.

5 28. The system of claim 1, further comprising:
a temperature sensor connected to the controller and configured to generate a measurement signal representing a temperature within the chamber; and
a temperature regulator connected to the controller,
wherein during operation of the system, the controller is configured to activate the
10 temperature regulator to control the temperature within the chamber based on the measurement signal.

29. The system of claim 28, wherein the temperature regulator comprises a heating element, a cooling element, or both heating and cooling elements.

15

30. The system of claim 1, further comprising a gas detector connected to the controller and configured to generate a measurement signal in response to a presence of one or more gas species within the chamber.

20 31. The system of claim 30, wherein the gas detector is configured to generate a measurement signal representing an amount of nitrous oxide in the chamber.

32. The system of claim 30, wherein the gas detector is configured to generate a measurement signal representing an amount of ammonia in the chamber.

25

33. The system of claim 10, further comprising an altitude sensor connected to the controller and configured to transmit altitude information to the controller, wherein the controller is configured to regulate gas delivery into the chamber based on the altitude information.

30

34. The system of claim 1, further comprising a light source connected to the controller, and wherein during operation of the system, the controller is configured to activate the light source to deliver light to the enclosed spatial volume in the chamber.

35. The system of claim 1, further comprising a humidity sensor connected to the controller and configured to transmit information about humidity within the enclosed spatial volume to the controller, and wherein during operation of the system, the controller is configured to adjust humidity within the enclosed spatial volume based on the humidity
5 information.

36. The system of claim 35, further comprising at least one of a humidifier and a de-humidifier connected to a port formed in the one or more walls, and connected to the controller, wherein during operation of the system, the controller is configured to activate the
10 at least one of the humidifier and the de-humidifier to adjust the humidity within the enclosed spatial volume.

37. The system of claim 1, wherein the nutrient delivery apparatus comprises a valve connected to the controller, and wherein during operation of the system, the controller is
15 configured to activate the valve to regulate delivery of a nutrient medium from the nutrient delivery apparatus.

38. The system of claim 37, wherein during operation of the system, with a plant present in the chamber, the controller is configured to:
20 obtain nutrient information associated with the plant; and
regulate delivery of the nutrient medium to the plant based on the nutrient information.

39. The system of claim 1, further comprising a growth monitoring apparatus connected
25 to the controller and configured to generate a measurement signal comprising information about growth of a plant within the chamber.

40. The system of claim 39, wherein the growth monitoring apparatus comprises:
a radiation source configured to direct illumination light to be incident on a plant
30 within the chamber; and
a detector configured to detect light emitted from the plant.

41. The system of claim 40, wherein the detector is configured to detect light emitted from the plant in three different spectral bands, a first one of the spectral bands having a local

maximum wavelength between 635 nm and 700 nm, a second one of the spectral bands having a local maximum wavelength between 520 nm and 560 nm, and a third one of the spectral bands having a local maximum wavelength between 450 nm and 490 nm.

5 42. The system of claim 40, wherein the detector is configured to detect light emitted from the plant in multiple distinct spectral bands, each comprising a local maximum spectral wavelength.

43. The system of claim 42, wherein the multiple distinct spectral bands comprise three or
10 more bands.

44. The system of claim 43, wherein the multiple distinct spectral bands comprise five or more bands.

15 45. The system of claim 40, wherein the detector is configured to obtain a hyperspectral image of at least a portion of the plant, the hyperspectral image comprising, at each of multiple pixels, distinct light intensity measurements corresponding to different wavelength bands.

20 46. The system of claim 40, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within a near-infrared spectral band having a local maximum wavelength between 800 nm and 1400 nm.

25 47. The system of claim 40, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within a short-wavelength infrared spectral band having a local maximum wavelength between 1400 nm and 3000 nm.

30 48. The system of claim 40, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within an infrared spectral band.

49. The system of claim 40, wherein the detector is configured to detect fluorescent light emitted from at least a portion of the plant.
50. The system of claim 40, wherein the radiation source is a laser scanner.
51. The system of claim 39, wherein the growth monitoring apparatus comprises a scale positioned on or integrated into the surface, and configured to measure a mass of the plant.
52. The system of claim 1, further comprising a soil moisture detector connected to the controller and configured to generate a measurement signal comprising information about a percentage of water in a soil within the chamber.
53. The system of claim 1, further comprising a scale connected to the controller and positioned on or integrated into the surface, and configured to measure a mass of a soil supported by the scale.
54. The system of claim 53, wherein the controller is configured to determine information about a percentage of water in the soil based on the soil mass.
55. The system of claim 1, further comprising at least one chemical sensor connected to the controller and configured to generate a measurement signal comprising information about an analyte within the chamber.
56. The system of claim 55, wherein the information about the analyte comprises an ammonia concentration within the chamber.
57. The system of claim 55, wherein the information about the analyte comprises an amount of at least one of nitrate ions and nitrate salts within the chamber.
58. The system of claim 55, wherein the information about the analyte comprises a nitrous oxide concentration within the chamber.
59. The system of claim 55, wherein the information about the analyte comprises a carbon dioxide concentration within the chamber.

60. The system of claim 1, further comprising at least one sensor connected to the controller and configured to generate a measurement signal comprising information about a change in plant mass within the chamber.

5

61. The system of claim 60, wherein the at least one sensor comprises a touch-sensitive sensor.

62. The system of claim 1, further comprising a fluid removal mechanism comprising a conduit connected to or extending through a port formed in the one or more walls and configured to extract a fluid from the chamber.

10

63. The system of claim 62, wherein the fluid removal mechanism comprises a fluid pump configured to cause a fluid to flow through the fluid removal mechanism and out of the chamber.

15

64. The system of claim 62, wherein the fluid removal mechanism comprises a pressure-reducing device that draws fluid through the fluid removal mechanism and out of the chamber.

20

65. The system of claim 62, wherein the conduit extends into the chamber and is configured to extract fluid from a plant within the chamber.

66. The system of claim 62, wherein the conduit extends into the chamber and is configured to extract fluid from a soil in which a plant is growing within the chamber.

25

67. The system of claim 62, wherein the conduit extends into the chamber and is configured to capture a portion of a growth medium delivered to a plant within the chamber.

30 68. The system of claim 62, wherein the extracted fluid is a liquid.

69. The system of claim 62, wherein the extracted fluid is a gas.

70. The system of claim 62, further comprising a fluid analysis apparatus connected to the fluid removal mechanism.

71. The system of claim 70, wherein the fluid analysis apparatus comprises a mass spectrometry apparatus.

72. The system of claim 70, wherein the fluid analysis apparatus comprises:
a light source configured to direct illumination light to be incident on at least a portion of the extracted fluid; and
a detector configured to measure light emitted from the at least a portion of the extracted fluid in response to the illumination light.

73. The system of claim 1, wherein the sampling apparatus comprises an auxiliary chamber connected through a sealing mechanism to the chamber such that when the sealing mechanism is deployed, an interior of the auxiliary chamber is disconnected from the enclosed spatial volume of the chamber.

74. The system of claim 1, wherein the sampling apparatus comprises a cover connected through a sealing mechanism to the chamber.

75. The system of claim 1, further comprising one or more gloves connected through sealing mechanisms to one or more ports in the one or more walls.

76. The system of claim 1, wherein the gas delivery apparatus is positioned within the chamber.

77. The system of claim 1, wherein the gas delivery apparatus is connected to at least one port formed in the one or more walls.

78. The system of claim 1, wherein the nutrient delivery apparatus is positioned within the chamber.

79. The system of claim 1, wherein the nutrient delivery apparatus is connected to at least one port formed in the one or more walls.

80. The system of claim 1, further comprising an inoculation mechanism configured to deliver an inoculation composition to a plant enclosed within the spatial volume.
- 5 81. The system of claim 80, wherein the inoculation mechanism comprises a reservoir for storing the inoculation composition.
82. The system of claim 80, wherein the inoculation mechanism comprises a syringe.
- 10 83. The system of claim 81, wherein the inoculation mechanism comprises a conduit connected to the reservoir and a metering mechanism connected to the controller, and wherein during operation of the system, the controller is configured to deliver a metered volume of the inoculation composition to the plant by activating the metering mechanism.
- 15 84. The system of claim 83, wherein the metering mechanism comprises a pump and a valve.
85. The system of claim 1, further comprising a port located in the one or more walls, wherein the port is configured to be selectively opened to deliver an inoculation composition
20 to a plant enclosed within the spatial volume.
86. The system of claim 10, wherein the gas delivery apparatus comprises an acetylene gas source, and wherein the system comprises an ethylene detector connected to the controller.
- 25 87. The system of claim 86, wherein the controller is configured to measure a rate of acetylene reduction by a microorganism present in a soil within the chamber by:
activating the valve of the gas delivery apparatus to deliver a quantity of acetylene to the soil;
30 after an elapsed measurement time, activating the ethylene detector to measure an amount of ethylene generated from the acetylene gas by the microorganism; and
determining a rate of acetylene reduction based on the amount of ethylene generated and the elapsed time.

88. A system for plant culture, comprising:
a chamber comprising one or more walls enclosing a spatial volume internal to the chamber, wherein the one or more walls comprise a surface for supporting a plant within the enclosed spatial volume;
- 5 a gas delivery apparatus comprising a nitrogen gas source and a carbon dioxide gas source;
- a gas removal apparatus connected to a port formed in the one or more walls;
- a gas detection apparatus comprising one or more sensors configured to generate measurement signals comprising information about amounts of oxygen and carbon dioxide in
- 10 the chamber;
- a nutrient delivery apparatus comprising a reservoir and a fluid conduit connected to the reservoir; and
- a controller connected to the gas delivery apparatus, the gas removal apparatus, the gas detection apparatus, and the nutrient delivery apparatus, and configured so that during
- 15 operation of the system, the controller:
- activates the nutrient delivery apparatus to deliver a nutrient medium to a plant within the chamber to facilitate growth of the plant; and
- activates the gas delivery apparatus and gas removal apparatus to adjust concentrations of oxygen, carbon dioxide, and nitrogen in the chamber, and to adjust an
- 20 isotopic ratio of ^{15}N to ^{14}N in the chamber to a value greater than an isotopic ratio of ^{15}N to ^{14}N in atmospheric nitrogen gas.
89. The system of claim 88, wherein a height of the enclosed spatial volume measured between the surface and a wall or wall portion opposite the surface is at least 0.5 meters.
- 25
90. The system of claim 89, wherein the height is at least 3.0 meters.
91. The system of claim 88, wherein the enclosed spatial volume is at least 500 L.
- 30 92. The system of claim 91, wherein the enclosed spatial volume is at least 1000 L.
93. The system of claim 88, wherein when the chamber is filled with a gas at a pressure of 1.5 atmospheres, a leakage rate of the gas from the chamber is less than 0.5 L/day.

94. The system of claim 93, wherein the leakage rate is less than 0.1 L/day.

95. The system of claim 88, wherein when the chamber is filled with a gas at a pressure p at a first time, the one or more walls of the chamber are sufficiently impermeable so that the
5 gas pressure within the chamber at a second time at least 7 days after the first time is $0.80p$ or more.

96. The system of claim 95, wherein the gas pressure within the chamber at the second time is $0.90p$ or more.

10

97. The system of claim 88, wherein the gas delivery apparatus comprises a valve connected to the controller, and wherein during operation of the system, the controller is configured to activate the valve to regulate gas delivery from the gas delivery apparatus.

15 98. The system of claim 97, wherein during operation of the system, the at least one gas source comprises a source of nitrogen gas for which an isotopic ratio of ^{15}N to ^{14}N is greater than a ratio of ^{15}N to ^{14}N in atmospheric nitrogen gas.

19 99. The system of claim 98, wherein the adjusted isotopic ratio of ^{15}N to ^{14}N is greater
20 than 0.01.

100. The system of claim 88, wherein following adjustment of the isotopic ratio of ^{15}N to ^{14}N in the chamber, the nitrogen gas in the chamber comprises at least 0.1 atom% ^{15}N .

25 101. The system of claim 100, wherein the nitrogen gas in the chamber comprises at least 0.5 atom% ^{15}N .

102. The system of claim 88, wherein the gas detection apparatus comprises a gas detector connected to the controller and configured to generate a measurement signal in response to a
30 presence of one or more gas species within the chamber.

103. The system of claim 102, wherein the gas detector is configured to generate a measurement signal representing an isotopic ratio of ^{15}N to ^{14}N in the chamber, and wherein

the controller is configured to adjust the isotopic ratio in the chamber based on the measurement signal.

104. The system of claim 88, wherein the gas removal apparatus comprises an oxygen gas
5 scrubber.

105. The system of claim 88, wherein the gas detection apparatus comprises a gas detector
configured to generate a measurement signal representing an amount of oxygen gas in the
chamber.
10

106. The system of claim 105, wherein the controller is configured to adjust the oxygen
gas concentration in the chamber based on the measurement signal.

107. The system of claim 88, wherein the gas detection apparatus comprises a gas detector
15 configured to generate a measurement signal representing an amount of carbon dioxide gas in
the chamber.

108. The system of claim 107, wherein during operation of the system, the controller is
configured to adjust the carbon dioxide concentration in the chamber based on the
20 measurement signal.

109. The system of claim 88, further comprising:
a temperature sensor connected to the controller and configured to generate a
measurement signal representing a temperature within the chamber; and
25 a temperature regulator connected to the controller,
wherein during operation of the system, the controller is configured to activate the
temperature regulator to control the temperature within the chamber based on the
measurement signal.

30 110. The system of claim 109, wherein the temperature regulator comprises a heating
element, a cooling element, or both heating and cooling elements.

111. The system of claim 88, wherein the gas detection apparatus comprises at least one gas configured to generate a measurement signal in response to a presence of one or more gas species within the chamber.

5 112. The system of claim 111, wherein the gas detector is configured to generate a measurement signal representing an amount of nitrous oxide in the chamber.

113. The system of claim 111, wherein the gas detector is configured to generate a measurement signal representing an amount of ammonia in the chamber.

10

114. The system of claim 97, further comprising an altitude sensor connected to the controller and configured to transmit altitude information to the controller, wherein the controller is configured to regulate gas delivery into the chamber based on the altitude information.

15

115. The system of claim 88, further comprising a light source connected to the controller, and wherein during operation of the system, the controller is configured to activate the light source to deliver light to the enclosed spatial volume in the chamber.

20 116. The system of claim 88, further comprising a humidity sensor connected to the controller and configured to transmit information about humidity within the enclosed spatial volume to the controller, and wherein during operation of the system, the controller is configured to adjust humidity within the enclosed spatial volume based on the humidity information.

25

117. The system of claim 116, further comprising at least one of a humidifier and a de-humidifier connected to a port formed in the one or more walls, and connected to the controller, wherein during operation of the system, the controller is configured to activate the at least one of the humidifier and the de-humidifier to adjust the humidity within the enclosed spatial volume.

30

118. The system of claim 88, wherein the nutrient delivery apparatus comprises a valve connected to the controller, and wherein during operation of the system, the controller is

configured to activate the valve to regulate the delivery of the nutrient medium from the nutrient delivery apparatus.

119. The system of claim 118, wherein during operation of the system, with a plant present
5 in the chamber, the controller is configured to:

obtain nutrient information associated with the plant; and
regulate delivery of the nutrient medium to the plant based on the nutrient
information.

120. The system of claim 88, further comprising a growth monitoring apparatus connected
10 to the controller and configured to generate a measurement signal comprising information
about growth of a plant within the chamber.

121. The system of claim 120, wherein the growth monitoring apparatus comprises:
15 a radiation source configured to direct illumination light to be incident on a plant
within the chamber; and
a detector configured to detect light emitted from the plant.

122. The system of claim 121, wherein the detector is configured to detect light emitted
20 from the plant in three different spectral bands, a first one of the spectral bands having a local
maximum wavelength between 635 nm and 700 nm, a second one of the spectral bands
having a local maximum wavelength between 520 nm and 560 nm, and a third one of the
spectral bands having a local maximum wavelength between 450 nm and 490 nm.

123. The system of claim 121, wherein the detector is configured to detect light emitted
25 from the plant in multiple distinct spectral bands, each comprising a local maximum spectral
wavelength.

124. The system of claim 123, wherein the multiple distinct spectral bands comprise three
30 or more bands.

125. The system of claim 124, wherein the multiple distinct spectral bands comprise five or
more bands.

126. The system of claim 121, wherein the detector is configured to obtain a hyperspectral image of at least a portion of the plant, the hyperspectral image comprising, at each of multiple pixels, distinct light intensity measurements corresponding to different wavelength bands.

5

127. The system of claim 121, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within a near-infrared spectral band having a local maximum wavelength between 800 nm and 1400 nm.

10

128. The system of claim 121, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within a short-wavelength infrared spectral band having a local maximum wavelength between 1400 nm and 3000 nm.

15

129. The system of claim 121, wherein the detector is configured to obtain an image of at least a portion of the plant, the image representing light emitted from the portion of the plant within an infrared spectral band.

20 130. The system of claim 121, wherein the detector is configured to detect fluorescent light emitted from at least a portion of the plant.

131. The system of claim 121, wherein the radiation source is a laser scanner.

25 132. The system of claim 120, wherein the growth monitoring apparatus comprises a scale positioned on or integrated into the surface, and configured to measure a mass of the plant.

133. The system of claim 88, further comprising a soil moisture detector connected to the controller and configured to generate a measurement signal comprising information about a
30 percentage of water in a soil within the chamber.

134. The system of claim 88, further comprising a scale connected to the controller and positioned on or integrated into the surface, and configured to measure a mass of a soil supported by the scale.

135. The system of claim 134, wherein the controller is configured to determine information about a percentage of water in the soil based on the soil mass.

- 5 136. The system of claim 88, further comprising at least one chemical sensor connected to the controller and configured to generate a measurement signal comprising information about an analyte within the chamber.

137. The system of claim 136, wherein the information about the analyte comprises an ammonia concentration within the chamber.
10

138. The system of claim 136, wherein the information about the analyte comprises an amount of at least one of nitrate ions and nitrate salts within the chamber.

- 15 139. The system of claim 136, wherein the information about the analyte comprises a nitrous oxide concentration within the chamber.

140. The system of claim 88, further comprising at least one sensor connected to the controller and configured to generate a measurement signal comprising information about a change in plant mass within the chamber.
20

141. The system of claim 140, wherein the at least one sensor comprises a touch-sensitive sensor.

- 25 142. The system of claim 88, further comprising a fluid removal mechanism comprising a conduit connected to or extending through a port formed in the one or more walls and configured to extract a fluid from the chamber.

143. The system of claim 142, wherein the fluid removal mechanism comprises a fluid pump configured to cause a fluid to flow through the fluid removal mechanism and out of the chamber.
30

144. The system of claim 142, wherein the fluid removal mechanism comprises a pressure-reducing device that draws fluid through the fluid removal mechanism and out of the chamber.

5 145. The system of claim 142, wherein the conduit extends into the chamber and is configured to extract fluid from a plant within the chamber.

146. The system of claim 142, wherein the conduit extends into the chamber and is configured to extract fluid from a soil in which a plant is growing within the chamber.

10

147. The system of claim 142, wherein the conduit extends into the chamber and is configured to capture a portion of a growth medium delivered to a plant within the chamber.

148. The system of claim 142, wherein the extracted fluid is a liquid.

15

149. The system of claim 142, wherein the extracted fluid is a gas.

150. The system of claim 142, further comprising a fluid analysis apparatus connected to the fluid removal mechanism.

20

151. The system of claim 150, wherein the fluid analysis apparatus comprises a mass spectrometry apparatus.

152. The system of claim 150, wherein the fluid analysis apparatus comprises:

25 a light source configured to direct illumination light to be incident on at least a portion of the extracted fluid; and

a detector configured to measure light emitted from the at least a portion of the extracted fluid in response to the illumination light.

30 153. The system of claim 88, further comprising a sampling apparatus connected to a port formed in the one or more walls.

154. The system of claim 153, wherein the sampling apparatus comprises an auxiliary chamber connected through a sealing mechanism to the chamber such that when the sealing

mechanism is deployed, an interior of the auxiliary chamber is disconnected from the enclosed spatial volume of the chamber.

155. The system of claim 153, wherein the sampling apparatus comprises a cover
5 connected through a sealing mechanism to the chamber.

156. The system of claim 88, further comprising one or more gloves connected through sealing mechanisms to one or more ports in the one or more walls.

10 157. The system of claim 88, wherein the gas delivery apparatus is positioned within the chamber.

158. The system of claim 88, wherein the gas delivery apparatus is connected to at least one port formed in the one or more walls.

15 159. The system of claim 88, wherein the nutrient delivery apparatus is positioned within the chamber.

160. The system of claim 88, wherein the nutrient delivery apparatus is connected to at
20 least one port formed in the one or more walls.

161. The system of claim 88, further comprising an inoculation mechanism configured to deliver an inoculation composition to a plant enclosed within the spatial volume.

25 162. The system of claim 161, wherein the inoculation mechanism comprises a reservoir for storing the inoculation composition.

163. The system of claim 161, wherein the inoculation mechanism comprises a syringe.

30 164. The system of claim 162, wherein the inoculation mechanism comprises a conduit connected to the reservoir and a metering mechanism connected to the controller, and wherein during operation of the system, the controller is configured to deliver a metered volume of the inoculation composition to the plant by activating the metering mechanism.

165. The system of claim 164, wherein the metering mechanism comprises a pump and a valve.

166. The system of claim 88, further comprising a port located in the one or more walls,
5 wherein the port is configured to be selectively opened to deliver an inoculation composition to a plant enclosed within the spatial volume.

167. The system of claim 97, wherein the gas delivery apparatus comprises an acetylene gas source, and wherein the system comprises an ethylene detector connected to the
10 controller.

168. The system of claim 167, wherein the controller is configured to measure a rate of acetylene reduction by a microorganism present in a soil within the chamber by:
activating the valve of the gas delivery apparatus to deliver a quantity of acetylene to
15 the soil;
after an elapsed measurement time, activating the ethylene detector to measure an amount of ethylene generated from the acetylene gas by the microorganism; and
determining a rate of acetylene reduction based on the amount of ethylene generated and the elapsed time.

20
169. A method of detecting nitrogen incorporation in a plant, the method comprising:
positioning a test plant in a support medium within an enclosed chamber of a plant culture system;
adjusting a composition of a nitrogen gas mixture within the chamber so that a ratio of
25 at least two nitrogen isotopes is different from a naturally occurring atmospheric ratio of the isotopes;
delivering an aqueous growth medium to the test plant to cause growth of the test plant over a growth period;
performing an isotope analysis of a test plant tissue to determine relative amounts of
30 the at least two nitrogen isotopes in the test plant tissue; and
comparing the relative amounts of the at least two nitrogen isotopes in the test plant tissue to reference information to detect nitrogen incorporation in the test plant.

170. The method of claim 169, wherein adjusting the composition of nitrogen gas comprises activating a gas delivery apparatus of the plant culture system to deliver nitrogen gas comprising a ratio of the at least two nitrogen isotopes that differs from a naturally occurring ratio of the at least two isotopes in atmospheric nitrogen gas.

5

171. The method of claim 169, wherein the at least two nitrogen isotopes comprise ^{15}N and ^{14}N .

172. The method of claim 169, wherein the at least two nitrogen isotopes comprise ^{13}N and ^{14}N .

10

173. The method of claim 169, wherein the at least two nitrogen isotopes comprise ^{15}N , ^{14}N , and ^{13}N .

174. The method of claim 170, wherein the delivered nitrogen gas comprises at least 20 atom% ^{15}N .

15

175. The method of claim 174, wherein the delivered nitrogen gas comprises at least 50 atom% ^{15}N .

20

176. The method of claim 174, wherein the delivered nitrogen gas comprises at least 90 atom% ^{15}N .

177. The method of claim 169, wherein following adjustment of the composition of the nitrogen gas mixture, the nitrogen gas mixture comprises at least 0.1 atom% ^{15}N or ^{13}N .

25

178. The method of claim 177, wherein the nitrogen gas mixture comprises at least 0.3 atom% ^{15}N or ^{13}N .

179. The method of claim 177, wherein the nitrogen gas mixture comprises at least 0.5 atom% ^{15}N or ^{13}N .

30

180. The method of claim 169, wherein the aqueous growth medium comprises a modified Hoaglund's solution.

181. The method of claim 169, wherein the growth period comprises at least 7 days.

182. The method of claim 169, wherein the test plant tissue comprises root tissue.

5

183. The method of claim 169, wherein the test plant tissue comprises newly emerged whorl tissue.

184. The method of claim 169, wherein the test plant tissue comprises top-collared leaf
10 tissue.

185. The method of claim 169, further comprising harvesting the test plant tissue.

186. The method of claim 185, further comprising:
15 drying the harvested tissue for a drying time;
grinding the dried, harvested tissue to form a powder; and
performing the isotope analysis on the powder.

187. The method of claim 169, wherein the reference information is derived from tissue of
20 a reference plant.

188. The method of claim 187, further comprising growing the reference plant with the test plant in the enclosed chamber of the plant culture system.

25 189. The method of claim 188, wherein growing the reference plant comprises:
positioning the reference plant in a growth medium within the enclosed chamber of the plant culture system; and
delivering an aqueous growth medium to the reference plant to cause growth of the reference plant over the growth period.

30

190. The method of claim 189, wherein the aqueous growth media delivered to the test and reference plants are the same.

191. The method of claim 189, further comprising, prior to positioning the test and reference plants within the enclosed chamber of the plant culture system, inoculating the test plant or a seed precursor of the test plant with a bacterial suspension.

- 5 192. The method of claim 191, wherein the bacterial suspension comprises one or more nitrogen-fixing bacteria.

193. The method of claim 187, further comprising determining the reference information by performing an isotope analysis of the reference plant tissue to determine relative amounts
10 of the at least two nitrogen isotopes in the reference plant tissue.

194. The method of claim 169, further comprising, during growth of the test plant over the growth period:
measuring a humidity within the enclosed chamber of the plant culture system; and
15 activating at least one of a humidifier and a de-humidifier to adjust the humidity according to a humidity reference value for the test plant.

195. The method of claim 169, further comprising, during growth of the test plant over the growth period:
20 measuring an oxygen concentration within the enclosed chamber of the plant culture system; and
activating a gas removal apparatus of the plant culture system to adjust the oxygen concentration according to a reference value for the test plant.

- 25 196. The method of claim 195, wherein the gas removal apparatus comprises an oxygen scrubber.

197. The method of claim 169, further comprising, during growth of the test plant over the growth period:
30 measuring a carbon dioxide concentration within the enclosed chamber of the plant culture system; and
activating a carbon dioxide gas source to adjust the carbon dioxide concentration according to a reference value for the test plant.

198. The method of claim 169, further comprising, during growth of the test plant over the growth period, adjusting a temperature within the enclosed chamber of the plant culture system by selectively activating at least one of a heating element and a cooling element of the system according to one or more temperature reference values for the test plant.

5

199. The method of claim 169, further comprising, during growth of the test plant over the growth period, activating one or more light sources of the plant culture system to deliver light to the test plant according to a illumination reference information for the test plant.

10 200. The method of claim 169, wherein at least one of the test plant and the support medium comprises at least one nitrogen-fixing bacterium.

201. The method of claim 200, further comprising inoculating the test plant or a seed precursor of the test plant with the at least one nitrogen-fixing bacterium prior to positioning
15 the test plant within the enclosed chamber of the plant culture system.

202. The method of claim 200, further comprising inoculating the test plant with the at least one nitrogen-fixing bacterium after positioning the test plant within the enclosed chamber of the plant culture system.

20

203. The method of claim 200, further comprising determining a relative measurement of nitrogen fixation by the at least one nitrogen-fixing bacterium.

204. The method of claim 203, wherein determining the relative measurement of nitrogen
25 fixation comprises:

activating an acetylene gas source to deliver a quantity of acetylene to a portion of the support medium;

after an exposure interval, measuring an amount of ethylene generated by the at least one nitrogen-fixing bacterium from the quantity of acetylene; and

30 determining a rate of acetylene reduction by the at least one nitrogen-fixing bacterium based on the amount of ethylene generated.

205. A method of identifying a nitrogen-fixing bacterial strain, the method comprising:

inoculating a test plant or a seed of a test plant with a composition comprising at least one bacterium of a candidate bacterial strain;

positioning the test plant in a support medium within an enclosed chamber of a plant culture system;

5 positioning a reference plant in a support medium within the enclosed chamber;
adjusting a composition of a nitrogen gas mixture within the chamber so that a ratio of at least two nitrogen isotopes is different from a naturally occurring atmospheric ratio of the isotopes;

growing the test and reference plants over a growth period within the enclosed
10 chamber;

determining relative amounts of nitrogen isotopes in test and reference plant tissues;
and

identifying the candidate bacterial strain as a nitrogen-fixing bacterial strain or a non-
nitrogen-fixing bacterial strain based on the relative amounts of at least one nitrogen isotope
15 in the test and reference plant tissues.

206. The method of claim 205, wherein the reference plant and a seed of the reference plant are not inoculated with a bacterium of the candidate bacterial strain.

20 207. The method of claim 205, wherein adjusting the composition of nitrogen gas comprises activating a gas delivery apparatus of the plant culture system to deliver nitrogen gas comprising a ratio of the at least two nitrogen isotopes that differs from a naturally occurring ratio of the at least two isotopes in atmospheric nitrogen gas.

25 208. The method of claim 205, wherein the at least two nitrogen isotopes comprise ^{15}N and ^{14}N .

209. The method of claim 205, wherein the at least two nitrogen isotopes comprise ^{13}N and ^{14}N .

30 210. The method of claim 205, wherein the at least two nitrogen isotopes comprise ^{15}N , ^{14}N , and ^{13}N .

211. The method of claim 207, wherein the delivered nitrogen gas comprises at least 20 atom% ^{15}N .
212. The method of claim 211, wherein the delivered nitrogen gas comprises at least 50 atom% ^{15}N .
213. The method of claim 211, wherein the delivered nitrogen gas comprises at least 90 atom% ^{15}N .
214. The method of claim 205, wherein following adjustment of the composition of the nitrogen gas mixture, the nitrogen gas mixture comprises at least 0.1 atom% ^{15}N or ^{13}N .
215. The method of claim 214, wherein the nitrogen gas mixture comprises at least 0.3 atom% ^{15}N or ^{13}N .
216. The method of claim 214, wherein the nitrogen gas mixture comprises at least 0.5 atom% ^{15}N or ^{13}N .
217. The method of claim 205, wherein the growth period comprises at least 7 days.
218. The method of claim 205, wherein the test and reference plant tissues each comprise root tissue.
219. The method of claim 205, wherein the test and reference plant tissues each comprise newly emerged whorl tissue.
220. The method of claim 205, wherein the test and reference plant tissues each comprises top-collared leaf tissue.
221. The method of claim 205, further comprising:
harvesting the test and reference plant tissues from the test and reference plants;
drying the harvested test and reference plant tissues for a drying time;
grinding the dried, harvested tissues to form respective test and reference powders;
and

analyzing the test and reference powers to determine the relative amounts of nitrogen isotopes in the test and reference plant tissues.

222. The method of claim 205, further comprising, if a seed of the test plant is inoculated
5 with the composition comprising the at least one bacterium of the candidate bacterial strain, depositing the seed in a support medium to induce germination of the seed to form the test plant.

223. The method of claim 222, further comprising, following formation of the test plant,
10 withholding growth medium from the test plant for an initial period of at least 7 days following germination.

224. The method of claim 223, further comprising, following the initial period, delivering a
15 growth medium to the test plant.

225. The method of claim 224, wherein the growth medium comprises a modified
Hoaglund's solution.

226. The method of claim 222, further comprising positioning the test plant within the
20 enclosed chamber of a plant culture system at a time at least 14 days following germination of the seed.

227. The method of claim 222, further comprising positioning the test plant within the
25 enclosed chamber of a plant culture system at a time at least 21 days following germination of the seed.

228. The method of claim 205, further comprising, during growth of the test and reference
plants over the growth period:

30 measuring a humidity within the enclosed chamber of the plant culture system; and
activating at least one of a humidifier and a de-humidifier to adjust the humidity
according to a humidity reference value for the test and reference plants.

229. The method of claim 205, further comprising, during growth of the test and reference
plants over the growth period:

measuring an oxygen concentration within the enclosed chamber of the plant culture system; and

activating a gas removal apparatus of the plant culture system to adjust the oxygen concentration according to a reference value for the test and reference plants.

5

230. The method of claim 205, further comprising, during growth of the test and reference plants over the growth period:

measuring a carbon dioxide concentration within the enclosed chamber of the plant culture system; and

10

activating a carbon dioxide gas source to adjust the carbon dioxide concentration according to a reference value for the test and reference plants.

15

231. The method of claim 205, further comprising, during growth of the test and reference plants over the growth period, adjusting a temperature within the enclosed chamber of the plant culture system by selectively activating at least one of a heating element and a cooling element of the system according to one or more temperature reference values for the test and reference plants.

20

232. The method of claim 205, further comprising, during growth of the test and reference plants over the growth period, activating one or more light sources of the plant culture system to deliver light to the test and reference plants according to a illumination reference information for the test and reference plants.

25

233. The method of claim 205, further comprising determining a relative measurement of nitrogen fixation by the at least one bacterium of the candidate strain.

234. The method of claim 233, wherein determining the relative measurement of nitrogen fixation comprises:

30

activating an acetylene gas source to deliver a quantity of acetylene to a portion of the support medium in which the test plant is supported;

after an exposure interval, measuring an amount of ethylene generated by the at least one bacterium from the quantity of acetylene; and

determining a rate of acetylene reduction by the at least one bacterium based on the amount of ethylene generated.

235. A genetically engineered bacterium comprising a modification in a gene regulating nitrogen fixation or assimilation, wherein said bacterium is capable of fixing atmospheric nitrogen substantially throughout the tissues of a plant.

5

236. The genetically engineered bacterium of claim 235, wherein said modification comprises a deletion of all or a portion of the coding sequence of the *nifL* gene.

237. The genetically engineered bacterium of claim 236, wherein all or a portion of the *nifL* coding sequence is replaced by the promoter of the *cspE* gene.

10

238. The genetically engineered bacterium of claim 235, wherein said modification comprises a deletion of a portion of the coding sequence of the *glnE* gene.

239. The genetically engineered bacterium of claim 238, wherein said deletion of said portion of the coding sequence of the *glnE* gene results in a truncated GlnE protein lacking an adenyl-removing (AR) domain.

15

240. The genetically engineered bacterium of claim 235, wherein said modification comprises a mutant *ntrC* gene, wherein the mutant *ntrC* gene encodes a NtrC protein comprising an alanine residue at position 54.

20

241. The genetically engineered bacterium of claim 235, wherein said bacterium comprises a deletion of all or a portion of the coding sequence of the *nifL* gene, a deletion of portion of the coding sequence of the *glnE* gene, and a mutant *ntrC* gene, wherein the mutant *ntrC* gene encodes a NtrC protein comprising an alanine residue at position 54.

25

242. The genetically engineered bacterium of any one of claims 235-241, wherein said bacterium is capable of fixing atmospheric nitrogen in one or more of the roots, stems, leaves, fruits, flowers, seeds, initial growth tissue, and top growth.

30

243. The genetically engineered bacterium of any one of claims 235-242, wherein said bacterium is a diazotroph.

244. The genetically engineered bacterium of any one of claims 235-243, wherein said bacterium is a *Klebsiella variicola*, *Kosakonia sacchari*, *Klebsiella pneumonia*, *Azotobacter vinelandii*, or *Rahnella aquatilis* bacterium.

5 245. The genetically engineered bacterium of any one of claims 235-244, wherein said bacterium is designated 137-3890, represented by 138-3890 bacteria deposited as ATCC Accession No. PTA-126479.

246. A composition comprising the genetically engineered bacterium of any one of claims
10 235-245.

247. A genetically engineered bacterium which provides sufficient fixed nitrogen to a plant for the fixed nitrogen to be detectable in multiple plant tissues, the genetically engineered bacterium comprising a modification in a gene regulating nitrogen fixation or assimilation,
15 wherein the modification in the gene regulating nitrogen fixation or assimilation results in one or more of: constitutive expression of a *nifA* gene in nitrogen limiting and non-nitrogen limiting conditions, activity of *nifA* in non-nitrogen limiting conditions, decreased uridylyl-removing activity of GlnD, decreased adenylyl-removing activity of GlnE, and increased ammonium excretion.

20

248. A genetically engineered bacterium which provides sufficient fixed nitrogen to a plant for the fixed nitrogen to be detectable in multiple plant tissues, the genetically engineered bacterium comprising a modification in a gene regulating nitrogen fixation or assimilation that results in constitutive expression of a *nifA* gene in nitrogen limiting and non-nitrogen
25 limiting conditions and optionally wherein the genetically engineered bacterium further comprises a modification in a gene regulating nitrogen fixation or assimilation that results in one or more of: activity of *nifA* in non-nitrogen limiting conditions, decreased uridylyl-removing activity of GlnD, decreased adenylyl-removing activity of GlnE, and increased ammonium excretion.

30

249. A genetically engineered bacterium which provides sufficient fixed nitrogen to a plant for the fixed nitrogen to be detectable in multiple plant tissues, the genetically engineered bacterium comprising a modification in a gene regulating nitrogen fixation or assimilation that results in constitutive expression of a *nifA* gene in nitrogen limiting and non-nitrogen

limiting conditions and wherein the genetically engineered bacterium further comprises a modification in a gene regulating nitrogen fixation or assimilation that results in one or more of: activity of *nifA* in non-nitrogen limiting conditions, decreased uridylyl-removing activity of *GlnD*, decreased adenylyl-removing activity of *GlnE*, and increased ammonium excretion.

5

250. A genetically engineered bacterium which provides sufficient fixed nitrogen to a plant for the fixed nitrogen to be detectable in multiple plant tissues, the genetically engineered bacterium comprising a mutation in the coding sequence of the bacterium's *ntrC* gene, wherein the coding sequence of the *ntrC* gene comprising the mutation encodes a NtrC protein with a D54A amino acid substitution, and wherein the genetically engineered bacterium is a genetically engineered diazotroph.

10

251. A genetically engineered bacterium which provides sufficient fixed nitrogen to a plant for the fixed nitrogen to be detectable in multiple plant tissues, the genetically engineered bacterium comprising:

15

a mutation in the coding sequence of the bacterium's *ntrC* gene, wherein the coding sequence of the *ntrC* gene comprising the mutation encodes a NtrC protein with a D54A amino acid substitution,

wherein the genetically engineered bacterium further comprises at least one modification in a gene regulating nitrogen fixation or assimilation that results in one or more of constitutive expression of a *nifA* gene in nitrogen limiting and non-nitrogen limiting conditions, activity of *nifA* in non-nitrogen limiting conditions, decreased uridylyl-removing activity of *GlnD*, decreased adenylyl-removing activity of *GlnE*, and increased ammonium excretion.

25

252. The genetically engineered bacterium of claim 250 or 251, wherein the mutation in the coding sequence of the *ntrC* results in increased ammonium excretion.

253. The genetically engineered bacterium of any one of claims 247-252, wherein the modification in a gene regulating nitrogen fixation or assimilation that results in activity of *nifA* in non-nitrogen limiting conditions comprises a deletion of all or a portion of the coding sequence of the bacterium's *nifL* gene.

30

254. The genetically engineered bacterium of claim 253, wherein the deletion of all or a portion of the coding sequence of the *nifL* gene results in the decreased expression of *nifL*.

255. The genetically engineered bacterium of any one of claims 253-254, wherein all or a
5 portion of the *nifL* coding sequence is replaced by a promoter.

256. The genetically engineered bacterium of claim 255, wherein the promoter is a non-intergeneric promoter.

10 257. The genetically engineered bacterium of any one of claims 255-256, wherein the promoter is a constitutive promoter.

258. The genetically engineered bacterium of any one of claims 255-257, wherein the promoter is an *infC* gene promoter, an *ompX* gene promoter, or a *cspE* gene promoter.

15 259. The genetically engineered bacterium of any one of claims 247-258, wherein the modification in a gene regulating nitrogen fixation or assimilation that results in the decreased adenylyl-removing activity of GlnE comprises a deletion of a portion of the coding sequence of the *glnE* gene.

20 260. The genetically engineered bacterium of claim 259, wherein the deletion of a portion of the coding sequence of the *glnE* gene results in a truncated GlnE protein lacking an adenylyl-removing (AR) domain.

25 261. The genetically engineered bacterium of any one of claims 247-249 and 252-260, wherein the modification in a gene regulating nitrogen fixation or assimilation that results in increased ammonium excretion comprises a mutation in the coding sequence of the bacterium's *ntnC* gene.

30 262. The genetically engineered bacterium of claim 261, wherein the coding sequence of the *ntnC* gene comprising the point mutation encodes a NtrC protein comprising a D54A amino acid substitution.

263. The genetically engineered bacterium of any one of claims 247-249 and 251-262, wherein the modification in a gene regulating nitrogen fixation or assimilation that results in constitutive expression of the *nifA* gene in nitrogen limiting and non-nitrogen limiting conditions comprises an insertion of the coding sequence of the *nifA* gene in the genome of
5 the genetically engineered bacterium.

264. The genetically engineered bacterium of any one of claims 247-263, wherein the modification in a gene regulating nitrogen fixation or assimilation that results in constitutive expression of the *nifA* gene in nitrogen limiting and non-nitrogen limiting conditions
10 comprises an insertion of the coding sequence of the *nifA* gene and a constitutive promoter in the genome of the genetically engineered *Klebsiella variicola* bacterium.

265. The genetically engineered bacterium of any one of claims 247-264, wherein the engineered bacterium is *Agrobacterium radiobacter*, *Bacillus acidocaldarius*, *Bacillus acidoterrestris*, *Bacillus agri*, *Bacillus aizawai*, *Bacillus albolactis*, *Bacillus alcalophilus*, *Bacillus alvei*, *Bacillus aminoglucosidicus*, *Bacillus aminovorans*, *Bacillus amylolyticus* (also known as *Paenibacillus amylolyticus*) *Bacillus amyloliquefaciens*, *Bacillus aneurinolyticus*, *Bacillus atrophaeus*, *Bacillus azotoformans*, *Bacillus badius*, *Bacillus cereus* (synonyms: *Bacillus endorhythmos*, *Bacillus medusa*), *Bacillus chitinosporus*, *Bacillus circulans*, *Bacillus coagulans*, *Bacillus endoparasiticus* *Bacillus fastidiosus*, *Bacillus firmus*, *Bacillus kurstaki*, *Bacillus lacticola*, *Bacillus lactimorbus*, *Bacillus lactis*, *Bacillus laterosporus* (also known as *Brevibacillus laterosporus*), *Bacillus lautus*, *Bacillus lentimorbus*, *Bacillus lentus*, *Bacillus licheniformis*, *Bacillus maroccanus*, *Bacillus megaterium*, *Bacillus metiens*, *Bacillus mycoides*, *Bacillus natto*, *Bacillus nematocida*, *Bacillus nigrificans*, *Bacillus nigrum*, *Bacillus pantothenicus*, *Bacillus popilliae*, *Bacillus psychrosaccharolyticus*, *Bacillus pumilus*, *Bacillus siamensis*, *Bacillus smithii*, *Bacillus sphaericus*, *Bacillus subtilis*, *Bacillus thuringiensis*, *Bacillus uniflagellatus*, *Bradyrhizobium japonicum*, *Brevibacillus brevis* *Brevibacillus laterosporus* (formerly *Bacillus laterosporus*), *Chromobacterium subtsugae*, *Delftia acidovorans*, *Lactobacillus acidophilus*, *Lysobacter antibioticus*, *Lysobacter enzymogenes*, *Paenibacillus alvei*, *Paenibacillus polymyxa*, *Paenibacillus popilliae* (formerly *Bacillus popilliae*), *Pantoea agglomerans*, *Pasteuria penetrans* (formerly *Bacillus penetrans*), *Pasteuria usgae*, *Pectobacterium carotovorum* (formerly *Erwinia carotovora*), *Pseudomonas aeruginosa*, *Pseudomonas aureofaciens*, *Pseudomonas cepacia* (formerly known as *Burkholderia cepacia*), *Pseudomonas chlororaphis*, *Pseudomonas fluorescens*,
25
30

Pseudomonas proradix, *Pseudomonas putida*, *Pseudomonas syringae*, *Serratia entomophila*, *Serratia marcescens*, *Streptomyces colombiensis*, *Streptomyces galbus*, *Streptomyces goshikiensis*, *Streptomyces griseoviridis*, *Streptomyces lavendulae*, *Streptomyces prasinus*, *Streptomyces saraceticus*, *Streptomyces venezuelae*, *Xanthomonas campestris*, *Xenorhabdus luminescens*, *Xenorhabdus nematophila*, *Rhodococcus globerulus* AQ719 (NRRL Accession No. B-21663), *Bacillus* sp. AQ175 (ATCC Accession No. 55608), *Bacillus* sp. AQ 177 (ATCC Accession No. 55609), *Bacillus* sp. AQ178 (ATCC Accession No. 53522), or *Streptomyces* sp. strain NRRL Accession No. B-30145.

266. The genetically engineered bacterium of any one of claims 247-265, wherein the engineered bacterium is a *Kosakonia sacchari* bacterium or a *Klebsiella variicola* bacterium.

267. The genetically engineered bacterium of any one of claims 247-266, wherein the genetically engineered bacterium comprises a deletion of all or a portion of the coding sequence of the *nifL* gene, a deletion of a portion of the coding sequence of the *glnE* gene, and a point mutation in the coding sequence of the *ntrC* gene .

268. The genetically engineered bacterium of any one of claims 247-267, wherein the genetically engineered bacterium is represented by 137-3890 bacteria deposited as ATCC Accession No. PTA-126749.

269. The genetically engineered bacterium of any one of claims 247-268, wherein the multiple plant tissues comprise multiple tissues selected from the group consisting of: root, leaf, and whorl tissues.

25