

1 4 FEB 2000

Process for fractionating dibutene

The invention relates to a process for fractionating a dibutene mixture and to the use of the dibutene fractions.

5

Dibutene is the term used for mixtures of isomeric C_8 olefins obtained by dimerizing n-butenes or C_4 streams containing n-butene. For this purpose it is particularly advantageous to employ the so-called raffinate II or raffinate III obtainable inexpensively from the processing of crude C_4 cuts.

10

In order to obtain raffinate II or III, butadiene is removed from crude C_4 cuts in a first step. This is done either by extracting the butadiene or selectively hydrogenating it to the linear butenes. Both cases produce a virtually butadiene-free C_4 cut, which is raffinate I. In the second step isobutene is removed from the C_4 stream by, for example, reacting it with methanol to prepare methyl tert-butyl ether (MTBE). MTBE is a sought-after motor fuel component. Other options are to react the isobutene from the raffinate I with water to give TBA (tertiary butanol) or to subject the isobutene to acid-catalyzed oligomerization to form diisobutene. The now isobutene-free C_4 cut, raffinate II, contains - as desired, the linear butenes and possibly butanes. As an option, it is also possible to separate off the 1-butene by distillation; if this is done, the cut free from 1-butene is referred to as raffinate III.

25 For the preparation of di-n-butene, raffinate II or raffinate III can be employed alternatively. The use of other industrial C_4 streams, such as those from Fischer-Tropsch olefins, for example, is possible. The critical feature is that essentially only linear butenes are present in the feedstock.

30 The oligomerization of such n-butene-containing C_4 streams to mixtures essentially comprising C_8 olefins is known in principle: there are three process variants.

The oligomerization over acidic catalysts (process A) has been known for a long time, and in industry, for example, zeolites or phosphoric acid on supports are employed. This process produces isomer mixtures of branched olefins which constitute primarily dimethylhexenes (WO 92/13818). A
5 process which is likewise carried out worldwide is the oligomerization with soluble Ni-complexes, known as the DIMERSOL process (process B) (B. Cornils, W.A. Herrmann, Applied Homogenous Catalysis with Organometallic Compounds, page 261-263, Verlag Chemie 1996). Mention should also be made, finally, of the oligomerization over nickel fixed-bed catalysts, such as,
10 for example, the process of OXENO-GmbH. The process has entered the literature has the OCTOL process (process C) (Hydrocarbon Process., Int. Ed. (1986) 65 (2. Sect. 1), page 31-33).

The dibutenes obtained by these processes are prized starting materials in
15 the chemical industry. For example, by hydroformylation it is possible to obtain aldehydes which are longer by one carbon atom - in the case of dibutene, therefore, C₉ aldehydes - which in turn are employed further for important industrial products. Examples are the hydrogenation of the aldehydes to give alcohols and their reaction with carboxylic acids to give
20 esters. For instance, the acidification of the alcohols with phthalic anhydride leads to diisononyl phthalates, which are highly prized plasticizers in the plastics processing industry. Also important and carried out industrially is the oxidation of the aldehydes to the corresponding carboxylic acids, which are reacted inter alia to give oil-soluble metal salts. These salts are employed,
25 for example, as drying accelerators for coatings (siccatives), or as stabilizers for PVC.

A further exemplary industrial application is the strong-acid-catalyzed reaction of olefins (dibutenes) with carbon monoxide and water to give the
30 carboxylic acids longer by one carbon atom, which has entered the literature under the name KOCH reaction. In this case, tertiary branched carboxylic acid mixtures are obtained which because of their branched nature are in

turn highly suitable for producing the abovementioned metal salts. A particularly important use of the tertiary carboxylic acids is the reaction with acetylene to give vinyl esters, which are used as comonomers for the internal plasticization of polymers. Copolymers of vinyl esters of tertiary
5 carboxylic acids with vinyl acetate, for example, are the basis for environmentally friendly water-dispersible paints and coating materials, and energy-saving thermal insulation renders in buildings.

Dibutene is not a uniform substance but rather is a mixture of many structural
10 isomers which in turn are composed of virtually all the double-bond isomers in different proportions, with many of the double-bond isomers also exhibiting a cis/trans isomerism. Depending on the production process, these constitutional and configurational isomers can be present in different proportions.

15

When dibutene is prepared starting from raffinate II or III, the product comprises olefin mixtures of essentially unbranched, singly branched and doubly branched substructures. The information given below is only a guide, since varying proportions of the individual structural groups are obtained
20 depending on the process conditions.

One measure of the degree of branching is the iso index. It is defined by the number of branchings per molecule. Accordingly, linear octenes (n-octenes) have an iso index of 0, methylheptenes an iso index of 1 and
25 dimethylhexenes an iso index of 2. The calculation of the iso index of mixtures must take account of the mass fractions of the individual groups of compounds.

	A Zeolite catalysis	B Dimersol	C Octol
n-Octene	~ 0%	~ 6%	~ 13%
3-Methylheptenes	~ 5%	~ 59%	~ 62%
5 3,4-Dimethylhexenes	~ 70%	~ 34%	~ 24%
Other C ₈ olefins	~ 25%	~ 1%	~ 1%
Iso index	> 1.9	≅ 1.29	≅ 1.12

10 **Table 1:** Typical structural distribution in dibutenes, each from different preparation processes, starting from raffinate III.

15 If instead of raffinate II or raffinate III other isobutene-containing C₄ cuts are used, such as raffinate I, there is also formation of a host of further, even more highly branched structures, essentially trimethylhexenes such as 2,2,4-trimethylpentenes, 2,2,3-trimethylpentenes, 2,3,4-trimethylpentenes, 2,3,3-trimethylpentenes, etc. Such dibutenes, with an iso index of more than 2, are also known by the name "codibutylene".

20 The performance properties of the products produced from dibutene are often dependent on the composition, and especially on the degree of branching, of the olefin employed. This may take on very extreme forms, as is evident from the examples below. "

25 An important field of use of dibutenes is the preparation of C₉ alcohols which in turn are esterified with carboxylic acids. For instance, dibutene produces isononanol mixtures which are esterified with phthalic anhydride to give isononyl phthalates; these are employed as plasticizers in plastics.

30 The degree of branching of the isononyl chains of the phthalates is closely related to the degree of branching of the olefin employed, so that the properties of the phthalates are significantly co-determined by the structure of the olefin mixture that is employed.

Crude material	Oligomerization process	Hydroformylation process	Viscosities of the isononyl phthalates (20°C)
Raffinate I	A	Co-HP	≈ 165 mPa s
Raffinate II or III	A	Co-HP	116-120 mPa s
Raffinate II or III	B or C	Co-HP	70-85 mPa s
Raffinate II or III	B or C	Rh-HP	90-100 mPa s

Table 2: Comparison of typical dynamic viscosities of nonyl phthalates employed industrially, where

Co-HP: Classic cobalt high-pressure process, 200-300 bar, 140-180°C

Rh-HP: Rhodium high-pressure process, 150-300 bar, 120-130°C,

unmodified or triphenylphosphine oxide-modified rhodium catalyst

Other performance properties of the plasticizers are similarly heavily dependent on their degree of branching. Wadey et al. in J. Vinyl Tech. (1990) 208-211 show the marked dependency of the plasticizer properties of dinonyl phthalates on the degree of branching of the nonyl radical.

The vinyl esters of tertiary carboxylic acids, which are frequently employed as a comonomer in the polymerization of vinyl acetates, are another example of the dependency of the plasticizer properties of a compound on its degree of branching. One measure of the plasticizing action of the comonomer is the glass transition point T_g [°C] of the homopolymer. For an identical empirical formula, the glass transition point can vary across a whole range depending on the structure of the olefin employed. For vinyl esters of C_9 carboxylic acids, for example, the literature gives:

Base olefin	Vinyl esters (VE) of	T _g [°C]
2,3,4-Trimethylpentene	2,3-Dimethyl-2-isopropylbutanoic acid	119
2,2,3-Trimethylpentene	2-Ethyl-2,3,3-trimethylbutanoic acid	115
Diisobutene	commercially available vinyl ester *	70 (60)*
2,2,4-Trimethylpentene	2,2,4,4-Tetramethylpentanoic acid	55
2,4-Dimethylhexene	2,2,4-Trimethylhexanoic acid	10

Table 3: (H.P.H. Scholten, J. Vermeulen, W.J. van Westrenen, Recent Developments in Latices based on Vinyl Esters of branched Monocarboxylic Acids, Seventh International Conference Water-Borne Coatings, London 1987; *W. Lau, VeoVa, a Vinyl Ester Monomer, Polymers Dotcom Magazine, 2(2), February 1996)

With plasticizers therefore, an important factor is generally a very low degree of branching of the initial olefins, as demonstrated using the example of the phthalates and vinyl esters.

This does not mean, however, that more highly branched olefins are worthless; what is critical is the correct choice of application. For example, metal salts of highly branched carboxylic acids obtainable from olefins with correspondingly high degrees of branching are, owing to the shielding of the polar carboxyl group, particularly soluble in oil and therefore particularly suitable for use for producing siccatives and PVC stabilizers. A general field of use for highly branched olefins is that of acid-catalyzed reactions, such as, for example, the acid-catalyzed alkylation of phenols. In such reactions, highly branched olefins can be used to give much better yields than with linear olefins or olefins with lower degrees of branching, since the former are able to develop tertiary carbenium ions with particular ease.

The great economic importance of the dibutenes and their successor products, and the heavy dependency of their performance properties on structure, therefore, suggested separation of the dibutene mixture.

Separation of the dibutene mixture by distillation, however, is possible only on an analytical scale - and even then not completely - owing to the small differences in boiling point. Distillative separation is therefore not economic. To illustrate this it may be noted that, within the boiling range of dibutene,
5 which is from 104 to 125°C under atmospheric pressure, about 40 components have been detected to date.

On the industrial scale, therefore, C₈ olefins are separated using various other processes, such as adsorption processes, distillation with azeotrope
10 formers, or separation processes with upstream isomerization steps.

US-A 5,262,015 describes the separation of 1-octene from other C₈ olefin isomers by azeotropic distillation using an azeotrope former. Examples of azeotrope formers used are ethyl acetate and amyl methyl ether. However,
15 this process only makes it possible to separate 1-octene, which is present in a large excess, and requires the use of one part of azeotrope former to one part of isomer mixture. In dibutene, on the other hand, the proportion of 1-octene is very low; the double bonds present are predominantly internal. The industrial application of this process to the separation of dibutene is
20 therefore not an option.

US-A 5,292,990 discloses the separation of C₈ olefin mixtures by way of the different adsorption/desorption behavior of the isomers on specific zeolites. This process requires highly specific zeolites which are difficult if not
25 impossible to obtain commercially, quite aside from the fact that the use of such processes is generally directed to analytical separation techniques. An industrial application is therefore not an option or at the very least is highly complex and uneconomic.

30 A further possibility of obtaining dibutene mixtures with a relatively low isomer fraction consists in theory in the isomerization of the dibutenes prior to the actual separation process. One example of such a process is given by

EP 0684721. The aim of the isomerization is to transform certain isomers into other isomers which are more thermodynamically stable under the chosen conditions, and thus to simplify subsequent separation. In general, however, more highly substituted olefins and/or internal olefins are more thermodynamically stable, so that the olefins with a lower degree of substitution, and/or terminal olefins, which are important for numerous purposes, are lost. Direct separation of the isomer mixture to give the desired structures is therefore not possible industrially by means of combined isomerization/separation processes.

10

In summary, it is found that the literature contains no industrially applicable and economic method of separating dibutene mixtures.

The properties of individual dibutene isomers, like their boiling points, are often very similar. Substantial separation into individual isomers is therefore virtually impossible, but is also not absolutely necessary economically. In contrast, it would be desirable to obtain - with no great complexity of apparatus and no great energy consumption - olefin mixtures suitable for the preparation of products having defined properties.

20

It is an object of the invention to develop a process for separating dibutene mixtures.

It has surprisingly been found that the fractionation of dibutenes by separation into a virtually n-octene-free fraction (iso index higher than that of the original dibutenes), which therefore comprises branched olefins, and into a second fraction (iso index lower than that of the original dibutenes), which in addition to virtually all the unbranched and singly branched olefins contains only small amounts of more highly branched olefins, takes place successfully in a single step.

30

The present invention therefore provides a process for separating dibutenes

into an n-octene-containing fraction having an iso index of less than 90% and a dimethylhexene-containing fraction having more than 110% of the iso index of the original dibutenes.

- 5 By means of the process of the invention, then, it is possible to prepare dibutene fractions and to pass on the individual fractions for specific further processing. In comparison to the successor products of the dibutene mixture, the successor products of the individual fractions have defined and durably improved properties.

10

Table 4 shows by way of example the isomer distribution of a typical dibutene sample produced by oligomerization of raffinate III in accordance with the Octol process, together with the associated mass fractions. As a measure of the boiling points, some of which are unknown, the retention indices are indicated, which were determined by gas chromatography and measured against squalene. The stated retention indices represent a boiling range from about 105 to 126°C. The small differences in the retention indices are an indication of very small differences in boiling point between the isomers. In addition, components with higher and lower degrees of branching alternate unsystematically in the sequence.

20

No.	Retention index based on squalene b.p.	Isomer	Mass fraction of the isomers
1	725.4 105.1°C	4,4-Dimethyl-1-hexene	0.17%
2	*	cis-2,4-Dimethyl-3-hexene	**
3	728.0	trans-2,4-Dimethyl-3-hexene	0.07%
4	730.7	2,4-Dimethyl-2-hexene	0.14%
5	733.7	2-Methyl-3-ethyl-1-pentene	0.05%
6	734.7	trans-4,5-Dimethyl-2-hexene	0.08%
7	736.0	cis-4,5-Dimethyl-2-hexene	0.08%
8	738.3	cis-5-Methyl-3-heptene	1.13%
9	740.1	3-Methyl-1-heptene	0.71%

10	741.0	trans-5-Methyl-3-heptene	6.37%
11	749.6	3-Methyl-2-ethyl-1-pentene	0.93%
12	752.0	trans-3,5-Dimethyl-2-hexene	0.37%
13	752.3	cis-3,5-Dimethyl-2-hexene	0.10%
5 14	755.7	cis-3,4-Dimethyl-2-hexene	4.69%
15	760.0	trans-3,4-Dimethyl-2-hexene	14.41%
16	767.6	trans-5-Methyl-2-heptene	9.62%
17	775.9	cis-5-Methyl-2-heptene	3.56%
18	777.1	trans-3,4-Dimethyl-3-hexene	2.99%
10 19	777.6	cis-3-Methyl-3-heptene	5.21%
20	779.1 120.0°C	2-Ethyl-1-hexene	1.07%
21	781.9 121.3°C	1-n-Octene	0.10%
22	782.9	cis-3,4-Dimethyl-3-hexene	2.79%
23	784.1	trans-3-Methyl-3-heptene	9.77%
15 24	* 122.3°C	trans-4-n-Octene	3.06%
25	786.6 122.5°C	cis-4-n-Octene	0.67%
26	790.8	2,3-Dimethyl-2-hexene	0.10%
27	788.3	cis-3-Methyl-2-heptene	6.58%
28	* 122.9°C	cis-3-n-Octene	1.11%
20 29	789.1 123.3°C	trans-3-n-Octene	5.08%
30	798.8	trans-3-Methyl-2-heptene	11.30%
31	* 125.0°C	trans-2-n-Octene	5.10%
32	802.0 125.6°C	cis-2-n-Octene	1.88%
25	Remainder	Alkanes and unknowns	0.71%

Table 4: Boiling point data from Handbook of Chemistry and Physics, 67th Ed., 1986-1987, CRC Press; *The retention indices lie between the adjacent values. They could not be determined precisely owing to superimposed peaks;
 **Traces

Nevertheless, separation by means of the process of the invention is successful, preferably by a distillative cut between compounds 15 and 16 of Table 4.

For the purpose of distillative separation, the small differences in boiling point between the isomers necessitate a column having an appropriately high separation efficiency, or the required number of theoretical plates. This can be achieved by incorporating column trays, perforated plates or
5 packings such as Raschig rings, wire meshes or dumped packings. On the basis of their high separation efficiency at low differential pressure, particular preference is given to mesh packings, such as CY packings from Sulzer, for example.

- 10 Complete, isomerically pure separation of the dibutene is unnecessary for many of its successor products; in practice, fractionation into a fraction predominantly comprising olefins with low degrees of branching (iso index less than 90% of that of the original dibutenes) and into a fraction
15 predominantly comprising olefins with higher degrees of branching (iso index greater than 110% of that of the original dibutenes) has been found to be entirely adequate.

The iso index of the n-octene-containing fraction is preferably below 1.0 and with particular preference below 0.9. This means in both cases that the iso
20 index of the dimethylhexene-containing fraction is greater than the iso index of the original dibutenes (starting olefin).

The fractionation of the dibutenes in the process of the invention can be carried out by means of continuous distillation. The distillation can be
25 performed within a wide pressure range, i.e., both under reduced-pressure conditions and under superatmospheric pressure conditions. However, distillation at atmospheric pressure is preferred in order to keep the technical complexity low.

- 30 In the process of the invention, the n-octene-containing fraction is obtained as the bottom product. This fraction has a boiling range of preferably from 110 to 126°C, particularly preferably from 115 to 123°C, under atmospheric

pressure.

The dimethylhexene-containing fraction, on the other hand, is obtained as the top product. The top product has a boiling range under atmospheric
5 pressure of from 95 to 120°C, more preferably from 105 to 115°C.

The boiling ranges indicated are pressure dependent. If the process of the invention is operated at different pressures, then the preferred boiling ranges must be converted accordingly.

10

The dibutene fractions produced with the process of the invention can be employed in subsequent reactions in which the untreated dibutene mixture is also customarily used. These include acid-catalyzed reactions such as the KOCH synthesis to give tertiary carboxylic acids and the subsequent use
15 thereof to prepare vinyl esters, or the alkylation of benzenes and phenols, and also the metal-catalyzed preparation of aldehydes by hydroformylation, and the further processing of these aldehydes to these corresponding alcohols and the plasticizers derived from them, and, still further, the oxidation of the aldehydes obtained by hydroformylation, to give non-tertiary
20 carboxylic acids.

The n-octene-containing bottom fraction, with a low degree of branching, is employed with particular advantage, for example, when the intention is to produce readily biodegradable products. As is known, alkyl chains with low
25 degrees of branching are more readily biodegradable than those with higher degrees of branching.

Furthermore, the low level of branching of the bottom product is of particular advantage when the successor products are plasticizers. For example, a
30 less highly branched isononyl is obtained by hydroformylating the bottom fraction with its low degree of branching than when using the unseparated mixture. This, following esterification with phthalic anhydride, for example,

gives a plasticizer having markedly improved properties (see comparative examples).

The dibutene fractions obtained in accordance with the invention (n-octene-
5 containing and/or dimethylhexene-containing fraction)" can be used to
prepare isononanols and/or their esters. The isononanols are prepared, for
example, by hydroformylating the dibutenes to the corresponding aldehydes
and then hydrogenating them. The hydroformylation can be carried out as
desired with cobalt catalysts or rhodium catalysts. As an example, mention
10 may be made of cobalt-catalyzed reaction systems in which cobalt salts are
reacted in aqueous solution with synthesis gas ($H_2:CO$ in a volume ratio of
1:1) to give cobalt hydridocarbonyls. These cobalt complexes catalyze the
reaction of the olefins with synthesis gas to the corresponding oxo
aldehydes. The oxo aldehydes are subsequently hydrogenated to the
15 desired alcohols. These processes are known and are described, for
example, in DE-A 21 39 630, DE-A 21 06 252, DE-A 22 44 373 or WO
93/24438.

In general, the hydroformylation is conducted with a reaction temperature of
20 from 50 to 200°C and a synthesis gas pressure of from 100 to 400 bar. The
olefin, with or without an alcohol as solubilizer, is used simultaneously as
starting material and solvent. Following hydroformylation, the catalyst is
destroyed by oxidation, the aqueous phase is separated from the product
mixture, the unreacted olefins are returned to the hydroformylation stage,
25 and the resulting oxo aldehydes are hydrogenated to the corresponding
isononanols. Their further processing to give the diisononyl phthalates takes
place by esterification with phthalic anhydride, with catalysis by butyl
titanates.

30 A further example of the use of the dibutene fractions prepared by the
process of the invention (n-octene-containing and/or dimethylhexene-
containing fraction) is the preparation of nonanoic acids and/or their vinyl

- esters. For this purpose, the respective olefin fraction is first of all reacted with carbon monoxide in the presence of strong acids such as sulfuric acid or boron fluoride hydrates to give tertiary carboxylic acids. The tertiary carboxylic acids are then reacted with acetylene in the presence of the zinc salt of the carboxylic acids (Encycl. Polym. Sci. Eng. 17, pp. 426-434) as catalyst to give the corresponding vinyl esters, or the latter are obtained by transesterification with vinyl acetate (Ullmann, 4th edition, volume 19, pp. 368 ff.). These esters are used as copolymers - for example, for the preparation of modified polyvinyl acetate, where they bring about internal plasticization while at the same time increasing the stability to hydrolysis. Here again, the use of the bottom fraction with its low degree of branching achieves a very substantial improvement in the plasticized properties, as shown by the examples.
- 15 The top fraction, containing highly branched isomers, on the other hand, is employed with particular advantage when rapid biological breakdown is not required or when particularly high oil solubility is a factor. Both of these apply in a particularly high measure to the metal salts of branched carboxylic acids, which are used as drying accelerators in paints and coatings. In this case, higher oil solubility means that higher concentrations of the metal salt in the organic medium can be obtained. Since the paints and coatings are intended to protect the substrate, a long service life without the addition of toxic agents is of essential importance.
- 25 These branched carboxylic acids can be obtained from the top fraction either by hydroformylating and oxidizing the resultant aldehydes or, preferably, by hydrocarboxylation. One example of an appropriate process in this case is the KOCH synthesis, as described in Falbe, New Synthesis with Carbon Monoxide, Springer Verlag, Berlin 1980, p. 372. Under the chosen reaction conditions, the more highly branched olefins of the dimethylhexene-containing fraction give stable Markovnikov products, i.e., predominantly tertiary carboxylic acids.

5 branched olefins. As a general rule, such reactions then take place with improved selectivity as compared with the use of olefins with little or no branching.

Furthermore, following hydrogenation, the dimethylhexene-containing
10 fraction can be used as a gasoline component with a high octane number.

The examples which follow are intended to illustrate the present invention but without restricting its scope.

15 **Example 1** **Dibutene fractionation**

An industrial dibutene mixture with a composition in accordance with Table 4 was fractionated. The column used had the following technical data:

20	Total length	27.5 m
	Diameter	DN 300
	Mesh packings	Sulzer CY (about 10 theoretical plates per meter)
	Packed length	18.72 m

In all, 117 elements of the mesh packings were installed on 9 support grids. The distribution of steam within the column took place by 9 tube distributors and 8 liquid collectors. The typical operating conditions were:

30	Inflow	100 l/h
	Distillate	~ 30 l/h
	Bottom discharge	~ 70 l/h

2,3-Dimethylhexenes	0.64%	< 0.1%	1.6%
3,3-Dimethylhexenes	0.27%	< 0.1%	1.0%
2,4-Dimethylhexenes	0.67%	< 0.1%	2.5%
Other C ₈ olefins	0.43%	0.7%	2.3%
Iso index	≈ 1.18	0.87	≈ 1.71

Table 5: Cumulative analysis

Examples 2 to 4

Preparation of tertiary carboxylic acids

10

Unfractionated dibutene (Example 2), the dimethylhexene-containing fraction prepared in accordance with the invention (top product, Example 4), and the n-octene-containing fraction prepared in accordance with the invention (bottom product, Example 3) were reacted in accordance with DE 23 39 947 to give tertiary carboxylic acids. The catalyst used was a complex comprising boron fluoride and water, with Cu⁺ as cocatalyst. The reactions took place in a stirred autoclave within a temperature range of 20-35°C and under a CO pressure of 30 bar. The pressure was held constant by metering in further CO. The reaction was ended as soon as uptake of CO was no longer observed.

20

Separation of the catalyst phase, water scrubbing and distillative workup of the crude carboxylic acids gave products of the following composition (figures in % by mass).

25

	Example 2	Example 3	Example 4
Product	Carboxylic acid A	Carboxylic acid B	Carboxylic acid C
2,2-Dimethylheptanoic acid	7.31	2.30	8.17
2-Methyl-2-ethyl-hexanoic acid	54.3	21.7	71.0
2-Methyl-2-propylpentanoic acid	7.09	3.62	6.99
2,2-Diethylpentanoic acid	3.40	2.02	2.54
2,2,5-Trimethylhexanoic acid	0.83	1.71	0.09
2,2,4-Trimethylhexanoic acid	0.81	2.13	0.18


30

	2,4-Dimethyl-2-ethylpentanoic acid	1.76	4.44	0.30
	2,2,3-Trimethylhexanoic acid	2.54	7.10	0.74
	2-Methyl-2-isopropylpentanoic acid	5.44	11.4	1.97
5	2,3-Dimethyl-2-ethylpentanoic acid A	7.27	18.9	3.40
	2,3-Dimethyl-2-ethyl-pentanoic acid B	7.59	20.1	3.54
	2-Ethyl-2-isopropylbutanoic acid	1.19	3.45	0.55
10	Other, unknown acids	0.50	1.13	0.48

Table 6

Examples 5 to 7

- 15 The mixtures of tertiary carboxylic acids obtained in Examples 2 to 4 were reacted with acetylene at atmospheric pressure at a temperature of 190-220°C in the presence of the zinc salt of the respective acids to be reacted, in accordance with the equation:



The reaction was conducted in accordance with the method of G. Hübner, Fette, Seifen, Anstrichmittel, 68, (4), pp. 290-292 (1966).

- Following distillation, vinyl esters were obtained with a purity of $\geq 99.8\%$,
 25 and according to analysis by gas chromatography these esters had essentially the same isomer composition as the carboxylic acids employed; these esters are referred to below as vinyl ester A (based on dibutene as such, precursor: carboxylic acid A), vinyl ester B (based on bottom product of the distillation of Example 1, precursor: carboxylic acid B), and vinyl ester
 30 C (based on top product of the distillation, Example 1, carboxylic acid C).

Examples 8 to 12

Homopolymers were prepared from the vinyl esters of Examples 5 to 7 in

accordance with the following standard procedure (Examples 10 to 12) and their glass transition point was determined as a measure of their suitability as copolymers for internal plasticization.

5 Starting materials

Monomer	Parts by weight
Vinyl ester of a tertiary C ₉ or C ₁₀ carboxylic acid	100.00
Aqueous phase	
10 DI water	70.00
Anionic surfactant, e.g. Marlon® A 390 (85% active substance)	0.03
Nonionic surfactant, e.g. Marlon® 820 (25% strength solution)	8.00
15 Potassium peroxodisulfate (K ₂ S ₂ O ₈)	0.10
Potassium carbonate	0.25
Hydroxylethylcellulose, e.g. Natrosol 250 L (or LR)	2.00
Acetic acid (100%)	0.20
Initiator solution	
20 Potassium peroxodisulfate	0.23
DI water	12.00

Procedure

The aqueous phase and about 10% of the monomer were heated with stirring to 75°C. After 15 minutes at this temperature, the remainder of the monomer and the initiator solution were metered in in separate streams. The monomer was added at a uniform rate over 120 minutes and the initiator solution over 135 minutes. During the metered additions, the temperature was maintained between 75 and 80°C. After a further 120 minutes of stirring at the same temperature, the batch was cooled to room temperature.

Directly, or following filtration, the resultant emulsion was used to produce moldings of which the glass transition points were determined by torsional vibration analysis in accordance with DIN 53455.

In addition, two commercially customary vinyl esters of known glass transition points were subjected to the same procedure in order to ensure the comparability of the test procedure. These were firstly a vinyl ester of tertiary C₁₀ acids (based on tripropene, Comparative Example 8), which is in
5 widespread use as an internal plasticizer for e.g. vinyl acetate (literature glass transition point -3°C). Secondly, use was made of a vinyl ester of tertiary C₉ acids (Comparative Example 9), i.e. a vinyl ester with the same empirical formula but a different degree of branching than the vinyl esters prepared in accordance with the above examples (literature glass transition
10 point in the region of +60°C).

The measurements gave the following data:

	Example	8 (com- parative)	9 (com- parative)	10	11 *	12
5	Vinyl ester	C10-VE*	C9-VE*	A (Dibu- tene)	B (Bottom)	C (Top)
	Glass transition point [°C]	-3	+ 60	-3	-12	+ 15

Table 7: * commercial vinyl esters based on tertiary C₉ and C₁₀ carboxylic acids (W. Lau, VeoVa, a Vinyl Ester Monomer, Polymers DotCom Magazine, 2, (2), February 1996)

Comparative Examples 8 and 9 show that the standard formulation brings results comparable with the literature. In addition, Example 9 shows that normally, with tertiary C₉ carboxylic acids, vinyl esters having an extremely high glass transition point are obtained, which are totally unsuitable for internal plasticization.

In contrast, even the vinyl ester based on the dibutene employed (Example 10) shows a plasticizing suitability comparable with the industrially customary product (Comparative Example 8). The vinyl ester based on the bottom product from the dibutene distillation (Example 11) with a glass transition point of -12°C is by comparison a comonomer having a very substantially improved plasticizing action. Even the product of the branched tertiary carboxylic acids (Example 12; based on top product of the distillation of Example 1) has a substantially lower glass transition point than the comparative product from Example 9. If use as a comonomer for internal plasticization is the parameter, therefore, the product from Example 11 is by far the most suitable in comparison to the products from Examples 8, 9, 10 and 12.

The tertiary carboxylic acids of Example 7, on the other hand (carboxylic acid C, based on top product of Example 1), give comonomers which have only a small plasticizing effect (see Example 12). Because of their greater branching, however, they are particularly suitable, for example, for the
5 preparation of oil-soluble metal salts such as drying accelerators for coating materials and stabilizers for PVC or for hydrolysis-stable esters as solvents.

Examples 13 to 15

10 Phthalate plasticizers were prepared from the fractions of Example 1 in the following way:

The respective olefin fraction (starting material, bottom product and top product) was hydroformylated as known from the literature using synthesis
15 gas ($\text{CO}/\text{H}_2 \sim 1/1$) in the presence of cobalt compounds as catalyst and at about 200 bar of 180°C . From the resultant reaction discharge, the useful products (C_9 aldehydes and C_9 alcohols) were separated off by distillation and, again in a known manner, were hydrogenated to the alcohols. The resulting isononanol mixture was finally reacted with phthalic anhydride, in a
20 known manner, to give the corresponding phthalates.

The phthalates were tested for the suitability as plasticizers by measuring their viscosity. For a given empirical formula, the viscosity of the esters decreases as the degree of branching goes up; conversely, the plasticizing
25 properties are improved as the degree of branching falls.

Table 8 clearly shows that from the bottom product of the distillation of Example 1 a particularly good plasticizer is obtained.

30 The table below indicates the isomer distribution of the known C_9 alcohols, which covers about 98% of the total alcohols. The remainder are unresolved other isomers of C_9 alcohols. The viscosity relates to the respective

phthalate prepared from the alcohol mixture (measured at 20°C).

Example	13	14	15
Olefin	Starting material	Bottom	Top
5 n-Octenes	17.5%	25.0%	0.0%
Methylheptenes	54.7%	65.0%	31.0%
Dimethylhexenes	27.7%	10.0%	69.0%
Isomer distribution of the C₉ alcohols			
10 n-Nonanol	8.4%	12.4%	0.0%
2-Methyloctanol	4.6%	6.4%	0.0%
2-Ethylheptanol	2.5%	3.3%	0.0%
2-Propylhexanol	2.0%	2.9%	0.0%
4-Methyloctanol	17.3%	20.5%	9.6%
15 2,3-Dimethylheptanol	1.8%	2.2%	1.2%
3-Ethylheptanol	7.0%	8.4%	4.0%
2-Propyl-3-ethylpentanol	0.2%	0.2%	0.1%
2-Ethyl-4-methylhexanol	2.5%	2.8%	1.5%
2,5-Dimethylheptanol	8.2%	9.9%	4.7%
20 6-Methyloctanol	17.5%	21.0%	9.9%
4,5-Dimethylheptanol	22.3%	8.1%	55.0%
3-Ethyl-4-methylhexanol	5.4%	1.9%	14.0%
Viscosity of the mixture at 20°C in mPas	77	68	103

25 **Table 8**

From the bottom product from dibutene distillation, therefore, a plasticizer having a particularly low viscosity is obtained.



What is claimed is:

1. A process for fractionating dibutenes, which comprises separating the
5 dibutenes into an n-octene-containing fraction having an iso index of
less than 90% and a dimethylhexene-containing fraction having an iso
index of more than 110% of the iso index of the original dibutenes.
2. The process as claimed in claim 1, wherein the n-octene-containing
10 fraction has an iso index of less than 1.0.
3. The process as claimed in claim 1, wherein the n-octene-containing
fraction has an iso index of less than 0.9.
- 15 4. A process as claimed in one of claims 1 to 3, wherein the fractionation
of the dibutenes takes place by continuous distillation.
5. The process as claimed in claim 4, wherein the distillation is
performed under atmospheric pressure.
- 20 6. The process as claimed in one of claims 1 to 5, wherein the n-octene-
containing fraction is obtained as the bottom product and the
dimethylhexene-containing fraction as the top product.
- 25 7. The process as claimed in one of claims 1 to 6, wherein the n-octene-
containing fraction has a boiling range of from 110 to 126°C under
atmospheric pressure.
8. The process as claimed in one of claim 7, wherein the n-octene-
30 containing fraction has a boiling range of from 115 to 123°C under
atmospheric pressure.



9. The process as claimed in one of claims 1 to 6, wherein the dimethylhexene-containing fraction has a boiling range of from 95 to 120°C under atmospheric pressure.
- 5 10. The process as claimed in claim 9, wherein the dimethylhexene-containing fraction has a boiling range of from 105 to 115°C under atmospheric pressure.
11. The use of the dimethylhexene-containing fraction as set forth in
10 claims 1 to 6, 9 and 10 for preparing nonanoic acids.
12. The use of the dimethylhexene-containing fraction as set forth in claims 1 to 6, 9 and 10 for preparing isononanol.
- 15 13. The use of the n-octene-containing fraction as set forth in claims 1 to 8 for preparing isononanol.
14. The use of the n-octene-containing fraction as set forth in claims 1 to 8 for preparing nonanoic acids.
- 20 15. The use of the dimethylhexene-containing fraction as set forth in claims 1 to 6, 9 and 10, following hydrogenation, as a motor fuel component.