WIRELESS LAN SYSTEM AND WIRELESS COMMUNICATION METHOD

This application is based upon and claims the benefit of priority from Japanese patent application No. 2006-279923, filed on October 13, 2006, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a wireless LAN system, or in particular, to a wireless LAN system in which various communication forms such as a one-to-many communication and a one-to-one communication coexist.

2. Description of the Related Art

Types of IP communication for the wireless LAN according to IEEE802.11 and the wired LAN such as Ethernet (registered trade mark) include unicast communication, broadcast communication and multicast communication. The unicast communication is the one-to-one communication in which a base station transmits data to a single terminal address. The broadcast communication and the multicast communication, in contrast, are the one-to-many communication for transmitting data collectively from a base station to a plurality of terminal addresses. In the broadcast communication, the data are transmitted toward all arbitrary terminals existing in a predetermined communication range. In the multicast communication, on the other hand, the data are transmitted to all the terminals designated as destination.

A method of what is called a power-save mode for suppressing a

power consumption of the wireless terminals is available as a standard technique according to IEEE802.11 related to the wireless LAN, as described in LAN MAN Standards Committee of the IEEE Computer Society, "Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications", ANSI/IEEE Std 802.11, 1999 Edition, p.128-133 (Non-Patent Document 1). According to this method, the wireless terminal switched from a awake mode to a power-save mode enters what is called a sleep mode in which it operates with low power.

Types of a sync signal (hereinafter referred to as a beacon) for the wireless terminals adapted for the power-save mode include TIM (Traffic Indication Map) and DTIM (Delivery TIM). Beacons for TIM and DTIM are transmitted periodically at a preset ratio such as 2 to 1 or 3 to 1. In the broadcast communication or the multicast communication described above, a presence or an absence of data to be received by a terminal is notified by the DTIM beacon. In the presence of the data to be received by the terminal, the data is transmitted immediately after the DTIM beacon from the base station. The wireless terminal constituting the destination address of the broadcast or multicast communication, with an arrival of the DTIM beacon receive timing, is awaken from the sleep mode and, after maintaining the awake state for a predetermined time, receives the data.

Fig. 7 shows an actual example of the broadcast/multicast (BC/MC) communication described above. In the shown case, assume that each wireless terminal (3A/3B) is in effective power-save mode. The wireless LAN base station 1, upon receipt of packets of the broadcast or multicast communication from a transmitter LAN terminal 2 (S701), accumulates the packets sequentially (S702). Also, with an arrival of the TIM beacon timing, the wireless LAN base station 1 sends out the TIM beacon (S703).

The wireless terminal 3A and the wireless terminal 3B, after being awaken from the sleep mode and receiving the TIM beacon from the wireless LAN base station 1, returns to the sleep mode again.

After that, with the arrival of the DTIM beacon timing, the wireless LAN base station 1 sends out the DTIM beacon having added thereto the information indicating the accumulation of the data of the BC/MC communication (S704). Then, the particular data is transmitted to the wireless terminal 3A and the wireless terminal 3B (S705). In the meantime, each wireless terminal (3A/3B) maintains the awake mode also after receiving the DTIM beacon and receives the data by BC/MC communication.

SUMMARY OF THE INVENTION

The data of the broadcast/multicast communication distributed by the procedure shown in Fig. 7, however, are not necessarily used by all the wireless terminals that have received it, but may be unnecessary for a part of the wireless terminals. Specifically, in Fig. 7, the data (S705) transmitted by BC/MC communication after the DTIM beacon (S704) may be the data required for the wireless terminal 3A but not required for the other wireless terminal 3B.

In the case where the broadcast/multicast data received is not required, the particular wireless terminal (3B) disposes of the received data, resulting in a waste of the data receiving process. This operation is not desirable for the wireless terminals utilizing the power-save mode intended for suppression of power consumption. Also, a network providing the service frequently using the broadcast/multicast communication generates the receiving process frequently regardless of whether the received data is

required or not, and therefore, poses a problem that the power consumption of the wireless terminals is difficult to suppress.

Embodiments of the invention provide a technique for appropriately suppressing the power consumption of the wireless terminals connected to the wireless LAN.

In a first aspect of the invention, there is provided a wireless LAN system comprising: a base station of a wireless LAN, being connected to a LAN terminal; and a plurality of wireless terminals connected to the base station, wherein each of the wireless terminals comprises a means for executing a sleep mode in which the wireless terminal operates with low power; a means for notifying the base station of a broadcast/multicast (BC/MC) address for receiving data from the base station by BC/MC communication when said wireless terminal executes a program using the BC/MC communication in the wireless LAN; a means for switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station; a means for switching the awake mode to the sleep mode of the unicast data is not accumulated by the base station; and a means for notifying the base station of the switching to the awake mode from the sleep mode of the unicast data is accumulated by the base station, and the base station comprises a means for registering said BC/MC address notified from the wireless terminal as information related to an unicast address of said wireless terminal; a means for converting BC/MC data addressed to said wireless terminal and received from the LAN terminal into unicast data by rewriting a BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC address; a

means for sending information indicating that the unicast data is accumulated by the base station to said wireless terminal; and a means for transmitting the unicast data to said wireless terminal which has notified the base station of the switching to the awake mode from the sleep mode.

In a second aspect of the invention, there is provided a wireless terminal connected to a base station of a wireless LAN, comprising: a means for executing a sleep mode in which the wireless terminal operated with low power; a means for notifying the base station of a broadcast/multicast (BC/MC) address for receiving data from the base station by BC/MC communication when the wireless terminal executes a program using the BC/MC communication in the wireless LAN, wherein the base station registers said BC/MC address notified from said wireless terminal as information related to an unicast address of said wireless terminal, converts BC/MC data to be addressed to said wireless terminal and received from the wireless terminal into the unicast data by rewriting the BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC data, and sends information of indicating that the unicast data is accumulated by the base station to said wireless terminal; a means for switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station; a means for switching the awake mode to the sleep mode if the unicast data is not accumulated by the base station; and a means for notifying the base station of the switching to the awake mode from the sleep mode if the unicast data is accumulated by the base station.

In a third aspect of the invention, there is provided a wireless communication method for a base station of a wireless LAN and a plurality

of wireless terminals connected to the base station, comprising: at the wireless terminal side executing a sleep mode in which the wireless terminal operates with low power; notifying the base station of a broadcast/multicast (BC/MC) address for receiving data from the base station by BC/MC communication by the wireless terminal which executes a program using the BC/MC communication in the wireless LAN; switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station; switching the awake mode to the sleep mode if the unicast data is not accumulated by the base station; and notifying the base station of the switching to the awake mode from the sleep mode if the unicast data is accumulated by the base station, and at the base station side registering said BC/MC address notified from said wireless terminal as information related to an unicast address of said wireless terminal; converting BC/MC data addressed to said wireless terminal and received from a LAN terminal into unicast data by rewriting a BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC address; sending information indicating that the unicast data is accumulated from the base station to said wireless terminal; and transmitting the unicast data to said wireless terminal which has notified the base station of the switching to the awake mode from the sleep mode.

According to embodiments of this invention, the one-to-many communication data to be sent out to the wireless LAN can be transmitted only to a wireless terminal which uses the particular data. As a result, the wireless terminals not requiring the one-to-many communication data can avoid the data receiving process and the power consumption can be suppressed.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing a configuration of the system according to an embodiment of this invention;

Fig. 2 is a block diagram showing a configuration of the wireless LAN base station according to an embodiment;

Fig. 3 is a block diagram showing a configuration of the wireless LAN terminal according to an embodiment;

Fig. 4 is a diagram for explaining the terminal management table according to an embodiment;

Fig. 5 is a diagram for explaining the address conversion process according to an embodiment;

Fig. 6 is a sequence chart showing the operation of the system according to an embodiment;

Fig. 7 is a sequence chart showing the operation of the system according to the art related to the invention;

Fig. 8 is a diagram for explaining the frame configuration based on IEEE802.11; and

Fig. 9 is a flowchart showing the wireless LAN terminal according to another embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Fig. 1 shows a configuration of a wireless LAN system according to an embodiment of the invention. A wireless LAN system 100 includes a wireless LAN base station 104 of a wireless LAN 102 and a plurality of wireless LAN terminals 105A, 105B accommodated in the wireless LAN base station 104. The wireless LAN base station 104 is connected to the LAN terminal 103 by a wired LAN 101. The wireless LAN terminal 105A (105B) has the function of power-save mode according to IEEE802.11.

Fig. 3 shows a configuration of the wireless LAN terminal 105A (105B). A wireless LAN interface (I/F) 303 executes the communication process of the wireless LAN 102 based on IEEE802.11. A control unit 301 controls the operation of the local terminal thereof. A BMC address notification unit 302 notifies the wireless LAN base station 104 of an address used for broadcast communication or multicast communication (hereinafter referred to as "the BC/MC communication") with the wireless LAN base station 104. An address list 304 has stored therein the addresses notified to the wireless LAN base station 104 and the address of the local terminal in the unicast communication.

While an application using the data of the BC/MC communication by the wireless LAN base station 104 is operating in the wireless LAN terminal 105A (105B), the control unit 301 supplies the BMC address notification unit 302 with the address for the BC/MC communication

described in the address list 304. This address for the BC/MC communication is used by the wireless LAN terminal 105A (105B) to receive the data from the wireless LAN base station 104 in the BC/MC communication. The BMC address notification unit 302 prepares the data for notifying the supplied BC/MC communication address to the wireless LAN base station 104 and transmits the particular data to the wireless LAN base station 104 through the wireless LAN interface 303.

Fig. 2 shows a configuration of the wireless LAN base station 104. The LAN interface (I/F) 201 executes the communication process of the wired LAN 101. A bridge unit 202 executes the bridge process between the LAN 101 and the wireless LAN 102. The control unit 206 controls the bridge unit 202 and executes the function of a wireless LAN access point standardized by IEEE802.11. A BMC-UC converter 203 converts a destination of the data transmitted to the wireless LAN 102 from a BC/MC communication address to an unicast communication address. A wireless LAN interface (I/F) 204 executes the communication process of the wireless LAN 102 based on IEEE802.11.

Also, the wireless LAN interface 204 transmits the TIM and DTIM beacons based on the provision of IEEE802.11 periodically to the wireless LAN 102. The BC/MC address notified from the wireless LAN terminal 105A (105B) is registered by the control unit 206 in a terminal management table 205 as information related to the unicast address of the particular wireless terminal.

Fig. 4 shows an example of a terminal management table 205. The terminal management table 205 has recorded therein the "broadcast/multicast address" constituting the address for the BC/MC communication notified from each wireless LAN terminal 105A, 105B and

the "wireless terminal MAC address" corresponding to the unicast address of the terminal that has notified the particular broadcast/multicast address. The unicast address recorded in the "wireless terminal MAC address" can be obtained from the header information of the frame transmitted from each wireless LAN terminal 105A, 105B to notify the BC/MC address. Incidentally, the recording pattern is not limited to the one shown but may be appropriately changed.

The control unit 206 of the wireless LAN base station 104, upon receipt of the frame from the LAN 101 or the wireless LAN 102, determines whether the destination address described in the header is registered or not in the "broadcast/multicast address" of the terminal management table 205. In the case where the determination shows that the destination address is so registered, the unicast address corresponding to the particular destination address (BC/MC address) is read from the "wireless terminal MAC address" of the terminal management table 205 and supplied to the BMC-UC converter 203.

The BMC-UC converter 203 converts the BC/MC address constituting the destination address of the frame into the unicast address read from the terminal management table 205. The frame of which the destination address has been converted is transmitted to the corresponding wireless terminal (105A, 105B) by the unicast communication through the wireless LAN interface 204.

A basic configuration of the MAC frame based on IEEE802.11 is shown in Fig. 8. The destination address converted by the BMC-UC converter 203 described above corresponds to a "destination MAC address" in the "MAC header" shown. Also, the address recorded in the "wireless terminal MAC address" of the terminal management table 205 corresponds

to the "transmitter MAC address" in the frame transmitted from the wireless LAN terminal 105A (105B) to notify the BC/MC address.

The operation of this embodiment is explained with reference to a sequence chart shown in Fig. 6. The wireless LAN terminal 105A, while executing the application program using the data of the BC/MC communication, notifies the wireless LAN base station 104 of the BC/MC address set in the particular application (S601). The wireless LAN terminal 105A, after notifying the BC/MC address, switches the operation mode thereof from awake mode to sleep (doze) mode. The other wireless LAN terminal 105B, not currently executing the application program of the BC/MC communication, operates in sleep mode.

The wireless LAN base station 104, upon receipt of the BC/MC address from the wireless LAN terminal 105A, registers it in the terminal management table 205 as information related to the unicast address of the wireless LAN terminal 105A (S602).

The wireless LAN base station 104, upon receipt, from the wired LAN 101, of the BC/MC communication packet transmitted from the LAN terminal 103 (S603), determines whether the destination address of the packet is registered or not in the terminal management table 205 (S604). Once the registration is recognized, the wireless LAN base station 104 reads the unicast address corresponding to the registered BC/MC address from the terminal management table 205, and rewrites the destination address (BC/MC address) of the received packet by the address that has been read.

Fig. 5 shows an example of address conversion. In this case, assume that the unicast address of the wireless LAN terminal 105A is "00:00:4C:AA:AA:AA". As shown in Fig. 5, the BC/MC address

"03:00:00:BB:BB:BB" set in the destination address of the received packet is converted to the unicast address "00:00:4C:AA:AA:AA" of the corresponding wireless LAN terminal 105A by the wireless LAN base station 104. Incidentally, the transmitter address and the address ("BSSID") of the wireless LAN base station 104 are not changed. The wireless LAN base station 104 sequentially accumulates the data whose destination address has been converted into unicast address (S606).

Then, with the arrival of TIM beacon transmission timing, the wireless LAN base station 104 sends out the TIM beacon to the wireless LAN 102 (S607). The TIM beacon output in the process has set therein an identifier indicating that the unicast data of the wireless LAN terminal 105A is accumulated by the wireless LAN base station 104. This identifier is set in accordance with the standard technique based on IEEE802.11, which is not explained herein.

The wireless LAN terminal 105B in sleep mode, after being awaken and receiving the TIM beacon from the wireless LAN base station 104 while recognizing that the data addressed to the particular local terminal is not accumulated, returns to the sleep mode.

The wireless LAN terminal 105A also in sleep mode, on the other hand, after being awaken from sleep mode and receiving the TIM beacon, recognizes that the unicast data addressed to the particular local terminal is accumulated in the wireless LAN base station 104. The wireless LAN terminal 105A, in order to acquire the accumulated data, sets the PS bit of the PS-Poll frame based on IEEE802.11 to off state and transmits it to the wireless LAN base station 104 (S608). The PS-Poll frame is used to notify the operating mode of a terminal to the base station. In the case where the PS bit is set to off state as described above, it indicates that the

terminal is awake, while the PS bit in on state indicates that the terminal is asleep.

The wireless LAN base station 104, upon recognition from the received PS-Poll that the wireless LAN terminal 105A has switched from sleep mode to awake mode, transmits the accumulated unicast data of the wireless LAN terminal 105A (S609). The wireless LAN terminal 105A receives the data from the wireless LAN base station 104, and upon complete receipt, is transferred to sleep mode.

After that, with the arrival of the DTIM transmission timing, the wireless LAN base station 104 sends out the DTIM beacon to the wireless LAN 102 (S610). Originally, the data of the BC/MC communication is transmitted immediately after the DTIM beacon indicating the data accumulation is sent out. In the case under consideration, however, the data of the BC/MC communication has already been transmitted from the LAN terminal 103 to the wireless LAN terminal 105A by unicast communication. As of this timing, therefore, the identifier indicating the accumulation of the data of the BC/MC communication is not set in the DTIM beacon.

The wireless LAN terminal 105A and the wireless LAN terminal 105B, when receiving the DTIM beacon described above, are awaken from sleep mode, and then return to sleep mode again.

As described above, according to this embodiment, the data of the BC/MC communication that have arrived at the wireless LAN base station 104 can be transferred only to the wireless LAN terminal 105A executing the application of the BC/MC communication. The other wireless LAN terminal 105B not executing the application of the BC/MC communication, therefore, requires no data receiving process. Thus, a longer sleep time

can be secured.

Next, a modification of the embodiment described above is explained with reference to the flowchart of Fig. 9. This modification assumes a communication form in which the wireless LAN terminal (105A), upon receipt of the data with a destination address converted from the BC/MC address to the unicast address, transfers the particular data to the other terminal.

The BMC-UC converter 203 of the wireless LAN base station 104 according to this modification has a function of adding an identifier, indicating the conversion of BC/MC address into unicast address, to a header of data to be transmitted.

In Fig. 9, the wireless LAN terminal (105A), upon receipt of the unicast data from the wireless LAN base station 104 (S901), determines whether an identifier which indicates the conversion of address is set in the header thereof or not. In the case where the determination shows that the identifier is not set (YES in S902), the destination address of the received data is returned from the unicast address to the BC/MC address (S903). Specifically, the BC/MC address notified to the wireless LAN base station 104 (Fig. 6, S601) is set again as a destination address. Then, the data with the destination address set again as the BC/MC address is transferred to the other terminal (S904).

Incidentally, in the case where the identifier is invalid in the data received from the wireless LAN base station 104 (NO in S902), the wireless LAN terminal (105A) recognizes that the particular data is for normal unicast communication, i.e. the data requiring no transfer.

In the steps shown in Fig. 9, the wireless LAN terminal (105A), upon receipt of the unicast data, can immediately recognize whether the

particular data is to be transferred or not. As a result, the data transfer to the other terminal can be smoothly carried out.

As another modification, assume that none of the wireless LAN terminals (105A, 105B) accommodated in the wireless LAN base station 104 is in sleep mode. Then, the data of the BC/MC communication may be sent out to the wireless LAN 102 without changing the destination address. The sleep mode or the awake mode of a terminal can be determined from the on/off state of the PS bit set in the frame from the terminal.

Although the exemplary embodiments of the present invention have been described in detail, it should be understood that various changes, substitutions and alternatives can be made therein without departing from the sprit and scope of the invention as defined by the appended claims. Further, it is the inventor's intent to retrain all equivalents of the claimed invention even if the claims are amended during prosecution.

CLAIMS:

1. A wireless LAN system comprising:

a base station of a wireless LAN, being connected to a LAN terminal; and

a plurality of wireless terminals connected to the base station, wherein

each of the wireless terminals comprises

a means for executing a sleep mode in which the wireless terminal operates with low power;

a means for notifying the base station of _a broadcast/multicast (BC/MC)_ address for receiving data from the base station by BC/MC communication when said wireless terminal executes a program using the BC/MC communication in the wireless LAN;

a means for switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station;

a means for switching the awake mode to the sleep mode if the unicast data is not accumulated by the base station; and

a means for notifying the base station of the switching to the awake mode from the sleep mode if the unicast data is accumulated by the base station, and

the base station comprises

a means for registering said BC/MC address notified from the wireless terminal as information related to an unicast address of said wireless terminal;

a means for converting BC/MC data addressed to said wireless terminal and received from the LAN terminal into unicast data by rewriting a BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC address;

a means for sending information indicating that the unicast data is accumulated by the base station to said wireless terminal; and

a means for transmitting the unicast data _to said wireless terminal which has notified the base station of the switching to the awake mode from the sleep mode.

2. The wireless LAN system according to claim 1, wherein the base station further comprising a means for sending out two types of sync signals to the wireless LAN in mutually different periods, and transmission timing of the BC/MC data is related to transmission timing of one of the two types of the sync signals.

3. A wireless terminal connected to a base station of a wireless LAN, comprising:

a means for executing a sleep mode in which the wireless terminal operates with low power;

a means for notifying the base station of a broadcast/multicast (BC/MC) address for receiving data from the base station by BC/MC communication when the wireless terminal executes a program using the BC/MC communication in the wireless LAN, wherein the base station registers said BC/MC address notified from said wireless terminal as information related to an unicast address of said wireless terminal, converts BC/MC data to be addressed to said wireless terminal and received from the wireless terminal into the unicast data by rewriting the BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC data, and sends information of indicating that the unicast data is accumulated by the base station to said wireless terminal;

a means for switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station;

a means for switching the awake mode to the sleep mode if the unicast data is not accumulated by the base station; and

a means for notifying the base station of the switching to the awake mode from the sleep mode if the unicast data is accumulated by the base station.

4. A wireless LAN base station to which a LAN terminal and a plurality of wireless terminals according to claim 3 are connected, comprising:

a means for registering said BC/BC address notified from the wireless terminal as information related to an unicast address of said wireless terminal;

a means for converting BC/MC data addressed to said wireless terminal and received from the LAN terminal into unicast data by rewriting_ a BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC address;

a means for sending information indicating that the unicast data is accumulated by the base station to said wireless terminal; and

a means for transmitting the unicast data to said wireless terminal which has notified the base station of the switching to the awake mode from the sleep mode.

5. The wireless LAN base station according to claim 4, further comprising a means for adding an identifier, indicating the conversion of the address of destination of BC/MC data into the unicast address, to said data to be transmitted when the base station executes said conversion.

6. The wireless LAN base station according to claim 4 or 5, further comprising a means for sending out two types of sync signals to the wireless IAN in mutually different periods, and transmission timing of the BC/MC data is related to transmission timing of one of the two types of the sync signals.

7. A wireless communication method for a base station of a

wireless LAN and a plurality of wireless terminals connected to the base station, comprising:

at the wireless terminal side

executing a sleep mode in which the wireless terminal operates with low power;

notifying the base station of a broadcast/multicast (BC/MC) address for receiving data from the base station by BC/MC communication by the wireless terminal which executes a program using the BC/MC communication in the wireless LAN;

switching the sleep mode to an awake mode and recognizing whether unicast data to be addressed to said wireless terminal by unicast communication is accumulated by the base station;

switching the awake mode to the sleep mode if the unicast data is not accumulated by the base station; and

notifying the base station of the switching to the awake mode from the sleep mode if the unicast data is accumulated by the base station, and

at the base station side

registering said BC/MC address notified from said wireless terminal as information related to an unicast address of said wireless terminal;

converting BC/MC data addressed to said wireless terminal and received from a LAN terminal into unicast data by rewriting a BC/MC address of said received BC/MC data by the unicast address related to said registered BC/MC address, which is the same as that of said BC/MC address;

sending information indicating that the unicast data is accumulated from the base station to said wireless terminal; and

transmitting the unicast data to said wireless terminal which has notified the base station of the switching to the awake mode from the sleep mode.

8. The wireless communication method according to claim 7, further comprising sending out two types of sync signals to the wireless LAN in mutually different periods,

wherein transmission timing of the BC/MC data is related to transmission timing of one of the two types of the sync signals.

9. The wireless LAN system according to claim 2, wherein the two types of sync signals are beacons for Traffic Indication Map (TIM) and Delivery TIM (DTIM) based on IEEE802.11, and transmission timing of the beacon for TIM is related to the transmission timing of the BM/MC data.

10. The wireless LAN base station according to claim 4, wherein the two types of sync signals are beacons for Traffic Indication Map (TIM) and Delivery TIM (DTIM) based on IEEE802.11, and transmission timing of the beacon for TIM is related to the transmission timing of the BM/MC data.

11. The wireless communication method according to claim 8, wherein the two types of sync signals are beacons for Traffic Indication Map (TIM) and Delivery TIM (DTIM) based on IEEE802.11, and transmission timing of the beacon for TIM is related to the transmission timing of the BM/MC data.

WIRELESS LAN SYSTEM AND WIRELESS COMMUNICATION METHOD

ABSTRACT

Each of a plurality of wireless terminals (105A, 105B) connected to a wireless LAN base station (104) notifies the base station of an address for receiving data by one-to-many communication from the base station when said wireless terminal executes a program using the one-to-many communication in the wireless LAN (S601). The base station records by relating the address notified from the wireless terminal with an address of the wireless terminal for one-to-one communication (S602). When the base station receives one-to-many communication data to be sent out the wireless LAN (S603), the base station converts an address of destination of the one-to-many communication data into the one-to-one communication address corresponding to said destination (S605) and transmits the data whose destination address has been converted into the one-to-one communication address (S609).

Fig. 1