CLAIMS

1. An antenna arrangement comprising:

a directional antenna assembly comprising a directional antenna mounted upon a stationary support structure through a connection base of the directional antenna, the directional antenna generally extending along a main vertical axis perpendicular to a plane defined by said stationary support structure, and

a rotatable base rotatably mounted about said stationary support structure and a pole assembly, said pole assembly comprising a pole mounted on said rotatable base, said pole extending in the direction of said main axis, the rotatable base being a base different from the connection base of the directional antenna assembly, the rotatable base surrounding the connection base of the directional antenna assembly, said rotatable base being rotatable about the main axis, said rotatable base being configured to control the rotation of the pole assembly in azimuth, about the main axis, a rotation of said rotatable base actuating and controlling the rotation of the pole about the main axis, so as to enable relocation of the pole, outside the line-of-sight of the directional antenna, the upper end of the pole lying above the upper point of the directional antenna assembly.

2. The antenna arrangement of claim 1, wherein the pole is configured to rotate outside the field of view of directional antenna.

3. The antenna arrangement of claim 1 or 2, wherein said antenna arrangement comprises a rotating control unit for controlling the rotation of the pole.

4. The antenna arrangement of any one of the preceding claims, wherein the directional antenna is rotatable at least about the main axis, the rotation of the directional antenna about the main axis defining the azimuth rotation of the directional antenna.

5. The antenna arrangement of any one of the preceding claims, wherein said antenna arrangement comprises a communication antenna mounted on the pole.

6. The antenna arrangement of claim 5, wherein the communication antenna is selected in the group consisting of an omnidirectional antenna and a directional antenna.

7. The antenna arrangement of any claim 5 or 6, wherein the communication antenna comprises a set of elementary antennas stacked in the direction of the main axis.

8. The antenna arrangement of any one of the preceding claims, wherein the directional antenna assembly comprises a radome in which the directional antenna is enclosed.

9. The antenna arrangement of claim 8, wherein the base of the radome is mounted upon the rotatable base.

10. The antenna arrangement of claim 8, wherein the base of the radome is surrounded by the rotatable base.

11. The antenna arrangement of any one of the preceding claims, wherein said antenna arrangement comprises a lightning arrestor arranged on the pole.

12. The antenna arrangement of claim 11 when dependent on any one of claims 5-7, wherein the lightning arrestor is arranged above the communication antenna.

13. An antenna arrangement comprising an interface and a directional antenna assembly, the directional antenna assembly comprising a directional antenna mounted on said interface the directional antenna being configured to transmit and/or receive spatially concentrated electromagnetic radiation in one direction at a time, the directional antenna generally extending along a main vertical axis perpendicular to the plane defined by said interface, wherein the antenna arrangement further comprises a rotatable base mounted on said interface and a pole arrangement comprising a pole integral with said rotatable base, said pole extending in the direction of said main axis, said rotatable base being rotatable about the main axis, said rotatable base being configured to control the rotation of the pole assembly in azimuth, about the main axis,

a rotation of said rotatable base actuating and controlling the rotation of the pole about the main axis, so as to enable relocation of the pole, outside the line-of-sight of the directional antenna, wherein the antenna arrangement comprises a radome in which the directional antenna is enclosed and/or a lightning arrestor arranged on the pole.

14. An antenna system comprising an antenna arrangement according to any one of claims 1 to 13, said support structure being mounted on a support system, said support structure being hollow, wherein the support structure comprises a through hole, the rotatable base delimiting an inner passage communicatively coupled with said through hole of the support structure and with an inner passage of the pole, the antenna arrangement comprising a cable running from a fixation point on the support system to the upper end of the pole, the cable passing through the support structure to the rotatable base via the through hole and said inner passages.

15. The antenna system of claim 14, wherein the cable is a conductive screened cable.

16. The antenna system of claim 15, wherein it comprises a connection component to connect the rotatable base to the support structure, said connection component being arranged at the level of said through hole and enabling the passage of the cable.

17. The antenna system of claim 16, wherein the connection component is a cable twist.

18. The antenna system of claim 16, wherein the connection component is a rotary joint.

19. The antenna arrangement of any one of claims 1 to 13, wherein the directional antenna is rotatable.

20. The antenna arrangement of claim 19, wherein the rotatable base is mechanically slaved to the rotation of the directional antenna.