

2002029353

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

162162

(43) International Publication Date
5 July 2001 (05.07.2001)

PCT

(10) International Publication Number
WO 01/48118 A1(51) International Patent Classification⁷: C10G 21/00,
21/12, 21/14, 21/16, 21/20, 7/20, B01D 3/40

(21) International Application Number: PCT/US00/35700

(22) International Filing Date:
28 December 2000 (28.12.2000)


(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/473,463 28 December 1999 (28.12.1999) US(71) Applicant: EXXON RESEARCH AND ENGINEER-
ING COMPANY [US/US]; P.O. Box 900, 1545 Route 22
East, Annandale, NJ 08801 (US).(72) Inventor: SCHUCKER, Robert, Charles; 26 Rillwood
Place, Woodlands, TX 77382 (US).(74) Agents: HUGHES, Gerard, J. et al.; Exxon Research
and Engineering Company, P.O. Box 900, Annandale, NJ
08801 (US).(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE,
ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP,
KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD,
MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD,
SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN,
YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: EXTRACTIVE DISTILLATION PROCESS FOR THE REDUCTION OF SULFUR SPECIES IN HYDROCARBON
STREAMS(57) Abstract: A method for separating sulfur species from hydrocarbon streams, particularly cracked naphtha streams, using ex-
tractive distillation. The method effectively separates sulfur species from cracked naphtha streams without substantially lowering
the olefin content. The process involves passing a feed through inlet (12) and a solvent through inlet (14) into a distillation column
(10) in order to produce a solvent bottoms which contains the sulfur species and an overhead product.

WO 01/48118 A1



ACTION