

OUTLET DEVICE FOR COIN PAYOUT HOPPERS

The present invention relates to an outlet device
5 for coin payout hoppers used in vending machines, game
machines, coin exchangers or the like, in particular
to an outlet chute adapted for guiding coins to a
vertically extending escalator out of the coin payout
hoppers.

10

Hitherto, there is a coin payout hopper as
described in Japanese Patent Application Publication
No. 45588/87 comprising a hopper for storing coins,
a rotary disc rotatably mounted on a supporting plate
15 inclined at an angle to the horizontal within said
hopper, a plurality of delivery pins spaced in the
peripheral direction of the rotary disc and a delivery
knife for guiding coins at an upper delivery portion
to a discharge chute.

20

Some coin payout hoppers of the type mentioned
above are provided with an outlet device which comprises
an outlet chute for receiving coins discharged from
the coin payout hopper, and an escalator which is con-
nected at the lower end thereof to an upper outlet of
25 the outlet chute and upwardly extended from the upper

outlet for transferring coins to an upper coin tray by pushing up each coin in the escalator by the following coins pushed into the outlet chute out of the coin payout hopper.

5 In the conventional outlet chute 1 of such an outlet device, as shown in Fig. 1, coins 2 are pushed edgewise out of a payout hopper into a lower inlet 3 of an arciform curved outlet chute passage 4 in the horizontal direction as shown by an arrow A and pushed up
10 from an upper outlet 5 into a vertically extending escalator passage 7 of an escalator 6 connected to the upper outlet 5 of the outlet chute 1.

 The conventional curved outlet chute passage 4, as shown in Fig. 2 is composed of a coin supporting
15 back plate 8, outside and inside edge plate 11 and 12, which are positioned at the outside and inside with respect to the center of the radius of curvature of the curved outlet chute passage 4, respectively, and outside and inside front plates 15 and 16 which are
20 rigidly secured to the back plate 8 together with the edge plates 11 and 12 by means of screws 13 and 14, respectively and have extensions 15a and 16a beyond the coin guiding tracks 9 and 10 of the edge plates 11 and 12 respectively, to engage outer peripheral
25 portions of the coins to guide the coins in the

curved outlet chute passage 4 and to prevent the coins from dropping out of the passage.

Such a conventional outlet device as mentioned above has drawbacks such that if a deformed coin is pushed in the guiding passage by a trailing coin, the front end of the deformed coin may be pushed over the rear end of the preceding coin or the trailing coin may be pushed into the under side of the rear end of the deformed coin whereby jamming the guiding passage, and even if upward movement of a normal coin is resisted by weight of a number of preceding coins to cause the rear end of the normal coin to be spaced from the back plate, the front end of the trailing coin may be pushed into the under side of the rear end of the normal coin whereby also jamming the guiding passage so that no coin is delivered from the outlet chute.

An object of the present invention is to eliminate the drawback mentioned above and to provide an outlet device without jamming in the curved coin guide passage.

The present invention is defined in appended claim 1, and in one embodiment as shown in Figure 3 provides an outlet device for a coin payout hopper comprises an outlet chute 1 including a curved outlet chute passage 4 having a lower inlet 3 through which coins are pushed edgewise into the passage substantially in

the horizontal direction and an upper outlet 5 through which coins are pushed out the passage substantially in the vertical direction, an outside edge plate 11 having an outside coin guide track 9 positioned at the outside with respect to the center of the radius of curvature of the curved outlet chute passage 4 and being fixed to a coin supporting back plate 8 such that the surface of the outside coin guide track 9 is inclined at an angle to the surface of the coin supporting back plate 8, an inside edge plate 12 having an inside coin guide track 10 positioned at the inside with respect to the center of the radius of curvature of the curved outlet chute passage 4 and being covered at the lower inlet portion thereof with a flexible front plate 20 such that a portion of the flexible front plate 20 is extended beyond the inside coin guide track 10 to engage outer peripheral portions of coins, and a rotatable tapered guide roller 22 having an inverted conical surface 22a provided at the upper outlet portions adjacent to the inside edge plate for engaging the outer periphery of the coin to urge the coin to the surface of the coin supporting back plate.

The tapered guide roller 22 may be rotatably supported on a roller shaft which is substantially perpendicularly extended through the coin supporting back plate 8 and

resiliently urged by means of a spring 18 or 26 so as to engage the inverted conical surface 22a with the outer periphery of the coin thereby
5 urging the coin to the surface of the coin supporting the back plate 8.

With the aforementioned arrangement of the present invention, coins 2 are pushed edgewise into the lower inlet 3 of the outlet chute 1 in substantially the horizontal direction by means of the coin payout hopper
10 and pushed in the curved outlet chute passage 4 toward the upper outlet 5 in the vertical direction by trailing coins as shown in Fig. 4. Thus, coins 2 are urged to the surface of the outside guide track 9 positioned at the outside with respect to the center of the radius of curvature of the curved outlet chute passage 4 to forcedly progress along the outside guide
15 track 9 in the curved outlet chute passage 4 which is defined by the coin supporting back plate 8, the outside guide track 9, the inside guide track 10 and the portion of the flexible front plate extended beyond the inside guide track 10. If a deformed coin enters in the curved outlet chute passage 4, the leading end of the deformed coin 2a rides on the trailing
20 end of the leading coin 2 and as the result the flexible front plate 20 is resiliently deformed to open the outlet chute passage as shown in Fig. 6.

Thus, the deformed coin 2a is complete pushed.....

out of the outlet chute passage 4 by the trailing coin 2 and removed from the outlet chute.

On the other hand, the normal coin 2 is pushed up in the outlet chute passage 4 covered with the flexible front plate 20 by the trailing coin and between the outside guide track 9 and the tapered roller 22 against the spring force of the spring 18. The inclined surface of the outside guide track 9 and the inverted conical surface 22a of the tapered guide roller 22 loaded by the spring engage the outer periphery of the coin to urge the coin to the surface of the coin supporting back plate 8 and guide the coin into the outlet escalator.

Thus, the outlet device according to the present invention satisfactorily prevent the coin jamming in the outlet chute by the cooperation of the flexible front plate, the inclined outside guide track and the tapered roll arranged in the outlet chute passage for removing the deformed coin and preventing the normal coin from rising above the surface of the supporting back plate.

Fig. 1 is an elevational view of an outlet chute of the prior art;

Fig. 2 is a sectional view taken along the line II-II in Fig. 1;

Fig. 3 is a schematic perspective view illustrating a coin payout hopper provided with an outlet chute according to the present invention;

Fig. 4 is an enlarged elevational view of the
5 outlet chute in the coin payout hopper shown in Fig. 3;

Fig. 5 is a sectional view taken along the line
V - V in Fig. 4;

Fig. 6 is a sectional view illustrating the operation of a flexible front plate;

10 Fig. 7 is an enlarged sectional view along the line VII - VII in Fig. 4; and

Fig. 8 is an enlarged sectional view illustrating other embodiment of urging means.

15 The invention will be described in more detail in the following with reference to the accompanying drawings.

Referring to Figs. 4 - 7 illustrating one embodiment of the present invention, an outlet chute 1 includes
20 a lower inlet 3 through which coins 2 are pushed edgewise into a curved outlet chute passage 4 in the horizontal direction as shown by an arrow A from a coin payout hopper. These coins 2 are driven in the curved outlet chute passage 4 toward an upper outlet 5 upwardly and pushed
25 out of the upper outlet 5 into an outlet escalator 6

which is substantially vertically extended from the upper outlet 5.

Referring to Fig. 4, an outside edge plate 11 having an outside coin guide track 9 positioned at the outside with respect to the center of the radius of curvature of the curved outlet chute passage 4 is fixed to a coin supporting back plate 8 by means of screws 13 and an inside edge plate 12 having an inside coin guide track 10 positioned at the inside with respect to the center of the radius of curvature of the curved outlet chute passage 4 is fixed to the coin supporting back plate 8 by means of a screw 14 together with a resiliently flexible retaining front plate 20 of elastomer material such as urethane rubber, which is positioned at the lower inlet portion.

The surface of the outer coin guide track 9 is inclined at an acute angle θ such as about 70 degrees to the coin supporting back plate 8 (Fig. 5).

The flexible retaining front plate 20 is preferably made of urethane rubber having a hardness in a range of 60°- 70° and a thickness in a range of 0.5 - 2.0 mm.

In this embodiment, a tapered roller 22 is provided at the upper outlet portion of the outlet chute adjacent to the upper end of the inside edge plate 12.

The tapered guide roller 22 as shown in Fig. 7,

has an inverted conical surface 22a and a central through hole 21 through which is extended a roller shaft 23 so that the tapered guide roller 22 is rotatably supported on the roller shaft 23.

5 The roller shaft 23 is extended through a guide slot 24 formed in the back plate 8 and is secured at the extended end to a slide shoe 17 such that the tapered roller 22 is permitted to move along the back plate 8 in the direction of the width of the outlet chute passage 4. The slide shoe 17 is drawn toward the outside edge plate 11 by means of a tension spring 18.

15 Thus, a coin A entered between the inclined surface of the outside coin guide track 9 of the outside edge plate 11 and the inverted conical surface 22a of the tapered guide roller 22, as shown in Fig. 7, is engaged the periphery thereof with the inclined track surface and the roller surface 22a to urge to the supporting surface of the back plate 8, thereby preventing the coin from rising above the supporting surface of the back plate 8. Furthermore, the tapered roller can be moved through the guide slot 24 along the back plate in the direction of the width of the outlet chute passage 4 so that some variations of the diameter of 25 coins are accepted without coin jamming.

Referring to Fig. 8 illustrating another embodiment of the invention, the tapered roller 22 having the inverted conical surface 22a is rotatably supported on the roller shaft 23, but the roller shaft 23 is extended
5 through a hole 25 formed in the back plate 8. A spiral spring 26 is interposed between the rear surface of the back plate 8 and a spring seat 19 secured to the extended end of the roller shaft 23 with the large diameter end 26a of the spiral spring 26 being engaged with the
10 rear surface of the back plate.

With such an arrangement, a coin A entered between the outside edge plate 11 and the tapered roller 22, as shown in Fig. 8, is urged to the supporting surface of the back plate 8 by the inclined surface of the out-
15 side coin guide track 9 and the tapered roller surface 22a, thereby preventing the normal coin from rising above the supporting surface of the back plate 8 in the same manner as mentioned above.



Claims:

1. An outlet device for a coin payout hopper including an outlet chute comprising a curved outlet chute passage having a lower inlet through which coins
5 are pushed edgewise into the passage substantially in the horizontal direction and an upper outlet through which coins are pushed out the passage substantially in the vertical direction, an outside edge plate having an outside coin guide track positioned at the outside
10 with respect to the center of the radius of curvature of the curved outlet chute passage and being fixed to a coin supporting back plate such that the surface of the outside coin guide track is inclined at an angle to the surface of the coin supporting back plate, an inside edge
15 plate having an inside coin guide track positioned at the inside with respect to the center of the radius of curvature of the curved outlet chute passage and being covered at the lower inlet portion thereof with a flexible front plate such that a portion of the
20 flexible front plate is extended beyond the inside coin guide track to engage outer peripheral portions of coins, a rotatable tapered guide roller having an inverted conical surface arranged at the upper outlet portion adjacent to the inside edge plate,
25 and means for urging the tapered roller to engage the



inverted conical surface with the outer periphery of the coin, thereby urging the coin to the surface of the coin supporting back plate.

5

2. The outlet device as claimed in claim 1, wherein the flexible front plate is made of urethane rubber having a hardness in a range of 60° - 70°.

10

3. The outlet device as claimed in claim 1, wherein the surface of the outer coin guide track is inclined at about 70 degrees to the coin supporting surface of the coin supporting back plate.

15

4. The outlet device as claimed in claim 1, wherein the tapered guide roller is rotatably supported on a roller shaft which is substantially perpendicularly extended through a guide slot formed in the back plate, and a slide shoe is secured to the extended end of the roller shaft and is drawn toward the outside edge plate by means of a tension spring.

20

5. The outlet device as claimed in claim 1, wherein the tapered guide roller is rotatably supported on a roller shaft which is substantially perpendicularly extended through a through hole formed in the back plate and a spiral spring is interposed between the rear surface of the back plate and a spring seat secured to the extended end of the roller shaft.

25

6. The outlet device constructed, arranged and adapted to operate substantially as hereindescribed with reference to Figures 3 to 8 of the accompanying drawings.
