


wherein X is hydrogen or a substituted or unsubstituted $C_1$ to $C_{20}$ hydrocarbyl group, wherein the substituted hydrocarbyl group is substituted with one or more substituents selected from hydroxyl, alkoxy, ester or amino groups and Y is $-CH_2OR$, $-C(=O)OR^1$ or $-C(=O)NHR^2$, wherein R, $R^1$ and $R^2$ are independently hydrogen or $C_1$ to $C_{20}$ alkyl or alkenyl groups,; and further wherein the organic liquid diluent does not contain a carboxylic acid ester.

**7.** The lubricating oil additive concentrate according to claim ~~17~~ 6 wherein Y is $CH_2OH$.

**8.** The lubricating oil additive concentrate according to claim ~~14~~ 6 wherein X is hydrogen.

**9.** The lubricating oil additive concentrate according to claim ~~18~~ 7 wherein X is hydrogen.

**10.** The lubricating oil additive concentrate according to claim ~~14~~ 6 wherein Y is $C(=O)OR^1$.

**11.** The lubricating oil additive concentrate according to claim ~~21~~ 10 wherein $R^1$ is butyl.

**12.** The lubricating oil ~~composition~~ additive concentrate according to claim ~~22~~ 11 wherein X is hydrogen.

**13.** A method for reducing wear in an internal combustion engine, the method comprising operating the internal combustion engine with the lubricating oil composition according to claim **1**.

**14.** A method for reducing wear in an internal combustion engine, the method comprising operating the internal combustion engine with the lubricating oil composition according to claim ~~73~~.

**15.** A method for reducing wear in an internal combustion engine, the method comprising operating the internal combustion engine with the lubricating oil composition according to claim ~~104~~.