

(19) World Intellectual Property Organization
International Bureau



G00002



(43) International Publication Date
11 July 2002 (11.07.2002)

PCT

(10) International Publication Number
WO 02/053840 A1

(51) International Patent Classification⁷: E01C 11/16, 3/00

(21) International Application Number: PCT/IB02/00005

(22) International Filing Date: 4 January 2002 (04.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01/0188 8 January 2001 (08.01.2001) ZA

(71) Applicant and

(72) Inventor: DENNISON, David, Peter [ZA/ZA]; P.O. Box 570, Link Hills, 3652, Unit No. 5, Brentwood, 21 Adams Road, 3201 Pietermaritzburg (ZA).

(74) Agent: ROTTEVEEL, Martin; Adams & Adams, Private Bag 16, Adams & Adams Place, 16 Cranbrook Crescent, La Lucia Ridge Office Park, 4320 Umhlanga (ZA).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THE CONSTRUCTION OF ROADS



162162



(57) Abstract: The invention relates to the use of stabilizing body in the construction of roads. The stabilizing body comprises a substantially rigid, planar body (20) that can be inter-engaged with other similar bodies in a configuration in which an extended, substantially planar stabilizing structure can be formed. Each stabilizing body defines a multi-cellular configuration with cells (26) defined by side walls extending from the operative top side of the body towards the operative bottom side thereof. The side walls (28) defining the cells have projecting formations (30) projecting therefrom into the cells. In use, the wearing course of a road is formed within and above a stabilizing structure formed above the base of the road, with the asphalt composition used filling the cells and being anchored to the stabilizing bodies via the projecting formations, thus forming a wearing course resistant to various different known of road failure.