



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 47/10	A1	(11) International Publication Number: WO 99/58414 (43) International Publication Date: 18 November 1999 (18.11.99)								
(21) International Application Number: PCT/US99/10724 (22) International Filing Date: 13 May 1999 (13.05.99) (30) Priority Data: <table border="0"> <tr> <td>60/085,311</td> <td>13 May 1998 (13.05.98)</td> <td>US</td> </tr> <tr> <td>60/089,456</td> <td>16 June 1998 (16.06.98)</td> <td>US</td> </tr> <tr> <td>09/307,626</td> <td>7 May 1999 (07.05.99)</td> <td>US</td> </tr> </table> (71) Applicant: THE TESTOR CORPORATION [US/US]; 620 Buckbee Street, Rockford, IL 61104 (US). (72) Inventor: MORRISON, Adam, P.; 1816 Oregon Avenue, Rockford, IL 64108 (US). (74) Agent: McKEE, James, W.; Fay, Sharpe, Beall, Fagan, Minnich & McKee, LLP, Suite 700, 1100 Superior Avenue, Cleveland, OH 44114 (US).	60/085,311	13 May 1998 (13.05.98)	US	60/089,456	16 June 1998 (16.06.98)	US	09/307,626	7 May 1999 (07.05.99)	US	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
60/085,311	13 May 1998 (13.05.98)	US								
60/089,456	16 June 1998 (16.06.98)	US								
09/307,626	7 May 1999 (07.05.99)	US								

(54) Title: FLUID DISPENSING APPARATUS WITH FITMENT SPOUT AND VALVE

(57) Abstract

A fluid dispensing system includes a base for attachment to an associated pouch (A) and a neck (34) extending outwardly therefrom away from the pouch. The neck and base (32) include a bore (40) formed therethrough in fluid communication with the pouch interior. The neck comprises first (36) and second portions (38), and the bore is closed at its outermost end by the second portion.

