

Description

Title of Invention: LIQUEFIED GAS TANK

5 Technical Field

[0001] The present invention relates to a liquefied gas tank for storing liquefied gas, and more particularly to a liquefied gas tank that is suitable for storing a cryogenic liquid such as LNG (liquefied natural gas).

10

Background Art

[0002] Conventionally, a transport ship (tanker), a floating storage unit, an above-ground storage facility, an underground storage facility and the like are used for transportation or storage of cryogenic liquids such as LNG (liquefied natural gas) and LPG (liquefied petroleum gas) (for example, see Patent Literature 1 and Patent Literature 2).

15

20

[0003] In Patent Literature 1, a liquefied gas carrying vessel is disclosed that includes an outer tank that constitutes the hull of a ship, and a tank (inner tank) that is disposed in a self-standing state inside the outer tank. In Patent Literature 2, an above-ground LNG tank is disclosed that includes an outer tank that is disposed on the ground and an inner tank that is disposed in a self-standing state inside the outer tank. By adopting a configuration in which an inner tank that stores liquid cargo is independent from an outer tank in this manner, the inner tank can be protected from the external environment while allowing expansion and contraction (thermal expansion and thermal contraction) of the inner tank that accompanies changes in the temperature of the liquid cargo.

25

30

Citation List

Patent Literature

[0004]

Patent Literature 1: Japanese Patent Laid-Open No. 2011-901

5 Patent Literature 2: Japanese Patent Laid-Open No. 2007-
278400

Summary of Invention

Technical Problem

10 [0005] In recent years, natural gas has been attracting
attention as an environmentally friendly energy because, in
comparison to petroleum, emissions such as carbon dioxide
and nitrogen oxides are small when natural gas is burnt,
and natural gas does not generate sulfur oxides. Further,
15 because natural gas is buried in the ground in abundance at
various places around the world, there is a high level of
stability with respect to the supply of natural gas, and
the introduction of natural gas as an alternative energy to
petroleum is being studied. When natural gas is used as an
20 energy source in this manner, liquefying the natural gas
makes it possible to reduce the volume thereof to 1/600 the
volume of natural gas in the gaseous state, and thus the
storage efficiency can be improved. Accordingly, adopting
a structure in which an inner tank is caused to stand
25 independently from an outer tank as an LNG storage facility
(liquefied gas tank) as disclosed in Patent Literature 1
and Patent Literature 2 is easily conceivable.

[0006] However, when using natural gas as an energy
source, in the case of adopting the above described
30 liquefied gas tank that has a self-standing structure in
which a storage amount is a comparatively small amount of
approximately 1/10 to 1/100 the storage amount of a
conventional transport ship or storage facility, a massive

facility is required to make the outer tank self-standing, and there are various problems such as that costs are liable to be high and the installation area is liable to increase. Further, according to the conventional liquefied gas tanks, since the tank is formed with a double-wall structure that is constituted by the inner tank and outer tank, there has also been the problem that the structure of an outlet for liquid cargo or piping or the like is liable to be complex. In addition, it is necessary to dispose the liquefied gas tank near equipment or facilities that use the liquefied gas tank as an energy source, and a case can arise in which a sufficient installation area cannot be secured, and it is also necessary to quickly replenish the natural gas in a case where natural gas that is used as fuel has run out.

[0007] The present invention has been created in view of the above described problems, and an object of the present invention is to provide a liquefied gas tank that can store liquefied gas that has a simple structure and requires a small installation area.

Solution to Problem

[0008] According to the present invention, there is provided a liquefied gas tank for storing liquefied gas, including: an inner tank that stores the liquefied gas and is disposed so as to be capable of self-standing on a floor surface; and an outer tank that is covered over the inner tank and is supported by an upper face portion of the inner tank; in which the outer tank is configured to be capable of sliding on the upper face portion of the inner tank in response to expansion and contraction in a horizontal direction of the inner tank and to be capable of moving in

response to expansion and contraction in a vertical direction of the inner tank.

[0009] The outer tank may have an expansion and contraction mechanism portion that is disposed along a lower outer circumference thereof, or a wall surface thereof may itself be formed as a structure that is capable of expanding and contracting. Further, the inner tank and the outer tank may be configured to be attachable to and detachable from the floor surface, and the inner tank or the outer tank may be configured to be replaceable.

[0010] A base portion that supports the inner tank may be disposed on the floor surface, and a support block may be disposed between the base portion and the inner tank. In addition, a weir-like structure may be disposed on the floor surface so as to surround the base portion, and the outer tank may be connected to the weir-like structure.

[0011] The outer tank may have a penetration portion for inserting equipment into the inner tank, and a lid member may be disposed on the penetration portion. Equipment that is inserted into the inner tank may be disposed at a bottom face portion of the inner tank. An inert gas may be filled between the inner tank and the outer tank. Further, an elastic body may be disposed between the inner tank and the outer tank.

Advantageous Effects of Invention

[0012] According to the liquefied gas tank of the present invention that is described above, by configuring the inner tank so as to capable of self-standing with respect to the floor surface and causing the inner tank to support the outer tank, the structure of the outer tank can be simplified, the installation area can be reduced, and costs can be lowered. In addition, by configuring the outer tank

so as to be capable of moving horizontally and capable of moving in the vertical direction, even when a cryogenic liquid such as LNG is stored in the inner tank, the inner tank can be protected from the external environment while
5 allowing expansion and contraction (thermal expansion and thermal contraction) of the inner tank that is caused by the cryogenic liquid. Further, by adopting a simple structure, installation or replacement of the liquefied gas tank can be easily performed, and even in a case where
10 liquid cargo is used as fuel, replenishment of the fuel can be quickly performed.

Brief Description of Drawings

[0013]

15 [Figure 1A] Figure 1A shows a schematic cross-sectional view of a liquefied gas tank according to a first embodiment of the present invention.

[Figure 1B] Figure 1B shows a top view of the liquefied gas tank according to the first embodiment of the present
20 invention.

[Figure 2A] Figure 2A shows an enlarged view of a portion A of the liquefied gas tank shown in Figure 1A.

[Figure 2B] Figure 2B shows an enlarged view of the portion A according to a first modification of the liquefied gas
25 tank shown in Figure 1A.

[Figure 3A] Figure 3A shows an enlarged view of a portion B of the liquefied gas tank shown in Figure 1B.

[Figure 3B] Figure 3B shows an enlarged view of the portion B according to a first modification of the liquefied gas
30 tank shown in Figure 1B.

[Figure 3C] Figure 3C shows an enlarged view of the portion B according to a second modification of the liquefied gas tank shown in Figure 1B.

[Figure 3D] Figure 3D shows an enlarged view of the portion B according to a third modification of the liquefied gas tank shown in Figure 1B.

[Figure 4A] Figure 4A shows a schematic cross-sectional
5 view of a liquefied gas tank according to a second embodiment of the present invention.

[Figure 4B] Figure 4B shows a top view of the liquefied gas tank according to the second embodiment of the present invention.

10 [Figure 5A] Figure 5A shows an enlarged view of a portion A of the liquefied gas tank according to the second embodiment shown in Figure 4A.

[Figure 5B] Figure 5B shows an enlarged view of the portion A according to a first modification of the liquefied gas
15 tank according to the second embodiment shown in Figure 4A.

[Figure 5C] Figure 5C shows an enlarged view of the portion A according to a second modification of the liquefied gas tank according to the second embodiment shown in Figure 4A.

[Figure 6A] Figure 6A shows a schematic cross-sectional
20 view of a liquefied gas tank according to a third embodiment of the present invention.

[Figure 6B] Figure 6B shows a first modification of the liquefied gas tank according to the third embodiment of the present invention.

25 [Figure 7A] Figure 7A is a view illustrating a method for installing the liquefied gas tank shown in Figures 4A and 4B, that illustrates a foundation construction process.

[Figure 7B] Figure 7B is a view illustrating the method for installing the liquefied gas tank shown in Figures 4A and
30 4B, that illustrates an inner tank installation process.

[Figure 7C] Figure 7C is a view illustrating the method for installing the liquefied gas tank shown in Figures 4A and 4B, that illustrates an outer tank installation process.

[Figure 8A] Figure 8A is a view illustrating a modification of the method for installing a liquefied gas tank, that illustrates a foundation construction process.

5 [Figure 8B] Figure 8B is a view illustrating a modification of the method for installing a liquefied gas tank, that illustrates an inner and outer tank installation process.

[Figure 9A] Figure 9A is a schematic cross-sectional view showing a liquefied gas tank according to a fourth embodiment of the present invention.

10 [Figure 9B] Figure 9B is a schematic cross-sectional view showing a liquefied gas tank according to a fifth embodiment of the present invention.

[Figure 9C] Figure 9C is a schematic cross-sectional view showing a liquefied gas tank according to a sixth
15 embodiment of the present invention.

[Figure 10A] Figure 10A shows a schematic cross-sectional view of a liquefied gas tank according to a seventh embodiment of the present invention.

[Figure 10B] Figure 10B shows a diagram illustrating the
20 structure of the outer tank wall surface in the liquefied gas tank according to the seventh embodiment of the present invention.

[Figure 10C] Figure 10C shows a first modification of the structure of the outer tank wall surface in the liquefied
25 gas tank according to the seventh embodiment of the present invention.

[Figure 10D] Figure 10D shows a second modification of the structure of the outer tank wall surface in the liquefied
30 gas tank according to the seventh embodiment of the present invention.

[Figure 11A] Figure 11A shows a schematic cross-sectional view of a liquefied gas tank according to an eighth embodiment of the present invention.

[Figure 11B] Figure 11B shows a side view of the liquefied gas tank according to the eighth embodiment of the present invention.

5 Description of Embodiments

[0014] Embodiments of the present invention are described hereunder using Figure 1 to Figure 11. Figures 1A and 1B are configuration diagrams of a liquefied gas tank according to a first embodiment of the present invention,
10 of which Figure 1A is a schematic cross-sectional view and Figure 1B is a top view. Figures 2A and 2B are enlarged views of a portion A of the liquefied gas tank shown in Figure 1A, in which Figure 2A illustrates the first embodiment and Figure 2B illustrates a first modification.
15 Figures 3A and 3B are enlarged views of a portion B of the liquefied gas tank shown in Figure 1A, in which Figure 3A illustrates the first embodiment, Figure 3B illustrates a first modification, Figure 3C illustrates a second modification, and Figure 3D illustrates a third
20 modification.

[0015] As shown in Figures 1 to 3, a liquefied gas tank 1 according to the first embodiment of the present invention includes an inner tank 2 that stores liquefied gas and that is disposed so as to be capable of self-standing on a floor
25 surface F, and an outer tank 3 that is covered over the inner tank 2 and is supported by an upper face portion 2a of the inner tank 2. The outer tank 3 is configured to be capable of sliding on the upper face portion 2a of the inner tank 2 in response to expansion and contraction in
30 the horizontal direction of the inner tank 2, and to be capable of moving in response to expansion and contraction in the vertical direction of the inner tank 2.

[0016] The inner tank 2 is, for example, a box-shaped structure, and stores liquefied gas such as LNG (liquefied natural gas) or LPG (liquefied petroleum gas) therein. In many cases, these kinds of liquid cargo are a low

5 temperature (for example, a very low temperature or an ultra-low temperature), and the wall surface of the inner tank 2 may have a heat insulating structure. Typically, a heat insulating material (see Figure 2A and 2B) is attached to the external surface of the inner tank 2.

10 [0017] Base portions 4 that support the inner tank 2 are disposed on the floor surface F, and support blocks 5 are disposed between the base portions 4 and the inner tank 2. The base portions 4 are metal components that are fixed to predetermined positions on the floor surface F. The
15 support blocks 5 have a function of thermally isolating the floor surface F from the inner tank 2. For example, the support blocks 5 are made of rectangular timber, and are pushed into frame body portions formed in the inner tank 2 and thereby fitted and locked thereto. The support blocks
20 5 are configured so as to be capable of sliding on the base portions 4, and to be movable in response to expansion and contraction in the horizontal direction of the inner tank 2. Note that, in a case where the floor surface F is the deck of a hull or the bottom of a ship, an anti-rolling chock or
25 anti-pitching chock may be disposed along the center line of the hull to support the horizontal load in a case where the inner tank 2 is swayed in the lateral direction or the front-and-rear direction by rolling or pitching of the hull.

[0018] Support blocks that are the same as those used for
30 conventional LNG tanks can be appropriately used as the support blocks 5. For example, support blocks that are made of a material that has a low thermal conductivity and an elastic force such as rubber or a resin, or that are

made by fixing these materials on the surface of rectangular timber may be used, and may be formed so as to be fixed to frame body portions by means of fixing fittings.

[0019] A locking portion (not shown in the drawings) that
5 locks the side portion of the support block 5 may be disposed on the base portion 4 at approximately a center part of the bottom face of the inner tank 2. By providing the locking portion, an immobile point G can be formed whose position in the horizontal direction does not change
10 when the inner tank 2 at expands or contracts. The locking portion, for example, is a frame body that is disposed on the center base portion 4 and surrounds all of the side portions of the support block 5.

[0020] In addition, as shown in Figure 1B, when an X axis
15 and a Y axis are set in directions along the horizontal direction of wall surfaces of the inner tank 2, locking portions that restrict movement in the Y-axis direction while allowing movement in the X-axis direction are formed on at least a pair of the base portions 4 disposed at
20 approximately the center part among a plurality of the base portions 4 arranged along the X-axis direction of the inner tank 2. Further, locking portions that restrict movement in the X-axis direction while allowing movement in the Y-axis direction are formed on at least a pair of the base
25 portions 4 disposed at approximately the center part among a plurality of the base portions 4 arranged along the Y-axis direction of the inner tank 2. Thus, a configuration may also be adopted so as to form the immobile point G at a point of intersection between an X-axis direction row and a
30 Y-axis direction row in which the locking portions are disposed.

[0021] In addition, penetration portions 22 for inserting equipment 21 such as piping are formed at approximately the

center part of an upper face portion 2a of the inner tank 2. The equipment 21 is supported by a supporting member (not shown in the drawings) that is disposed inside the inner tank 2 or outside the inner tank 2. As shown in Figure 1B, the penetration portions 22 are formed over the immobile point G. By providing the penetration portions 22 for the equipment 21 such as piping over the immobile point G, even in a case where the inner tank 2 thermally expands or contracts in the horizontal direction, movement in the horizontal direction of the equipment 21 can be effectively suppressed.

[0022] The outer tank 3 is a cover for protecting the inner tank 2 (including the heat insulating material 24) from the entry of moisture into the inside thereof and also from contact or collision with a foreign body (people, weather elements, flying objects, vehicles or the like) and the like, and the outer tank 3 may be subjected to an ultraviolet ray countermeasure or a salt damage countermeasure or the like. To exert these functions, the outer tank 3 may be a multi-layered structure, may be given a surface coating (application of paint or the like), and a panel or tape may be attached to an inner surface or external surface thereof.

[0023] The outer tank 3 is constituted by, for example, a thin metal plate such as an aluminum alloy plate, a stainless steel plate, or a colored steel plate, and has a box-shaped structure that is substantially the same as that of the inner tank 2, and surrounds the external surface of the inner tank 2. At such time, the self-weight of the outer tank 3 is supported by the outer tank 3 being placed on the upper face portion 2a of the inner tank 2. The outer tank 3 has penetration portions 30 for inserting the equipment 21 into the inner tank 2. In a case where the

penetration portions 22 and the penetration portions 30 are disposed over the immobile point G, because a relative movement amount between the penetration portions 22 and the outer tank 3 is not large, the equipment 21 and the
5 penetration portions 30 can be joined by welding or the like.

[0024] Further, depending on the stored amount of liquefied gas in the inner tank 2 and the circumstances regarding the use thereof, in some cases the equipment 21
10 thermally contracts, thermally expands, or a deviation arises with respect to intervals between a plurality of items of the equipment 21. Therefore, a configuration may be adopted so as to form a rimped structure that is capable of expanding and contracting around the equipment
15 21, in the outer tank 3 in an area around the penetration portions 30. In this respect, although a case in which a rimped structure is formed at one part of the outer tank 3 in an area around the penetration portions 30 is illustrated in the drawing, all of the outer tank 3 in the
20 area around the penetration portions 30 may have a rimped structure, and a configuration may also be adopted that is provided with an expandable and contractible concavo-convex structure other than the rimped structure illustrated in the drawing.

25 [0025] The outer tank 3 also includes a ceiling portion 3a that is placed on the upper face portion 2a of the inner tank 2. The ceiling portion 3a is not fixed to the upper face portion 2a of the inner tank 2, and the inner tank 2 and the outer tank 3 are configured so as to be capable of
30 sliding relative to each other in the horizontal direction. Because liquefied gas having a very low temperature is stored in the inner tank 2, the inner tank 2 will thermally contract or thermally expand depending on the stored amount

of liquefied gas. On the other hand, because the outer tank 3 is exposed to a normal temperature environment, a thermal contraction difference arises between the inner tank 2 and the outer tank 3. Therefore, a configuration is adopted in which a width D_c of the outer tank 3 is made larger than a width D_t of the inner tank 2 (including the heat insulating material 24), so that an expansion/contraction amount in the horizontal direction of the inner tank 2 can be absorbed by a gap ΔD ($= D_c - D_t$) between the inner tank 2 and the outer tank 3.

[0026] The size of the gap ΔD is appropriately set in accordance with expansion and contraction amounts of the inner tank 2 that are determined in accordance with conditions such as the capacity and shape of the inner tank 2, the kind of liquefied gas to be stored therein, and the structure of the outer tank 3. For example, in a case where the size of the inner tank 2 reaches a maximum size at the time of a normal temperature in an operational state of the liquefied gas tank 1, the size of the outer tank 3 can be set so that the outer tank 3 is disposed on the inner tank 2 without a gap therebetween at the time of a normal temperature.

[0027] A modification of the penetration portions 30 will now be described. A first modification that is shown in Figure 2B is one in which the penetration portions 30 are separated from the outer tank 3. More specifically, the outer tank 3 has an opening portion 31 for inserting the equipment 21 into the inner tank 2, a lid member 32 is disposed on the opening portion 31, and the penetration portions 30 are disposed in the lid member 32. By separating the penetration portions 30 from the outer tank 3 in this manner, installation work and maintenance and the like can be easily performed. The penetration portions 30

for the equipment 21 in the lid member 32 are connected thereto in an airtight manner by welding or the like. A configuration may also be adopted in which a seal member for maintaining airtightness is disposed between the lid member 32 and the outer tank 3 or in the penetration portions 30 of the lid member 32.

[0028] Further, depending on the stored amount of liquefied gas in the inner tank 2 and the circumstances regarding the use thereof, in some cases the equipment 21 thermally contracts, thermally expands, or a deviation arises with respect to intervals between a plurality of items of the equipment 21. Therefore, a configuration may be adopted so as to form a rimpled structure that is capable of expanding and contracting around the equipment 21 in the lid member 32. In this respect, although a case in which a rimpled structure is formed at one part of the lid member 32 is illustrated in the drawing, all of the lid member 32 may have a rimpled structure, and a configuration may also be adopted that is provided with an expandable and contractible concavo-convex structure other than the rimpled structure illustrated in the drawing.

[0029] Further, a weir-like structure 6 is disposed so as to surround the base portions 4 on the floor surface F. A lower end portion of the outer tank 3 is connected to the weir-like structure 6. The outer tank 3 also has an expansion and contraction mechanism portion 33 that is disposed along the lower outer circumference thereof. As shown in Figure 3A, the weir-like structure 6 is a metal component that is installed upright on the floor surface F, and is fixed to the floor surface F by means such as welding or a bolt. A thick portion 34 is formed at the lower end portion of the outer tank 3, and the expansion and contraction mechanism portion 33 is connected between

the weir-like structure 6 and the thick portion 34. The thick portion 34 is a component that compensates for the fact that the thin metal plate constituting the outer tank 3 is liable to deform, and functions to maintain sufficient fastening and airtightness between the expansion and contraction mechanism portion 33 and the outer tank 3.

[0030] The expansion and contraction mechanism portion 33 is a flexible component that absorbs a movement amount of the outer tank 3 accompanying thermal expansion or

contraction in the vertical direction (a perpendicular direction or a standing direction) and the horizontal direction of the inner tank 2. The inner tank 2 thermally contracts or thermally expands in the horizontal direction and the vertical direction depending on the stored amount of liquefied gas, and the outer tank 3 is configured to be capable of moving to follow the thermal contraction or thermal expansion of the inner tank 2. On the other hand, to maintain airtightness, it is necessary to connect the outer tank 3 to the weir-like structure 6 that is fixed to the floor surface F. Therefore, the outer tank 3 moves relative to the weir-like structure 6 in the horizontal direction and vertical direction. The expansion and contraction mechanism portion 33 is a component for absorbing such relative movement.

[0031] The expansion and contraction mechanism portion 33 is formed with an airtight material and structure. For example, a flexible structure obtained by forming chloroprene rubber or natural rubber or the like in a curved shape is adopted. Further, the expansion and contraction mechanism portion 33 is fixed by a fastener such as a bolt to the weir-like structure 6 and the thick portion 34 via an O-ring 33a that maintains airtightness. Note that a configuration may also be adopted in which the

expansion and contraction mechanism portion 33 is fixed in an airtight manner to the weir-like structure 6 and the thick portion 34 by welding or the like. The expansion and contraction mechanism portion 33 is not limited to the configuration shown in Figure 3A and, for example, may have the configuration of modifications that are illustrated in Figure 3B to Figure 3D.

[0032] A first modification that is illustrated in Figure 3B is one in which the expansion and contraction mechanism portion 33 is constituted by an urging member 33b. More specifically, the first modification has a configuration in which the urging member 33b that is capable of pressing from the inner side of the outer tank 3 to the outer side is fixed to the weir-like structure 6, and in which it is possible to slide the outer tank 3 in the vertical direction by means of contact pressure between the urging member 33b and the thick portion 34 and also maintain airtightness. The urging member 33b is constituted, for example, by a curved leaf spring member that is made of metal. A contact portion thereof may be coated with a coating that improves the sliding properties or the abrasion resistance thereof.

[0033] A second modification that is illustrated in Figure 3C is one in which the expansion and contraction mechanism portion 33 is constituted by a bellows member 33c. More specifically, the second modification has a configuration in which the bellows member 33c that is obtained by forming a metal plate in a bellows shape is connected to the weir-like structure 6 and the thick portion 34. Similarly to the embodiment illustrated in Figure 3A, a configuration may be adopted so as to arrange an O-ring in a sandwiched condition at the connection portions.

[0034] A third modification that is illustrated in Figure 3D is one in which the expansion and contraction mechanism portion 33 is constituted by a leaf spring member 33d.

More specifically, the third modification has a

5 configuration in which end faces of the leaf spring member 33d that is obtained by bending a metal plate are connected to the weir-like structure 6 and the thick portion 34.

Similarly to the embodiment illustrated in Figure 3A, a configuration may be adopted so as to arrange an O-ring in

10 a sandwiched condition at the connection portions. A configuration may also be adopted in which the leaf spring member 33d is obtained by molding chloroprene rubber or natural rubber or the like instead of using a metal plate.

Note that, as illustrated in the drawing, the weir-like
15 structure 6 and the thick portion 34 are formed in an L shape, and each has a connection face that faces the corresponding end face of the leaf spring member 33d.

[0035] An inert gas such as nitrogen gas may be filled

between the inner tank 2 and the outer tank 3. For example,

20 an inert gas can be filled into the gap between the inner tank 2 and the outer tank 3 by connecting an inert gas introduction pipe 61 to the weir-like structure 6 and connecting an inert gas discharge pipe 35 to the outer tank 3. The inert gas has a function as a carrier gas for

25 pushing out moisture or air that is present in the gap between the inner tank 2 and the outer tank 3 to the outside, and acts to expel air from the area surrounding the inner tank 2 that stores liquefied gas and prevent the occurrence of an explosion even in a case where liquefied
30 gas leaks from the inner tank 2.

[0036] Introduction of inert gas may be performed only

when installing the liquefied gas tank 1 or may be

performed continuously. Further, by sealing the inert gas

in the gap between the inner tank 2 and the outer tank 3 and setting the pressure inside the outer tank 3 to a somewhat higher pressure than the pressure of the external environment (for example, atmospheric pressure) of the outer tank 3, entry of moisture or air or the like into the gap can be effectively suppressed. Note that the arrangement of the inert gas introduction pipe 61 and the inert gas discharge pipe 35 is not limited to the example illustrated in the drawings, and the inert gas discharge pipe 35 may be arranged in a side portion of the outer tank 3 and the inert gas introduction pipe 61 may be arranged in the outer tank 3.

[0037] Next, a liquefied gas tank according to a second embodiment of the present invention will be described with reference to Figures 4A and 4B and Figures 5A to 5C.

Figures 4A and 4B are configuration diagrams of a liquefied gas tank according to the second embodiment of the present invention, in which Figure 4A shows a schematic cross-sectional view and Figure 4B shows a top view. Figures 5A to 5C are enlarged views of a portion A of the liquefied gas tank shown in Figure 4A and 4B, in which Figure 5A illustrates the second embodiment, Figure 5B illustrates a first modification, and Figure 5C illustrates a second modification. Note that components that are the same as in the above described first embodiment are denoted by the same reference characters and duplicated descriptions are omitted.

[0038] In the second embodiment and the modifications thereof that are shown in Figures 4A and 4B and Figures 5A to 5C, a coaming portion 23 is formed in the inner tank 2. Accordingly, the configuration is one in which the method of connecting the inner tank 2 and the outer tank 3 is different from the first embodiment. More specifically,

penetration portions 22 for inserting the equipment 21 such as piping are formed at approximately the center part of the upper face portion 2a of the inner tank 2, and as shown in Figure 5A the coaming portion 23 is formed along the outer circumference of the penetration portions 22. For example, the coaming portion 23 is formed so as to be approximately the same height as the heat insulating material 24 of the inner tank 2.

[0039] In addition, as shown in Figure 5A, an edge portion 31a that is bent towards the inner side is formed in the opening portion 31 of the outer tank 3, and positioning of the outer tank 3 is performed by inserting the edge portion 31a along the coaming portion 23 that is formed at the outer circumference of the penetration portions 22 of the inner tank 2. The edge portion 31a may be inserted without any gap between the edge portion 31a and the coaming portion 23, or may be inserted with a certain gap therebetween. In a case where the penetration portions 22 and the opening portion 31 are disposed over the immobile point G, because a relative movement amount between the coaming portion 23 and the outer tank 3 is not large, the edge portion 31a and the coaming portion 23 may be joined by welding or the like. Note that in a case where the outer tank 3 can be positioned by means of another component, the edge portion 31a may be omitted.

[0040] After the heat insulating material 24 is filled into the space formed by the edge portion 31a, the lid member 32 is disposed on the opening portion 31 and is connected thereto in an airtight manner by welding or the like. The penetration portions 30 for the equipment 21 in the lid member 32 are also connected in an airtight manner by welding or the like. A configuration may also be adopted in which a seal member for maintaining airtightness

is disposed between the lid member 32 and the outer tank 3 or in the penetration portions 30 of the lid member 32.

[0041] Modifications of the opening portion 31 will now be described. A first modification illustrated in Figure

5 5B is configured so that the space between the coaming portion 23 and the outer tank 3 (edge portion 31a) is airtightly sealed and a space including the heat insulating material 24 and the like that is formed between the inner tank 2 and the outer tank 3 and a space formed by the
10 opening portion 31 are separated. More specifically, a seal member 31b may be disposed between the coaming portion 23 and the edge portion 31a, and the space between the coaming portion 23 and the outer tank 3 may be airtightly sealed by means of a fastener 31c such as a bolt and nut,
15 and the space between the coaming portion 23 and the edge portion 31a may be airtightly sealed by welding or the like. In this case, it is not necessary for the lid member 32 to be airtight, and the lid member 32 is fixed to the outer tank 3 by a simple connection method.

20 [0042] A second modification shown in Figure 5C illustrates a case where the opening portion 31 of the outer tank 3 does not have the edge portion 31a. More specifically, a tip portion of the coaming portion 23 has a flange portion 23a whose diameter is expanded in the
25 horizontal direction, and the outer tank 3 having the opening portion 31 is disposed on the flange portion 23a. According to the second modification, a configuration may be adopted so as to airtightly connect the lid member 32 to the outer tank 3 in a similar manner to the second
30 embodiment shown in Figure 5A, or a configuration may be adopted so as to airtightly connect the outer tank 3 and the flange portion 23a in a similar manner to the first modification shown in Figure 5B.

[0043] Next, a liquefied gas tank according to a third embodiment of the present invention will be described with reference to Figures 6A and 6B. Figures 6A and 6B are views that illustrate a liquefied gas tank according to the third embodiment of the present invention, in which Figure 6A illustrates a schematic cross-sectional view and Figure 6B illustrates a first modification. Note that components that are the same as in the above described first embodiment are denoted by the same reference characters and duplicated descriptions are omitted.

[0044] The third embodiment illustrated in Figure 6A and Figure 6B is one in which the equipment 21 that is inserted into the inner tank 2 is disposed at a bottom face portion 2c of the inner tank 2. More specifically, as shown in Figure 6A, one part of the equipment 21 is configured to pass through the weir-like structure 6 and be inserted into the bottom of the inner tank 2, and thereafter pass through the bottom face portion 2c and enter the inside of the inner tank 2. The equipment 21 has, at an intermediate portion thereof, an opening/closing valve 21a that operates to open/close the equipment 21 (piping), a connection portion 21b that connects a fixed portion on the inner tank 2 side of the equipment 21 and a fixed portion of the weir-like structure 6, and a pipe expansion joint 21c that absorbs a movement amount of the equipment 21 accompanying thermal expansion or contraction of the inner tank 2. In the third embodiment shown in Figure 6A, a configuration is adopted in which the opening/closing valve 21a, the connection portion 21b, and the pipe expansion joint 21c are arranged in that order and disposed between the inner tank 2 and the outer tank 3. According to this configuration, the length of the equipment 21 such as piping can be shortened, and the support structure can be

simplified since it is not necessary for the outer tank 3 to support the equipment 21. In addition, in a case where the equipment 21 is fixed to the weir-like structure 6, when installing or replacing the liquefied gas tank 1, the fixed portion on the inner tank 2 side of the equipment 21 and the fixed portion of the weir-like structure 6 can be connected individually, and thereafter these fixed portions can be connected to each other by means of the connection portion 21b.

[0045] In contrast, in the first modification of the third embodiment that is shown in Figure 6B, one part of the equipment 21 is configured to pass through a lower portion of the expansion and contraction mechanism portion 33 and be inserted into the bottom of the inner tank 2, and then pass through the bottom face portion 2c and enter the inside of the inner tank 2. According to the first modification, a configuration is adopted in which the pipe expansion joint 21c, the opening/closing valve 21a, and the connection portion 21b are arranged in that order, with the pipe expansion joint 21c being disposed between the inner tank 2 and the outer tank 3, and the opening/closing valve 21a and the connection portion 21b being disposed outside the outer tank 3. In this case, the pipe expansion joint 21c absorbs a movement amount of the equipment 21 accompanying relative movement between the inner tank 2 and the outer tank 3. Further, in a case where the equipment 21 is fixed to the expansion and contraction mechanism portion 33, when installing or replacing the liquefied gas tank 1, work to install or replace the equipment 21 can be performed along with work relating to the outer tank 3.

[0046] In the above described third embodiment and the first modification thereof, the configuration of the opening/closing valve 21a, the connection portion 21b, and

the pipe expansion joint 21c is not limited to the configurations shown in the drawings, and the number of the components, the position at which to dispose the equipment 21, and the order in which the components are arranged and the like can be appropriately changed as necessary. A configuration may also be adopted in which all of the equipment 21 is concentrated at the bottom of the inner tank 2. Note that, although the above description of the third embodiment and the first modification thereof is based on the liquefied gas tank 1 described in the first embodiment, the third embodiment and the first modification thereof can also be applied to the liquefied gas tank 1 according to other embodiments such as the second embodiment.

[0047] Next, a method of installing the above described liquefied gas tank 1 is described with reference to Figures 7A to 7C and Figures 8A and 8B. Figures 7A to 7C are views that illustrate a method of installing the liquefied gas tank according to the second embodiment that is illustrated in Figures 4A and 4B, in which Figure 7A illustrates a foundation construction process, Figure 7B illustrates an inner tank installation process, and Figure 7C illustrates an outer tank installation process. Figures 8A and 8B are views that illustrate a modification of the method of installing the liquefied gas tank, in which Figure 8A illustrates a foundation construction process and Figure 8B illustrates an inner and outer tank installation process.

[0048] The foundation construction process illustrated in Figure 7A is a process for installing the base portions 4 and the weir-like structure 6 on the floor surface F. The inner tank installation process illustrated in Figure 7B is a process for installing the inner tank 2 on the base portions 4. More specifically, the support blocks 5 are

locked to the underside of the inner tank 2, and the support blocks 5 are placed on the base portions 4. The outer tank installation process illustrated in Figure 7C is a process for covering the outer tank 3 over the inner tank 2 and connecting the outer tank 3 to the weir-like structure 6. More specifically, the outer tank 3 is covered over the inner tank 2 so that the ceiling portion 3a of the outer tank 3 is supported by the upper face portion 2a of the inner tank 2, and the outer tank 3 is fixed to the weir-like structure 6 by connecting the thick portion 34 at the lower end portion of the outer tank 3 and the weir-like structure 6 by means of the expansion and contraction mechanism portion 33. Thereafter, the equipment 21 is inserted into the inside of the inner tank 2 and fitted, and the lid member 32 is connected to the outer tank 3 by passing the equipment 21 through the lid member 32. Loading equipment such as a crane is used to transport and move the inner tank 2, the outer tank 3, the equipment 21 and the like. Note that fitting of the equipment 21 may be performed before installing the inner tank 2 on the base portions 4, or may be performed before mounting the outer tank 3. Further, the expansion and contraction mechanism portion 33 may be installed at the thick portion 34 of the outer tank 3 before mounting the outer tank 3.

[0049] The outer tank 3 and the inner tank 2 can be easily moved from the base portions 4 by detaching the expansion and contraction mechanism portion 33. That is, the inner tank 2 and the outer tank 3 are configured to be attachable to and detachable from the floor surface F, and the inner tank 2 and the outer tank 3 are each configured to be replaceable. Accordingly, even in a case where there is no remaining liquefied gas stored in the inner tank 2,

liquefied gas to be used as fuel can be replenished by merely replacing the inner tank 2. Further, it is possible to fill liquefied gas into the inner tank 2 in advance at a factory or a storage depot or the like and transport the inner tank 2 using a vehicle or the like, and thus the liquefied gas tank 1 can be easily installed even at a location that is far from a storage depot.

[0050] The modification of the method of installing the liquefied gas tank 1 that is illustrated in Figures 8A and 8B is one in which the outer tank 3 is covered over the inner tank 2 beforehand, and thereafter the inner tank 2 and the outer tank 3 are placed in that state on the base portions 4. A foundation construction process illustrated in Figure 8A is a process for installing the base portions 4 and the weir-like structure 6 on the floor surface F. In the inner and outer tank installation process shown in Figure 8B, an assembly formed by covering the outer tank 3 over the inner tank 2 and connecting the equipment 21 and the like thereto that is constructed in advance at a factory or a storage depot or the like is placed on the base portions 4. A configuration is adopted so that the expansion and contraction mechanism portion 33 connects the thick portion 34 of the outer tank 3 and the weir-like structure 6. According to this method also, the inner tank 2 and the outer tank 3 can be configured to be attachable to and detachable from the floor surface F. Further, the expansion and contraction mechanism portion 33 may be installed at the thick portion 34 of the outer tank 3 before placing the inner and outer tank assembly on the base portions 4.

[0051] According to the above described liquefied gas tank 1 of the present embodiment, by configuring the inner tank 2 so as to capable of self-standing with respect to

the floor surface F and causing the inner tank 2 to support the outer tank 3, the structure of the outer tank 3 can be simplified, the installation area can be reduced, and costs can be lowered. In addition, by configuring the outer tank 3 to be capable of moving horizontally and capable of moving in the vertical direction relative to the inner tank 2, even when liquefied gas such as LNG is stored in the inner tank 2, the inner tank 2 can be protected from the external environment while allowing expansion and contraction (thermal expansion and thermal contraction) of the inner tank 2 that is caused thereby. Further, by adopting a simple structure, installation or replacement of the liquefied gas tank 1 can be easily performed, and even in a case where liquefied gas is used as fuel, replenishment of the fuel can be quickly performed.

[0052] In particular, even at a remote location that does not have a depot that accepts LNG or at an area (exposed part) that is not surrounded by a hull construction or the like such as an area on the deck of a ship or a floating structure, a liquefied gas tank can be easily installed, and liquefied gas can be used as fuel for generating electric power or as a propellant.

[0053] Next, the liquefied gas tank 1 according to other embodiments of the present invention is described referring to Figures 9 to 11. Figures 9A to 9C are schematic cross-sectional views that illustrate liquefied gas tanks according to other embodiments of the present invention, in which Figure 9A illustrates a fourth embodiment, Figure 9B illustrates a fifth embodiment, and Figure 9C illustrates a sixth embodiment. Figures 10A to 10D are diagrams illustrating the structure of a liquefied gas tank according to a seventh embodiment of the present invention, in which Figure 10A shows a schematic cross-sectional view,

Figure 10B shows a diagram that illustrates the structure of the outer tank wall surface, Figure 10C illustrates a first modification of the structure of the outer tank wall surface, and Figure 10D illustrates a second modification of the structure of the outer tank wall surface. Figures 11A and 11B are configuration diagrams of a liquefied gas tank according to an eighth embodiment of the present invention, in which Figure 11A shows a schematic cross-sectional view and Figure 11B shows a side view. Note that components that are the same as in the above described first embodiment or second embodiment are denoted by the same reference characters and duplicated descriptions are omitted.

[0054] The liquefied gas tank 1 according to the fourth embodiment that is illustrated in Figure 9A is one in which an penetration portion for the equipment 21 is formed in a dome structure. More specifically, the fourth embodiment has a structure in which the coaming portion 23 that is formed in the inner tank 2 is caused to protrude further upward than the ceiling portion 3a of the outer tank 3. As shown in the drawing, the lid member 32 may have a convex portion that covers the opening portion 31, or may be a flat shape that covers only the upper face portion of the coaming portion 23. The penetration portion for the equipment 21 in the inner tank 2 and outer tank 3, for example, has the same configuration as the configuration shown in Figure 5A to Figure 5C. Note that although the fourth embodiment that is illustrated in the drawing is based on the second embodiment, a similar configuration can also be applied with respect to the first embodiment.

[0055] The liquefied gas tank 1 according to the fifth embodiment that is illustrated in Figure 9B is one in which an elastic body 7 is disposed between the inner tank 2 and

the outer tank 3. The elastic body 7 is a component that suppresses movement of the outer tank 3 by transmitting an external force that acts on the outer tank 3 due to wind pressure or the like to the inner tank 2. More

5 specifically, a plurality of the elastic bodies 7 are disposed between side portions 2b of the inner tank 2 and side portions 3b of the outer tank 3, and are configured so as to urge the outer tank 3 in the horizontal direction.

Components of various forms such as a coiled spring, a
10 rubber member, or a hydraulic damper can be used as the elastic body 7. Note that although the fifth embodiment that is illustrated in the drawing is based on the second embodiment, a similar configuration can also be applied with respect to the first embodiment.

15 [0056] The liquefied gas tank 1 according to the sixth embodiment that is illustrated in Figure 9C is one in which the entire surface of the inner tank 2 is covered by the outer tank 3. More specifically, a configuration is adopted so as to cover the bottom face portion 2c of the
20 inner tank 2 with a bottom face portion 3c of the outer tank 3. At such time, the bottom face portion 3c of the outer tank 3 is disposed so as to avoid the support blocks 5, and may be configured so as to be capable of sliding in the vertical direction along the support blocks 5. A seal
25 member may be disposed between the support blocks 5 and the bottom face portion 3c of the outer tank 3, and a configuration may also be adopted so as to supply an inert gas from the inert gas introduction pipe 61 into the gap between the inner tank 2 and the outer tank 3 to achieve a
30 pressurized state therein. In the sixth embodiment, the weir-like structure 6 can be omitted. Note that although the sixth embodiment that is illustrated in the drawing is

based on the second embodiment, a similar configuration can also be applied with respect to the first embodiment.

[0057] Further, a configuration may also be adopted in which the outer tank 3 is constituted by aluminum tape for moisture prevention instead of a thin metal plate. Because the aluminum tape has adhesiveness, according to this configuration the outer tank 3 is directly attached to the external surface of the inner tank 2. At such time, it is good to provide the aluminum tape with a moderate amount of slack so that the aluminum tape can change shape in response to expansion and contraction of the inner tank 2.

[0058] The liquefied gas tank 1 according to the seventh embodiment that is illustrated in Figure 10A is one in which, with respect to the sixth embodiment illustrated in Figure 9C, the side portions 3b and the bottom face portion 3c of the outer tank 3 are formed in a structure such that the wall surfaces themselves are capable of expanding and contracting. More specifically, as shown in Figure 10B, the wall surface constituting the side portions 3b and the bottom face portion 3c of the outer tank 3 has a rimped structure in which a plurality of minute concavities and convexities are formed in succession. Note that in the respective drawings of Figure 10B to Figure 10D, the upper section shows a plan view and the lower section shows a cross-sectional view.

[0059] Furthermore, as shown in Figure 10C, a wall surface constituting the side portions 3b and the bottom face portion 3c of the outer tank 3 may be a lattice-like structure in which groove portions are formed at regular intervals in the horizontal direction and vertical direction, or as shown in Figure 10D, may be a diamond-cut structure in which a concavo-convex face of a predetermined shape is formed over the entire surface. In each of these

configurations, the wall surfaces constituting the side portions 3b and the bottom face portion 3c of the outer tank 3 are capable of expanding and contracting in the horizontal direction and vertical direction, and can absorb
5 a difference in an expansion/contraction amount with respect to the inner tank 2. Note that a configuration may also be adopted in which the expansion/contraction structure shown in any of Figure 10B to Figure 10D is applied to the ceiling portion 3a of the outer tank 3.

10 Furthermore, the expansion/contraction structures shown in Figure 10B to Figure 10D may also be applied to the side portions 3b of the outer tank 3 and the ceiling portion 3a of the outer tank 3 according to the first to fifth embodiments.

15 [0060] The liquefied gas tank 1 according to an eighth embodiment that is illustrated in Figure 11A and Figure 11B is one in which the inner tank 2 is constructed in a cylindrical shape. When importance is placed on storage efficiency, it is preferable to make the inner tank 2 a
20 rectangular shape as shown in Figure 1. On the other hand, when importance is placed on the pressure-resistance performance of the inner tank 2, the inner tank 2 may be made a cylindrical shape as shown in Figure 11A and Figure 11B. When the inner tank 2 is made a cylindrical shape,
25 the ceiling portion 3a of the outer tank 3 can be formed in a curved shape along the upper face portion 2a of the inner tank 2, and the lid member 32 can also be formed in a curved shape that follows the shape of the ceiling portion 3a of the outer tank 3. Note that the cross-sectional
30 shape of the inner tank 2 is not limited to the circular shape shown in the drawing, and may also be an elliptical shape.

[0061] In the first embodiment to eighth embodiment that are described above, when liquefied gas is used as a fuel, the capacity of the inner tank 2 is, for example, a size of approximately 500 to 5000 m³, and by making the structure of the liquefied gas tank 1 (in particular, the outer tank 3) a simple structure it is possible to save space.

Accordingly, the liquefied gas tank 1 can be easily installed even in a comparatively narrow space in a part of a factory or on the deck of a hull or the like. In

particular, when installing the liquefied gas tank 1 on the deck of a hull, because the visibility will be obstructed if the liquefied gas tank 1 is constructed with a large height, a configuration may be adopted in which the inner tank 2 is formed in a substantially tabular rectangular

shape with a low height, or is formed in a cylindrical shape that is laid onto its side as in the eighth embodiment, or in a shape obtained by forming a cylindrical shape into a flat shape. Note that the shapes of the inner tank 2 and the outer tank 3 are not limited to the shapes described above, and the inner tank 2 and the outer tank 3 can be formed in various shapes, such as a polygonal cross-sectional shape and a concavo-convex cross-sectional shape, in accordance with the installation area and the installation space.

[0062] The present invention is not limited to the above described embodiments, and naturally various modifications can be made without departing from the spirit and scope of the present invention, such as that the present invention can also be applied to liquefied gas (for example, LPG) other than LNG (liquefied natural gas), and that the first embodiment to eighth embodiment can be suitably combined and used.

Reference Signs List

[0063]

	1	Liquefied gas tank
	2	Inner tank
5	2a	Upper face portion
	3	Outer tank
	4	Base portion
	5	Support block
	6	Weir-like structure
10	7	Elastic body
	21	Equipment
	30	Penetration portion
	31	Opening portion
	32	Lid member
15	33	Expansion and contraction mechanism portion

Claims

[Claim 1]

A liquefied gas tank for storing liquefied gas,
5 comprising:

an inner tank that stores the liquefied gas and is
disposed so as to be capable of self-standing on a floor
surface; and

an outer tank that is covered over the inner tank
10 and is supported by an upper face portion of the inner
tank;

wherein the outer tank is configured to be capable
of sliding on the upper face portion of the inner tank in
response to expansion and contraction in a horizontal
15 direction of the inner tank and to be capable of moving in
response to expansion and contraction in a vertical
direction of the inner tank.

[Claim 2]

The liquefied gas tank according to claim 1,
20 wherein the outer tank comprises an expansion and
contraction mechanism portion that is disposed along a
lower outer circumference thereof, or a wall surface
thereof is itself formed as a structure that is capable of
expanding and contracting.

25 [Claim 3]

The liquefied gas tank according to claim 1,
wherein the inner tank and the outer tank are configured to
be attachable to and detachable from the floor surface, and
the inner tank or the outer tank is configured to be
30 replaceable.

[Claim 4]

The liquefied gas tank according to claim 1,
wherein a base portion that supports the inner tank is

disposed on the floor surface, and a support block is disposed between the base portion and the inner tank.

[Claim 5]

5 The liquefied gas tank according to claim 4,
wherein a weir-like structure is disposed on the floor surface so as to surround the base portion, and the outer tank is connected to the weir-like structure.

[Claim 6]

10 The liquefied gas tank according to claim 1,
wherein the outer tank comprises a penetration portion for inserting equipment into the inner tank, and a lid member is disposed on the penetration portion.

[Claim 7]

15 The liquefied gas tank according to claim 1,
wherein equipment that is inserted into the inner tank is disposed at a bottom face portion of the inner tank.

[Claim 8]

20 The liquefied gas tank according to claim 1,
wherein an inert gas is filled between the inner tank and the outer tank.

[Claim 9]

25 The liquefied gas tank according to claim 1,
wherein an elastic body is disposed between the inner tank and the outer tank.