



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>6</sup>:

B29C 51/10, 51/14, 51/26, 51/42

A1

(11) International Publication Number:

WO 99/64221

(43) International Publication Date:

16 December 1999 (16.12.99)

(21) International Application Number: PCT/NZ99/00079

(22) International Filing Date: 10 June 1999 (10.06.99)

(30) Priority Data:

330648

10 June 1998 (10.06.98)

NZ

(71) Applicant (for all designated States except US): FISCHER &amp; PAYKEL LIMITED [NZ/NZ]; 78 Springs Road, East Tamaki, Auckland (NZ).

(71)(72) Applicant and Inventor: WITTEN-HANNAH, Daniel [NZ/NZ]; 33 Nottingham Street, Westmere, Auckland (NZ).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VAUGHAN, Stewart [NZ/NZ]; 21 Hoheria Street, One Tree Hill, Auckland (NZ).

(74) Agents: CALHOUN, Douglas, C. et al.; A J Park &amp; Son, 6th floor, Huddart Parker Building, Post Office Square, P.O. Box 949, Wellington 6015 (NZ).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: APPARATUS AND METHODS FOR TWIN SHEET THERMOFORMING

## (57) Abstract

Apparatus for twin sheet thermoforming has each mould half incorporating a sheet support means which can hold a sheet by its edge and support the sheet during heating and wherein at least one of the sheet support means can retract during thermoforming. The sheets are supported clear of each mould half by the supports but are heated from between. A movable heater may carry sheets while simultaneously heating and transfer heated sheets to the mould halves of the thermoforming apparatus.

