22 July 2003

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61B 5/00, G01N 21/47 — A1

(11) International Publication Number: WO 00/42902

(43) International Publication Date: 27 July 2000 (27.07.00)

(21) International Application Number: PCT/CA00/00052

(22) International Filing Date: 21 January 2000 (21.01.00)

(30) Priority Data:
2,259,900 22 January 1999 (22.01.99) CA

(71) Applicant: ART ADVANCED RESEARCH TECHNOLOGIES INC. [CA/CA]; 2300 Alfred Nobel Boulevard, St-Laurent, Quebec H4S 2A4 (CA).

(72) Inventors: PAINCHAUD, Yves; 1850 Bourbonnière, Sillery, Quebec G1S 1N2 (CA). CHATIGNY, Stéphane; 353 des Franciscains, Quebec G1S 2P9 (CA). MORIN, Michel; 4736 Caroline-Valin, Apartment 3, Cap-Rouge, Quebec G1Y 3R7 (CA).

(74) Agent: KOSIE, Ronald, S.; Brouillette Kosie, Suite 2500, 1100, René-Lévesque Boulevard, Montreal, Quebec H3B 5C9 (CA).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.



G00002

(54) Title: DEPTH DISCRIMINATION OF HETOROGENEITIES IN TURBID MEDIA





162162

(57) Abstract

In accordance with the method a turbid medium (8) is scanned by displacing an optical signal source and a corresponding optical detector (5) from one respective spatial location to another about the turbid medium, each spatial location being associated with corresponding input regions on opposite faces of the turbid medium (8). The optical signal source directs an optical signal (1) to each of said input regions. The optical detector (5) sends corresponding detector output signal data to an image processing means (5a) for generating a set of image data of the turbid medium (8). The improvement comprises generating in addition to a primary set of image data, secondary and/or tertiary image data which are derived by scanning the turbid medium (8) using input regions and output regions of different sizes. The various sets of image data obtained may be manipulated to highlight the differences or similarities between the images (e.g. to obtain a composite set of image data indicative of an anomaly(ies) in the body of the turbid medium (8).