

The invention relates to a truncated triangular insulator in combination with a truncated triangular structural member.

In furnaces used throughout the metallurgical and related industries to heat a slab, billet, bloom and other steel shapes, a typical pusher furnace includes a complex network of vertical and horizontal water-cooled pipes which support an additional network of horizontal water-cooled skid rails along which the metal shapes are pushed through the furnace. The metallurgical furnace is an open system; that is, heat which is transferred to the metal pipe network is conducted by the flowing water in the pipes to a point outside the furnace and is thus not recoverable. Accordingly, vast amounts of heat losses occur and correspondingly unnecessary amounts of energy are expended to replace the heat loss through the pipes.

Historically, insulators have failed for several reasons. For instance, because of the severe vibrations set up in the skid rails and pipe network as the metal shapes are pushed through the furnace, the mechanical fastening devices which secure the refractory or insulator to the pipe breaks thereby permitting the insulator to fall from the pipe. Additionally, especially regarding the skid pipe and insulator, high temperature slag is deposited around the uppermost portion of the skid pipe which in turn migrates downwardly and into the seams between the insulator and the skid pipe. Hence, the high temperature slag degrades the insulator from within, and causes large pieces of the insulator to break off and fall to the furnace floor.

There has, therefore, been a long felt need in the steel industry for an insulator which reduces the migration of the slag into the seams between the insulator and pipe, and a long felt need for a means to secure an insulator to a support structure such as a skid rail or cross pipe which will remain in place around the support structure during furnace operations.

Various prior insulators are known.

The device in U.S. Patent specification No. 3,941,160 relates to a dense, preburned ceramic refractory formed in interlocking shapes which are positioned by a number of studs 35 welded to the cross-pipe which are received by the arcuate recesses 17 in the refractory shape. This device is intended for use around a cross-pipe but not a skid pipe as in the present invention. A ceramic blanket is positioned between the water pipe and the preburned ceramic tile. The massive weight of the preburned ceramic tile induces the fracture of the studs which support the refractory. Moreover, the seams which are formed within each pair of interlocking segments are fully exposed to slag migration.

The device in U.S. Patent Specification No.

3451661 involved an interlocking outer refractory layer unsupported by studs welded to the pipe. The amount of time and labour expended in interlocking the numerous outer pieces is significant, as is the number of seams defined by the individual pieces. This device is most easily used when applied to vertical pipes and is not suitable for use with a skid pipe.

The device described in U.S. Patent Specification No. 4015636 again used a preburned ceramic tile material having an inner layer of semi-cylindrical tiles held together on the pipe by a "C"-shaped ceramic refractory collar which is slid over the split tiles as they are held together. Again, the labour and time expended in insulating the pipe is less than satisfactory. Moreover, Figure 5 shows the conventional use of a refractory cement to cover the margins between the pipe and insulator from the harmful effects of slag migration.

The device in U.S. Patent Specification No. 4056350 shows an insulator 3 which is partially protected from falling work pieces by intermittent pieces 7; however, between the pieces 7 and 8, the insulator remains exposed to the effects of slag migration and is not maintained on the structure by its geometry.

The device in U.S. Patent Specification No. 3706448 shows an insulator 17 with a wire mesh 18 welded to the pipe. Again, the insulator is exposed to the effects of slag migration, and, even with the converging side configuration, when the wire mesh is broken, the insulator falls from the structure 9.

The device in U.S. Patent Specification No. 3642261 again shows a wire mesh 16 welded at point 17 and requires the use of a refractory filling material 18 to seal the gaps between the refractory and the pipe from the effects of slag migration.

The device in U.S. Patent Specification No. 337641 discloses an exposed insulator 21 exposed to the effects of slag migration and having none of the benefits of the novel geometric shape of the present invention.

The device in U.S. Patent Specification No. 3552729 discloses an insulator 11 which is not discussed by number in the description of the preferred embodiments. U.S. Patent Specification No. 3236507 discloses a device having an insulator 16 which is fully exposed to the effects of slag migration and does not include the novel geometric design of the present invention.

The device in U.S. Patent Specification No. 3214152 includes a heat-resistant means 7, 8, not acting as or intended to be an external insulator as such, and an insulator 2 which is again fully exposed to the effects of slag migration and does not include the advantages of the novel geometric design of the present invention.

The document EP—A1—25357 discloses a skid pipe for supporting a metal shape in a high temperature furnace environment comprising a base member having first and second ends, converging first and second side members having upper and lower ends, the lower ends of the first and second side members secured to the first and second ends of the base member respectively, the upper ends of the side members spaced apart and secured to an apex member, and a pair of shoulders extending outwardly from each upper end of the side member in proximity to where the side members are secured to the apex member. The skid pipe thus has a substantially truncated triangular configuration and is suitable for conveying internally a cooling fluid. If desired, a suitable insulator can be applied around the exterior of the base member and the converging side members and may about the adjacent portions of the shoulders. The insulator relies for its support solely on contact with the converging side members of the skid pipe. In use the insulator becomes hot and pyroplastic action may cause it to slip down the pipe thus exposing it to increased risk of slag migration into the area between the insulator and the support member.

The object of the invention is to provide an improved insulator/structural member combination providing (i) improved physical characteristics of the support member, and (ii) providing an improved shield for the new insulator against slag migration into the area between the insulator and the support member.

According to the invention there is provided an insulator in combination with a truncated triangular structural member including a base member having first and second ends, converging first and second side members having upper and lower ends, the lower ends of the first and second side members secured to the first and second ends of the base member respectively, the upper ends of the side members spaced apart and secured to an apex member, and a pair of shoulders extending outwardly from each upper end of the side member in proximity to where the side members are secured to the apex member, each shoulder including a lower lip; and the insulator comprising a base unit having first and second ends, first and second converging side walls, each having an upper and lower end, the lower ends of the first and second side walls being secured to the first and second ends respectively of the base unit the upper ends of the side walls each terminating in a face and being in spaced apart relationship to each other, and an axially aligned recess in at least one of the side walls of the insulator for slidably receiving a complementary rib in at least one of the corresponding side members of the structural member.

According to another aspect of the invention there is provided an insulator in combination with a truncated triangular structural member including a base member having first and

second ends, converging first and second side members having upper and lower ends, the lower ends of the first and second side members secured to the first and second ends of the base member respectively, the upper ends of the side members spaced apart and secured to an apex member, and a pair of shoulders extending outwardly from each upper end of the side member in proximity to where the side members are secured to the apex member, each shoulder including a lower lip; and an insulator comprising a base unit having first and second ends, first and second converging side walls, each having an upper and lower end, the lower ends of the first and second side walls being secured to the first and second ends respectively of the base unit the upper ends of the side walls each terminating in a face and being in spaced apart relationship to each other, and at least one recess in at least one of the side walls of the insulator for receiving a corresponding nodule on one of the respective side members of the structural member.

When the combination of the support member and the insulator design is used as a skid pipe, the base unit and side walls of the unique insulator closely conform to the periphery of the base member and side members of the support member. Hence, the unique design of the present invention permits the insulator to be slidably received around the skid pipe.

Preferably, the converging side walls of the insulator are in close proximity to the lower lips of the projecting shoulders. Because the lower lips of the projecting shoulders are sufficiently misaligned from the vertical, the design greatly reduces or eliminates the migration of slag between the insulator and the support member as the slag accumulates at the apex of the support member.

To help understanding of the invention, various specific embodiments thereof will now be described by way of example and with reference to the accompanying drawings in which:—

Figure 1 is a view in perspective showing a segment of a reheat furnace including a portion of skid pipe with insulators in accordance with the present invention;

Figure 2 is an elevational view in cross-section of the new insulator shape in accordance with the invention when used to insulate a skid pipe;

Figure 3 is an elevational view in cross-section of another embodiment of the present invention as used to insulate a skid pipe, further showing an accumulation of slag on top of the apex member of the structural member;

Figure 4A is a partial elevational view in cross-section of an embodiment of the prior art including a circular pipe, a skid welded on top of the pipe, a partially surrounding circular insulator anchored to the pipe with welded wire mesh, and a mortar seal and a representation of

(19)

a portion of a metal shape on top of the skid;

Figure 4B is a partial elevational view in cross-section of another embodiment of the prior art including a circular pipe, a partially surrounding circular insulator, a mortar seal and a stud welded to the pipe which supports the refractory around the pipe; and

Figure 5 is another embodiment of the present invention additionally showing nodules on the converging side members of the pipe were are received in corresponding recesses in the new insulator.

As shown in Figure 1, a section of a structural member 2 serves as a water-cooled skid pipe supported by a series of cross pipes, one cross pipe 5 being representative of the series. A conventional skid pipe 34 as shown in Figures 4A and 4B is representative of a skid pipe in common use throughout the industry today. A skid 36 is welded on top of the skid pipe 34, which skid directly supports a metal shape or workpiece 38 is partially shown in Figure 4. A passageway 35 is defined within the pipe 34 through which passageway cool water flows in order to reduce the operating temperature of the skid pipe in the furnace. A heavy pre-fired refractory or insulator 42 surrounds a portion of the skid pipe 34. Because of the weight and configuration of the conventional insulator 42, an additional means to secure the insulator 42 in location around the skid pipe 34 is required. Typically, a wire mesh 48, which is secured to the insulator 42 is welded to the skid pipe 34 at a point 60 as shown in Figure 4A. Another conventional means for securing the insulator 42 around the skid pipe 34 is the welding of a support stud 44 to the skid pipe 34, which welding stud is received within a recess 46 in the insulator 42 as shown in Figure 4B.

As shown in Figures 4A and 4B, a metal slag 52 accumulates on the skid pipe 34 during furnace operation. When the slag 52 migrates into the margin 54 between the insulator 42 and the skid pipe 34, the slag 52 then surrounds the insulator 42 on both sides thereby causing it to fracture and fall away from the skid pipe 34.

In any event, the studs 44 continuously degrade in the high furnace temperatures and break away from the skid pipe 34 as the skid pipe vibrates during furnace operations. The net result is that the insulator 42 quickly falls away from the skid pipe 34 thereby directly exposing the skid pipe 34 to the high furnace temperatures and corrosive convective gases within the furnace. A refractory cement 50 is disposed as shown in Figure 4A and 4B in order to reduce the migration of the slag 52 into the margin 54. Because of the brittle nature of the refractory cement 50, the cement cracks under the flexion and vibration of the skid pipe and permits migration of the slag 52 between the insulator 42 and the skid pipe 34. The prior art as represented by Figures 4A and 4B therefore has proven less than satisfactory.

The embodiments of the present invention illustrated in Figures 2 and 3 comprise an insulator 3 with a truncated triangular skid pipe 2 having outwardly projecting shoulders 12. The skid pipe itself comprises a base member 4 having first and second ends 7 and 9 respectively. A pair of converging side members 6 and 8 converge in a direction away from the base member 4. The side member 6 has a lower end 11 and an upper end 15 while the side member 8 has a lower end 13 and an upper end 17. The side walls 6 and 8 join an apex member 10 having a pair of shoulders 12 projecting outwardly generally from the points where the upper ends of the side members 6 and 8 are secured to the apex member 10. The resulting truncated triangular shaped skid pipe 2 defines a passageway 16 therethrough suitable for conducting a fluid, and is preferably a seamless, integral extruded pipe. A conventional skid 18, which could be rectangular in accordance with the prior art, can be welded or extruded onto the apex member 10.

The embodiments shown in Figures 2 and 3 include a truncated triangular insulator 3 having a base unit 20 with first and second ends 62 and 64. A first side wall 22, having a lower end 66 and an upper end 68, and a second side wall 24, having a lower end 70 and an upper end 72, converge but the upper ends 68 and 72 remain spaced apart. The lower ends 66 and 70 of the side walls are secured to and preferably integral with the ends 7 and 9 respectively of the base unit. As shown in Figures 2 and 3, the truncated triangular-shaped insulator 3 closely conforms to the periphery of and substantially surrounds the base member 4 and side walls 6 and 8 of the skid pipe 2. The insulator 3 can be manufactured from any suitable insulating material such as, for example, ramming mixes, plastics, prefired vibrocast refractory tiles, dry pressed prefired or chemically bonded refractory tiles, hydraulic or chemically bonded castable refractory tiles, and ceramic fibre materials.

As shown, the upper end 68 of the side wall 22 and/or the upper end 72 of the side wall 24 extends outwardly no farther than the corresponding shoulder. Also as shown in Figure 2, the border defined by the lower lip 26 of the shoulder and the face 28 of the upper end of the insulator is sufficiently misaligned from the vertical to reduce the deleterious effects of slag migration as the slag 58 as exemplified in Figure 3 is deposited on top of the apex member 10.

As shown in another embodiment of the invention in Figure 3, the side walls 56 and 57 of the insulator can extend outwardly farther than the side walls 22 and 24 as shown in Figure 2 in order to increase the amount of insulation around the skid pipe 2. It is preferred, however, that the upper ends 74 and 76 of the side walls 56 and 57 as shown in Figure 3 extend outwardly no farther than their corre-

sponding shoulders 12 as shown in both Figure 2 and 3. Hence, the harmful effects of slag migration between the lower lip of the skid pipe shoulder and the face of the upper end of the surrounding insulator have been materially reduced.

The geometry of the insulator 3 of Figure 2 provides yet another unique and beneficial result. Because the side walls 22 and 24 of the insulator closely conform to the converging side members 6 and 8 respectively of the skid pipe 2, the side walls of the insulator abut and bear against the corresponding side members of the skid pipe. Hence, the geometric design of the insulator 3 when used with a skid pipe having converging walls, permits the insulator 3 to maintain its position around the skid pipe. The insulator, however, is secured to the skid pipe by use of a support rib 30 axially aligned along at least one side member of the skid pipe which is slideably received within a compatible recess 32 in the corresponding side wall of the insulator. A portion of the skid pipe 2 as shown in Figure 1 includes the support rib 30.

Another suitable embodiment is shown in Figure 5. The nodules 81 of the skid pipe closely conform to the recesses 83 in the insulator thereby further supporting the insulator on the skid pipe. The nodule 81 can be located anywhere along the exterior of the side member so long as the recess 83 of the insulator is correspondingly positioned to receive the nodule.

As shown in Figure 1, the insulator 3 is quickly and efficiently applied to the skid pipe 2 by aligning the insulator 3 in a cutaway 80 so that a rail 82 is received through the spaced apart upper ends of the insulator. The insulator is then slidably received around the skid pipe 2 until it abuts an adjacent segment of the insulator. Clearly, the equipment, time and amount of labour expended in equipping the skid pipe with the new insulator is greatly reduced thereby reducing the expensive nonoperating time of the furnace itself.

It can be seen that the above described embodiments of the invention have the following advantages. Firstly, when utilized for insulating skid pipes, the insulators reduce the effects of slag migration into the margins between the insulator and the support member.

Secondly, the insulators, when used with a skid pipe in a metallurgical reheat furnace, reduce the number of exposed margins within the insulator.

Thirdly, the insulators, when used with a skid pipe, can be easily and quickly applied to the skid pipe.

Claims

1. An insulator in combination with a truncated triangular structural member (2) including a base member (4) having first and second ends (7, 9), converging first and second side members (6, 8) having upper and lower ends

(11, 13, 15, 17), the lower ends (11, 13) of the first and second side members (6, 8) secured to the first and second ends (7, 9) of the base member (4) respectively, the upper ends (15, 17) of the side members (6, 8) spaced apart and secured to an apex member (10), and a pair of shoulders (12) extending outwardly from each upper end (15, 17) of the side member (6, 8) in proximity to where the side members (6, 8) are secured to the apex member (10), each shoulder (12) including a lower lip (26); and the insulator comprising a base unit (20) having first and second ends (62, 64), first and second converging side walls (22, 24), each having an upper and lower end (66, 68, 70, 72), the lower ends (66, 70) of the first and second side walls (22, 24) being secured to the first and second ends (62, 64) respectively of the base unit (20) the upper ends (68, 72) of the side walls (22, 24) each terminating in a face (28) and being in spaced apart relationship to each other, and an axially aligned recess (32) in at least one of the side walls (22, 24) of the insulator (3) for slidably receiving a complementary rib (30) in at least one of the corresponding side members (6, 8) of the structural member.

2. The combination as claimed in Claim 1 wherein the insulator (3) is in substantially intimate contact with the structural member (2).

3. An insulator in combination with a truncated triangular structural member (2) including a base member (4) having first and second ends (7, 9), converging first and second side members (6, 8) having upper and lower ends (11, 13, 15, 17), the lower ends (11, 13) of the first and second side members (6, 8) secured to the first and second ends (7, 9) of the base member (4) respectively, the upper ends (15, 17) of the side members (6, 8) spaced apart and secured to an apex member (10), and a pair of shoulders (12) extending outwardly from each upper end (15, 17) of the side member (6, 8) in proximity to where the side members (6, 8) are secured to the apex member (10), each shoulder (12) including a lower lip (26); and the insulator comprising a base unit (20) having first and second ends (62, 64), first and second converging side walls (22, 24), each having an upper and lower end (66, 68, 70, 72), the lower ends (66, 70) of the first and second side walls (22, 24) being secured to the first and second ends (62, 64) respectively of the base unit (20) the upper ends (68, 72) of the side walls (22, 24) each terminating in a face (28) and being in spaced apart relationship to each other, and at least one recess (83) in at least one of the side walls (22, 24), of the insulator for receiving a corresponding nodule (81) on one of the respective side members (6, 8) of the structural member.

4. The combination as claimed in Claims 1 or 3 wherein the face of at least one upper end (68, 72) of the insulator (3) is disposed in close proximity to the corresponding lower lip (26) of the support member (2) to form a border.

sponding shoulders 12 as shown in both Figure 2 and 3. Hence, the harmful effects of slag migration between the lower lip of the skid pipe shoulder and the face of the upper end of the surrounding insulator have been materially reduced.

The geometry of the insulator 3 of Figure 2 provides yet another unique and beneficial result. Because the side walls 22 and 24 of the insulator closely conform to the converging side members 6 and 8 respectively of the skid pipe 2, the side walls of the insulator abut and bear against the corresponding side members of the skid pipe. Hence, the geometric design of the insulator 3 when used with a skid pipe having converging walls, permits the insulator 3 to maintain its position around the skid pipe. The insulator, however, is secured to the skid pipe by use of a support rib 30 axially aligned along at least one side member of the skid pipe which is slideably received within a compatible recess 32 in the corresponding side wall of the insulator. A portion of the skid pipe 2 as shown in Figure 1 includes the support rib 30.

Another suitable embodiment is shown in Figure 5. The nodules 81 of the skid pipe closely conform to the recesses 83 in the insulator thereby further supporting the insulator on the skid pipe. The nodule 81 can be located anywhere along the exterior of the side member so long as the recess 83 of the insulator is correspondingly positioned to receive the nodule.

As shown in Figure 1, the insulator 3 is quickly and efficiently applied to the skid pipe 2 by aligning the insulator 3 in a cutaway 80 so that a rail 82 is received through the spaced apart upper ends of the insulator. The insulator is then slidingly received around the skid pipe 2 until it abuts an adjacent segment of the insulator. Clearly, the equipment, time and amount of labour expended in equipping the skid pipe with the new insulator is greatly reduced thereby reducing the expensive nonoperating time of the furnace itself.

It can be seen that the above described embodiments of the invention have the following advantages. Firstly, when utilized for insulating skid pipes, the insulators reduce the effects of slag migration into the margins between the insulator and the support member.

Secondly, the insulators, when used with a skid pipe in a metallurgical reheat furnace, reduce the number of exposed margins within the insulator.

Thirdly, the insulators, when used with a skid pipe, can be easily and quickly applied to the skid pipe.

Claims

1. An insulator in combination with a truncated triangular structural member (2) including a base member (4) having first and second ends (7, 9), converging first and second side members (6, 8) having upper and lower ends

(11, 13, 15, 17), the lower ends (11, 13) of the first and second side members (6, 8) secured to the first and second ends (7, 9) of the base member (4) respectively, the upper ends (15, 17) of the side members (6, 8) spaced apart and secured to an apex member (10), and a pair of shoulders (12) extending outwardly from each upper end (15, 17) of the side member (6, 8) in proximity to where the side members (6, 8) are secured to the apex member (10), each shoulder (12) including a lower lip (26); and the insulator comprising a base unit (20) having first and second ends (62, 64), first and second converging side walls (22, 24), each having an upper and lower end (66, 68, 70, 72), the lower ends (66, 70) of the first and second side walls (22, 24) being secured to the first and second ends (62, 64) respectively of the base unit (20) the upper ends (68, 72) of the side walls (22, 24) each terminating in a face (28) and being in spaced apart relationship to each other, and an axially aligned recess (32) in at least one of the side walls (22, 24) of the insulator (3) for slidably receiving a complementary rib (30) in at least one of the corresponding side members (6, 8) of the structural member.

2. The combination as claimed in Claim 1 wherein the insulator (3) is in substantially intimate contact with the structural member (2).

3. An insulator in combination with a truncated triangular structural member (2) including a base member (4) having first and second ends (7, 9), converging first and second side members (6, 8) having upper and lower ends (11, 13, 15, 17), the lower ends (11, 13) of the first and second side members (6, 8) secured to the first and second ends (7, 9) of the base member (4) respectively, the upper ends (15, 17) of the side members (6, 8) spaced apart and secured to an apex member (10), and a pair of shoulders (12) extending outwardly from each upper end (15, 17) of the side member (6, 8) in proximity to where the side members (6, 8) are secured to the apex member (10), each shoulder (12) including a lower lip (26); and the insulator comprising a base unit (20) having first and second ends (62, 64), first and second converging side walls (22, 24), each having an upper and lower end (66, 68, 70, 72), the lower ends (66, 70) of the first and second side walls (22, 24) being secured to the first and second ends (62, 64) respectively of the base unit (20) the upper ends (68, 72) of the side walls (22, 24) each terminating in a face (28) and being in spaced apart relationship to each other, and at least one recess (83) in at least one of the side walls (22, 24), of the insulator for receiving a corresponding nodule (81) on one of the respective side members (6, 8) of the structural member.

4. The combination as claimed in Claims 1 or 3 wherein the face of at least one upper end (68, 72) of the insulator (3) is disposed in close proximity to the corresponding lower lip (26) of the support member (2) to form a border.



21

5. The combination as claimed in Claim 4 wherein the border is inclined sufficiently from the vertical to obviate the migration of metal slag from the apex member (10) within the border.

6. The combination as claimed in any one of Claims 1 to 5 wherein the side walls (22, 24, 56, 57) of the insulator (3) extend from each side member (6, 8) no farther than the corresponding shoulders (12).

Revendications

1. Isolateur combiné à un membre structural triangulaire tronqué (2) avec un membre de base (4) qui comprend: une première et une seconde extrémité (7, 9); un premier et un second membre latéral (6, 8) qui convergent et qui ont des extrémités supérieures et inférieures (11, 13, 15, 17), les extrémités inférieures (11, 13) du premier et du second membre latéral (6, 8) se trouvant rattachées respectivement à la première et à la seconde extrémité (7, 9) du membre de base (4), les extrémités supérieures (15, 17) des membres latéraux (6, 8) se trouvant espacées l'une de l'autre et rattachées à un membre apical (10); et une paire d'épaules (12) qui s'étendent vers l'extérieur à partir de chaque extrémité (15, 17) du membre latéral (6, 8) et près de la région où les membres latéraux sont rattachés au membre apical (10), chaque épaule (14) comprenant une lèvre inférieure (26); et l'isolateur comprenant une unité de base (20) avec une première et une seconde extrémité (62, 64) et une première et une seconde paroi latérale convergente (22, 24), dont chacune a une extrémité supérieure et inférieure (66, 68, 70, 72), les extrémités inférieures (66, 70) de la première et de la seconde paroi latérale (22, 24) se trouvant rattachées respectivement à la première et à la seconde extrémité de l'unité de base (20), chacune des extrémités (68, 72) des parois latérales (22, 24) se terminant en une face (28) et espacée l'une de l'autre, et un recoin (32) aligné axialement dans au moins une des parois latérales (22, 24) de l'isolateur (3), lequel recoin (32) reçoit une nervure complémentaire (30), qui glisse dans au moins un des membres latéraux correspondants (6, 8) du membre structural.

2. La combinaison selon la revendication 1, dans laquelle l'isolateur (3) se trouve substantiellement en contact intime avec le membre structural (2).

3. Isolateur combiné à un membre structural triangulaire tronqué (2) avec un membre de base (4) qui comprend: une première et une seconde extrémité (7, 9); un premier et un second membre latéral (6, 8) qui convergent et qui ont des extrémités supérieures et inférieures (11, 13, 15, 17), les extrémités inférieures (11, 13) du premier et du second membre latéral (6, 8) se trouvant rattachées respectivement à la première et à la seconde extrémité (7, 9) du membre de base (4), les

extrémités supérieures (15, 17) des membres latéraux (6, 8) se trouvant espacées l'une de l'autre et rattachées à un membre apical (10); et une paire d'épaules (12) qui s'étendent vers l'extérieur à partir de chaque extrémité (15, 17) du membre latéral (6, 8) et près de la région où les membres latéraux sont rattachés au membre apical (10), chaque épaule (14) comprenant une lèvre inférieure (26); et l'isolateur comprenant une unité de base (20) avec une première et une seconde extrémité (62, 64) et une première et une seconde paroi latérale convergente (22, 24), dont chacune a une extrémité supérieure et inférieure (66, 68, 70, 72) les extrémités inférieures (66, 70) de la première et de la seconde paroi latérale (22, 24) se trouvant rattachées respectivement à la première et à la seconde extrémité de l'unité de base (20), chacune des extrémités (68, 72) des parois latérales (22, 24) se terminant en une face (28) et espacée l'une de l'autre, et au moins un recoin (83) dans au moins une des parois latérales (22, 24) de l'isolateur, lequel recoin (83) reçoit un nodule correspondant (81) qui se trouve sur un des membres latéraux respectifs (6, 8) du membre structural.

4. La combinaison selon la revendication 1 ou 3, dans laquelle la face d'au moins une extrémité supérieure (68, 72) de l'isolateur (3) est arrangée très proche de la lèvre inférieure correspondante (26) du membre de support (2) afin de former un bord.

5. La combinaison selon la revendication 4, dans laquelle le bord est incliné suffisamment vis-à-vis le plan vertical afin d'empêcher la migration de la scorie à partir du membre apical (10) en dedans du bord.

6. La combinaison selon l'une des revendications 1 à 5, dans laquelle les parois latérales (22, 24, 56, 57) de l'isolateur (3), à partir de chaque membre latéral, ne s'étendent pas au delà des épaules latérales.

Patentansprüche

1. Isolator in Verbindung mit einem abgestumpften dreieckigen Bauglied (2) mit einem Grundglied (4) mit einem ersten und einem zweiten Ende (7, 9), und einem ersten und einem zweiten konvergierenden Seitenglied (6, 8) mit oberem und unteren Ende (11, 13, 15, 17), wobei die unteren Enden (11, 13) der ersten und der zweiten Seitenglieder (6, 8) jeweils mit dem ersten und dem zweiten Ende (7, 9) des Grundglieds angeschlossen sind, und die oberen Ende (15, 17) der Seitenglieder (6, 8) von einander versetzt und an ein Scheitglied (10) angeschlossen sind, sowie mit einem Paar Schultern (12) die, im Bereich der Verbindung zwischen den Seitengliedern (6, 8) und dem Scheitglied (10), sich auswärts von jedem oberen Ende (15, 17) des Seitenglieds (6, 8) erstrecken, wobei jede Schulter (12) eine untere Lippe (26) aufweist; welcher Isolator auch eine ein erstes und ein zweites Ende (62, 64)



sowie eine erste und eine zweite konvergierende Seitenwand (22, 24) aufweisende Grundeinheit (20) besitzt, wobei jede Seitenwand (22, 24) ein oberes und ein unteres Ende (66, 68, 70, 72) aufweist und wobei die unteren Ende (66, 70) der ersten und zweiten Seitenwände (22, 24) an dem ersten bzw. zweiten Ende (62, 64) der Grundeinheit (20) angeschlossen sind, welche oberen Enden (68, 72) der Seitenwände (22, 24) sich jeweils an einer Fläche (28) erstrecken und von einander versetzt sind, wobei eine achsial ausgerichtete Ausparung (32) in mindestens einer der Seitenwände (22, 24) des Isolators (3) geformt ist, so dass eine entsprechende Rippe (30) in mindestens einem der entsprechenden Seitenglieder (6, 8) des Bauglieds (2) gleiten kann.

2. Verbindung nach Anspruch 1, wobei der Isolator (3) im wesentlichen in enger Berührung mit dem Bauglied (2) steht.

3. Isolator in Verbindung mit einem abgestumpften dreieckigen Bauglied (2) mit einem Grundglied (4) mit einem ersten und einem zweiten Ende (7, 9), und einem ersten und einem zweiten konvergierenden Seitenglieder (6, 8) mit oberen und unteren Enden (11, 13, 15, 17), wobei die unteren Ende (11, 13) der ersten und der zweiten Seitenglieder (6, 8) jeweils mit dem ersten und dem zweiten Ende (7, 9) des Grundglieds angeschlossen sind, und die oberen Enden (15, 17) der Seitenglieder (6, 8) von einander versetzt und an ein Scheitelglied (10) angeschlossen sind, sowie mit einem Paar Schultern (12) die, im Bereich der Verbindung zwischen den Seitengliedern (6, 8) und dem Scheitelglied (10), sich auswärts von

jedem oberen Ende (15, 17) des Seitenglieds (6, 8) erstrecken, wobei jede Schulter (12) eine untere Lippe (26) aufweist; welcher Isolator auch eine ein erstes und ein zweites Ende (62, 64) sowie eine erste und eine zweite konvergierende Seitenwand (22, 24) aufweisende Grundeinheit (20) besitzt, wobei jede Seitenwand (22, 24) ein oberes und ein unteres Ende (66, 68, 70, 72) aufweist und wobei die unteren Enden (66, 70) der ersten und zweiten Seitenwände (22, 24) an dem ersten bzw. zweiten Ende (62, 64) der Grundeinheit (20) angeschlossen sind, welche oberen Ende (68, 72) der Seitenwände (22, 24) sich jeweils an einer Fläche (28) erstrecken und von einander versetzt sind, wobei mindestens eine Ausparung (83) zur Einnahme eines entsprechenden Wulstes (81) auf einem der Seitenglieder (6, 8) in mindestens einer der Seitenwände (22, 24) geformt ist.

4. Verbindung nach Anspruch 1 oder 3, wobei die Fläche mindestens eines oberen Endes (68, 72) des Isolators (3) in der Nähe der entsprechenden unteren Lippe (26) des Bauglieds (2) angeordnet ist, so dass eine Umrandung geformt wird.

5. Verbindung nach Anspruch 4, wobei die Umrandung so weit bezüglich der vertikalen Ebene geneigt ist, dass eine Wanderung der Metallschlacke von dem Scheitelglied (10) innerhalb der Umrandung her verhindert wird.

6. Verbindung nach einem der Ansprüche 1 bis 5, wobei sich die Seitenwände (22, 24, 56, 57) des Isolators (3) von jedem Seitenglied (6, 8) her aber nicht über die entsprechenden Schultern (12) erstrecken.

