



(51) International Patent Classification:

E21B 33/00 (2006.01) *E21B 34/00* (2006.01)
E21B 33/13 (2006.01)

(21) International Application Number:

PCT/US2013/064674

(22) International Filing Date:

11 October 2013 (11.10.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/719,274 26 October 2012 (26.10.2012) US
61/878,461 16 September 2013 (16.09.2013) US

(71) Applicant (for all designated States except US): **EXXON-MOBIL UPSTREAM RESEARCH COMPANY** [US/US]; CORP-URC-SW359, P.O. Box 2189, Houston, TX 77252-2189 (US).

(72) Inventors; and

(71) Applicants (for US only): **YEH, Charles, G.** [US/US]; 9511 Morlins Oaks Court, Spring, TX 77379 (US). **BARRY, Michael, D.** [US/US]; 251 N. Maple Glade Circle, The Woodlands, TX 77382 (US). **HECKER, Michael, T.** [US/US]; 16211 Castlegrove Court, Tomball, TX 77377 (US). **MOFFETT, Tracy, J.** [US/US]; 1615 Forest Trace Dr., Sugar Land, TX 77479 (US).

(74) Agents: **CROMWELL, Michael, A.** et al.; Exxonmobil Upstream Research Company, CORP-URC-SW359, P.O. Box 2189, Houston, TX 77252-2189 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,

[Continued on next page]

(54) Title: DOWNHOLE FLOW CONTROL, JOINT ASSEMBLY AND METHOD




FIG. 1

(57) Abstract: A method for completing a wellbore in a subsurface formation includes providing a first base pipe and a second base pipe. Each base pipe comprises a tubular body forming a primary flow path and has transport conduits along an outer diameter for transporting fluids as a secondary flow path. The method also includes connecting the base pipes using a coupling assembly. The coupling assembly has a manifold, and a flow port adjacent the manifold that places the primary flow path in fluid communication with the secondary flow path. The method also includes running the base pipes into the wellbore, and then causing fluid to travel between the primary and secondary flow paths. A wellbore completion apparatus is also provided that allows for control of fluid between the primary and secondary flow paths.



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))
- with amended claims (Art. 19(1))

Date of publication of the amended claims: 19 June 2014