

DEVICE AND PROCESS FOR THE PREPARATION OF A BEVERAGE WITH ENHANCED AROMA

5 The present invention concerns a device for preparing a beverage with enhanced
aroma.

Many beverages like espresso and other coffee drinks, milk drinks, soups, are often prepared by mixing a food soluble powder or a food liquid concentrate with a diluent. Mixing devices are known for speedier preparation of such beverages by mixing the
10 soluble food component with the diluent, such as hot water. These devices typically comprise a mixing chamber in which the soluble component and the diluent are fed. The diluent is usually introduced into the mixing chamber in order to create a whirlpool to efficiently dissolve the soluble component in the water. The mixture is then usually evacuated from the mixing chamber through the bottom of the mixing chamber and
15 dispensed into a receptacle for drinking.

The object of the present invention is to improve such mixing devices in order to provide beverages presenting higher aroma properties when they are delivered in the receptacle.

US 5,514,111 describes a device for obtaining hot drinks in solution, especially
20 cappuccino from a mixture of coffee in granules, milk and steam. The coffee granules are dispensed in a predetermined dose into a treatment chamber. The treatment chamber is closed by a cover and then air, liquid and steam are injected into the treatment chamber. The granules are mixed and dissolved in the liquid in the presence of steam and air. The beverage is removed from the treatment chamber in a first time through an outlet inside
25 the cover of the treatment chamber and in a second time through a valve in the bottom of the treatment chamber. Yet the operation of such a device is complex due to the dual evacuation of the beverage through the cover and through the bottom.

There is a need for a simpler and low cost solution enabling to dissolve a concentrate and produce a beverage from the combination of a diluent and soluble
30 ingredient or liquid concentrate and avoiding the aromas generated during the dissolution to escape.

The invention is firstly based on a device for the preparation of a beverage comprising :

- a mixing chamber for mixing a soluble ingredient and a diluent, said chamber comprising :
 - . a top opening,
 - 5 . a diluent inlet opening,
 - . a beverage outlet opening,
- sealing means, said sealing means being able to seal the top opening of the mixing chamber and to prevent any fluid from leaving the mixing chamber through said sealing means.

10 The mixing chamber of the device can be of any known kind and can take various shapes. In a preferred mode, the longitudinal upward wall is substantially cylindrical. Other shapes could be envisaged such as a polygonal, e.g., hexagonal, or oval section of the chamber, for instance. The bottom wall can be substantially a portion of truncated cone. The mixing chamber presents a top opening that is usually used for the introduction of
 15 soluble ingredient that can be introduced by gravimetric fall inside the mixing chamber. The mixing chamber also comprises a diluent inlet opening. Said diluent inlet opening is preferably in a side wall of the mixing chamber. The mixing chamber comprises a beverage outlet opening for delivering the beverage issued from the dissolution of soluble ingredient with the diluent inside the mixing chamber. Said beverage outlet of the mixing
 20 chamber is preferably in the bottom wall of the mixing chamber.

According to the invention, the device comprises sealing means that are able to seal the top opening of the mixing chamber and to prevent any fluid from leaving the mixing chamber through said sealing means or through the connection between the sealing means and the mixing chamber edges. These sealing means are preferably a cover. It
 25 means that the cover is preferably made of one full piece without presenting any aperture and that said cover, once placed above the top opening of the mixing chamber hermetically enters into contact with the mixing chamber top opening without leaving any aperture between the cover and the edge(s) of the mixing chamber top opening. The connection between the sealing means and the mixing chamber top opening is an
 30 hermetic seal. No fluid, either liquid or gaseous, can enter in or leave the chamber once the sealing means seal the mixing chamber top opening.

Once the sealing means seal the top opening of the mixing chamber the only opened outlet of the mixing chamber is the beverage outlet.

The sealing of the mixing chamber top opening can be realised according to different modes : generally the sealing means are a cover and said cover and the mixing chamber are able to move relative to each other so that in a first position the top opening of the mixing chamber is opened and in a second position the cover closes the top opening of the mixing chamber. According to a first mode, the cover is fixed and the mixing chamber is able to move between two positions in order to be sealed or not by the cover. According to a second preferred mode, the cover is displaceable. The cover can be linearly and/or rotationally moveable, from one position to the other while the mixing chamber is fixed. According to this second mode, the cover is linearly and/or rotationally moveable from a position where it covers the mixing chamber top opening to a position where it leaves the mixing chamber top opening uncovered.

The cover is preferably composed of a soft material. By soft, it is meant that the material is sufficiently elastic to establish a tight contact with the mixing chamber top opening in order to hermetically seal it when it is pushed against it. The soft material can be chosen between at least one of the following materials : Plasmol®, silicone, elastomer, rubber, preferably a thermoplastic rubber or elastomer (TPE). Actually a TPE polymer is a polymer blend or compound which, above its melt temperature, exhibits a thermoplastic character that enables it to be shaped into a fabricated article and which, within its design temperature range, possesses elastomeric behaviour. The interest of using a cover made of a deformable soft material is that this material can efficiently stick to the edges of the mixing chamber top opening during the beverage preparation : in particular, during the evacuation of the beverage from the mixing chamber, a depression occurs inside the mixing chamber that induces the sucking and the deformation of the soft cover improving its sealing function.

Apart from the soft part, the cover can also comprise a rigid material part for supporting the soft material. According to the preferred embodiment of the present invention, the soft material is held between two frames of rigid material. Then, the frames of rigid material can be linked to a motor to control the movement of the assembly of the frames and of the soft material. The rigid material can be chosen between at least one of the following materials : HDPE (high density polyethylene), LDPE (low density polyethylene), POM (polyoxymethylene), PP (polypropylene), nylon, metal, polycarbonate. This rigid part of the cover is useful to enable the displacement of the cover on and out of the mixing chamber top opening particularly if the second mode is implemented, for

example a mechanism for moving the cover can be fixed on the rigid material, the latter supporting the soft material of the cover.

In a preferred embodiment of the present invention, the mixing chamber can be connected to a fan able to suck or to flow back gaseous fluids present inside the mixing chamber. The connection between the fan and the mixing chamber can be a pipe that opens in the mixing chamber side wall.

The device of the present invention usually also comprises a metering device able to deliver a soluble ingredient dose through the top opening of the mixing chamber when the latter is opened. The metering device can comprise dosing means which can be of any known types like a screw, an auger, a barrel, a sliding chamber, a rotary pierced disc, ... for delivering a dose of powder to the mixing chamber of the apparatus or a pump like a peristaltic pump if the soluble ingredient is a liquid. The outlet of the metering device is directed to or cooperates with the mixing chamber top opening- e.g. through a pipe - when the cover does not seal the opening.

The device can comprise a whipping chamber, said whipping chamber being connected to the mixing chamber beverage outlet. The whipping chamber can help in the dissolution if the soluble ingredient is difficult to dissolve by only a simple contact with the diluent or if the beverage needs to be foamed.

The invention is secondly based on a method for preparing a beverage with a device as described above comprising at least the following steps :

- introducing a soluble ingredient inside the mixing chamber through the top opening of the mixing chamber,
- closing the top opening of the mixing chamber with the sealing means,
- introducing a diluent inside the chamber so that it mixes with the soluble ingredient,
- evacuating the mixed product from the mixing chamber through the beverage outlet opening,
- opening the top opening of the mixing chamber.

Preferably, the top opening of the mixing chamber is opened once the mixed product has been totally evacuated from the mixing chamber.

According to the preferred mode, the closure of the mixing chamber is realised by moving the cover to the mixing chamber top opening and the mixing chamber is opened by moving the cover away from the mixing chamber top opening.

If the device comprises a whipping chamber connected to the mixing chamber outlet, then during the evacuation of the mixed product the mixed product can be whipped and the depression due to the evacuation of the beverage from the mixing chamber is increased. This depression helps in sucking the aromas and delivering them with the beverage in the final receptacle.

If the device comprises a fan connected to the inside of the mixing chamber, said fan can suck gaseous fluids from the mixing chamber when the mixing chamber is opened and said fan can also flow back gaseous fluids from the mixing chamber to the beverage outlet opening of the mixing chamber when the mixing chamber is closed. When the sealing means are opened sucking operation enables the elimination of humidity like steam above the mixing chamber and avoids said humidity to enter inside the metering device generally placed above the mixing chamber particularly for powder soluble products. When the sealing means close the mixing chamber, flowing back operation enables an improved recovery of the aromas in the final receptacle.

According to a preferred embodiment of the process of the present invention, during the closure of the top opening of the mixing chamber with the sealing means, the sealing means are first brought above the top opening and secondly moved vertically to enter in contact with the top opening and close it. The movement for bringing the sealing means above the top opening can be a rotational or translation movement.

The device and the method of the present invention enable the production of beverage, especially coffee beverage, presenting enhanced in-cup aroma by directing most of the steam and vapors produced during the mixing operation into the final cup, in particular compounds like sulphur compounds and aldehydes that are representative of coffee aroma and that are more perceptible by the consumer.

Embodiments of the invention are described in more with reference to the accompanying drawings, wherein :

- Figure 1 depicts a device according to the present invention in its stand-by state.

- Figures 2 to 6 schematically depict the preparation of a beverage according to the present invention by the means of said device.

- Figure 7 is a top view of the preferred embodiment of the sealing means.

- Figure 8 is a section view of the sealing means of Figure 7 according to XX'.

- Figures 9A to 11B schematically depict the preparation of a beverage according to the preferred embodiment of the present invention.

It should be understood that the figures are merely schematic and are not drawn to scale. It should also be understood that the same reference numerals are used throughout the Figures to indicate the same or similar parts.

Figure 1 depicts a device for preparing beverages comprising a mixing chamber 1 presenting a top opening 4, a diluent inlet 5 and a beverage outlet opening 6. The device also comprises a metering device 3 comprising a hopper full of soluble ingredient like coffee powder 2 and a motor 9 to activate the introduction of a soluble ingredient dose inside the mixing chamber 1 through its top opening 4. The device comprises a cover 7 that can slide above and away from the top opening 4 of the mixing chamber 1 further to the action of a motor 10. The beverage outlet opening 6 opens in a whipping chamber 8 comprising a whipper to help in the dissolution the foaming of the beverage. Figure 1 corresponds to the stand-by step of the device of the invention : the metering device 3 is not activated, the mixing chamber top opening 4 is opened and no diluent is introduced in the mixing chamber 1.

Figure 2 illustrates the dosing step of the preparation of a beverage with the device of the present invention : the motor 9 of the metering device 3 pushes a dose of soluble ingredient 2 in the mixing chamber top opening 4.

Figure 3 illustrates the mixing chamber sealing step : the motor 9 of the metering device has been put off. The motor 10 for moving the cover 7 is activated in order to close the mixing chamber top opening 4.

Figure 4 illustrates the dissolution step : the diluent is introduced through the inlet 5 inside the mixing chamber to dissolve the soluble ingredient. The dissolved ingredient escapes from the mixing chamber 1 through the outlet 6.

Figure 5 illustrates the delivery step : the dissolved ingredient is eventually whipped in the whipping chamber 8 and delivered in a receptacle 11. Due to the closure of the mixing chamber 1 by the cover 7 and the depression induced by the evacuation of the beverage in the receptacle 11 and eventually by the operation of the whipper, the aromas 12 of the beverage that are still inside the mixing chamber are sucked with the beverage flow.

Figure 6 illustrates the mixing chamber opening step : once the beverage has been totally evacuated in the receptacle, then the motor 10 of the cover is activated to move the cover 7 away from the mixing chamber top opening 4 in order to come back to the stand-by step as illustrated in Figure 1.

5 Figures 7 and 8 is depicts sealing means according to the preferred embodiment of the present invention. Said sealing means are composed of a soft part 13 which is a disc of soft material and of a rigid part 14 which is made of two rings of a rigid material encircling the disc of soft material to hold it.

10 Figure 9A depicts a device for preparing beverages as described in Figure 1 except that the sealing means 7 correspond to the embodiment defined in Figures 7 and 8. Figure 9B is a top view of the device of Figure 9A representing the relative positions of the sealing means 7 and of the mixing chamber top opening 4. In this stand-by position of the device, the sealing means 7 are placed away from the mixing chamber top opening 4 so as to let this opening free for the next step of introduction of a soluble ingredient dose inside the
15 mixing chamber 1.

 Figures 10A, 10B, 11A and 11B depict the movement of the sealing means of the device of Figure 9A during the mixing chamber sealing step (equivalent to Figure 3 step). The sealing step implements two movements of the sealing means 7 : first the sealing means are rotated by motor 10 so that they are brought above the mixing chamber top opening 4 (Fig. 10A and 10B) and then the sealing means are moved downward by motor
20 10 so that the soft material part 13 of the cover stick to the edge of the mixing chamber and hermetically close it. The inner surface defined by the two rings 14 of rigid material of the sealing means 7 is designed as to be greater than the outer diameter of the mixing chamber top opening 4 so that the soft part 13 of the sealing means can easily cover the
25 whole top opening 4 and contact all the top opening edges.

EXAMPLE

 Coffee beverages were prepared using either a coffee machine integrating a device according to the present invention and according to the method of the present invention or
30 with a coffee machine of the state of the art.

 The both coffee machines were identical except that the coffee machine according to the present invention included a cover for the mixing chamber and a mechanism to close the mixing chamber once the coffee powder was introduced inside the mixing

chamber and before the diluent was introduced inside the mixing chamber. The cover was not removed from the mixing chamber opening before the beverage was totally evacuated from the mixing chamber. The cover was made of one full piece and its connection with the mixing chamber was hermetic from the step of the introduction of the diluent until the complete evacuation of the coffee from the mixing chamber inside the receptacle. The coffee machine did not present any cover above the mixing chamber.

The coffee preparation consisted in both cases in introducing 1,25 g of the same soluble coffee powder inside the mixing chamber and dissolving it with 23 ml of hot water. Immediately after the coffee beverage had dropped inside the receptacle, the receptacle was hermetically closed and is cooled in cold water. Before the coffee preparation, deuterium or C-13 were added in the bottom of the receptacle to quantify the aroma compounds and cysteine was added to release matrix bound thiols.

The aromas of the coffee beverage inside the receptacle were analysed by combined solid phase micro-extraction and gas chromatography. The results are presented in Table 1.

Table 1

Aroma nature	Aroma concentration (ppm/dry matter)		Increase of aroma concentration (%)
	Prior art	Invention	
methanethiol	0,82	1,45	175 %
dimethyl sulfide	0,80	1,39	174 %
furfurylthiol	2,05	3,20	156 %
3-mercapto-3-methylbutylformate	0,46	0,49	107 %
sulfur compounds	4,13	6,53	158 %
acetaldehyde	620,39	776,69	125 %
2-methylpropanal	1,00	1,84	184 %
3-methylbutanal	9,33	12,48	134 %
aldehydes	630,72	791,01	125 %
N-methylpyrrole	20,93	22,68	108 %
2,3-pentanedione	0,68	0,98	143 %
diketones	0,68	0,98	143 %
2-3-5-trimethylpyrazine	4,42	4,58	104 %
pyrazines	4,42	4,58	104 %
high volatiles aroma compounds (methanethiol + dimethyl sulfide + 2-methylpropanal + 3-methylbutanal)	11,95	17,15	144 %
medium volatiles aroma compounds (3-mercapto-3-methylbutylformate + acetaldehyde + N-methylpyrrole + 2,3-pentanedione)	642,46	800,85	125 %

The results of Table 1 show that significant higher contents of key sulphur compounds and aldehydes, that are known to contribute significantly to the coffeeness, are obtained with the coffee machine implementing a cover on the mixing chamber according to the present invention.

CLAIMS

1. Device for the preparation of a beverage comprising :

- a mixing chamber (1) for mixing a soluble ingredient (2) and a diluent, said chamber
5 comprising :

. a top opening (4),

. a diluent inlet opening (5),

. a beverage outlet opening (6),

- sealing means (7), said sealing means being able to seal the top opening (4) of the
10 mixing chamber (1) and to prevent any fluid from leaving the mixing chamber through said
sealing means wherein :

- the sealing means are a cover, and

- the cover and the mixing chamber are able to move relative to each other so that in a
first position the top opening of the mixing chamber is opened and in a second position the
15 cover closes the top opening of the mixing chamber, and

- the cover is composed of at least one soft material part (13).

2. Device according to Claim 1 wherein the cover is rotationally and/or linearly moveable
from one position to the other.

3. Device according to Claim 1 or 2, wherein the soft material is chosen between at least
one of the following materials : Plasmol®, silicone, elastomer, rubber, a thermoplastic
rubber or elastomer (TPE).

4. Device according to Claims 1 to 3 wherein the cover comprises a rigid material part (14)
for supporting the soft material.

5. Device according to Claim 4 wherein the soft material part (13) is hold between two
frames of rigid material (14).

6. Device according to Claims 4 or 5 wherein the rigid material is chosen between at least
one of the following materials : HDPE, LDPE, POM, PP, nylon.

7. Device according to Claims 1 and 4 wherein a mechanism for moving the cover is fixed on the rigid material part (14).

5 8. Device according to any previous claims wherein the mixing chamber is connected to a fan able to suck or to flow back gaseous fluids present inside the mixing chamber.

9. A method for preparing a beverage with a device according to any of Claims 1 to 8 comprising at least the following steps :

- 10 - introducing a soluble ingredient (2) inside the mixing chamber (1) through the top opening (4) of the mixing chamber (1),
- closing the top opening (4) of the mixing chamber with the sealing means (7),
- introducing a diluent inside the mixing chamber so that it mixes with the soluble ingredient,
- 15 - evacuating the mixed product from the mixing chamber through the beverage outlet opening (6),
- opening the top opening (4) of the mixing chamber.

20 10. A method according to Claim 9 wherein the top opening of the mixing chamber is opened once the mixed product is totally evacuated from the mixing chamber.

11. A method according to any of Claims 9 or 10, wherein the device comprises a fan connected to the inside of the mixing chamber, said fan sucking gaseous fluids from the mixing chamber when the mixing chamber is opened and said fan flowing back gaseous fluids from the mixing chamber to the beverage outlet opening of the mixing chamber
25 when the mixing chamber is closed.

12. A method according to any of Claims 9 to 11, wherein during the closure of the top opening (4) of the mixing chamber with the sealing means (7), the sealing means are first brought above the top opening (4) and secondly moved vertically to enter in contact with
30 the top opening (4) and close it.

Abstract**DEVICE AND PROCESS FOR THE PREPARATION OF
A BEVERAGE WITH ENHANCED AROMA**

5

The present invention relates to a device for the preparation of a beverage comprising :

- 10 - a mixing chamber (1) for mixing a soluble ingredient (2) and a diluent, said chamber comprising :
- . a top opening (4),
 - . a diluent inlet opening (5),
 - . a beverage outlet opening (6),
- 15 - sealing means (7), said sealing means being able to seal the top opening (4) of the mixing chamber (1) and to prevent any fluid from leaving the mixing chamber through said sealing means.

The invention also relates to a method for using this device.

Figure 1