

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

200007578-8

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : D06N 7/06, E04B 1/66, E04D 1/36, 7/00		A1	(11) International Publication Number: WO 99/53132
			(43) International Publication Date: 21 October 1999 (21.10.99)
(21) International Application Number: PCT/AU99/00269		(81) Designated States: CA, NZ, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 9 April 1999 (09.04.99)			
(30) Priority Data: ① 60774/98 ✓ 9 April 1998 (09.04.98) ✓ AU		Published With international search report. ✓ With amended claims. ✓	
(71)(72) Applicant and Inventor: BOYLE, Peter, Hamilton [AU/AU]; 14 Bowen Terrace, Rockhampton, QLD 4700 (AU).			
(74) Agent: PULLEN, Kevin, M.; P.O. Box 241, Landsborough, QLD 4550 (AU).		1 PD. 1 appl ⁿ = 1 inv. IPC : D06N 7/06 E04B 1/66 E04D 1/36 E04D 7/00	
(54) Title: IMPREGNATED FOAM MATERIALS ✓			
(57) Abstract			
Polyether-polyurethane foam materials impregnated with bitumen are disclosed. These foam materials find use as sealing strips against moisture, draughts and dust, particularly in the construction of roofs and walls of a building with overlapping formed metal or cement or similar sheets where a strip is inserted in the overlap of two adjacent sheets to provided the required sealing therebetween. The sealing strips can also be used to seal adjacent tiles on a roof between the underside of the tile and its supporting batten or rafter. The bitumen may be a bitumen emulsion, hot bitumen or kerosene-diluted bitumen. The concentration of bitumen in the foam materials can be in excess of 600 kg/m³.			

IPER 8/11/99.